```
root@bac4b884357e:/cloud-computing-544# aws --version
aws-cli/2.36.34 Python/3.14.6 Linux/6.4.16-linuxkit exe/x86_64.ubuntu.22
root@bac4b884357e:/cloud-computing-544#
```

```
(base) mac@Chais-MacBook-Air ~ % aws --version
aws-cli/2.36.34 Python/3.14.6 Darwin/21.6.0 exe/x86_64
```

IMAGE: AWS Version

```
root@bac4b884357e:/cloud-computing-544# git config --global --list
credential.helper=cache --timeout=3600
user.name=Chayasri Kirankumar
user.email=ckirankumar@hawk.illinoistech.edu
```

IMAGE: Git Global list





IMAGE: List_bucket.sh folder

```
root@bac4b884357e:/# aws sts get-caller-identity
{
    "UserId": "AIDA5A3UNQH56MHRF45SP",
    "Account": "895207965179",
    "Arn": "arn:aws:iam::895207965179:user/chaya"
}
```

IMAGE: Get caller identity

**One paragraph explaining why you should never commit AWS credentials or GitHub tokens to a repository, even a private one.**

AWS credentials and GitHub tokens should never be committed to a repository because they can provide unauthorized access to cloud resources, source code, and other sensitive information. Even if a repository is private, credentials can still be exposed through accidental sharing, compromised accounts, incorrect repository permissions, forks, backups, or other security issues. Once a secret is committed to Git history, simply deleting the file does not completely remove the secret because previous commits may still contain it. If credentials or tokens are accidentally exposed, they should be revoked or rotated immediately. Instead of storing secrets in source code or configuration files, secure methods such as environment variables, credential managers, or AWS IAM roles should be used.