

Parameter	Description	Type	Size	Default						
fragment	Pass/drop fragments that match L3 information.	option	-	pass						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>pass</td><td>Pass fragments that match interface, srcaddr, and dstaddr.</td></tr><tr><td>drop</td><td>Drop fragments that match interface, srcaddr, and dstaddr.</td></tr></table>				Option	Description	pass	Pass fragments that match interface, srcaddr, and dstaddr.	drop	Drop fragments that match interface, srcaddr, and dstaddr.
Option	Description									
pass	Pass fragments that match interface, srcaddr, and dstaddr.									
drop	Drop fragments that match interface, srcaddr, and dstaddr.									
interface	Interface name.	string	Maximum length: 35							
name	Policy name.	string	Maximum length: 35							
policyid	Policy ID.	integer	Minimum value: 0 Maximum value: 9999	0						
service <name>	Service name. Service name.	string	Maximum length: 79							
srcaddr <name>	Source address name. Address name.	string	Maximum length: 79							
status	Enable/disable access control list status.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable access control list status.</td></tr><tr><td>disable</td><td>Disable access control list status.</td></tr></table>				Option	Description	enable	Enable access control list status.	disable	Disable access control list status.
Option	Description									
enable	Enable access control list status.									
disable	Disable access control list status.									

config firewall address

Configure IPv4 addresses.

```
config firewall address
  Description: Configure IPv4 addresses.
  edit <name>
    set allow-routing [enable|disable]
    set associated-interface {string}
    set cache-ttl {integer}
    set clearpass-spt [unknown|healthy|...]
    set color {integer}
    set comment {var-string}
    set country {string}
    set end-ip {ipv4-address-any}
    set epg-name {string}
    set fabric-object [enable|disable]
    set filter {var-string}
    set fqdn {string}
    set fsso-group <name1>, <name2>, ...
```

```

set hw-model {string}
set hw-vendor {string}
set interface {string}
config list
    Description: IP address list.
    edit <ip>
    next
end
set macaddr <macaddr1>, <macaddr2>, ...
set node-ip-only [enable|disable]
set obj-id {var-string}
set obj-tag {string}
set obj-type [ip|mac]
set organization {string}
set os {string}
set policy-group {string}
set route-tag {integer}
set sdn {string}
set sdn-addr-type [private|public|...]
set sdn-tag {string}
set start-ip {ipv4-address-any}
set sub-type [sdn|clearpass-spt|...]
set subnet {ipv4-classnet-any}
set subnet-name {string}
set sw-version {string}
set tag-detection-level {string}
set tag-type {string}
config tagging
    Description: Config object tagging.
    edit <name>
        set category {string}
        set tags <name1>, <name2>, ...
    next
end
set tenant {string}
set type [ipmask|iprange|...]
set uuid {uuid}
set wildcard {ipv4-classnet-any}
set wildcard-fqdn {string}
next
end

```

config firewall address

Parameter	Description	Type	Size	Default						
allow-routing	Enable/disable use of this address in the static route configuration.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable use of this address in the static route configuration.</td></tr><tr><td><i>disable</i></td><td>Disable use of this address in the static route configuration.</td></tr></table>				Option	Description	<i>enable</i>	Enable use of this address in the static route configuration.	<i>disable</i>	Disable use of this address in the static route configuration.
Option	Description									
<i>enable</i>	Enable use of this address in the static route configuration.									
<i>disable</i>	Disable use of this address in the static route configuration.									

Parameter	Description	Type	Size	Default														
associated-interface	Network interface associated with address.	string	Maximum length: 35															
cache-ttl	Defines the minimal TTL of individual IP addresses in FQDN cache measured in seconds.	integer	Minimum value: 0 Maximum value: 86400	0														
clearpass-spt	SPT (System Posture Token) value.	option	-	unknown														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>unknown</i></td><td>UNKNOWN.</td></tr><tr><td><i>healthy</i></td><td>HEALTHY.</td></tr><tr><td><i>quarantine</i></td><td>QUARANTINE.</td></tr><tr><td><i>checkup</i></td><td>CHECKUP.</td></tr><tr><td><i>transient</i></td><td>TRANSIENT.</td></tr><tr><td><i>infected</i></td><td>INFECTED.</td></tr></table>				Option	Description	<i>unknown</i>	UNKNOWN.	<i>healthy</i>	HEALTHY.	<i>quarantine</i>	QUARANTINE.	<i>checkup</i>	CHECKUP.	<i>transient</i>	TRANSIENT.	<i>infected</i>	INFECTED.
	Option	Description																
	<i>unknown</i>	UNKNOWN.																
	<i>healthy</i>	HEALTHY.																
	<i>quarantine</i>	QUARANTINE.																
	<i>checkup</i>	CHECKUP.																
	<i>transient</i>	TRANSIENT.																
<i>infected</i>	INFECTED.																	
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0														
comment	Comment.	var-string	Maximum length: 255															
country	IP addresses associated to a specific country.	string	Maximum length: 2															
end-ip	Final IP address (inclusive) in the range for the address.	ipv4-address-any	Not Specified	0.0.0.0														
epg-name	Endpoint group name.	string	Maximum length: 255															
fabric-object	Security Fabric global object setting.	option	-	disable														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Object is set as a security fabric-wide global object.</td></tr><tr><td><i>disable</i></td><td>Object is local to this security fabric member.</td></tr></table>				Option	Description	<i>enable</i>	Object is set as a security fabric-wide global object.	<i>disable</i>	Object is local to this security fabric member.								
	Option	Description																
	<i>enable</i>	Object is set as a security fabric-wide global object.																
<i>disable</i>	Object is local to this security fabric member.																	
filter	Match criteria filter.	var-string	Maximum length: 2047															

Parameter	Description	Type	Size	Default						
fqdn	Fully Qualified Domain Name address.	string	Maximum length: 255							
fsso-group <name>	FSSO group(s). FSSO group name.	string	Maximum length: 511							
hw-model	Dynamic address matching hardware model.	string	Maximum length: 35							
hw-vendor	Dynamic address matching hardware vendor.	string	Maximum length: 35							
interface	Name of interface whose IP address is to be used.	string	Maximum length: 35							
macaddr <macaddr>	Multiple MAC address ranges. MAC address ranges <start>[-<end>] separated by space.	string	Maximum length: 127							
name	Address name.	string	Maximum length: 79							
node-ip-only	Enable/disable collection of node addresses only in Kubernetes.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable collection of node addresses only in Kubernetes.</td></tr><tr><td>disable</td><td>Disable collection of node addresses only in Kubernetes.</td></tr></table>				Option	Description	enable	Enable collection of node addresses only in Kubernetes.	disable	Disable collection of node addresses only in Kubernetes.
Option	Description									
enable	Enable collection of node addresses only in Kubernetes.									
disable	Disable collection of node addresses only in Kubernetes.									
obj-id	Object ID for NSX.	var-string	Maximum length: 255							
obj-tag	Tag of dynamic address object.	string	Maximum length: 255							
obj-type	Object type.	option	-	ip						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ip</td><td>IP address.</td></tr><tr><td>mac</td><td>MAC address</td></tr></table>				Option	Description	ip	IP address.	mac	MAC address
Option	Description									
ip	IP address.									
mac	MAC address									
organization	Organization domain name (Syntax: organization/domain).	string	Maximum length: 35							
os	Dynamic address matching operating system.	string	Maximum length: 35							
policy-group	Policy group name.	string	Maximum length: 15							

Parameter	Description	Type	Size	Default																				
route-tag	route-tag address.	integer	Minimum value: 1 Maximum value: 4294967295	0																				
sdn	SDN.	string	Maximum length: 35																					
sdn-addr-type	Type of addresses to collect.	option	-	private																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>private</td><td>Collect private addresses only.</td></tr><tr><td>public</td><td>Collect public addresses only.</td></tr><tr><td>all</td><td>Collect both public and private addresses.</td></tr></table>				Option	Description	private	Collect private addresses only.	public	Collect public addresses only.	all	Collect both public and private addresses.												
	Option	Description																						
	private	Collect private addresses only.																						
	public	Collect public addresses only.																						
all	Collect both public and private addresses.																							
sdn-tag	SDN Tag.	string	Maximum length: 15																					
start-ip	First IP address (inclusive) in the range for the address.	ipv4-address-any	Not Specified	0.0.0.0																				
sub-type	Sub-type of address.	option	-	sdn																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>sdn</td><td>SDN address.</td></tr><tr><td>clearpass-spt</td><td>ClearPass SPT (System Posture Token) address.</td></tr><tr><td>fsso</td><td>FSSO address.</td></tr><tr><td>ems-tag</td><td>FortiClient EMS tag.</td></tr><tr><td>fortivoice-tag</td><td>FortiVoice tag.</td></tr><tr><td>fortinac-tag</td><td>FortiNAC tag.</td></tr><tr><td>fortipolicy-tag</td><td>FortiPolicy tag.</td></tr><tr><td>swc-tag</td><td>Switch Controller NAC policy tag.</td></tr><tr><td>device-identification</td><td>Device address.</td></tr></table>				Option	Description	sdn	SDN address.	clearpass-spt	ClearPass SPT (System Posture Token) address.	fsso	FSSO address.	ems-tag	FortiClient EMS tag.	fortivoice-tag	FortiVoice tag.	fortinac-tag	FortiNAC tag.	fortipolicy-tag	FortiPolicy tag.	swc-tag	Switch Controller NAC policy tag.	device-identification	Device address.
	Option	Description																						
	sdn	SDN address.																						
	clearpass-spt	ClearPass SPT (System Posture Token) address.																						
	fsso	FSSO address.																						
	ems-tag	FortiClient EMS tag.																						
	fortivoice-tag	FortiVoice tag.																						
	fortinac-tag	FortiNAC tag.																						
	fortipolicy-tag	FortiPolicy tag.																						
	swc-tag	Switch Controller NAC policy tag.																						
device-identification	Device address.																							
subnet	IP address and subnet mask of address.	ipv4-classnet-any	Not Specified	0.0.0.0 0.0.0.0																				
subnet-name	Subnet name.	string	Maximum length: 255																					

Parameter	Description	Type	Size	Default																				
sw-version	Dynamic address matching software version.	string	Maximum length: 35																					
tag-detection-level	Tag detection level of dynamic address object.	string	Maximum length: 15																					
tag-type	Tag type of dynamic address object.	string	Maximum length: 63																					
tenant	Tenant.	string	Maximum length: 35																					
type	Type of address.	option	-	ipmask																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ipmask</i></td><td>Standard IPv4 address with subnet mask.</td></tr><tr><td><i>iprange</i></td><td>Range of IPv4 addresses between two specified addresses (inclusive).</td></tr><tr><td><i>fqdn</i></td><td>Fully Qualified Domain Name address.</td></tr><tr><td><i>geography</i></td><td>IP addresses from a specified country.</td></tr><tr><td><i>wildcard</i></td><td>Standard IPv4 using a wildcard subnet mask.</td></tr><tr><td><i>dynamic</i></td><td>Dynamic address object.</td></tr><tr><td><i>interface-subnet</i></td><td>IP and subnet of interface.</td></tr><tr><td><i>mac</i></td><td>Range of MAC addresses.</td></tr><tr><td><i>route-tag</i></td><td>route-tag addresses.</td></tr></table>				Option	Description	<i>ipmask</i>	Standard IPv4 address with subnet mask.	<i>iprange</i>	Range of IPv4 addresses between two specified addresses (inclusive).	<i>fqdn</i>	Fully Qualified Domain Name address.	<i>geography</i>	IP addresses from a specified country.	<i>wildcard</i>	Standard IPv4 using a wildcard subnet mask.	<i>dynamic</i>	Dynamic address object.	<i>interface-subnet</i>	IP and subnet of interface.	<i>mac</i>	Range of MAC addresses.	<i>route-tag</i>	route-tag addresses.
Option	Description																							
<i>ipmask</i>	Standard IPv4 address with subnet mask.																							
<i>iprange</i>	Range of IPv4 addresses between two specified addresses (inclusive).																							
<i>fqdn</i>	Fully Qualified Domain Name address.																							
<i>geography</i>	IP addresses from a specified country.																							
<i>wildcard</i>	Standard IPv4 using a wildcard subnet mask.																							
<i>dynamic</i>	Dynamic address object.																							
<i>interface-subnet</i>	IP and subnet of interface.																							
<i>mac</i>	Range of MAC addresses.																							
<i>route-tag</i>	route-tag addresses.																							
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000																				
wildcard	IP address and wildcard netmask.	ipv4-classnet-any	Not Specified	0.0.0.0 0.0.0.0																				
wildcard-fqdn	Fully Qualified Domain Name with wildcard characters.	string	Maximum length: 255																					

config list

Parameter	Description	Type	Size	Default
ip	IP.	string	Maximum length: 35	

config tagging

Parameter	Description	Type	Size	Default
category	Tag category.	string	Maximum length: 63	
name	Tagging entry name.	string	Maximum length: 63	
tags <name>	Tags. Tag name.	string	Maximum length: 79	

config firewall address6-template

Configure IPv6 address templates.

```
config firewall address6-template
  Description: Configure IPv6 address templates.
  edit <name>
    set fabric-object [enable|disable]
    set ip6 {ipv6-network}
    config subnet-segment
      Description: IPv6 subnet segments.
      edit <id>
        set bits {integer}
        set exclusive [enable|disable]
        set name {string}
        config values
          Description: Subnet segment values.
          edit <name>
            set value {string}
          next
        end
      next
    end
  next
end
```

config firewall address6-template

Parameter	Description	Type	Size	Default						
fabric-object	Security Fabric global object setting.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Object is set as a security fabric-wide global object.</td></tr><tr><td><i>disable</i></td><td>Object is local to this security fabric member.</td></tr></table>				Option	Description	<i>enable</i>	Object is set as a security fabric-wide global object.	<i>disable</i>	Object is local to this security fabric member.
Option	Description									
<i>enable</i>	Object is set as a security fabric-wide global object.									
<i>disable</i>	Object is local to this security fabric member.									