

config firewall on-demand-sniffer

Parameter	Description	Type	Size	Default						
advanced-filter	Advanced freeform filter that will be used over existing filter settings if set. Can only be used by super admin.	var-string	Maximum length: 255							
hosts <host>	IPv4 or IPv6 hosts to filter in this traffic sniffer. IPv4 or IPv6 host.	string	Maximum length: 255							
interface	Interface name that on-demand packet sniffer will take place.	string	Maximum length: 35							
max-packet-count	Maximum number of packets to capture per on-demand packet sniffer.	integer	Minimum value: 1 Maximum value: 20000 **	0						
name	On-demand packet sniffer name.	string	Maximum length: 35							
non-ip-packet	Include non-IP packets.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable non-IP packets to be included capture.</td></tr><tr><td>disable</td><td>Disable non-IP packets to be included in capture.</td></tr></table>				Option	Description	enable	Enable non-IP packets to be included capture.	disable	Disable non-IP packets to be included in capture.
Option	Description									
enable	Enable non-IP packets to be included capture.									
disable	Disable non-IP packets to be included in capture.									
ports <port>	Ports to filter for in this traffic sniffer. Port to filter in this traffic sniffer.	integer	Minimum value: 1 Maximum value: 65536							
protocols <protocol>	Protocols to filter in this traffic sniffer. Integer value for the protocol type as defined by IANA (0 - 255).	integer	Minimum value: 0 Maximum value: 255							

** Values may differ between models.

config firewall policy

Configure IPv4/IPv6 policies.

```
config firewall policy
  Description: Configure IPv4/IPv6 policies.
  edit <policyid>
    set action [accept|deny|...]
    set anti-replay [enable|disable]
    set application-list {string}
    set auth-cert {string}
```

```
set auth-path [enable|disable]
set auth-redirect-addr {string}
set auto-asic-offload [enable|disable]
set av-profile {string}
set block-notification [enable|disable]
set captive-portal-exempt [enable|disable]
set capture-packet [enable|disable]
set casb-profile {string}
set cifs-profile {string}
set comments {var-string}
set custom-log-fields <field-id1>, <field-id2>, ...
set decrypted-traffic-mirror {string}
set delay-tcp-npu-session [enable|disable]
set diameter-filter-profile {string}
set diffserv-copy [enable|disable]
set diffserv-forward [enable|disable]
set diffserv-reverse [enable|disable]
set diffservcode-forward {user}
set diffservcode-rev {user}
set disclaimer [enable|disable]
set dlp-profile {string}
set dnsfilter-profile {string}
set dsri [enable|disable]
set dstaddr <name1>, <name2>, ...
set dstaddr-negate [enable|disable]
set dstaddr6 <name1>, <name2>, ...
set dstaddr6-negate [enable|disable]
set dstintf <name1>, <name2>, ...
set dynamic-shaping [enable|disable]
set email-collect [enable|disable]
set emailfilter-profile {string}
set fec [enable|disable]
set file-filter-profile {string}
set firewall-session-dirty [check-all|check-new]
set fixedport [enable|disable]
set fsso-agent-for-ntlm {string}
set fsso-groups <name1>, <name2>, ...
set geoup-anycast [enable|disable]
set geoup-match [physical-location|registered-location]
set groups <name1>, <name2>, ...
set http-policy-redirect [enable|disable]
set icap-profile {string}
set identity-based-route {string}
set inbound [enable|disable]
set inspection-mode [proxy|flow]
set internet-service [enable|disable]
set internet-service-custom <name1>, <name2>, ...
set internet-service-custom-group <name1>, <name2>, ...
set internet-service-group <name1>, <name2>, ...
set internet-service-name <name1>, <name2>, ...
set internet-service-negate [enable|disable]
set internet-service-src [enable|disable]
set internet-service-src-custom <name1>, <name2>, ...
set internet-service-src-custom-group <name1>, <name2>, ...
set internet-service-src-group <name1>, <name2>, ...
set internet-service-src-name <name1>, <name2>, ...
```

```
set internet-service-src-negate [enable|disable]
set internet-service6 [enable|disable]
set internet-service6-custom <name1>, <name2>, ...
set internet-service6-custom-group <name1>, <name2>, ...
set internet-service6-group <name1>, <name2>, ...
set internet-service6-name <name1>, <name2>, ...
set internet-service6-negate [enable|disable]
set internet-service6-src [enable|disable]
set internet-service6-src-custom <name1>, <name2>, ...
set internet-service6-src-custom-group <name1>, <name2>, ...
set internet-service6-src-group <name1>, <name2>, ...
set internet-service6-src-name <name1>, <name2>, ...
set internet-service6-src-negate [enable|disable]
set ippool [enable|disable]
set ips-sensor {string}
set ips-voip-filter {string}
set logtraffic [all|utm|...]
set logtraffic-start [enable|disable]
set match-vip [enable|disable]
set match-vip-only [enable|disable]
set name {string}
set nat [enable|disable]
set nat46 [enable|disable]
set nat64 [enable|disable]
set natinbound [enable|disable]
set natip {ipv4-classnet}
set natoutbound [enable|disable]
set network-service-dynamic <name1>, <name2>, ...
set network-service-src-dynamic <name1>, <name2>, ...
set np-acceleration [enable|disable]
set ntlm [enable|disable]
set ntlm-enabled-browsers <user-agent-string1>, <user-agent-string2>, ...
set ntlm-guest [enable|disable]
set outbound [enable|disable]
set passive-wan-health-measurement [enable|disable]
set pcp-inbound [enable|disable]
set pcp-outbound [enable|disable]
set pcp-poolname <name1>, <name2>, ...
set per-ip-shaper {string}
set permit-any-host [enable|disable]
set permit-stun-host [enable|disable]
set policy-expiry [enable|disable]
set policy-expiry-date {datetime}
set policy-expiry-date-utc {user}
set poolname <name1>, <name2>, ...
set poolname6 <name1>, <name2>, ...
set port-preserve [enable|disable]
set profile-group {string}
set profile-protocol-options {string}
set profile-type [single|group]
set radius-mac-auth-bypass [enable|disable]
set redirect-url {var-string}
set replacemsg-override-group {string}
set reputation-direction [source|destination]
set reputation-direction6 [source|destination]
set reputation-minimum {integer}
```

```
set reputation-minimum6 {integer}
set rtp-addr <name1>, <name2>, ...
set rtp-nat [disable|enable]
set schedule {string}
set schedule-timeout [enable|disable]
set sctp-filter-profile {string}
set send-deny-packet [disable|enable]
set service <name1>, <name2>, ...
set service-negate [enable|disable]
set session-ttl {user}
set sgt <id1>, <id2>, ...
set sgt-check [enable|disable]
set src-vendor-mac <id1>, <id2>, ...
set srcaddr <name1>, <name2>, ...
set srcaddr-negate [enable|disable]
set srcaddr6 <name1>, <name2>, ...
set srcaddr6-negate [enable|disable]
set srcintf <name1>, <name2>, ...
set ssh-filter-profile {string}
set ssh-policy-redirect [enable|disable]
set ssl-ssh-profile {string}
set status [enable|disable]
set tcp-mss-receiver {integer}
set tcp-mss-sender {integer}
set tcp-session-without-syn [all|data-only|...]
set timeout-send-rst [enable|disable]
set tos {user}
set tos-mask {user}
set tos-negate [enable|disable]
set traffic-shaper {string}
set traffic-shaper-reverse {string}
set users <name1>, <name2>, ...
set utm-status [enable|disable]
set uuid {uuid}
set videofilter-profile {string}
set virtual-patch-profile {string}
set vlan-cos-fwd {integer}
set vlan-cos-rev {integer}
set vlan-filter {user}
set voip-profile {string}
set vpntunnel {string}
set waf-profile {string}
set wanopt [enable|disable]
set wanopt-detection [active|passive|...]
set wanopt-passive-opt [default|transparent|...]
set wanopt-peer {string}
set wanopt-profile {string}
set wccp [enable|disable]
set webcache [enable|disable]
set webcache-https [disable|enable]
set webfilter-profile {string}
set webproxy-forward-server {string}
set webproxy-profile {string}
set ztna-device-ownership [enable|disable]
set ztna-ems-tag <name1>, <name2>, ...
set ztna-ems-tag-secondary <name1>, <name2>, ...
```

```

set ztna-geo-tag <name1>, <name2>, ...
set ztna-policy-redirect [enable|disable]
set ztna-status [enable|disable]
set ztna-tags-match-logic [or|and]
next
end

```

config firewall policy

Parameter	Description	Type	Size	Default
action	Policy action (accept/deny/ipsec).	option	-	deny
	Option	Description		
	<i>accept</i>	Allows session that match the firewall policy.		
	<i>deny</i>	Blocks sessions that match the firewall policy.		
	<i>ipsec</i>	Firewall policy becomes a policy-based IPsec VPN policy.		
anti-replay	Enable/disable anti-replay check.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable anti-replay check.		
	<i>disable</i>	Disable anti-replay check.		
application-list	Name of an existing Application list.	string	Maximum length: 35	
auth-cert	HTTPS server certificate for policy authentication.	string	Maximum length: 35	
auth-path	Enable/disable authentication-based routing.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable authentication-based routing.		
	<i>disable</i>	Disable authentication-based routing.		
auth-redirect-addr	HTTP-to-HTTPS redirect address for firewall authentication.	string	Maximum length: 63	
auto-asic-offload *	Enable/disable policy traffic ASIC offloading.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable auto ASIC offloading.		
	<i>disable</i>	Disable ASIC offloading.		

Parameter	Description	Type	Size	Default						
av-profile	Name of an existing Antivirus profile.	string	Maximum length: 35							
block-notification	Enable/disable block notification.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
captive-portal-exempt	Enable to exempt some users from the captive portal.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable exemption of captive portal.</td></tr><tr><td><i>disable</i></td><td>Disable exemption of captive portal.</td></tr></table>	Option	Description	<i>enable</i>	Enable exemption of captive portal.	<i>disable</i>	Disable exemption of captive portal.			
Option	Description									
<i>enable</i>	Enable exemption of captive portal.									
<i>disable</i>	Disable exemption of captive portal.									
capture-packet *	Enable/disable capture packets.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable capture packets.</td></tr><tr><td><i>disable</i></td><td>Disable capture packets.</td></tr></table>	Option	Description	<i>enable</i>	Enable capture packets.	<i>disable</i>	Disable capture packets.			
Option	Description									
<i>enable</i>	Enable capture packets.									
<i>disable</i>	Disable capture packets.									
casb-profile	Name of an existing CASB profile.	string	Maximum length: 35							
cifs-profile	Name of an existing CIFS profile.	string	Maximum length: 35							
comments	Comment.	var-string	Maximum length: 1023							
custom-log-fields <field-id>	Custom fields to append to log messages for this policy. Custom log field.	string	Maximum length: 35							
decrypted-traffic-mirror	Decrypted traffic mirror.	string	Maximum length: 35							
delay-tcp-npu-session	Enable TCP NPU session delay to guarantee packet order of 3-way handshake.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable TCP NPU session delay in order to guarantee packet order of 3-way handshake.</td></tr></table>	Option	Description	<i>enable</i>	Enable TCP NPU session delay in order to guarantee packet order of 3-way handshake.					
Option	Description									
<i>enable</i>	Enable TCP NPU session delay in order to guarantee packet order of 3-way handshake.									

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>disable</i>	Disable TCP NPU session delay in order to guarantee packet order of 3-way handshake.		
diameter-filter-profile	Name of an existing Diameter filter profile.	string	Maximum length: 35	
diffserv-copy	Enable to copy packet's DiffServ values from session's original direction to its reply direction.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable DSCP copy.		
	<i>disable</i>	Disable DSCP copy.		
diffserv-forward	Enable to change packet's DiffServ values to the specified diffservcode-forward value.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting forward (original) traffic Diffserv.		
	<i>disable</i>	Disable setting forward (original) traffic Diffserv.		
diffserv-reverse	Enable to change packet's reverse (reply) DiffServ values to the specified diffservcode-rev value.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting reverse (reply) traffic DiffServ.		
	<i>disable</i>	Disable setting reverse (reply) traffic DiffServ.		
diffservcode-forward	Change packet's DiffServ to this value.	user	Not Specified	
diffservcode-rev	Change packet's reverse (reply) DiffServ to this value.	user	Not Specified	
disclaimer	Enable/disable user authentication disclaimer.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable user authentication disclaimer.		
	<i>disable</i>	Disable user authentication disclaimer.		

Parameter	Description	Type	Size	Default						
dlp-profile	Name of an existing DLP profile.	string	Maximum length: 35							
dnsfilter-profile	Name of an existing DNS filter profile.	string	Maximum length: 35							
dsri	Enable DSRI to ignore HTTP server responses.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable DSRI.</td></tr><tr><td>disable</td><td>Disable DSRI.</td></tr></table>	Option	Description	enable	Enable DSRI.	disable	Disable DSRI.			
Option	Description									
enable	Enable DSRI.									
disable	Disable DSRI.									
dstaddr <name>	Destination IPv4 address and address group names. Address name.	string	Maximum length: 79							
dstaddr-negate	When enabled dstaddr specifies what the destination address must NOT be.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable destination address negate.</td></tr><tr><td>disable</td><td>Disable destination address negate.</td></tr></table>	Option	Description	enable	Enable destination address negate.	disable	Disable destination address negate.			
Option	Description									
enable	Enable destination address negate.									
disable	Disable destination address negate.									
dstaddr6 <name>	Destination IPv6 address name and address group names. Address name.	string	Maximum length: 79							
dstaddr6-negate	When enabled dstaddr6 specifies what the destination address must NOT be.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable IPv6 destination address negate.</td></tr><tr><td>disable</td><td>Disable IPv6 destination address negate.</td></tr></table>	Option	Description	enable	Enable IPv6 destination address negate.	disable	Disable IPv6 destination address negate.			
Option	Description									
enable	Enable IPv6 destination address negate.									
disable	Disable IPv6 destination address negate.									
dstintf <name>	Outgoing (egress) interface. Interface name.	string	Maximum length: 79							
dynamic-shaping	Enable/disable dynamic RADIUS defined traffic shaping.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable dynamic RADIUS defined traffic shaping.</td></tr><tr><td>disable</td><td>Disable dynamic RADIUS defined traffic shaping.</td></tr></table>	Option	Description	enable	Enable dynamic RADIUS defined traffic shaping.	disable	Disable dynamic RADIUS defined traffic shaping.			
Option	Description									
enable	Enable dynamic RADIUS defined traffic shaping.									
disable	Disable dynamic RADIUS defined traffic shaping.									

Parameter	Description	Type	Size	Default
email-collect	Enable/disable email collection.	option	-	disable
	Option Description			
	<i>enable</i>	Enable email collection.		
	<i>disable</i>	Disable email collection.		
emailfilter-profile	Name of an existing email filter profile.	string	Maximum length: 35	
fec	Enable/disable Forward Error Correction on traffic matching this policy on a FEC device.	option	-	disable
	Option Description			
	<i>enable</i>	Enable Forward Error Correction.		
	<i>disable</i>	Disable Forward Error Correction.		
file-filter-profile	Name of an existing file-filter profile.	string	Maximum length: 35	
firewall-session-dirty	How to handle sessions if the configuration of this firewall policy changes.	option	-	check-all
	Option Description			
	<i>check-all</i>	Flush all current sessions accepted by this policy. These sessions must be started and re-matched with policies.		
	<i>check-new</i>	Continue to allow sessions already accepted by this policy.		
fixedport	Enable to prevent source NAT from changing a session's source port.	option	-	disable
	Option Description			
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
fsso-agent-for-ntlm	FSSO agent to use for NTLM authentication.	string	Maximum length: 35	
fsso-groups <name>	Names of FSSO groups. Names of FSSO groups.	string	Maximum length: 511	
geoip-anycast	Enable/disable recognition of anycast IP addresses using the geography IP database.	option	-	disable

Parameter	Description	Type	Size	Default
	Option Description			
	<i>enable</i>	Enable recognition of anycast IP addresses using the geography IP database.		
	<i>disable</i>	Disable recognition of anycast IP addresses using the geography IP database.		
geoip-match	Match geography address based either on its physical location or registered location.	option	-	physical-location
	Option Description			
	<i>physical-location</i>	Match geography address to its physical location using the geography IP database.		
	<i>registered-location</i>	Match geography address to its registered location using the geography IP database.		
groups <name>	Names of user groups that can authenticate with this policy. Group name.	string	Maximum length: 79	
http-policy-redirect	Redirect HTTP(S) traffic to matching transparent web proxy policy.	option	-	disable
	Option Description			
	<i>enable</i>	Enable HTTP(S) policy redirect.		
	<i>disable</i>	Disable HTTP(S) policy redirect.		
icap-profile	Name of an existing ICAP profile.	string	Maximum length: 35	
identity-based-route	Name of identity-based routing rule.	string	Maximum length: 35	
inbound	Policy-based IPsec VPN: only traffic from the remote network can initiate a VPN.	option	-	disable
	Option Description			
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
inspection-mode	Policy inspection mode (Flow/proxy). Default is Flow mode.	option	-	flow

Parameter	Description	Type	Size	Default
	Option Description			
	<i>proxy</i>	Proxy based inspection.		
	<i>flow</i>	Flow based inspection.		
internet-service	Enable/disable use of Internet Services for this policy. If enabled, destination address and service are not used.	option	-	disable
	Option Description			
	<i>enable</i>	Enable use of Internet Services in policy.		
	<i>disable</i>	Disable use of Internet Services in policy.		
internet-service-custom <name>	Custom Internet Service name. Custom Internet Service name.	string	Maximum length: 79	
internet-service-custom-group <name>	Custom Internet Service group name. Custom Internet Service group name.	string	Maximum length: 79	
internet-service-group <name>	Internet Service group name. Internet Service group name.	string	Maximum length: 79	
internet-service-name <name>	Internet Service name. Internet Service name.	string	Maximum length: 79	
internet-service-negate	When enabled internet-service specifies what the service must NOT be.	option	-	disable
	Option Description			
	<i>enable</i>	Enable negated Internet Service match.		
	<i>disable</i>	Disable negated Internet Service match.		
internet-service-src	Enable/disable use of Internet Services in source for this policy. If enabled, source address is not used.	option	-	disable
	Option Description			
	<i>enable</i>	Enable use of Internet Services source in policy.		
	<i>disable</i>	Disable use of Internet Services source in policy.		
internet-service-src-custom <name>	Custom Internet Service source name. Custom Internet Service name.	string	Maximum length: 79	

Parameter	Description	Type	Size	Default						
internet-service-src-custom-group <name>	Custom Internet Service source group name. Custom Internet Service group name.	string	Maximum length: 79							
internet-service-src-group <name>	Internet Service source group name. Internet Service group name.	string	Maximum length: 79							
internet-service-src-name <name>	Internet Service source name. Internet Service name.	string	Maximum length: 79							
internet-service-src-negate	When enabled internet-service-src specifies what the service must NOT be.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable negated Internet Service source match.</td></tr><tr><td>disable</td><td>Disable negated Internet Service source match.</td></tr></table>	Option	Description	enable	Enable negated Internet Service source match.	disable	Disable negated Internet Service source match.			
Option	Description									
enable	Enable negated Internet Service source match.									
disable	Disable negated Internet Service source match.									
internet-service6	Enable/disable use of IPv6 Internet Services for this policy. If enabled, destination address and service are not used.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable use of IPv6 Internet Services in policy.</td></tr><tr><td>disable</td><td>Disable use of IPv6 Internet Services in policy.</td></tr></table>	Option	Description	enable	Enable use of IPv6 Internet Services in policy.	disable	Disable use of IPv6 Internet Services in policy.			
Option	Description									
enable	Enable use of IPv6 Internet Services in policy.									
disable	Disable use of IPv6 Internet Services in policy.									
internet-service6-custom <name>	Custom IPv6 Internet Service name. Custom Internet Service name.	string	Maximum length: 79							
internet-service6-custom-group <name>	Custom Internet Service6 group name. Custom Internet Service6 group name.	string	Maximum length: 79							
internet-service6-group <name>	Internet Service group name. Internet Service group name.	string	Maximum length: 79							
internet-service6-name <name>	IPv6 Internet Service name. IPv6 Internet Service name.	string	Maximum length: 79							
internet-service6-negate	When enabled internet-service6 specifies what the service must NOT be.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option Description			
	<i>enable</i>	Enable negated IPv6 Internet Service match.		
	<i>disable</i>	Disable negated IPv6 Internet Service match.		
internet-service6-src	Enable/disable use of IPv6 Internet Services in source for this policy. If enabled, source address is not used.	option	-	disable
	Option Description			
	<i>enable</i>	Enable use of IPv6 Internet Services source in policy.		
	<i>disable</i>	Disable use of IPv6 Internet Services source in policy.		
internet-service6-src-custom <name>	Custom IPv6 Internet Service source name. Custom Internet Service name.	string	Maximum length: 79	
internet-service6-src-custom-group <name>	Custom Internet Service6 source group name. Custom Internet Service6 group name.	string	Maximum length: 79	
internet-service6-src-group <name>	Internet Service6 source group name. Internet Service group name.	string	Maximum length: 79	
internet-service6-src-name <name>	IPv6 Internet Service source name. Internet Service name.	string	Maximum length: 79	
internet-service6-src-negate	When enabled internet-service6-src specifies what the service must NOT be.	option	-	disable
	Option Description			
	<i>enable</i>	Enable negated IPv6 Internet Service source match.		
	<i>disable</i>	Disable negated IPv6 Internet Service source match.		
ippool	Enable to use IP Pools for source NAT.	option	-	disable
	Option Description			
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		

Parameter	Description	Type	Size	Default								
ips-sensor	Name of an existing IPS sensor.	string	Maximum length: 35									
ips-voip-filter	Name of an existing VoIP (ips) profile.	string	Maximum length: 35									
logtraffic	Enable or disable logging. Log all sessions or security profile sessions.	option	-	utm								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>all</i></td><td>Log all sessions accepted or denied by this policy.</td></tr><tr><td><i>utm</i></td><td>Log traffic that has a security profile applied to it.</td></tr><tr><td><i>disable</i></td><td>Disable all logging for this policy.</td></tr></table>	Option	Description	<i>all</i>	Log all sessions accepted or denied by this policy.	<i>utm</i>	Log traffic that has a security profile applied to it.	<i>disable</i>	Disable all logging for this policy.			
Option	Description											
<i>all</i>	Log all sessions accepted or denied by this policy.											
<i>utm</i>	Log traffic that has a security profile applied to it.											
<i>disable</i>	Disable all logging for this policy.											
logtraffic-start	Record logs when a session starts.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.					
Option	Description											
<i>enable</i>	Enable setting.											
<i>disable</i>	Disable setting.											
match-vip	Enable to match packets that have had their destination addresses changed by a VIP.	option	-	enable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Match DNATed packet.</td></tr><tr><td><i>disable</i></td><td>Do not match DNATed packet.</td></tr></table>	Option	Description	<i>enable</i>	Match DNATed packet.	<i>disable</i>	Do not match DNATed packet.					
Option	Description											
<i>enable</i>	Match DNATed packet.											
<i>disable</i>	Do not match DNATed packet.											
match-vip-only	Enable/disable matching of only those packets that have had their destination addresses changed by a VIP.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable matching of only those packets that have had their destination addresses changed by a VIP.</td></tr><tr><td><i>disable</i></td><td>Disable matching of only those packets that have had their destination addresses changed by a VIP.</td></tr></table>	Option	Description	<i>enable</i>	Enable matching of only those packets that have had their destination addresses changed by a VIP.	<i>disable</i>	Disable matching of only those packets that have had their destination addresses changed by a VIP.					
Option	Description											
<i>enable</i>	Enable matching of only those packets that have had their destination addresses changed by a VIP.											
<i>disable</i>	Disable matching of only those packets that have had their destination addresses changed by a VIP.											
name	Policy name.	string	Maximum length: 35									
nat	Enable/disable source NAT.	option	-	disable								

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
nat46	Enable/disable NAT46.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable NAT46.		
	<i>disable</i>	Disable NAT46.		
nat64	Enable/disable NAT64.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable NAT64.		
	<i>disable</i>	Disable NAT64.		
natinbound	Policy-based IPsec VPN: apply destination NAT to inbound traffic.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
natip	Policy-based IPsec VPN: source NAT IP address for outgoing traffic.	ipv4-classnet	Not Specified	0.0.0.0 0.0.0.0
natoutbound	Policy-based IPsec VPN: apply source NAT to outbound traffic.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
network-service-dynamic <name>	Dynamic Network Service name. Dynamic Network Service name.	string	Maximum length: 79	
network-service-src-dynamic <name>	Dynamic Network Service source name. Dynamic Network Service name.	string	Maximum length: 79	

Parameter	Description	Type	Size	Default						
np-acceleration *	Enable/disable UTM Network Processor acceleration.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable UTM Network Processor acceleration.</td></tr><tr><td><i>disable</i></td><td>Disable UTM Network Processor acceleration.</td></tr></table>	Option	Description	<i>enable</i>	Enable UTM Network Processor acceleration.	<i>disable</i>	Disable UTM Network Processor acceleration.			
Option	Description									
<i>enable</i>	Enable UTM Network Processor acceleration.									
<i>disable</i>	Disable UTM Network Processor acceleration.									
ntlm	Enable/disable NTLM authentication.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
ntlm-enabled-browsers <user-agent-string>	HTTP-User-Agent value of supported browsers. User agent string.	string	Maximum length: 79							
ntlm-guest	Enable/disable NTLM guest user access.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
outbound	Policy-based IPsec VPN: only traffic from the internal network can initiate a VPN.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
passive-wan-health-measurement	Enable/disable passive WAN health measurement. When enabled, auto-asic-offload is disabled.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable Passive WAN health measurement.</td></tr><tr><td><i>disable</i></td><td>Disable Passive WAN health measurement.</td></tr></table>	Option	Description	<i>enable</i>	Enable Passive WAN health measurement.	<i>disable</i>	Disable Passive WAN health measurement.			
Option	Description									
<i>enable</i>	Enable Passive WAN health measurement.									
<i>disable</i>	Disable Passive WAN health measurement.									
pcp-inbound	Enable/disable PCP inbound DNAT.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable PCP inbound DNAT.		
	<i>disable</i>	Disable PCP inbound DNAT.		
pcp-outbound	Enable/disable PCP outbound SNAT.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable PCP outbound SNAT.		
	<i>disable</i>	Disable PCP outbound SNAT.		
pcp-poolname <name>	PCP pool names. PCP pool name.	string	Maximum length: 79	
per-ip-shaper	Per-IP traffic shaper.	string	Maximum length: 35	
permit-any-host	Accept UDP packets from any host.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
permit-stun-host	Accept UDP packets from any Session Traversal Utilities for NAT (STUN) host.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
policy-expiry	Enable/disable policy expiry.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable policy expiry.		
	<i>disable</i>	Disable policy expiry.		
policy-expiry-date	Policy expiry date (YYYY-MM-DD HH:MM:SS).	datetime	Not Specified	0000-00-00 00:00:00
policy-expiry-date-utc	Policy expiry date and time, in epoch format.	user	Not Specified	

Parameter	Description	Type	Size	Default						
policyid	Policy ID.	integer	Minimum value: 0 Maximum value: 4294967294	0						
poolname <name>	IP Pool names. IP pool name.	string	Maximum length: 79							
poolname6 <name>	IPv6 pool names. IPv6 pool name.	string	Maximum length: 79							
port-preserve	Enable/disable preservation of the original source port from source NAT if it has not been used.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Use the original source port if it has not been used.</td></tr><tr><td>disable</td><td>Source NAT always changes the source port.</td></tr></table>				Option	Description	enable	Use the original source port if it has not been used.	disable	Source NAT always changes the source port.
Option	Description									
enable	Use the original source port if it has not been used.									
disable	Source NAT always changes the source port.									
profile-group	Name of profile group.	string	Maximum length: 35							
profile-protocol-options	Name of an existing Protocol options profile.	string	Maximum length: 35	default						
profile-type	Determine whether the firewall policy allows security profile groups or single profiles only.	option	-	single						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>single</td><td>Do not allow security profile groups.</td></tr><tr><td>group</td><td>Allow security profile groups.</td></tr></table>				Option	Description	single	Do not allow security profile groups.	group	Allow security profile groups.
Option	Description									
single	Do not allow security profile groups.									
group	Allow security profile groups.									
radius-mac-auth-bypass	Enable MAC authentication bypass. The bypassed MAC address must be received from RADIUS server.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable MAC authentication bypass.</td></tr><tr><td>disable</td><td>Disable MAC authentication bypass.</td></tr></table>				Option	Description	enable	Enable MAC authentication bypass.	disable	Disable MAC authentication bypass.
Option	Description									
enable	Enable MAC authentication bypass.									
disable	Disable MAC authentication bypass.									
redirect-url	URL users are directed to after seeing and accepting the disclaimer or authenticating.	var-string	Maximum length: 1023							
replacemsg-override-group	Override the default replacement message group for this policy.	string	Maximum length: 35							

Parameter	Description	Type	Size	Default
reputation-direction	Direction of the initial traffic for reputation to take effect.	option	-	destination
	Option Description			
	<i>source</i>	Check reputation for source address.		
	<i>destination</i>	Check reputation for destination address.		
reputation-direction6	Direction of the initial traffic for IPv6 reputation to take effect.	option	-	destination
	Option Description			
	<i>source</i>	Check reputation for IPv6 source address.		
	<i>destination</i>	Check reputation for IPv6 destination address.		
reputation-minimum	Minimum Reputation to take action.	integer	Minimum value: 0 Maximum value: 4294967295	0
reputation-minimum6	IPv6 Minimum Reputation to take action.	integer	Minimum value: 0 Maximum value: 4294967295	0
rtp-addr <name>	Address names if this is an RTP NAT policy. Address name.	string	Maximum length: 79	
rtp-nat	Enable Real Time Protocol (RTP) NAT.	option	-	disable
	Option Description			
	<i>disable</i>	Disable setting.		
	<i>enable</i>	Enable setting.		
schedule	Schedule name.	string	Maximum length: 35	
schedule-timeout	Enable to force current sessions to end when the schedule object times out. Disable allows them to end from inactivity.	option	-	disable
	Option Description			
	<i>enable</i>	Enable schedule timeout.		
	<i>disable</i>	Disable schedule timeout.		

Parameter	Description	Type	Size	Default						
sctp-filter-profile	Name of an existing SCTP filter profile.	string	Maximum length: 35							
send-deny-packet	Enable to send a reply when a session is denied or blocked by a firewall policy.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable deny-packet sending.</td></tr><tr><td>enable</td><td>Enable deny-packet sending.</td></tr></table>				Option	Description	disable	Disable deny-packet sending.	enable	Enable deny-packet sending.
Option	Description									
disable	Disable deny-packet sending.									
enable	Enable deny-packet sending.									
service <name>	Service and service group names. Service and service group names.	string	Maximum length: 79							
service-negate	When enabled service specifies what the service must NOT be.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable negated service match.</td></tr><tr><td>disable</td><td>Disable negated service match.</td></tr></table>				Option	Description	enable	Enable negated service match.	disable	Disable negated service match.
Option	Description									
enable	Enable negated service match.									
disable	Disable negated service match.									
session-ttl	TTL in seconds for sessions accepted by this policy.	user	Not Specified							
sgt <id>	Security group tags. Security group tag (1 - 65535).	integer	Minimum value: 1 Maximum value: 65535							
sgt-check	Enable/disable security group tags (SGT) check.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable SGT check.</td></tr><tr><td>disable</td><td>Disable SGT check.</td></tr></table>				Option	Description	enable	Enable SGT check.	disable	Disable SGT check.
Option	Description									
enable	Enable SGT check.									
disable	Disable SGT check.									
src-vendor-mac <id>	Vendor MAC source ID. Vendor MAC ID.	integer	Minimum value: 0 Maximum value: 4294967295							
srcaddr <name>	Source IPv4 address and address group names. Address name.	string	Maximum length: 79							

Parameter	Description	Type	Size	Default
srcaddr-negate	When enabled srcaddr specifies what the source address must NOT be.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable source address negate.		
	<i>disable</i>	Disable source address negate.		
srcaddr6 <name>	Source IPv6 address name and address group names. Address name.	string	Maximum length: 79	
srcaddr6-negate	When enabled srcaddr6 specifies what the source address must NOT be.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable IPv6 source address negate.		
	<i>disable</i>	Disable IPv6 source address negate.		
srcintf <name>	Incoming (ingress) interface. Interface name.	string	Maximum length: 79	
ssh-filter-profile	Name of an existing SSH filter profile.	string	Maximum length: 35	
ssh-policy-redirect	Redirect SSH traffic to matching transparent proxy policy.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable SSH policy redirect.		
	<i>disable</i>	Disable SSH policy redirect.		
ssl-ssh-profile	Name of an existing SSL SSH profile.	string	Maximum length: 35	no-inspection
status	Enable or disable this policy.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
tcp-mss-receiver	Receiver TCP maximum segment size (MSS).	integer	Minimum value: 0 Maximum value: 65535	0

Parameter	Description	Type	Size	Default								
tcp-mss-sender	Sender TCP maximum segment size (MSS).	integer	Minimum value: 0 Maximum value: 65535	0								
tcp-session-without-syn	Enable/disable creation of TCP session without SYN flag.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>all</i></td><td>Enable TCP session without SYN.</td></tr><tr><td><i>data-only</i></td><td>Enable TCP session data only.</td></tr><tr><td><i>disable</i></td><td>Disable TCP session without SYN.</td></tr></table>	Option	Description	<i>all</i>	Enable TCP session without SYN.	<i>data-only</i>	Enable TCP session data only.	<i>disable</i>	Disable TCP session without SYN.			
Option	Description											
<i>all</i>	Enable TCP session without SYN.											
<i>data-only</i>	Enable TCP session data only.											
<i>disable</i>	Disable TCP session without SYN.											
timeout-send-rst	Enable/disable sending RST packets when TCP sessions expire.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable sending of RST packet upon TCP session expiration.</td></tr><tr><td><i>disable</i></td><td>Disable sending of RST packet upon TCP session expiration.</td></tr></table>	Option	Description	<i>enable</i>	Enable sending of RST packet upon TCP session expiration.	<i>disable</i>	Disable sending of RST packet upon TCP session expiration.					
Option	Description											
<i>enable</i>	Enable sending of RST packet upon TCP session expiration.											
<i>disable</i>	Disable sending of RST packet upon TCP session expiration.											
tos	ToS (Type of Service) value used for comparison.	user	Not Specified									
tos-mask	Non-zero bit positions are used for comparison while zero bit positions are ignored.	user	Not Specified									
tos-negate	Enable negated TOS match.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable TOS match negate.</td></tr><tr><td><i>disable</i></td><td>Disable TOS match negate.</td></tr></table>	Option	Description	<i>enable</i>	Enable TOS match negate.	<i>disable</i>	Disable TOS match negate.					
Option	Description											
<i>enable</i>	Enable TOS match negate.											
<i>disable</i>	Disable TOS match negate.											
traffic-shaper	Traffic shaper.	string	Maximum length: 35									
traffic-shaper-reverse	Reverse traffic shaper.	string	Maximum length: 35									
users <name>	Names of individual users that can authenticate with this policy. Names of individual users that can authenticate with this policy.	string	Maximum length: 79									
utm-status	Enable to add one or more security profiles (AV, IPS, etc.) to the firewall policy.	option	-	disable								

Parameter	Description	Type	Size	Default
	Option	Description		
	enable	Enable setting.		
	disable	Disable setting.		
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000
videofilter-profile	Name of an existing VideoFilter profile.	string	Maximum length: 35	
virtual-patch-profile	Name of an existing virtual-patch profile.	string	Maximum length: 35	
vlan-cos-fwd	VLAN forward direction user priority: 255 passthrough, 0 lowest, 7 highest.	integer	Minimum value: 0 Maximum value: 7	255
vlan-cos-rev	VLAN reverse direction user priority: 255 passthrough, 0 lowest, 7 highest.	integer	Minimum value: 0 Maximum value: 7	255
vlan-filter	VLAN ranges to allow	user	Not Specified	
voip-profile	Name of an existing VoIP (voipd) profile.	string	Maximum length: 35	
vpntunnel	Policy-based IPsec VPN: name of the IPsec VPN Phase 1.	string	Maximum length: 35	
waf-profile	Name of an existing Web application firewall profile.	string	Maximum length: 35	
wanopt *	Enable/disable WAN optimization.	option	-	disable
	Option	Description		
	enable	Enable setting.		
	disable	Disable setting.		
wanopt-detection *	WAN optimization auto-detection mode.	option	-	active
	Option	Description		
	active	Active WAN optimization peer auto-detection.		

Parameter	Description	Type	Size	Default
	Option Description			
	<i>passive</i>	Passive WAN optimization peer auto-detection.		
	<i>off</i>	Turn off WAN optimization peer auto-detection.		
wanopt-passive-opt *	WAN optimization passive mode options. This option decides what IP address will be used to connect server.	option	-	default
	Option Description			
	<i>default</i>	Allow client side WAN opt peer to decide.		
	<i>transparent</i>	Use address of client to connect to server.		
	<i>non-transparent</i>	Use local FortiGate address to connect to server.		
wanopt-peer *	WAN optimization peer.	string	Maximum length: 35	
wanopt-profile *	WAN optimization profile.	string	Maximum length: 35	
wccp	Enable/disable forwarding traffic matching this policy to a configured WCCP server.	option	-	disable
	Option Description			
	<i>enable</i>	Enable WCCP setting.		
	<i>disable</i>	Disable WCCP setting.		
webcache *	Enable/disable web cache.	option	-	disable
	Option Description			
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
webcache-https *	Enable/disable web cache for HTTPS.	option	-	disable
	Option Description			
	<i>disable</i>	Disable web cache for HTTPS.		
	<i>enable</i>	Enable web cache for HTTPS.		
webfilter-profile	Name of an existing Web filter profile.	string	Maximum length: 35	

Parameter	Description	Type	Size	Default
webproxy-forward-server	Webproxy forward server name.	string	Maximum length: 63	
webproxy-profile	Webproxy profile name.	string	Maximum length: 63	
ztna-device-ownership	Enable/disable zero trust device ownership.	option	-	disable
	Option		Description	
	<i>enable</i>		Enable ZTNA device ownership check.	
	<i>disable</i>		Disable ZTNA device ownership check.	
ztna-ems-tag <name>	Source ztna-ems-tag names. Address name.	string	Maximum length: 79	
ztna-ems-tag-secondary <name>	Source ztna-ems-tag-secondary names. Address name.	string	Maximum length: 79	
ztna-geo-tag <name>	Source ztna-geo-tag names. Address name.	string	Maximum length: 79	
ztna-policy-redirect	Redirect ZTNA traffic to matching Access-Proxy proxy-policy.	option	-	disable
	Option		Description	
	<i>enable</i>		Enable ZTNA proxy-policy redirect.	
	<i>disable</i>		Disable ZTNA proxy-policy redirect.	
ztna-status	Enable/disable zero trust access.	option	-	disable
	Option		Description	
	<i>enable</i>		Enable zero trust network access.	
	<i>disable</i>		Disable zero trust network access.	
ztna-tags-match-logic	ZTNA tag matching logic.	option	-	or
	Option		Description	
	<i>or</i>		Match ZTNA tags using a logical OR operator.	
	<i>and</i>		Match ZTNA tags using a logical AND operator.	

* This parameter may not exist in some models.