

Parameter	Description	Type	Size	Default
ztna-ems-tag <name>	ZTNA EMS Tag names. EMS Tag name.	string	Maximum length: 79	
ztna-tags- match-logic	ZTNA tag matching logic.	option	-	or
		Option	Description	
		or	Match ZTNA tags using a logical OR operator.	
		and	Match ZTNA tags using a logical AND operator.	

* This parameter may not exist in some models.

config firewall region

Define region table. Read-only.

```
config firewall region
    Description: Define region table. Read-only.
    edit <id>
        set city <id1>, <id2>, ...
        set name {string}
    next
end
```

config firewall region

Parameter	Description	Type	Size	Default
city <id>	City ID list. City ID.	integer	Minimum value: 0 Maximum value: 65535	
id	Region ID.	integer	Minimum value: 0 Maximum value: 65535	0
name	Region name.	string	Maximum length: 63	

config firewall schedule group

Schedule group configuration.

```

config firewall schedule group
    Description: Schedule group configuration.
    edit <name>
        set color {integer}
        set fabric-object [enable|disable]
        set member <name1>, <name2>, ...
    next
end

```

config firewall schedule group

Parameter	Description	Type	Size	Default						
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0						
fabric-object	Security Fabric global object setting.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Object is set as a security fabric-wide global object.</td></tr><tr><td><i>disable</i></td><td>Object is local to this security fabric member.</td></tr></table>				Option	Description	<i>enable</i>	Object is set as a security fabric-wide global object.	<i>disable</i>	Object is local to this security fabric member.
Option	Description									
<i>enable</i>	Object is set as a security fabric-wide global object.									
<i>disable</i>	Object is local to this security fabric member.									
member <name>	Schedules added to the schedule group. Schedule name.	string	Maximum length: 79							
name	Schedule group name.	string	Maximum length: 31							

config firewall schedule onetime

Onetime schedule configuration.

```

config firewall schedule onetime
    Description: Onetime schedule configuration.
    edit <name>
        set color {integer}
        set end {user}
        set end-utc {user}
        set expiration-days {integer}
        set fabric-object [enable|disable]
        set start {user}
        set start-utc {user}
    next
end

```

config firewall schedule onetime

Parameter	Description	Type	Size	Default
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0
end	Schedule end date and time, format hh:mm yyyy/mm/dd.	user	Not Specified	
end-utc	Schedule end date and time, in epoch format.	user	Not Specified	
expiration-days	Write an event log message this many days before the schedule expires.	integer	Minimum value: 0 Maximum value: 100	3
fabric-object	Security Fabric global object setting.	option	-	disable
	Option	Description		
	<i>enable</i>	Object is set as a security fabric-wide global object.		
	<i>disable</i>	Object is local to this security fabric member.		
name	Onetime schedule name.	string	Maximum length: 31	
start	Schedule start date and time, format hh:mm yyyy/mm/dd.	user	Not Specified	
start-utc	Schedule start date and time, in epoch format.	user	Not Specified	

config firewall schedule recurring

Recurring schedule configuration.

```
config firewall schedule recurring
  Description: Recurring schedule configuration.
  edit <name>
    set color {integer}
    set day {option1}, {option2}, ...
    set end {user}
    set fabric-object [enable|disable]
    set start {user}
  next
end
```

config firewall schedule recurring

Parameter	Description	Type	Size	Default
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0
day	One or more days of the week on which the schedule is valid. Separate the names of the days with a space.	option	-	none
	Option Description			
	<i>sunday</i>	Sunday.		
	<i>monday</i>	Monday.		
	<i>tuesday</i>	Tuesday.		
	<i>wednesday</i>	Wednesday.		
	<i>thursday</i>	Thursday.		
	<i>friday</i>	Friday.		
	<i>saturday</i>	Saturday.		
	<i>none</i>	None.		
end	Time of day to end the schedule, format hh:mm.	user	Not Specified	
fabric-object	Security Fabric global object setting.	option	-	disable
	Option Description			
	<i>enable</i>	Object is set as a security fabric-wide global object.		
	<i>disable</i>	Object is local to this security fabric member.		
name	Recurring schedule name.	string	Maximum length: 31	
start	Time of day to start the schedule, format hh:mm.	user	Not Specified	

config firewall security-policy

Configure NGFW IPv4/IPv6 application policies.

```
config firewall security-policy
  Description: Configure NGFW IPv4/IPv6 application policies.
  edit <policyid>
    set action [accept|deny]
    set app-category <id1>, <id2>, ...
```