

Parameter	Description	Type	Size	Default
status	Enable or disable this policy.	option	-	enable
	Option	Description		
	enable	Enable setting.		
	disable	Disable setting.		
url-category	URL categories or groups.	user	Not Specified	
users <name>	Names of individual users that can authenticate with this policy. User name.	string	Maximum length: 79	
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000
videofilter-profile	Name of an existing VideoFilter profile.	string	Maximum length: 35	
virtual-patch-profile	Name of an existing virtual-patch profile.	string	Maximum length: 35	
voip-profile	Name of an existing VoIP (voipd) profile.	string	Maximum length: 35	
webfilter-profile	Name of an existing Web filter profile.	string	Maximum length: 35	

config firewall service category

Configure service categories.

```
config firewall service category
    Description: Configure service categories.
    edit <name>
        set comment {var-string}
        set fabric-object [enable|disable]
    next
end
```

config firewall service category

Parameter	Description	Type	Size	Default
comment	Comment.	var-string	Maximum length: 255	
fabric-object	Security Fabric global object setting.	option	-	disable

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Object is set as a security fabric-wide global object.		
	<i>disable</i>	Object is local to this security fabric member.		
name	Service category name.	string	Maximum length: 63	

config firewall service custom

Configure custom services.

```
config firewall service custom
  Description: Configure custom services.
  edit <name>
    set app-category <id1>, <id2>, ...
    set app-service-type [disable|app-id|...]
    set application <id1>, <id2>, ...
    set category {string}
    set check-reset-range [disable|strict|...]
    set color {integer}
    set comment {var-string}
    set fabric-object [enable|disable]
    set fqdn {string}
    set helper [auto|disable|...]
    set icmpcode {integer}
    set icmptype {integer}
    set iprange {user}
    set protocol [TCP/UDP/SCTP/ICMP|...]
    set protocol-number {integer}
    set proxy [enable|disable]
    set sctp-portrange {user}
    set session-ttl {user}
    set tcp-halfclose-timer {integer}
    set tcp-halfopen-timer {integer}
    set tcp-portrange {user}
    set tcp-rst-timer {integer}
    set tcp-timewait-timer {integer}
    set udp-idle-timer {integer}
    set udp-portrange {user}
    set uuid {uuid}
  next
end
```

config firewall service custom

Parameter	Description	Type	Size	Default								
app-category <id>	Application category ID. Application category id.	integer	Minimum value: 0 Maximum value: 4294967295									
app-service-type	Application service type.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable application type.</td></tr><tr><td>app-id</td><td>Application ID.</td></tr><tr><td>app-category</td><td>Applicatin category.</td></tr></table>	Option	Description	disable	Disable application type.	app-id	Application ID.	app-category	Applicatin category.			
Option	Description											
disable	Disable application type.											
app-id	Application ID.											
app-category	Applicatin category.											
application <id>	Application ID. Application id.	integer	Minimum value: 0 Maximum value: 4294967295									
category	Service category.	string	Maximum length: 63									
check-reset-range	Configure the type of ICMP error message verification.	option	-	default								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable RST range check.</td></tr><tr><td>strict</td><td>Check RST range strictly.</td></tr><tr><td>default</td><td>Using system default setting.</td></tr></table>	Option	Description	disable	Disable RST range check.	strict	Check RST range strictly.	default	Using system default setting.			
Option	Description											
disable	Disable RST range check.											
strict	Check RST range strictly.											
default	Using system default setting.											
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0								
comment	Comment.	var-string	Maximum length: 255									
fabric-object	Security Fabric global object setting.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Object is set as a security fabric-wide global object.</td></tr><tr><td>disable</td><td>Object is local to this security fabric member.</td></tr></table>	Option	Description	enable	Object is set as a security fabric-wide global object.	disable	Object is local to this security fabric member.					
Option	Description											
enable	Object is set as a security fabric-wide global object.											
disable	Object is local to this security fabric member.											

Parameter	Description	Type	Size	Default
fqdn	Fully qualified domain name.	string	Maximum length: 255	
helper	Helper name.	option	-	auto
	Option	Description		
	<i>auto</i>	Automatically select helper based on protocol and port.		
	<i>disable</i>	Disable helper.		
	<i>ftp</i>	FTP.		
	<i>tftp</i>	TFTP.		
	<i>ras</i>	RAS.		
	<i>h323</i>	H323.		
	<i>tns</i>	TNS.		
	<i>mms</i>	MMS.		
	<i>sip</i>	SIP.		
	<i>pptp</i>	PPTP.		
	<i>rtsp</i>	RTSP.		
	<i>dns-udp</i>	DNS UDP.		
	<i>dns-tcp</i>	DNS TCP.		
	<i>pmap</i>	PMAP.		
	<i>rsh</i>	RSH.		
	<i>dcerpc</i>	DCERPC.		
	<i>mgcp</i>	MGCP.		
	icmpcode	ICMP code.	integer	Minimum value: 0 Maximum value: 255
icmptype	ICMP type.	integer	Minimum value: 0 Maximum value: 4294967295	
iprange	Start and end of the IP range associated with service.	user	Not Specified	

Parameter	Description	Type	Size	Default																						
name	Custom service name.	string	Maximum length: 79																							
protocol	Protocol type based on IANA numbers.	option	-	TCP/UDP/SCTP																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>TCP/UDP/SCTP</i></td><td>TCP, UDP and SCTP.</td></tr><tr><td><i>ICMP</i></td><td>ICMP.</td></tr><tr><td><i>ICMP6</i></td><td>ICMP6.</td></tr><tr><td><i>IP</i></td><td>IP.</td></tr><tr><td><i>HTTP</i></td><td>HTTP - for web proxy.</td></tr><tr><td><i>FTP</i></td><td>FTP - for web proxy.</td></tr><tr><td><i>CONNECT</i></td><td>Connect - for web proxy.</td></tr><tr><td><i>SOCKS-TCP</i></td><td>Socks TCP - for web proxy.</td></tr><tr><td><i>SOCKS-UDP</i></td><td>Socks UDP - for web proxy.</td></tr><tr><td><i>ALL</i></td><td>All - for web proxy.</td></tr></table>	Option	Description	<i>TCP/UDP/SCTP</i>	TCP, UDP and SCTP.	<i>ICMP</i>	ICMP.	<i>ICMP6</i>	ICMP6.	<i>IP</i>	IP.	<i>HTTP</i>	HTTP - for web proxy.	<i>FTP</i>	FTP - for web proxy.	<i>CONNECT</i>	Connect - for web proxy.	<i>SOCKS-TCP</i>	Socks TCP - for web proxy.	<i>SOCKS-UDP</i>	Socks UDP - for web proxy.	<i>ALL</i>	All - for web proxy.			
	Option	Description																								
	<i>TCP/UDP/SCTP</i>	TCP, UDP and SCTP.																								
	<i>ICMP</i>	ICMP.																								
	<i>ICMP6</i>	ICMP6.																								
	<i>IP</i>	IP.																								
	<i>HTTP</i>	HTTP - for web proxy.																								
	<i>FTP</i>	FTP - for web proxy.																								
	<i>CONNECT</i>	Connect - for web proxy.																								
	<i>SOCKS-TCP</i>	Socks TCP - for web proxy.																								
	<i>SOCKS-UDP</i>	Socks UDP - for web proxy.																								
<i>ALL</i>	All - for web proxy.																									
protocol-number	IP protocol number.	integer	Minimum value: 0 Maximum value: 254	0																						
proxy	Enable/disable web proxy service.	option	-	disable																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.																			
	Option	Description																								
	<i>enable</i>	Enable setting.																								
<i>disable</i>	Disable setting.																									
sctp-portrange	Multiple SCTP port ranges.	user	Not Specified																							
session-ttl	Session TTL.	user	Not Specified																							
tcp-halfclose-timer	Wait time to close a TCP session waiting for an unanswered FIN packet.	integer	Minimum value: 0 Maximum value: 86400	0																						
tcp-halfopen-timer	Wait time to close a TCP session waiting for an unanswered open session packet.	integer	Minimum value: 0 Maximum value: 86400	0																						

Parameter	Description	Type	Size	Default
tcp-portrange	Multiple TCP port ranges.	user	Not Specified	
tcp-rst-timer	Set the length of the TCP CLOSE state in seconds.	integer	Minimum value: 5 Maximum value: 300	0
tcp-timewait-timer	Set the length of the TCP TIME-WAIT state in seconds.	integer	Minimum value: 0 Maximum value: 300	0
udp-idle-timer	Number of seconds before an idle UDP connection times out.	integer	Minimum value: 0 Maximum value: 86400	0
udp-portrange	Multiple UDP port ranges.	user	Not Specified	
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000

config firewall service group

Configure service groups.

```
config firewall service group
    Description: Configure service groups.
    edit <name>
        set color {integer}
        set comment {var-string}
        set fabric-object [enable|disable]
        set member <name1>, <name2>, ...
        set proxy [enable|disable]
        set uuid {uuid}
    next
end
```

config firewall service group

Parameter	Description	Type	Size	Default
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0

Parameter	Description	Type	Size	Default						
comment	Comment.	var-string	Maximum length: 255							
fabric-object	Security Fabric global object setting.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Object is set as a security fabric-wide global object.</td></tr><tr><td><i>disable</i></td><td>Object is local to this security fabric member.</td></tr></table>	Option	Description	<i>enable</i>	Object is set as a security fabric-wide global object.	<i>disable</i>	Object is local to this security fabric member.			
Option	Description									
<i>enable</i>	Object is set as a security fabric-wide global object.									
<i>disable</i>	Object is local to this security fabric member.									
member <name>	Service objects contained within the group. Service or service group name.	string	Maximum length: 79							
name	Service group name.	string	Maximum length: 79							
proxy	Enable/disable web proxy service group.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000						

config firewall shaper per-ip-shaper

Configure per-IP traffic shaper.

```

config firewall shaper per-ip-shaper
  Description: Configure per-IP traffic shaper.
  edit <name>
    set bandwidth-unit [kbps|mbps|...]
    set diffserv-forward [enable|disable]
    set diffserv-reverse [enable|disable]
    set diffservcode-forward {user}
    set diffservcode-rev {user}
    set max-bandwidth {integer}
    set max-concurrent-session {integer}
    set max-concurrent-tcp-session {integer}
    set max-concurrent-udp-session {integer}
  next
end

```