

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable this TTL policy.		
	<i>disable</i>	Disable this TTL policy.		
tll	Value/range to match against the packet's Time to Live value.	user	Not Specified	

config firewall vendor-mac

Show vendor and the MAC address they have. Read-only.

```
config firewall vendor-mac
  Description: Show vendor and the MAC address they have. Read-only.
  edit <id>
    set mac-number {integer}
    set name {string}
    set obsolete {integer}
  next
end
```

config firewall vendor-mac

Parameter	Description	Type	Size	Default
id	Vendor ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0
mac-number	Total number of MAC addresses. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0
name	Vendor name. Read-only.	string	Maximum length: 63	
obsolete	Indicates whether the Vendor ID can be used. Read-only.	integer	Minimum value: 0 Maximum value: 255	0

config firewall vip

Configure virtual IP for IPv4.

```

config firewall vip
    Description: Configure virtual IP for IPv4.
    edit <name>
        set add-nat46-route [disable|enable]
        set arp-reply [disable|enable]
        set color {integer}
        set comment {var-string}
        set dns-mapping-ttl {integer}
        set extaddr <name1>, <name2>, ...
        set extintf {string}
        set extip {user}
        set extport {user}
        set gratuitous-arp-interval {integer}
        set gslb-domain-name {string}
        set gslb-hostname {string}
    config gslb-public-ips
        Description: Publicly accessible IP addresses for the FortiGSLB service.
        edit <index>
            set ip {ipv4-address-any}
        next
    end
    set h2-support [enable|disable]
    set h3-support [enable|disable]
    set http-cookie-age {integer}
    set http-cookie-domain {string}
    set http-cookie-domain-from-host [disable|enable]
    set http-cookie-generation {integer}
    set http-cookie-path {string}
    set http-cookie-share [disable|same-ip]
    set http-ip-header [enable|disable]
    set http-ip-header-name {string}
    set http-multiplex [enable|disable]
    set http-multiplex-max-concurrent-request {integer}
    set http-multiplex-max-request {integer}
    set http-multiplex-ttl {integer}
    set http-redirect [enable|disable]
    set https-cookie-secure [disable|enable]
    set id {integer}
    set ipv6-mappedip {user}
    set ipv6-mappedport {user}
    set ldb-method [static|round-robin|...]
    set mapped-addr {string}
    set mappedip <range1>, <range2>, ...
    set mappedport {user}
    set max-embryonic-connections {integer}
    set monitor <name1>, <name2>, ...
    set nat-source-vip [disable|enable]
    set nat44 [disable|enable]
    set nat46 [disable|enable]
    set one-click-gslb-server [disable|enable]
    set outlook-web-access [disable|enable]
    set persistence [none|http-cookie|...]
    set portforward [disable|enable]
    set portmapping-type [1-to-1|m-to-n]
    set protocol [tcp|udp|...]
config quic

```

```

    Description: QUIC setting.
    set ack-delay-exponent {integer}
    set active-connection-id-limit {integer}
    set active-migration [enable|disable]
    set grease-quic-bit [enable|disable]
    set max-ack-delay {integer}
    set max-datagram-frame-size {integer}
    set max-idle-timeout {integer}
    set max-udp-payload-size {integer}
end
config realservers
    Description: Select the real servers that this server load balancing VIP will
distribute traffic to.
    edit <id>
        set address {string}
        set client-ip {user}
        set healthcheck [disable|enable|...]
        set holddown-interval {integer}
        set http-host {string}
        set ip {user}
        set max-connections {integer}
        set monitor <name1>, <name2>, ...
        set port {integer}
        set status [active|standby|...]
        set translate-host [enable|disable]
        set type [ip|address]
        set weight {integer}
    next
end
set server-type [http|https|...]
set service <name1>, <name2>, ...
set src-filter <range1>, <range2>, ...
set src-vip-filter [disable|enable]
set srcintf-filter <interface-name1>, <interface-name2>, ...
set ssl-accept-ffdhe-groups [enable|disable]
set ssl-algorithm [high|medium|...]
set ssl-certificate <name1>, <name2>, ...
config ssl-cipher-suites
    Description: SSL/TLS cipher suites acceptable from a client, ordered by
priority.
    edit <priority>
        set cipher [TLS-AES-128-GCM-SHA256|TLS-AES-256-GCM-SHA384|...]
        set versions {option1}, {option2}, ...
    next
end
set ssl-client-fallback [disable|enable]
set ssl-client-rekey-count {integer}
set ssl-client-renegotiation [allow|deny|...]
set ssl-client-session-state-max {integer}
set ssl-client-session-state-timeout {integer}
set ssl-client-session-state-type [disable|time|...]
set ssl-dh-bits [768|1024|...]
set ssl-hpkip [disable|enable|...]
set ssl-hpkip-age {integer}
set ssl-hpkip-backup {string}
set ssl-hpkip-include-subdomains [disable|enable]

```

```

set ssl-hpkp-primary {string}
set ssl-hpkp-report-uri {var-string}
set ssl-hsts [disable|enable]
set ssl-hsts-age {integer}
set ssl-hsts-include-subdomains [disable|enable]
set ssl-http-location-conversion [enable|disable]
set ssl-http-match-host [enable|disable]
set ssl-max-version [ssl-3.0|tls-1.0|...]
set ssl-min-version [ssl-3.0|tls-1.0|...]
set ssl-mode [half|full]
set ssl-pfs [require|deny|...]
set ssl-send-empty-frags [enable|disable]
set ssl-server-algorithm [high|medium|...]
config ssl-server-cipher-suites
    Description: SSL/TLS cipher suites to offer to a server, ordered by priority.
    edit <priority>
        set cipher [TLS-AES-128-GCM-SHA256|TLS-AES-256-GCM-SHA384|...]
        set versions {option1}, {option2}, ...
    next
end
set ssl-server-max-version [ssl-3.0|tls-1.0|...]
set ssl-server-min-version [ssl-3.0|tls-1.0|...]
set ssl-server-renegotiation [enable|disable]
set ssl-server-session-state-max {integer}
set ssl-server-session-state-timeout {integer}
set ssl-server-session-state-type [disable|time|...]
set status [disable|enable]
set type [static-nat|load-balance|...]
set uuid {uuid}
set weblogic-server [disable|enable]
set websphere-server [disable|enable]
next
end

```

config firewall vip

Parameter	Description	Type	Size	Default
add-nat46-route	Enable/disable adding NAT46 route.	option	-	enable
	Option	Description		
	<i>disable</i>	Disable adding NAT46 route.		
	<i>enable</i>	Enable adding NAT46 route.		
arp-reply	Enable to respond to ARP requests for this virtual IP address. Enabled by default.	option	-	enable
	Option	Description		
	<i>disable</i>	Disable ARP reply.		
	<i>enable</i>	Enable ARP reply.		

Parameter	Description	Type	Size	Default						
color	Color of icon on the GUI.	integer	Minimum value: 0 Maximum value: 32	0						
comment	Comment.	var-string	Maximum length: 255							
dns-mapping-ttl	DNS mapping TTL.	integer	Minimum value: 0 Maximum value: 604800	0						
extaddr <name>	External FQDN address name. Address name.	string	Maximum length: 79							
extintf	Interface connected to the source network that receives the packets that will be forwarded to the destination network.	string	Maximum length: 35							
extip	IP address or address range on the external interface that you want to map to an address or address range on the destination network.	user	Not Specified							
extport	Incoming port number range that you want to map to a port number range on the destination network.	user	Not Specified							
gratuitous-arp-interval	Enable to have the VIP send gratuitous ARPs. 0=disabled. Set from 5 up to 8640000 seconds to enable.	integer	Minimum value: 5 Maximum value: 8640000	0						
gslb-domain-name	Domain to use when integrating with FortiGSLB.	string	Maximum length: 255							
gslb-hostname	Hostname to use within the configured FortiGSLB domain.	string	Maximum length: 35							
h2-support	Enable/disable HTTP2 support.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable HTTP2 support.</td></tr><tr><td>disable</td><td>Disable HTTP2 support.</td></tr></table>				Option	Description	enable	Enable HTTP2 support.	disable	Disable HTTP2 support.
Option	Description									
enable	Enable HTTP2 support.									
disable	Disable HTTP2 support.									
h3-support	Enable/disable HTTP3/QUIC support.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable HTTP3/QUIC support.		
	<i>disable</i>	Disable HTTP3/QUIC support.		
http-cookie-age	Time in minutes that client web browsers should keep a cookie. Default is 60 minutes. 0 = no time limit.	integer	Minimum value: 0 Maximum value: 525600	60
http-cookie-domain	Domain that HTTP cookie persistence should apply to.	string	Maximum length: 35	
http-cookie-domain-from-host	Enable/disable use of HTTP cookie domain from host field in HTTP.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable use of HTTP cookie domain from host field in HTTP (use http-cooke-domain setting).		
	<i>enable</i>	Enable use of HTTP cookie domain from host field in HTTP.		
http-cookie-generation	Generation of HTTP cookie to be accepted. Changing invalidates all existing cookies.	integer	Minimum value: 0 Maximum value: 4294967295	0
http-cookie-path	Limit HTTP cookie persistence to the specified path.	string	Maximum length: 35	
http-cookie-share	Control sharing of cookies across virtual servers. Use of same-ip means a cookie from one virtual server can be used by another. Disable stops cookie sharing.	option	-	same-ip
	Option	Description		
	<i>disable</i>	Only allow HTTP cookie to match this virtual server.		
	<i>same-ip</i>	Allow HTTP cookie to match any virtual server with same IP.		
http-ip-header	For HTTP multiplexing, enable to add the original client IP address in the XForwarded-For HTTP header.	option	-	disable

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable adding HTTP header.		
	<i>disable</i>	Disable adding HTTP header.		
http-ip-header-name	For HTTP multiplexing, enter a custom HTTPS header name. The original client IP address is added to this header. If empty, X-Forwarded-For is used.	string	Maximum length: 35	
http-multiplex	Enable/disable HTTP multiplexing.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable HTTP session multiplexing.		
	<i>disable</i>	Disable HTTP session multiplexing.		
http-multiplex-max-concurrent-request	Maximum number of concurrent requests that a multiplex server can handle.	integer	Minimum value: 0 Maximum value: 2147483647	0
http-multiplex-max-request	Maximum number of requests that a multiplex server can handle before disconnecting sessions.	integer	Minimum value: 0 Maximum value: 2147483647	0
http-multiplex-ttl	Time-to-live for idle connections to servers.	integer	Minimum value: 0 Maximum value: 2147483647	15
http-redirect	Enable/disable redirection of HTTP to HTTPS.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable redirection of HTTP to HTTPS.		
	<i>disable</i>	Disable redirection of HTTP to HTTPS.		
https-cookie-secure	Enable/disable verification that inserted HTTPS cookies are secure.	option	-	disable

Parameter	Description	Type	Size	Default																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Do not mark cookie as secure, allow sharing between an HTTP and HTTPS connection.</td></tr><tr><td><i>enable</i></td><td>Mark inserted cookie as secure, cookie can only be used for HTTPS a connection.</td></tr></table>				Option	Description	<i>disable</i>	Do not mark cookie as secure, allow sharing between an HTTP and HTTPS connection.	<i>enable</i>	Mark inserted cookie as secure, cookie can only be used for HTTPS a connection.										
	Option	Description																		
	<i>disable</i>	Do not mark cookie as secure, allow sharing between an HTTP and HTTPS connection.																		
<i>enable</i>	Mark inserted cookie as secure, cookie can only be used for HTTPS a connection.																			
id	Custom defined ID.	integer	Minimum value: 0 Maximum value: 65535	0																
ipv6-mappedip	Range of mapped IPv6 addresses. Specify the start IPv6 address followed by a space and the end IPv6 address.	user	Not Specified																	
ipv6-mappedport	IPv6 port number range on the destination network to which the external port number range is mapped.	user	Not Specified																	
ldb-method	Method used to distribute sessions to real servers.	option	-	static																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>static</i></td><td>Distribute to server based on source IP.</td></tr><tr><td><i>round-robin</i></td><td>Distribute to server based round robin order.</td></tr><tr><td><i>weighted</i></td><td>Distribute to server based on weight.</td></tr><tr><td><i>least-session</i></td><td>Distribute to server with lowest session count.</td></tr><tr><td><i>least-rtt</i></td><td>Distribute to server with lowest Round-Trip-Time.</td></tr><tr><td><i>first-alive</i></td><td>Distribute to the first server that is alive.</td></tr><tr><td><i>http-host</i></td><td>Distribute to server based on host field in HTTP header.</td></tr></table>				Option	Description	<i>static</i>	Distribute to server based on source IP.	<i>round-robin</i>	Distribute to server based round robin order.	<i>weighted</i>	Distribute to server based on weight.	<i>least-session</i>	Distribute to server with lowest session count.	<i>least-rtt</i>	Distribute to server with lowest Round-Trip-Time.	<i>first-alive</i>	Distribute to the first server that is alive.	<i>http-host</i>	Distribute to server based on host field in HTTP header.
	Option	Description																		
	<i>static</i>	Distribute to server based on source IP.																		
	<i>round-robin</i>	Distribute to server based round robin order.																		
	<i>weighted</i>	Distribute to server based on weight.																		
	<i>least-session</i>	Distribute to server with lowest session count.																		
	<i>least-rtt</i>	Distribute to server with lowest Round-Trip-Time.																		
	<i>first-alive</i>	Distribute to the first server that is alive.																		
<i>http-host</i>	Distribute to server based on host field in HTTP header.																			
mapped-addr	Mapped FQDN address name.	string	Maximum length: 79																	
mappedip <range>	IP address or address range on the destination network to which the external IP address is mapped. Mapped IP range.	string	Maximum length: 79																	
mappedport	Port number range on the destination network to which the external port number range is mapped.	user	Not Specified																	

Parameter	Description	Type	Size	Default						
max-embryonic-connections	Maximum number of incomplete connections.	integer	Minimum value: 0 Maximum value: 100000	1000						
monitor <name>	Name of the health check monitor to use when polling to determine a virtual server's connectivity status. Health monitor name.	string	Maximum length: 79							
name	Virtual IP name.	string	Maximum length: 79							
nat-source-vip	Enable/disable forcing the source NAT mapped IP to the external IP for all traffic.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Force only the source NAT mapped IP to the external IP for traffic egressing the external interface of the VIP.</td></tr><tr><td>enable</td><td>Force the source NAT mapped IP to the external IP for all traffic.</td></tr></table>	Option	Description	disable	Force only the source NAT mapped IP to the external IP for traffic egressing the external interface of the VIP.	enable	Force the source NAT mapped IP to the external IP for all traffic.			
Option	Description									
disable	Force only the source NAT mapped IP to the external IP for traffic egressing the external interface of the VIP.									
enable	Force the source NAT mapped IP to the external IP for all traffic.									
nat44	Enable/disable NAT44.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable NAT44.</td></tr><tr><td>enable</td><td>Enable NAT44.</td></tr></table>	Option	Description	disable	Disable NAT44.	enable	Enable NAT44.			
Option	Description									
disable	Disable NAT44.									
enable	Enable NAT44.									
nat46	Enable/disable NAT46.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable NAT46.</td></tr><tr><td>enable</td><td>Enable NAT46.</td></tr></table>	Option	Description	disable	Disable NAT46.	enable	Enable NAT46.			
Option	Description									
disable	Disable NAT46.									
enable	Enable NAT46.									
one-click-gslb-server	Enable/disable one click GSLB server integration with FortiGSLB.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable integration with FortiGSLB.</td></tr><tr><td>enable</td><td>Enable integration with FortiGSLB.</td></tr></table>	Option	Description	disable	Disable integration with FortiGSLB.	enable	Enable integration with FortiGSLB.			
Option	Description									
disable	Disable integration with FortiGSLB.									
enable	Enable integration with FortiGSLB.									
outlook-web-access	Enable to add the Front-End-Https header for Microsoft Outlook Web Access.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option Description			
	<i>disable</i>	Disable Outlook Web Access support.		
	<i>enable</i>	Enable Outlook Web Access support.		
persistence	Configure how to make sure that clients connect to the same server every time they make a request that is part of the same session.	option	-	none
	Option Description			
	<i>none</i>	None.		
	<i>http-cookie</i>	HTTP cookie.		
	<i>ssl-session-id</i>	SSL session ID.		
portforward	Enable/disable port forwarding.	option	-	disable
	Option Description			
	<i>disable</i>	Disable port forward.		
	<i>enable</i>	Enable port forward.		
portmapping-type	Port mapping type.	option	-	1-to-1
	Option Description			
	<i>1-to-1</i>	One to one.		
	<i>m-to-n</i>	Many to many.		
protocol	Protocol to use when forwarding packets.	option	-	tcp
	Option Description			
	<i>tcp</i>	TCP.		
	<i>udp</i>	UDP.		
	<i>sctp</i>	SCTP.		
	<i>icmp</i>	ICMP.		
server-type	Protocol to be load balanced by the virtual server (also called the server load balance virtual IP).	option	-	

Parameter	Description	Type	Size	Default																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>http</i></td><td>HTTP.</td></tr><tr><td><i>https</i></td><td>HTTPS.</td></tr><tr><td><i>imaps</i></td><td>IMAPS.</td></tr><tr><td><i>pop3s</i></td><td>POP3S.</td></tr><tr><td><i>smtps</i></td><td>SMTPS.</td></tr><tr><td><i>ssl</i></td><td>SSL.</td></tr><tr><td><i>tcp</i></td><td>TCP.</td></tr><tr><td><i>udp</i></td><td>UDP.</td></tr><tr><td><i>ip</i></td><td>IP.</td></tr></table>	Option	Description	<i>http</i>	HTTP.	<i>https</i>	HTTPS.	<i>imaps</i>	IMAPS.	<i>pop3s</i>	POP3S.	<i>smtps</i>	SMTPS.	<i>ssl</i>	SSL.	<i>tcp</i>	TCP.	<i>udp</i>	UDP.	<i>ip</i>	IP.			
	Option	Description																						
	<i>http</i>	HTTP.																						
	<i>https</i>	HTTPS.																						
	<i>imaps</i>	IMAPS.																						
	<i>pop3s</i>	POP3S.																						
	<i>smtps</i>	SMTPS.																						
	<i>ssl</i>	SSL.																						
	<i>tcp</i>	TCP.																						
	<i>udp</i>	UDP.																						
<i>ip</i>	IP.																							
service <name>	Service name. Service name.	string	Maximum length: 79																					
src-filter <range>	Source address filter. Each address must be either an IP/subnet (x.x.x.x/n) or a range (x.x.x.x-y.y.y.y). Separate addresses with spaces. Source-filter range.	string	Maximum length: 79																					
src-vip-filter	Enable/disable use of 'src-filter' to match destinations for the reverse SNAT rule.	option	-	disable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Match any destination for the reverse SNAT rule.</td></tr><tr><td><i>enable</i></td><td>Match only destinations in 'src-filter' for the reverse SNAT rule.</td></tr></table>	Option	Description	<i>disable</i>	Match any destination for the reverse SNAT rule.	<i>enable</i>	Match only destinations in 'src-filter' for the reverse SNAT rule.																	
	Option	Description																						
	<i>disable</i>	Match any destination for the reverse SNAT rule.																						
<i>enable</i>	Match only destinations in 'src-filter' for the reverse SNAT rule.																							
srcintf-filter <interface-name>	Interfaces to which the VIP applies. Separate the names with spaces. Interface name.	string	Maximum length: 79																					
ssl-accept-ffdhe-groups	Enable/disable FFDHE cipher suite for SSL key exchange.	option	-	enable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Accept FFDHE groups.</td></tr><tr><td><i>disable</i></td><td>Do not accept FFDHE groups.</td></tr></table>	Option	Description	<i>enable</i>	Accept FFDHE groups.	<i>disable</i>	Do not accept FFDHE groups.																	
	Option	Description																						
	<i>enable</i>	Accept FFDHE groups.																						
<i>disable</i>	Do not accept FFDHE groups.																							
ssl-algorithm	Permitted encryption algorithms for SSL sessions according to encryption strength.	option	-	high																				

Parameter	Description	Type	Size	Default										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>high</i></td><td>High encryption. Allow only AES and ChaCha.</td></tr><tr><td><i>medium</i></td><td>Medium encryption. Allow AES, ChaCha, 3DES, and RC4.</td></tr><tr><td><i>low</i></td><td>Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.</td></tr><tr><td><i>custom</i></td><td>Custom encryption. Use config ssl-cipher-suites to select the cipher suites that are allowed.</td></tr></table>	Option	Description	<i>high</i>	High encryption. Allow only AES and ChaCha.	<i>medium</i>	Medium encryption. Allow AES, ChaCha, 3DES, and RC4.	<i>low</i>	Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.	<i>custom</i>	Custom encryption. Use config ssl-cipher-suites to select the cipher suites that are allowed.			
	Option	Description												
	<i>high</i>	High encryption. Allow only AES and ChaCha.												
	<i>medium</i>	Medium encryption. Allow AES, ChaCha, 3DES, and RC4.												
	<i>low</i>	Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.												
<i>custom</i>	Custom encryption. Use config ssl-cipher-suites to select the cipher suites that are allowed.													
ssl-certificate <name>	Name of the certificate to use for SSL handshake. Certificate list.	string	Maximum length: 79											
ssl-client-fallback	Enable/disable support for preventing Downgrade Attacks on client connections (RFC 7507).	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable.</td></tr><tr><td><i>enable</i></td><td>Enable.</td></tr></table>	Option	Description	<i>disable</i>	Disable.	<i>enable</i>	Enable.							
	Option	Description												
	<i>disable</i>	Disable.												
<i>enable</i>	Enable.													
ssl-client-rekey-count	Maximum length of data in MB before triggering a client rekey (0 = disable).	integer	Minimum value: 200 Maximum value: 1048576	0										
ssl-client-renegotiation	Allow, deny, or require secure renegotiation of client sessions to comply with RFC 5746.	option	-	secure										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>allow</i></td><td>Allow a SSL client to renegotiate.</td></tr><tr><td><i>deny</i></td><td>Abort any client initiated SSL re-negotiation attempt.</td></tr><tr><td><i>secure</i></td><td>Abort any client initiated SSL re-negotiation attempt that does not use RFC 5746 Secure Renegotiation.</td></tr></table>	Option	Description	<i>allow</i>	Allow a SSL client to renegotiate.	<i>deny</i>	Abort any client initiated SSL re-negotiation attempt.	<i>secure</i>	Abort any client initiated SSL re-negotiation attempt that does not use RFC 5746 Secure Renegotiation.					
	Option	Description												
	<i>allow</i>	Allow a SSL client to renegotiate.												
	<i>deny</i>	Abort any client initiated SSL re-negotiation attempt.												
<i>secure</i>	Abort any client initiated SSL re-negotiation attempt that does not use RFC 5746 Secure Renegotiation.													
ssl-client-session-state-max	Maximum number of client to FortiGate SSL session states to keep.	integer	Minimum value: 1 Maximum value: 10000	1000										
ssl-client-session-state-timeout	Number of minutes to keep client to FortiGate SSL session state.	integer	Minimum value: 1 Maximum value: 14400	30										

Parameter	Description	Type	Size	Default
ssl-client-session-state-type	How to expire SSL sessions for the segment of the SSL connection between the client and the FortiGate.	option	-	both
	Option	Description		
	<i>disable</i>	Do not keep session states.		
	<i>time</i>	Expire session states after this many minutes.		
	<i>count</i>	Expire session states when this maximum is reached.		
	<i>both</i>	Expire session states based on time or count, whichever occurs first.		
ssl-dh-bits	Number of bits to use in the Diffie-Hellman exchange for RSA encryption of SSL sessions.	option	-	2048
	Option	Description		
	<i>768</i>	768-bit Diffie-Hellman prime.		
	<i>1024</i>	1024-bit Diffie-Hellman prime.		
	<i>1536</i>	1536-bit Diffie-Hellman prime.		
	<i>2048</i>	2048-bit Diffie-Hellman prime.		
	<i>3072</i>	3072-bit Diffie-Hellman prime.		
	<i>4096</i>	4096-bit Diffie-Hellman prime.		
ssl-hpkp	Enable/disable including HPKP header in response.	option	-	disable
	Option	Description		
	<i>disable</i>	Do not add a HPKP header to each HTTP response.		
	<i>enable</i>	Add a HPKP header to each a HTTP response.		
	<i>report-only</i>	Add a HPKP Report-Only header to each HTTP response.		
ssl-hpkp-age	Number of seconds the client should honor the HPKP setting.	integer	Minimum value: 60 Maximum value: 157680000	5184000
ssl-hpkp-backup	Certificate to generate backup HPKP pin from.	string	Maximum length: 79	
ssl-hpkp-include-subdomains	Indicate that HPKP header applies to all subdomains.	option	-	disable

Parameter	Description	Type	Size	Default
	Option Description			
	<i>disable</i>	HPKP header does not apply to subdomains.		
	<i>enable</i>	HPKP header applies to subdomains.		
ssl-hpkp-primary	Certificate to generate primary HPKP pin from.	string	Maximum length: 79	
ssl-hpkp-report-uri	URL to report HPKP violations to.	var-string	Maximum length: 255	
ssl-hsts	Enable/disable including HSTS header in response.	option	-	disable
	Option Description			
	<i>disable</i>	Do not add a HSTS header to each a HTTP response.		
	<i>enable</i>	Add a HSTS header to each HTTP response.		
ssl-hsts-age	Number of seconds the client should honor the HSTS setting.	integer	Minimum value: 60 Maximum value: 157680000	5184000
ssl-hsts-include-subdomains	Indicate that HSTS header applies to all subdomains.	option	-	disable
	Option Description			
	<i>disable</i>	HSTS header does not apply to subdomains.		
	<i>enable</i>	HSTS header applies to subdomains.		
ssl-http-location-conversion	Enable to replace HTTP with HTTPS in the reply's Location HTTP header field.	option	-	disable
	Option Description			
	<i>enable</i>	Enable HTTP location conversion.		
	<i>disable</i>	Disable HTTP location conversion.		
ssl-http-match-host	Enable/disable HTTP host matching for location conversion.	option	-	enable
	Option Description			
	<i>enable</i>	Match HTTP host in response header.		
	<i>disable</i>	Do not match HTTP host.		

Parameter	Description	Type	Size	Default												
ssl-max-version	Highest SSL/TLS version acceptable from a client.	option	-	tls-1.3												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ssl-3.0</td><td>SSL 3.0.</td></tr><tr><td>tls-1.0</td><td>TLS 1.0.</td></tr><tr><td>tls-1.1</td><td>TLS 1.1.</td></tr><tr><td>tls-1.2</td><td>TLS 1.2.</td></tr><tr><td>tls-1.3</td><td>TLS 1.3.</td></tr></table>	Option	Description	ssl-3.0	SSL 3.0.	tls-1.0	TLS 1.0.	tls-1.1	TLS 1.1.	tls-1.2	TLS 1.2.	tls-1.3	TLS 1.3.			
Option	Description															
ssl-3.0	SSL 3.0.															
tls-1.0	TLS 1.0.															
tls-1.1	TLS 1.1.															
tls-1.2	TLS 1.2.															
tls-1.3	TLS 1.3.															
ssl-min-version	Lowest SSL/TLS version acceptable from a client.	option	-	tls-1.1												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ssl-3.0</td><td>SSL 3.0.</td></tr><tr><td>tls-1.0</td><td>TLS 1.0.</td></tr><tr><td>tls-1.1</td><td>TLS 1.1.</td></tr><tr><td>tls-1.2</td><td>TLS 1.2.</td></tr><tr><td>tls-1.3</td><td>TLS 1.3.</td></tr></table>	Option	Description	ssl-3.0	SSL 3.0.	tls-1.0	TLS 1.0.	tls-1.1	TLS 1.1.	tls-1.2	TLS 1.2.	tls-1.3	TLS 1.3.			
Option	Description															
ssl-3.0	SSL 3.0.															
tls-1.0	TLS 1.0.															
tls-1.1	TLS 1.1.															
tls-1.2	TLS 1.2.															
tls-1.3	TLS 1.3.															
ssl-mode	Apply SSL offloading between the client and the FortiGate (half) or from the client to the FortiGate and from the FortiGate to the server (full).	option	-	half												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>half</td><td>Client to FortiGate SSL.</td></tr><tr><td>full</td><td>Client to FortiGate and FortiGate to Server SSL.</td></tr></table>	Option	Description	half	Client to FortiGate SSL.	full	Client to FortiGate and FortiGate to Server SSL.									
Option	Description															
half	Client to FortiGate SSL.															
full	Client to FortiGate and FortiGate to Server SSL.															
ssl-pfs	Select the cipher suites that can be used for SSL perfect forward secrecy (PFS). Applies to both client and server sessions.	option	-	require												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>require</td><td>Allow only Diffie-Hellman cipher-suites, so PFS is applied.</td></tr><tr><td>deny</td><td>Allow only non-Diffie-Hellman cipher-suites, so PFS is not applied.</td></tr><tr><td>allow</td><td>Allow use of any cipher suite so PFS may or may not be used depending on the cipher suite selected.</td></tr></table>	Option	Description	require	Allow only Diffie-Hellman cipher-suites, so PFS is applied.	deny	Allow only non-Diffie-Hellman cipher-suites, so PFS is not applied.	allow	Allow use of any cipher suite so PFS may or may not be used depending on the cipher suite selected.							
Option	Description															
require	Allow only Diffie-Hellman cipher-suites, so PFS is applied.															
deny	Allow only non-Diffie-Hellman cipher-suites, so PFS is not applied.															
allow	Allow use of any cipher suite so PFS may or may not be used depending on the cipher suite selected.															

Parameter	Description	Type	Size	Default														
ssl-send-empty-frags	Enable/disable sending empty fragments to avoid CBC IV attacks (SSL 3.0 & TLS 1.0 only). May need to be disabled for compatibility with older systems.	option	-	enable														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Send empty fragments.</td></tr><tr><td><i>disable</i></td><td>Do not send empty fragments.</td></tr></table>	Option	Description	<i>enable</i>	Send empty fragments.	<i>disable</i>	Do not send empty fragments.											
Option	Description																	
<i>enable</i>	Send empty fragments.																	
<i>disable</i>	Do not send empty fragments.																	
ssl-server-algorithm	Permitted encryption algorithms for the server side of SSL full mode sessions according to encryption strength.	option	-	client														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>high</i></td><td>High encryption. Allow only AES and ChaCha.</td></tr><tr><td><i>medium</i></td><td>Medium encryption. Allow AES, ChaCha, 3DES, and RC4.</td></tr><tr><td><i>low</i></td><td>Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.</td></tr><tr><td><i>custom</i></td><td>Custom encryption. Use ssl-server-cipher-suites to select the cipher suites that are allowed.</td></tr><tr><td><i>client</i></td><td>Use the same encryption algorithms for both client and server sessions.</td></tr></table>	Option	Description	<i>high</i>	High encryption. Allow only AES and ChaCha.	<i>medium</i>	Medium encryption. Allow AES, ChaCha, 3DES, and RC4.	<i>low</i>	Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.	<i>custom</i>	Custom encryption. Use ssl-server-cipher-suites to select the cipher suites that are allowed.	<i>client</i>	Use the same encryption algorithms for both client and server sessions.					
Option	Description																	
<i>high</i>	High encryption. Allow only AES and ChaCha.																	
<i>medium</i>	Medium encryption. Allow AES, ChaCha, 3DES, and RC4.																	
<i>low</i>	Low encryption. Allow AES, ChaCha, 3DES, RC4, and DES.																	
<i>custom</i>	Custom encryption. Use ssl-server-cipher-suites to select the cipher suites that are allowed.																	
<i>client</i>	Use the same encryption algorithms for both client and server sessions.																	
ssl-server-max-version	Highest SSL/TLS version acceptable from a server. Use the client setting by default.	option	-	client														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ssl-3.0</i></td><td>SSL 3.0.</td></tr><tr><td><i>tls-1.0</i></td><td>TLS 1.0.</td></tr><tr><td><i>tls-1.1</i></td><td>TLS 1.1.</td></tr><tr><td><i>tls-1.2</i></td><td>TLS 1.2.</td></tr><tr><td><i>tls-1.3</i></td><td>TLS 1.3.</td></tr><tr><td><i>client</i></td><td>Use same value as client configuration.</td></tr></table>	Option	Description	<i>ssl-3.0</i>	SSL 3.0.	<i>tls-1.0</i>	TLS 1.0.	<i>tls-1.1</i>	TLS 1.1.	<i>tls-1.2</i>	TLS 1.2.	<i>tls-1.3</i>	TLS 1.3.	<i>client</i>	Use same value as client configuration.			
Option	Description																	
<i>ssl-3.0</i>	SSL 3.0.																	
<i>tls-1.0</i>	TLS 1.0.																	
<i>tls-1.1</i>	TLS 1.1.																	
<i>tls-1.2</i>	TLS 1.2.																	
<i>tls-1.3</i>	TLS 1.3.																	
<i>client</i>	Use same value as client configuration.																	
ssl-server-min-version	Lowest SSL/TLS version acceptable from a server. Use the client setting by default.	option	-	client														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ssl-3.0</i></td><td>SSL 3.0.</td></tr><tr><td><i>tls-1.0</i></td><td>TLS 1.0.</td></tr></table>	Option	Description	<i>ssl-3.0</i>	SSL 3.0.	<i>tls-1.0</i>	TLS 1.0.											
Option	Description																	
<i>ssl-3.0</i>	SSL 3.0.																	
<i>tls-1.0</i>	TLS 1.0.																	

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>tls-1.1</i>	TLS 1.1.		
	<i>tls-1.2</i>	TLS 1.2.		
	<i>tls-1.3</i>	TLS 1.3.		
	<i>client</i>	Use same value as client configuration.		
ssl-server-renegotiation	Enable/disable secure renegotiation to comply with RFC 5746.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable secure renegotiation.		
	<i>disable</i>	Disable secure renegotiation.		
ssl-server-session-state-max	Maximum number of FortiGate to Server SSL session states to keep.	integer	Minimum value: 1 Maximum value: 10000	100
ssl-server-session-state-timeout	Number of minutes to keep FortiGate to Server SSL session state.	integer	Minimum value: 1 Maximum value: 14400	60
ssl-server-session-state-type	How to expire SSL sessions for the segment of the SSL connection between the server and the FortiGate.	option	-	both
	Option	Description		
	<i>disable</i>	Do not keep session states.		
	<i>time</i>	Expire session states after this many minutes.		
	<i>count</i>	Expire session states when this maximum is reached.		
	<i>both</i>	Expire session states based on time or count, whichever occurs first.		
status	Enable/disable VIP.	option	-	enable
	Option	Description		
	<i>disable</i>	Disable the VIP.		
	<i>enable</i>	Enable the VIP.		

Parameter	Description	Type	Size	Default
type	Configure a static NAT, load balance, server load balance, access proxy, DNS translation, or FQDN VIP.	option	-	static-nat
	Option	Description		
	<i>static-nat</i>	Static NAT.		
	<i>load-balance</i>	Load balance.		
	<i>server-load-balance</i>	Server load balance.		
	<i>dns-translation</i>	DNS translation.		
	<i>fqdn</i>	Fully qualified domain name.		
	<i>access-proxy</i>	Access proxy.		
uuid	Universally Unique Identifier (UUID; automatically assigned but can be manually reset).	uuid	Not Specified	00000000-0000-0000-0000-000000000000
weblogic-server	Enable to add an HTTP header to indicate SSL offloading for a WebLogic server.	option	-	disable
	Option	Description		
	<i>disable</i>	Do not add HTTP header indicating SSL offload for WebLogic server.		
	<i>enable</i>	Add HTTP header indicating SSL offload for WebLogic server.		
websphere-server	Enable to add an HTTP header to indicate SSL offloading for a WebSphere server.	option	-	disable
	Option	Description		
	<i>disable</i>	Do not add HTTP header indicating SSL offload for WebSphere server.		
	<i>enable</i>	Add HTTP header indicating SSL offload for WebSphere server.		

config gslb-public-ips

Parameter	Description	Type	Size	Default
index	Index of this public IP setting.	integer	Minimum value: 0 Maximum value: 4294967295	0
ip	The publicly accessible IP address.	ipv4-address-any	Not Specified	0.0.0.0

config quic

Parameter	Description	Type	Size	Default
ack-delay-exponent	ACK delay exponent.	integer	Minimum value: 1 Maximum value: 20	3
active-connection-id-limit	Active connection ID limit.	integer	Minimum value: 1 Maximum value: 8	2
active-migration	Enable/disable active migration.	option	-	disable
	Option	Description		
	enable	Enable active migration.		
	disable	Disable active migration.		
grease-quic-bit	Enable/disable grease QUIC bit.	option	-	enable
	Option	Description		
	enable	Enable grease QUIC bit.		
	disable	Disable grease QUIC bit.		
max-ack-delay	Maximum ACK delay in milliseconds.	integer	Minimum value: 1 Maximum value: 16383	25
max-datagram-frame-size	Maximum datagram frame size in bytes.	integer	Minimum value: 1 Maximum value: 1500	1500
max-idle-timeout	Maximum idle timeout milliseconds.	integer	Minimum value: 1 Maximum value: 60000	30000
max-udp-payload-size	Maximum UDP payload size in bytes.	integer	Minimum value: 1200 Maximum value: 1500	1500

config realservers

Parameter	Description	Type	Size	Default								
address	Dynamic address of the real server.	string	Maximum length: 79									
client-ip	Only clients in this IP range can connect to this real server.	user	Not Specified									
healthcheck	Enable to check the responsiveness of the real server before forwarding traffic.	option	-	vip								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable per server health check.</td></tr><tr><td><i>enable</i></td><td>Enable per server health check.</td></tr><tr><td><i>vip</i></td><td>Use health check defined in VIP.</td></tr></table>				Option	Description	<i>disable</i>	Disable per server health check.	<i>enable</i>	Enable per server health check.	<i>vip</i>	Use health check defined in VIP.
Option	Description											
<i>disable</i>	Disable per server health check.											
<i>enable</i>	Enable per server health check.											
<i>vip</i>	Use health check defined in VIP.											
holddown-interval	Time in seconds that the system waits before re-activating a previously down active server in the active-standby mode. This is to prevent any flapping issues.	integer	Minimum value: 30 Maximum value: 65535	300								
http-host	HTTP server domain name in HTTP header.	string	Maximum length: 63									
id	Real server ID.	integer	Minimum value: 0 Maximum value: 4294967295	0								
ip	IP address of the real server.	user	Not Specified									
max-connections	Max number of active connections that can be directed to the real server. When reached, sessions are sent to other real servers.	integer	Minimum value: 0 Maximum value: 2147483647	0								
monitor <name>	Name of the health check monitor to use when polling to determine a virtual server's connectivity status. Health monitor name.	string	Maximum length: 79									
port	Port for communicating with the real server. Required if port forwarding is enabled.	integer	Minimum value: 1 Maximum value: 65535	0								

Parameter	Description	Type	Size	Default								
status	Set the status of the real server to active so that it can accept traffic, or on standby or disabled so no traffic is sent.	option	-	active								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>active</td><td>Server status active.</td></tr><tr><td>standby</td><td>Server status standby.</td></tr><tr><td>disable</td><td>Server status disable.</td></tr></table>	Option	Description	active	Server status active.	standby	Server status standby.	disable	Server status disable.			
Option	Description											
active	Server status active.											
standby	Server status standby.											
disable	Server status disable.											
translate-host	Enable/disable translation of hostname/IP from virtual server to real server.	option	-	enable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable virtual hostname/IP translation.</td></tr><tr><td>disable</td><td>Disable virtual hostname/IP translation.</td></tr></table>	Option	Description	enable	Enable virtual hostname/IP translation.	disable	Disable virtual hostname/IP translation.					
Option	Description											
enable	Enable virtual hostname/IP translation.											
disable	Disable virtual hostname/IP translation.											
type	Type of address.	option	-	ip								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ip</td><td>Standard IPv4 address.</td></tr><tr><td>address</td><td>Dynamic address object.</td></tr></table>	Option	Description	ip	Standard IPv4 address.	address	Dynamic address object.					
Option	Description											
ip	Standard IPv4 address.											
address	Dynamic address object.											
weight	Weight of the real server. If weighted load balancing is enabled, the server with the highest weight gets more connections.	integer	Minimum value: 1 Maximum value: 255	1								

config ssl-cipher-suites

Parameter	Description	Type	Size	Default						
cipher	Cipher suite name.	option	-							
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>TLS-AES-128-GCM-SHA256</i></td><td>Cipher suite TLS-AES-128-GCM-SHA256.</td></tr><tr><td><i>TLS-AES-256-GCM-SHA384</i></td><td>Cipher suite TLS-AES-256-GCM-SHA384.</td></tr></table>				Option	Description	<i>TLS-AES-128-GCM-SHA256</i>	Cipher suite TLS-AES-128-GCM-SHA256.	<i>TLS-AES-256-GCM-SHA384</i>	Cipher suite TLS-AES-256-GCM-SHA384.
Option	Description									
<i>TLS-AES-128-GCM-SHA256</i>	Cipher suite TLS-AES-128-GCM-SHA256.									
<i>TLS-AES-256-GCM-SHA384</i>	Cipher suite TLS-AES-256-GCM-SHA384.									

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-CHACHA20-POLY1305-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-DHE-RSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-GCM-SHA384.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-DHE-DSS-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-GCM-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-GCM-SHA384.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA384.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-ECDHE-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA384.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-128-CBC-SHA256.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-RSA-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-256-CBC-SHA256.		
	<i>TLS-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-RSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-RSA-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-128-CBC-SHA.		
	<i>TLS-RSA-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-256-CBC-SHA.		
	<i>TLS-RSA-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-RSA-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-3DES-EDE-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-DSS-RSA-WITH-CAMELLIA-128-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-SEED-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-SEED-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-SEED-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-SEED-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-DHE-RSA-WITH-ARIA-256-CBC-SHA384.		
	<i>TLS-DHE-DSS-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-DHE-DSS-WITH-ARIA-256-CBC-SHA384.		

Parameter	Description	Type	Size	Default																								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>TLS-RSA-WITH-SEED-CBC-SHA</td><td>Cipher suite TLS-RSA-WITH-SEED-CBC-SHA.</td></tr><tr><td>TLS-RSA-WITH-ARIA-128-CBC-SHA256</td><td>Cipher suite TLS-RSA-WITH-ARIA-128-CBC-SHA256.</td></tr><tr><td>TLS-RSA-WITH-ARIA-256-CBC-SHA384</td><td>Cipher suite TLS-RSA-WITH-ARIA-256-CBC-SHA384.</td></tr><tr><td>TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256</td><td>Cipher suite TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256.</td></tr><tr><td>TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384</td><td>Cipher suite TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384.</td></tr><tr><td>TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC-SHA256</td><td>Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC_SHA256.</td></tr><tr><td>TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC-SHA384</td><td>Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC_SHA384.</td></tr><tr><td>TLS-ECDHE-RSA-WITH-RC4-128-SHA</td><td>Cipher suite TLS-ECDHE-RSA-WITH-RC4-128-SHA.</td></tr><tr><td>TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA</td><td>Cipher suite TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA.</td></tr><tr><td>TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA</td><td>Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.</td></tr><tr><td>TLS-RSA-WITH-3DES-EDE-CBC-SHA</td><td>Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.</td></tr></table>	Option	Description	TLS-RSA-WITH-SEED-CBC-SHA	Cipher suite TLS-RSA-WITH-SEED-CBC-SHA.	TLS-RSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-RSA-WITH-ARIA-128-CBC-SHA256.	TLS-RSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-RSA-WITH-ARIA-256-CBC-SHA384.	TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256.	TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384.	TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC_SHA256.	TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC_SHA384.	TLS-ECDHE-RSA-WITH-RC4-128-SHA	Cipher suite TLS-ECDHE-RSA-WITH-RC4-128-SHA.	TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA.	TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.	TLS-RSA-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.			
Option	Description																											
TLS-RSA-WITH-SEED-CBC-SHA	Cipher suite TLS-RSA-WITH-SEED-CBC-SHA.																											
TLS-RSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-RSA-WITH-ARIA-128-CBC-SHA256.																											
TLS-RSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-RSA-WITH-ARIA-256-CBC-SHA384.																											
TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256.																											
TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384.																											
TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC-SHA256	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC_SHA256.																											
TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC-SHA384	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC_SHA384.																											
TLS-ECDHE-RSA-WITH-RC4-128-SHA	Cipher suite TLS-ECDHE-RSA-WITH-RC4-128-SHA.																											
TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA.																											
TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.																											
TLS-RSA-WITH-3DES-EDE-CBC-SHA	Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.																											

Parameter	Description	Type	Size	Default												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>TLS-RSA-WITH-RC4-128-MD5</i></td><td>Cipher suite TLS-RSA-WITH-RC4-128-MD5.</td></tr><tr><td><i>TLS-RSA-WITH-RC4-128-SHA</i></td><td>Cipher suite TLS-RSA-WITH-RC4-128-SHA.</td></tr><tr><td><i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.</td></tr><tr><td><i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.</td></tr><tr><td><i>TLS-RSA-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-RSA-WITH-DES-CBC-SHA.</td></tr></table>	Option	Description	<i>TLS-RSA-WITH-RC4-128-MD5</i>	Cipher suite TLS-RSA-WITH-RC4-128-MD5.	<i>TLS-RSA-WITH-RC4-128-SHA</i>	Cipher suite TLS-RSA-WITH-RC4-128-SHA.	<i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.	<i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.	<i>TLS-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-DES-CBC-SHA.			
	Option	Description														
	<i>TLS-RSA-WITH-RC4-128-MD5</i>	Cipher suite TLS-RSA-WITH-RC4-128-MD5.														
	<i>TLS-RSA-WITH-RC4-128-SHA</i>	Cipher suite TLS-RSA-WITH-RC4-128-SHA.														
	<i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.														
	<i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.														
<i>TLS-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-DES-CBC-SHA.															
priority	SSL/TLS cipher suites priority.	integer	Minimum value: 0 Maximum value: 4294967295	0												
versions	SSL/TLS versions that the cipher suite can be used with.	option	-	ssl-3.0 tls-1.0 tls-1.1 tls-1.2 tls-1.3												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ssl-3.0</i></td><td>SSL 3.0.</td></tr><tr><td><i>tls-1.0</i></td><td>TLS 1.0.</td></tr><tr><td><i>tls-1.1</i></td><td>TLS 1.1.</td></tr><tr><td><i>tls-1.2</i></td><td>TLS 1.2.</td></tr><tr><td><i>tls-1.3</i></td><td>TLS 1.3.</td></tr></table>	Option	Description	<i>ssl-3.0</i>	SSL 3.0.	<i>tls-1.0</i>	TLS 1.0.	<i>tls-1.1</i>	TLS 1.1.	<i>tls-1.2</i>	TLS 1.2.	<i>tls-1.3</i>	TLS 1.3.			
	Option	Description														
	<i>ssl-3.0</i>	SSL 3.0.														
	<i>tls-1.0</i>	TLS 1.0.														
	<i>tls-1.1</i>	TLS 1.1.														
	<i>tls-1.2</i>	TLS 1.2.														
<i>tls-1.3</i>	TLS 1.3.															

config ssl-server-cipher-suites

Parameter	Description	Type	Size	Default
cipher	Cipher suite name.	option	-	

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-AES-128-GCM-SHA256</i>	Cipher suite TLS-AES-128-GCM-SHA256.		
	<i>TLS-AES-256-GCM-SHA384</i>	Cipher suite TLS-AES-256-GCM-SHA384.		
	<i>TLS-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-CHACHA20-POLY1305-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-DHE-RSA-WITH-CHACHA20-POLY1305-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CHACHA20-POLY1305-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-DHE-RSA-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-CBC-SHA256.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-DHE-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-DHE-RSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-DHE-DSS-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-128-GCM-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-DHE-DSS-WITH-AES-256-GCM-SHA384.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA384.		
	<i>TLS-ECDHE-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-ECDHE-RSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA384.		
	<i>TLS-ECDHE-ECDSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-RSA-WITH-AES-128-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-AES-128-CBC-SHA.		
	<i>TLS-RSA-WITH-AES-256-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-AES-256-CBC-SHA.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-RSA-WITH-AES-128-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-128-CBC-SHA256.		
	<i>TLS-RSA-WITH-AES-128-GCM-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-128-GCM-SHA256.		
	<i>TLS-RSA-WITH-AES-256-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-AES-256-CBC-SHA256.		
	<i>TLS-RSA-WITH-AES-256-GCM-SHA384</i>	Cipher suite TLS-RSA-WITH-AES-256-GCM-SHA384.		
	<i>TLS-RSA-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-128-CBC-SHA.		
	<i>TLS-RSA-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-256-CBC-SHA.		
	<i>TLS-RSA-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-RSA-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-3DES-EDE-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA</i>	Cipher suite TLS-DSS-RSA-WITH-CAMELLIA-128-CBC-SHA.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-CAMELLIA-256-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-SEED-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-SEED-CBC-SHA.		
	<i>TLS-DHE-DSS-WITH-SEED-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-SEED-CBC-SHA.		
	<i>TLS-DHE-RSA-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-RSA-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-DHE-RSA-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-DHE-RSA-WITH-ARIA-256-CBC-SHA384.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>TLS-DHE-DSS-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-DHE-DSS-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-DHE-DSS-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-DHE-DSS-WITH-ARIA-256-CBC-SHA384.		
	<i>TLS-RSA-WITH-SEED-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-SEED-CBC-SHA.		
	<i>TLS-RSA-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-RSA-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-RSA-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-RSA-WITH-ARIA-256-CBC-SHA384.		
	<i>TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-128-CBC-SHA256.		
	<i>TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-RSA-WITH-ARIA-256-CBC-SHA384.		
	<i>TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC-SHA256</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-128-CBC_SHA256.		
	<i>TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC-SHA384</i>	Cipher suite TLS-ECDHE-ECDSA-WITH-ARIA-256-CBC_SHA384.		
	<i>TLS-ECDHE-RSA-WITH-RC4-128-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-RC4-128-SHA.		
	<i>TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-ECDHE-RSA-WITH-3DES-EDE-CBC-SHA.		

Parameter	Description	Type	Size	Default																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA</i></td><td>Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.</td></tr><tr><td><i>TLS-RSA-WITH-3DES-EDE-CBC-SHA</i></td><td>Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.</td></tr><tr><td><i>TLS-RSA-WITH-RC4-128-MD5</i></td><td>Cipher suite TLS-RSA-WITH-RC4-128-MD5.</td></tr><tr><td><i>TLS-RSA-WITH-RC4-128-SHA</i></td><td>Cipher suite TLS-RSA-WITH-RC4-128-SHA.</td></tr><tr><td><i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.</td></tr><tr><td><i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.</td></tr><tr><td><i>TLS-RSA-WITH-DES-CBC-SHA</i></td><td>Cipher suite TLS-RSA-WITH-DES-CBC-SHA.</td></tr></table>	Option	Description	<i>TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.	<i>TLS-RSA-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.	<i>TLS-RSA-WITH-RC4-128-MD5</i>	Cipher suite TLS-RSA-WITH-RC4-128-MD5.	<i>TLS-RSA-WITH-RC4-128-SHA</i>	Cipher suite TLS-RSA-WITH-RC4-128-SHA.	<i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.	<i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.	<i>TLS-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-DES-CBC-SHA.			
	Option	Description																		
	<i>TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-3DES-EDE-CBC-SHA.																		
	<i>TLS-RSA-WITH-3DES-EDE-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-3DES-EDE-CBC-SHA.																		
	<i>TLS-RSA-WITH-RC4-128-MD5</i>	Cipher suite TLS-RSA-WITH-RC4-128-MD5.																		
	<i>TLS-RSA-WITH-RC4-128-SHA</i>	Cipher suite TLS-RSA-WITH-RC4-128-SHA.																		
	<i>TLS-DHE-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-RSA-WITH-DES-CBC-SHA.																		
	<i>TLS-DHE-DSS-WITH-DES-CBC-SHA</i>	Cipher suite TLS-DHE-DSS-WITH-DES-CBC-SHA.																		
<i>TLS-RSA-WITH-DES-CBC-SHA</i>	Cipher suite TLS-RSA-WITH-DES-CBC-SHA.																			
priority	SSL/TLS cipher suites priority.	integer	Minimum value: 0 Maximum value: 4294967295	0																
versions	SSL/TLS versions that the cipher suite can be used with.	option	-	ssl-3.0 tls-1.0 tls-1.1 tls-1.2 tls-1.3																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ssl-3.0</i></td><td>SSL 3.0.</td></tr><tr><td><i>tls-1.0</i></td><td>TLS 1.0.</td></tr><tr><td><i>tls-1.1</i></td><td>TLS 1.1.</td></tr><tr><td><i>tls-1.2</i></td><td>TLS 1.2.</td></tr><tr><td><i>tls-1.3</i></td><td>TLS 1.3.</td></tr></table>	Option	Description	<i>ssl-3.0</i>	SSL 3.0.	<i>tls-1.0</i>	TLS 1.0.	<i>tls-1.1</i>	TLS 1.1.	<i>tls-1.2</i>	TLS 1.2.	<i>tls-1.3</i>	TLS 1.3.							
	Option	Description																		
	<i>ssl-3.0</i>	SSL 3.0.																		
	<i>tls-1.0</i>	TLS 1.0.																		
	<i>tls-1.1</i>	TLS 1.1.																		
	<i>tls-1.2</i>	TLS 1.2.																		
<i>tls-1.3</i>	TLS 1.3.																			

config firewall vip6

Configure virtual IP for IPv6.