

config metadata

Parameter	Description	Type	Size	Default
id	ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0
metaid	Meta ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0
valueid	Value ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0

config ips sensor

Configure IPS sensor.

```
config ips sensor
  Description: Configure IPS sensor.
  edit <name>
    set block-malicious-url [disable|enable]
    set comment {var-string}
    config entries
      Description: IPS sensor filter.
      edit <id>
        set action [pass|block|...]
        set application {user}
        set cve <cve-entry1>, <cve-entry2>, ...
        set default-action [all|pass|...]
        set default-status [all|enable|...]
        config exempt-ip
          Description: Traffic from selected source or destination IP addresses is
          exempt from this signature.
          edit <id>
            set dst-ip {ipv4-classnet}
            set src-ip {ipv4-classnet}
          next
        end
        set last-modified {user}
        set location {user}
        set log [disable|enable]
        set log-attack-context [disable|enable]
        set log-packet [disable|enable]
        set os {user}
```

```

        set protocol {user}
        set quarantine [none|attacker]
        set quarantine-expiry {user}
        set quarantine-log [disable|enable]
        set rate-count {integer}
        set rate-duration {integer}
        set rate-mode [periodical|continuous]
        set rate-track [none|src-ip|...]
        set rule <id1>, <id2>, ...
        set severity {user}
        set status [disable|enable|...]
        set vuln-type <id1>, <id2>, ...
    next
end
set extended-log [enable|disable]
set replacemsg-group {string}
set scan-botnet-connections [disable|block|...]
next
end

```

config ips sensor

Parameter	Description	Type	Size	Default						
block-malicious-url	Enable/disable malicious URL blocking.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable malicious URL blocking.</td></tr><tr><td><i>enable</i></td><td>Enable malicious URL blocking.</td></tr></table>	Option	Description	<i>disable</i>	Disable malicious URL blocking.	<i>enable</i>	Enable malicious URL blocking.			
Option	Description									
<i>disable</i>	Disable malicious URL blocking.									
<i>enable</i>	Enable malicious URL blocking.									
comment	Comment.	var-string	Maximum length: 255							
extended-log	Enable/disable extended logging.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
name	Sensor name.	string	Maximum length: 35							
replacemsg-group	Replacement message group.	string	Maximum length: 35							
scan-botnet-connections	Block or monitor connections to Botnet servers, or disable Botnet scanning.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>disable</i>	Do not scan connections to botnet servers.		
	<i>block</i>	Block connections to botnet servers.		
	<i>monitor</i>	Log connections to botnet servers.		

config entries

Parameter	Description	Type	Size	Default
action	Action taken with traffic in which signatures are detected.	option	-	default
	Option	Description		
	<i>pass</i>	Pass or allow matching traffic.		
	<i>block</i>	Block or drop matching traffic.		
	<i>reset</i>	Reset sessions for matching traffic.		
	<i>default</i>	Pass or drop matching traffic, depending on the default action of the signature.		
application	Operating systems to be protected. Use all for every application and other for unlisted application.	user	Not Specified	all
cve <cve-entry>	List of CVE IDs of the signatures to add to the sensor. CVE IDs or CVE wildcards.	string	Maximum length: 19	
default-action	Signature default action filter.	option	-	all
	Option	Description		
	<i>all</i>	Selects signatures with any default action.		
	<i>pass</i>	Selects signatures with default action 'pass'.		
	<i>block</i>	Selects signatures with default action 'block'.		
default-status	Signature default status filter.	option	-	all
	Option	Description		
	<i>all</i>	Selects signatures with any default status.		
	<i>enable</i>	Selects signatures enabled by default.		
	<i>disable</i>	Selects signatures disabled by default.		

Parameter	Description	Type	Size	Default						
id	Rule ID in IPS database.	integer	Minimum value: 0 Maximum value: 4294967295	0						
last-modified	Filter by signature last modified date. Formats: before <date>, after <date>, between <start-date> <end-date>.	user	Not Specified							
location	Protect client or server traffic.	user	Not Specified	all						
log	Enable/disable logging of signatures included in filter.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable logging of selected rules.</td></tr><tr><td>enable</td><td>Enable logging of selected rules.</td></tr></table>	Option	Description	disable	Disable logging of selected rules.	enable	Enable logging of selected rules.			
Option	Description									
disable	Disable logging of selected rules.									
enable	Enable logging of selected rules.									
log-attack-context	Enable/disable logging of attack context: URL buffer, header buffer, body buffer, packet buffer.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable logging of detailed attack context.</td></tr><tr><td>enable</td><td>Enable logging of detailed attack context.</td></tr></table>	Option	Description	disable	Disable logging of detailed attack context.	enable	Enable logging of detailed attack context.			
Option	Description									
disable	Disable logging of detailed attack context.									
enable	Enable logging of detailed attack context.									
log-packet	Enable/disable packet logging. Enable to save the packet that triggers the filter. You can download the packets in pcap format for diagnostic use.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable packet logging of selected rules.</td></tr><tr><td>enable</td><td>Enable packet logging of selected rules.</td></tr></table>	Option	Description	disable	Disable packet logging of selected rules.	enable	Enable packet logging of selected rules.			
Option	Description									
disable	Disable packet logging of selected rules.									
enable	Enable packet logging of selected rules.									
os	Operating systems to be protected. Use all for every operating system and other for unlisted operating systems.	user	Not Specified	all						
protocol	Protocols to be examined. Use all for every protocol and other for unlisted protocols.	user	Not Specified	all						
quarantine	Quarantine method.	option	-	none						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>none</td><td>Quarantine is disabled.</td></tr></table>	Option	Description	none	Quarantine is disabled.					
Option	Description									
none	Quarantine is disabled.									

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>attacker</i>	Block all traffic sent from attacker's IP address. The attacker's IP address is also added to the banned user list. The target's address is not affected.		
quarantine-expiry	Duration of quarantine. Requires quarantine set to attacker.	user	Not Specified	5m
quarantine-log	Enable/disable quarantine logging.	option	-	enable
	Option	Description		
	<i>disable</i>	Disable quarantine logging.		
	<i>enable</i>	Enable quarantine logging.		
rate-count	Count of the rate.	integer	Minimum value: 0 Maximum value: 65535	0
rate-duration	Duration (sec) of the rate.	integer	Minimum value: 1 Maximum value: 65535	60
rate-mode	Rate limit mode.	option	-	continuous
	Option	Description		
	<i>periodical</i>	Allow configured number of packets every rate-duration.		
	<i>continuous</i>	Block packets once the rate is reached.		
rate-track	Track the packet protocol field.	option	-	none
	Option	Description		
	<i>none</i>	none		
	<i>src-ip</i>	Source IP.		
	<i>dest-ip</i>	Destination IP.		
	<i>dhcp-client-mac</i>	DHCP client.		
	<i>dns-domain</i>	DNS domain.		

Parameter	Description	Type	Size	Default								
rule <id>	Identifies the predefined or custom IPS signatures to add to the sensor. Rule IPS.	integer	Minimum value: 0 Maximum value: 4294967295									
severity	Relative severity of the signature, from info to critical. Log messages generated by the signature include the severity.	user	Not Specified	all								
status	Status of the signatures included in filter. Only those filters with a status to enable are used.	option	-	default								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable status of selected rules.</td></tr><tr><td>enable</td><td>Enable status of selected rules.</td></tr><tr><td>default</td><td>Default.</td></tr></table>				Option	Description	disable	Disable status of selected rules.	enable	Enable status of selected rules.	default	Default.
Option	Description											
disable	Disable status of selected rules.											
enable	Enable status of selected rules.											
default	Default.											
vuln-type <id>	List of signature vulnerability types to filter by. Vulnerability type ID.	integer	Minimum value: 0 Maximum value: 4294967295									

config exempt-ip

Parameter	Description	Type	Size	Default
dst-ip	Destination IP address and netmask (applies to packet matching the signature).	ipv4-classnet	Not Specified	0.0.0.0 0.0.0.0
id	Exempt IP ID.	integer	Minimum value: 0 Maximum value: 4294967295	0
src-ip	Source IP address and netmask (applies to packet matching the signature).	ipv4-classnet	Not Specified	0.0.0.0 0.0.0.0

config ips settings

Configure IPS VDOM parameter.

```
config ips settings
  Description: Configure IPS VDOM parameter.
  set ips-packet-quota {integer}
  set packet-log-history {integer}
```