

Parameter	Description	Type	Size	Default
set-weight	BGP weight for routing table.	integer	Minimum value: 0 Maximum value: 4294967295	

config router setting

Configure router settings.

```
config router setting
    Description: Configure router settings.
    set hostname {string}
    set show-filter {string}
end
```

config router setting

Parameter	Description	Type	Size	Default
hostname	Hostname for this virtual domain router.	string	Maximum length: 14	
show-filter	Prefix-list as filter for showing routes.	string	Maximum length: 35	

config router static

Configure IPv4 static routing tables.

```
config router static
    Description: Configure IPv4 static routing tables.
    edit <seq-num>
        set bfd [enable|disable]
        set blackhole [enable|disable]
        set comment {var-string}
        set device {string}
        set distance {integer}
        set dst {ipv4-classnet}
        set dstaddr {string}
        set dynamic-gateway [enable|disable]
        set gateway {ipv4-address}
        set internet-service {integer}
        set internet-service-custom {string}
        set link-monitor-exempt [enable|disable]
        set preferred-source {ipv4-address}
        set priority {integer}
        set sdwan-zone <name1>, <name2>, ...
        set src {ipv4-classnet}
```

```

        set status [enable|disable]
        set tag {integer}
        set vrf {integer}
        set weight {integer}
    next
end

```

config router static

Parameter	Description	Type	Size	Default						
bfd	Enable/disable Bidirectional Forwarding Detection (BFD).	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable Bidirectional Forwarding Detection (BFD).</td></tr><tr><td><i>disable</i></td><td>Disable Bidirectional Forwarding Detection (BFD).</td></tr></table>	Option	Description	<i>enable</i>	Enable Bidirectional Forwarding Detection (BFD).	<i>disable</i>	Disable Bidirectional Forwarding Detection (BFD).			
Option	Description									
<i>enable</i>	Enable Bidirectional Forwarding Detection (BFD).									
<i>disable</i>	Disable Bidirectional Forwarding Detection (BFD).									
blackhole	Enable/disable black hole.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable black hole.</td></tr><tr><td><i>disable</i></td><td>Disable black hole.</td></tr></table>	Option	Description	<i>enable</i>	Enable black hole.	<i>disable</i>	Disable black hole.			
Option	Description									
<i>enable</i>	Enable black hole.									
<i>disable</i>	Disable black hole.									
comment	Optional comments.	var-string	Maximum length: 255							
device	Gateway out interface or tunnel.	string	Maximum length: 35							
distance	Administrative distance.	integer	Minimum value: 1 Maximum value: 255	10						
dst	Destination IP and mask for this route.	ipv4-classnet	Not Specified	0.0.0.0 0.0.0.0						
dstaddr	Name of firewall address or address group.	string	Maximum length: 79							
dynamic-gateway	Enable use of dynamic gateway retrieved from a DHCP or PPP server.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable dynamic gateway.</td></tr><tr><td><i>disable</i></td><td>Disable dynamic gateway.</td></tr></table>	Option	Description	<i>enable</i>	Enable dynamic gateway.	<i>disable</i>	Disable dynamic gateway.			
Option	Description									
<i>enable</i>	Enable dynamic gateway.									
<i>disable</i>	Disable dynamic gateway.									

Parameter	Description	Type	Size	Default						
gateway	Gateway IP for this route.	ipv4-address	Not Specified	0.0.0.0						
internet-service	Application ID in the Internet service database.	integer	Minimum value: 0 Maximum value: 4294967295	0						
internet-service-custom	Application name in the Internet service custom database.	string	Maximum length: 64							
link-monitor-exempt	Enable/disable withdrawal of this static route when link monitor or health check is down.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Keep this static route when link monitor or health check is down.</td></tr><tr><td><i>disable</i></td><td>Withdraw this static route when link monitor or health check is down. (default)</td></tr></table>				Option	Description	<i>enable</i>	Keep this static route when link monitor or health check is down.	<i>disable</i>	Withdraw this static route when link monitor or health check is down. (default)
Option	Description									
<i>enable</i>	Keep this static route when link monitor or health check is down.									
<i>disable</i>	Withdraw this static route when link monitor or health check is down. (default)									
preferred-source	Preferred source IP for this route.	ipv4-address	Not Specified	0.0.0.0						
priority	Administrative priority.	integer	Minimum value: 1 Maximum value: 65535	1						
sdwan-zone <name>	Choose SD-WAN Zone. SD-WAN zone name.	string	Maximum length: 79							
seq-num	Sequence number.	integer	Minimum value: 0 Maximum value: 4294967295	0						
src	Source prefix for this route.	ipv4-classnet	Not Specified	0.0.0.0 0.0.0.0						
status	Enable/disable this static route.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable static route.</td></tr><tr><td><i>disable</i></td><td>Disable static route.</td></tr></table>				Option	Description	<i>enable</i>	Enable static route.	<i>disable</i>	Disable static route.
Option	Description									
<i>enable</i>	Enable static route.									
<i>disable</i>	Disable static route.									

Parameter	Description	Type	Size	Default
tag	Route tag.	integer	Minimum value: 0 Maximum value: 4294967295	0
vrf	Virtual Routing Forwarding ID.	integer	Minimum value: 0 Maximum value: 251	unspecified
weight	Administrative weight.	integer	Minimum value: 0 Maximum value: 255	0

config router static6

Configure IPv6 static routing tables.

```

config router static6
    Description: Configure IPv6 static routing tables.
    edit <seq-num>
        set bfd [enable|disable]
        set blackhole [enable|disable]
        set comment {var-string}
        set device {string}
        set devindex {integer}
        set distance {integer}
        set dst {ipv6-network}
        set dstaddr {string}
        set dynamic-gateway [enable|disable]
        set gateway {ipv6-address}
        set link-monitor-exempt [enable|disable]
        set priority {integer}
        set sdwan-zone <name1>, <name2>, ...
        set status [enable|disable]
        set vrf {integer}
        set weight {integer}
    next
end

```

config router static6

Parameter	Description	Type	Size	Default
bfd	Enable/disable Bidirectional Forwarding Detection (BFD).	option	-	disable