

```

config system sdn-proxy
  Description: Configure SDN proxy.
  edit <name>
    set password {password_aes256}
    set server {string}
    set server-port {integer}
    set type [general|fortimanager]
    set username {string}
  next
end

```

config system sdn-proxy

Parameter	Description	Type	Size	Default
name	SDN proxy name.	string	Maximum length: 35	
password	SDN proxy password.	password_aes256	Not Specified	
server	Server address of the SDN proxy.	string	Maximum length: 127	
server-port	Port number of the SDN proxy.	integer	Minimum value: 0 Maximum value: 65535	0
type	Type of SDN proxy.	option	-	general
	Option	Description		
	general	General HTTP proxy.		
	fortimanager	FortiManager SDN proxy.		
username	SDN proxy username.	string	Maximum length: 64	

config system sdwan

Configure redundant Internet connections with multiple outbound links and health-check profiles.

```

config system sdwan
  Description: Configure redundant Internet connections with multiple outbound links and health-check profiles.
  set app-perf-log-period {integer}
  config duplication
    Description: Create SD-WAN duplication rule.
    edit <id>
      set dstaddr <name1>, <name2>, ...
      set dstaddr6 <name1>, <name2>, ...
    next
  next
end

```

```

set dstintf <name1>, <name2>, ...
set packet-de-duplication [enable|disable]
set packet-duplication [disable|force|...]
set service <name1>, <name2>, ...
set service-id <id1>, <id2>, ...
set sla-match-service [enable|disable]
set srcaddr <name1>, <name2>, ...
set srcaddr6 <name1>, <name2>, ...
set srcintf <name1>, <name2>, ...

```

```

next
end

```

```

set duplication-max-num {integer}
set fail-alert-interfaces <name1>, <name2>, ...
set fail-detect [enable|disable]
config health-check

```

Description: SD-WAN status checking or health checking. Identify a server on the Internet and determine how SD-WAN verifies that the FortiGate can communicate with it.

```

edit <name>
set addr-mode [ipv4|ipv6]
set class-id {integer}
set detect-mode [active|passive|...]
set diffservcode {user}
set dns-match-ip {ipv4-address}
set dns-request-domain {string}
set embed-measured-health [enable|disable]
set failtime {integer}
set ftp-file {string}
set ftp-mode [passive|port]
set ha-priority {integer}
set http-agent {string}
set http-get {string}
set http-match {string}
set interval {integer}
set members <seq-num1>, <seq-num2>, ...
set mos-codec [g711|g722|...]
set packet-size {integer}
set password {password}
set port {integer}
set probe-count {integer}
set probe-packets [disable|enable]
set probe-timeout {integer}
set protocol [ping|tcp-echo|...]
set quality-measured-method [half-open|half-close]
set recoverytime {integer}
set security-mode [none|authentication]
set server {string}
config sla

```

Description: Service level agreement (SLA).

```

edit <id>
set jitter-threshold {integer}
set latency-threshold {integer}
set link-cost-factor {option1}, {option2}, ...
set mos-threshold {string}
set packetloss-threshold {integer}
set priority-in-sla {integer}
set priority-out-sla {integer}

```

```

        next
    end
    set sla-fail-log-period {integer}
    set sla-id-redistribute {integer}
    set sla-pass-log-period {integer}
    set source {ipv4-address}
    set source6 {ipv6-address}
    set system-dns [disable|enable]
    set threshold-alert-jitter {integer}
    set threshold-alert-latency {integer}
    set threshold-alert-packetloss {integer}
    set threshold-warning-jitter {integer}
    set threshold-warning-latency {integer}
    set threshold-warning-packetloss {integer}
    set update-cascade-interface [enable|disable]
    set update-static-route [enable|disable]
    set user {string}
    set vrf {integer}
    next
end
set load-balance-mode [source-ip-based|weight-based|...]
config members
    Description: FortiGate interfaces added to the SD-WAN.
    edit <seq-num>
        set comment {var-string}
        set cost {integer}
        set gateway {ipv4-address}
        set gateway6 {ipv6-address}
        set ingress-spillover-threshold {integer}
        set interface {string}
        set preferred-source {ipv4-address}
        set priority {integer}
        set priority6 {integer}
        set source {ipv4-address}
        set source6 {ipv6-address}
        set spillover-threshold {integer}
        set status [disable|enable]
        set transport-group {integer}
        set volume-ratio {integer}
        set weight {integer}
        set zone {string}
    next
end
config neighbor
    Description: Create SD-WAN neighbor from BGP neighbor table to control route
    advertisements according to SLA status.
    edit <ip>
        set health-check {string}
        set member <seq-num1>, <seq-num2>, ...
        set minimum-sla-meet-members {integer}
        set mode [sla|speedtest]
        set role [standalone|primary|...]
        set service-id {integer}
        set sla-id {integer}
    next
end

```

```
set neighbor-hold-boot-time {integer}
set neighbor-hold-down [enable|disable]
set neighbor-hold-down-time {integer}
config service
```

Description: Create SD-WAN rules (also called services) to control how sessions are distributed to interfaces in the SD-WAN.

```
edit <id>
  set addr-mode [ipv4|ipv6]
  set agent-exclusive [enable|disable]
  set bandwidth-weight {integer}
  set default [enable|disable]
  set dscp-forward [enable|disable]
  set dscp-forward-tag {user}
  set dscp-reverse [enable|disable]
  set dscp-reverse-tag {user}
  set dst <name1>, <name2>, ...
  set dst-negate [enable|disable]
  set dst6 <name1>, <name2>, ...
  set end-port {integer}
  set end-src-port {integer}
  set gateway [enable|disable]
  set groups <name1>, <name2>, ...
  set hash-mode [round-robin|source-ip-based|...]
  set health-check <name1>, <name2>, ...
  set hold-down-time {integer}
  set input-device <name1>, <name2>, ...
  set input-device-negate [enable|disable]
  set input-zone <name1>, <name2>, ...
  set internet-service [enable|disable]
  set internet-service-app-ctrl <id1>, <id2>, ...
  set internet-service-app-ctrl-category <id1>, <id2>, ...
  set internet-service-app-ctrl-group <name1>, <name2>, ...
  set internet-service-custom <name1>, <name2>, ...
  set internet-service-custom-group <name1>, <name2>, ...
  set internet-service-group <name1>, <name2>, ...
  set internet-service-name <name1>, <name2>, ...
  set jitter-weight {integer}
  set latency-weight {integer}
  set link-cost-factor [latency|jitter|...]
  set link-cost-threshold {integer}
  set load-balance [enable|disable]
  set minimum-sla-meet-members {integer}
  set mode [auto|manual|...]
  set name {string}
  set packet-loss-weight {integer}
  set passive-measurement [enable|disable]
  set priority-members <seq-num1>, <seq-num2>, ...
  set priority-zone <name1>, <name2>, ...
  set protocol {integer}
  set quality-link {integer}
  set role [standalone|primary|...]
  set shortcut [enable|disable]
  set shortcut-priority [enable|disable|...]
config sla
  Description: Service level agreement (SLA).
  edit <health-check>
```

```

        set id {integer}
    next
end
set sla-compare-method [order|number]
set sla-stickiness [enable|disable]
set src <name1>, <name2>, ...
set src-negate [enable|disable]
set src6 <name1>, <name2>, ...
set standalone-action [enable|disable]
set start-port {integer}
set start-src-port {integer}
set status [enable|disable]
set tie-break [zone|cfg-order|...]
set tos {user}
set tos-mask {user}
set use-shortcut-sla [enable|disable]
set users <name1>, <name2>, ...
set zone-mode [enable|disable]
next
end
set speedtest-bypass-routing [disable|enable]
set status [disable|enable]
config zone
    Description: Configure SD-WAN zones.
    edit <name>
        set advpn-health-check {string}
        set advpn-select [enable|disable]
        set minimum-sla-meet-members {integer}
        set service-sla-tie-break [cfg-order|fib-best-match|...]
    next
end
end

```

config system sdwan

Parameter	Description	Type	Size	Default
app-perf-log-period	Time interval in seconds that application performance logs are generated.	integer	Minimum value: 0 Maximum value: 3600	0
duplication-max-num	Maximum number of interface members a packet is duplicated in the SD-WAN zone.	integer	Minimum value: 2 Maximum value: 4	2
fail-alert-interfaces <name>	Physical interfaces that will be alerted. Physical interface name.	string	Maximum length: 79	
fail-detect	Enable/disable SD-WAN Internet connection status checking (failure detection).	option	-	disable

Parameter	Description	Type	Size	Default												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable status checking.</td></tr><tr><td><i>disable</i></td><td>Disable status checking.</td></tr></table>	Option	Description	<i>enable</i>	Enable status checking.	<i>disable</i>	Disable status checking.									
	Option	Description														
	<i>enable</i>	Enable status checking.														
<i>disable</i>	Disable status checking.															
load-balance-mode	Algorithm or mode to use for load balancing Internet traffic to SD-WAN members.	option	-	source-ip-based												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>source-ip-based</i></td><td>Source IP load balancing. All traffic from a source IP is sent to the same interface.</td></tr><tr><td><i>weight-based</i></td><td>Weight-based load balancing. Interfaces with higher weights have higher priority and get more traffic.</td></tr><tr><td><i>usage-based</i></td><td>Usage-based load balancing. All traffic is sent to the first interface on the list. When the bandwidth on that interface exceeds the spill-over limit new traffic is sent to the next interface.</td></tr><tr><td><i>source-dest-ip-based</i></td><td>Source and destination IP load balancing. All traffic from a source IP to a destination IP is sent to the same interface.</td></tr><tr><td><i>measured-volume-based</i></td><td>Volume-based load balancing. Traffic is load balanced based on traffic volume (in bytes). More traffic is sent to interfaces with higher volume ratios.</td></tr></table>	Option	Description	<i>source-ip-based</i>	Source IP load balancing. All traffic from a source IP is sent to the same interface.	<i>weight-based</i>	Weight-based load balancing. Interfaces with higher weights have higher priority and get more traffic.	<i>usage-based</i>	Usage-based load balancing. All traffic is sent to the first interface on the list. When the bandwidth on that interface exceeds the spill-over limit new traffic is sent to the next interface.	<i>source-dest-ip-based</i>	Source and destination IP load balancing. All traffic from a source IP to a destination IP is sent to the same interface.	<i>measured-volume-based</i>	Volume-based load balancing. Traffic is load balanced based on traffic volume (in bytes). More traffic is sent to interfaces with higher volume ratios.			
	Option	Description														
	<i>source-ip-based</i>	Source IP load balancing. All traffic from a source IP is sent to the same interface.														
	<i>weight-based</i>	Weight-based load balancing. Interfaces with higher weights have higher priority and get more traffic.														
	<i>usage-based</i>	Usage-based load balancing. All traffic is sent to the first interface on the list. When the bandwidth on that interface exceeds the spill-over limit new traffic is sent to the next interface.														
	<i>source-dest-ip-based</i>	Source and destination IP load balancing. All traffic from a source IP to a destination IP is sent to the same interface.														
<i>measured-volume-based</i>	Volume-based load balancing. Traffic is load balanced based on traffic volume (in bytes). More traffic is sent to interfaces with higher volume ratios.															
neighbor-hold-boot-time	Waiting period in seconds when switching from the primary neighbor to the secondary neighbor from the neighbor start.	integer	Minimum value: 0 Maximum value: 10000000	0												
neighbor-hold-down	Enable/disable hold switching from the secondary neighbor to the primary neighbor.	option	-	disable												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable hold switching from the secondary neighbor to the primary neighbor.</td></tr><tr><td><i>disable</i></td><td>Disable hold switching from the secondary neighbor to the primary neighbor.</td></tr></table>	Option	Description	<i>enable</i>	Enable hold switching from the secondary neighbor to the primary neighbor.	<i>disable</i>	Disable hold switching from the secondary neighbor to the primary neighbor.									
	Option	Description														
<i>enable</i>	Enable hold switching from the secondary neighbor to the primary neighbor.															
<i>disable</i>	Disable hold switching from the secondary neighbor to the primary neighbor.															
neighbor-hold-down-time	Waiting period in seconds when switching from the secondary neighbor to the primary neighbor when hold-down is disabled.	integer	Minimum value: 0 Maximum value: 10000000	0												
speedtest-bypass-routing	Enable/disable bypass routing when speedtest on a SD-WAN member.	option	-	disable												

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>disable</i>	Disable SD-WAN.		
	<i>enable</i>	Enable SD-WAN.		
status	Enable/disable SD-WAN.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable SD-WAN.		
	<i>enable</i>	Enable SD-WAN.		

config duplication

Parameter	Description	Type	Size	Default
dstaddr <name>	Destination address or address group names. Address or address group name.	string	Maximum length: 79	
dstaddr6 <name>	Destination address6 or address6 group names. Address6 or address6 group name.	string	Maximum length: 79	
dstintf <name>	Outgoing (egress) interfaces or zones. Interface, zone or SDWAN zone name.	string	Maximum length: 79	
id	Duplication rule ID.	integer	Minimum value: 1 Maximum value: 255	0
packet-de- duplication	Enable/disable discarding of packets that have been duplicated.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable discarding of packets that have been duplicated.		
	<i>disable</i>	Disable discarding of packets that have been duplicated.		
packet- duplication	Configure packet duplication method.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable packet duplication.		
	<i>force</i>	Duplicate packets across all interface members of the SD-WAN zone.		
	<i>on-demand</i>	Duplicate packets across all interface members of the SD-WAN zone based on the link quality.		

Parameter	Description	Type	Size	Default						
service <name>	Service and service group name. Service and service group name.	string	Maximum length: 79							
service-id <id>	SD-WAN service rule ID list. SD-WAN service rule ID.	integer	Minimum value: 0 Maximum value: 4294967295							
sla-match-service	Enable/disable packet duplication matching health-check SLAs in service rule.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable packet duplication matching health-check SLAs in service rule (matching all SLAs of current defined service).</td></tr><tr><td><i>disable</i></td><td>Disable packet duplication matching health-check SLAs in service rule (matching all SLAs of all defined health-check).</td></tr></table>				Option	Description	<i>enable</i>	Enable packet duplication matching health-check SLAs in service rule (matching all SLAs of current defined service).	<i>disable</i>	Disable packet duplication matching health-check SLAs in service rule (matching all SLAs of all defined health-check).
Option	Description									
<i>enable</i>	Enable packet duplication matching health-check SLAs in service rule (matching all SLAs of current defined service).									
<i>disable</i>	Disable packet duplication matching health-check SLAs in service rule (matching all SLAs of all defined health-check).									
srcaddr <name>	Source address or address group names. Address or address group name.	string	Maximum length: 79							
srcaddr6 <name>	Source address6 or address6 group names. Address6 or address6 group name.	string	Maximum length: 79							
srcintf <name>	Incoming (ingress) interfaces or zones. Interface, zone or SDWAN zone name.	string	Maximum length: 79							

config health-check

Parameter	Description	Type	Size	Default
addr-mode	Address mode (IPv4 or IPv6).	option	-	ipv4
	Option	Description		
	ipv4	IPv4 mode.		
	ipv6	IPv6 mode.		
class-id	Traffic class ID.	integer	Minimum value: 0 Maximum value: 4294967295	0
detect-mode	The mode determining how to detect the server.	option	-	active

Parameter	Description	Type	Size	Default												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>active</i></td><td>The probes are sent actively.</td></tr><tr><td><i>passive</i></td><td>The traffic measures health without probes.</td></tr><tr><td><i>prefer-passive</i></td><td>The probes are sent in case of no new traffic.</td></tr><tr><td><i>remote</i></td><td>Link health obtained from remote peers.</td></tr><tr><td><i>agent-based</i></td><td>Traffic health is measured from the fabric connectors.</td></tr></table>	Option	Description	<i>active</i>	The probes are sent actively.	<i>passive</i>	The traffic measures health without probes.	<i>prefer-passive</i>	The probes are sent in case of no new traffic.	<i>remote</i>	Link health obtained from remote peers.	<i>agent-based</i>	Traffic health is measured from the fabric connectors.			
	Option	Description														
	<i>active</i>	The probes are sent actively.														
	<i>passive</i>	The traffic measures health without probes.														
	<i>prefer-passive</i>	The probes are sent in case of no new traffic.														
	<i>remote</i>	Link health obtained from remote peers.														
<i>agent-based</i>	Traffic health is measured from the fabric connectors.															
diffservcode	Differentiated services code point (DSCP) in the IP header of the probe packet.	user	Not Specified													
dns-match-ip	Response IP expected from DNS server if the protocol is DNS.	ipv4-address	Not Specified	0.0.0.0												
dns-request-domain	Fully qualified domain name to resolve for the DNS probe.	string	Maximum length: 255	www.example.com												
embed-measured-health	Enable/disable embedding measured health information.	option	-	disable												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable embed measured health.</td></tr><tr><td><i>disable</i></td><td>Disable embed measured health.</td></tr></table>	Option	Description	<i>enable</i>	Enable embed measured health.	<i>disable</i>	Disable embed measured health.									
	Option	Description														
	<i>enable</i>	Enable embed measured health.														
<i>disable</i>	Disable embed measured health.															
failtime	Number of failures before server is considered lost.	integer	Minimum value: 1 Maximum value: 3600	5												
ftp-file	Full path and file name on the FTP server to download for FTP health-check to probe.	string	Maximum length: 254													
ftp-mode	FTP mode.	option	-	passive												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>passive</i></td><td>The FTP health-check initiates and establishes the data connection.</td></tr><tr><td><i>port</i></td><td>The FTP server initiates and establishes the data connection.</td></tr></table>	Option	Description	<i>passive</i>	The FTP health-check initiates and establishes the data connection.	<i>port</i>	The FTP server initiates and establishes the data connection.									
	Option	Description														
	<i>passive</i>	The FTP health-check initiates and establishes the data connection.														
<i>port</i>	The FTP server initiates and establishes the data connection.															
ha-priority	HA election priority.	integer	Minimum value: 1 Maximum value: 50	1												

Parameter	Description	Type	Size	Default								
http-agent	String in the http-agent field in the HTTP header.	string	Maximum length: 1024	Chrome/ Safari/								
http-get	URL used to communicate with the server if the protocol is HTTP.	string	Maximum length: 1024	/								
http-match	Response string expected from the server if the protocol is HTTP.	string	Maximum length: 1024									
interval	Status check interval in milliseconds, or the time between attempting to connect to the server.	integer	Minimum value: 20 Maximum value: 3600000	500								
members <seq-num>	Member sequence number list. Member sequence number.	integer	Minimum value: 0 Maximum value: 4294967295									
mos-codec	Codec to use for MOS calculation.	option	-	g711								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>g711</td><td>Calculate MOS based on the G.711 codec.</td></tr><tr><td>g722</td><td>Calculate MOS based on the G.722 codec.</td></tr><tr><td>g729</td><td>Calculate MOS based on the G.729 codec.</td></tr></table>				Option	Description	g711	Calculate MOS based on the G.711 codec.	g722	Calculate MOS based on the G.722 codec.	g729	Calculate MOS based on the G.729 codec.
Option	Description											
g711	Calculate MOS based on the G.711 codec.											
g722	Calculate MOS based on the G.722 codec.											
g729	Calculate MOS based on the G.729 codec.											
name	Status check or health check name.	string	Maximum length: 35									
packet-size	Packet size of a TWAMP test session.	integer	Minimum value: 0 Maximum value: 65535	124								
password	TWAMP controller password in authentication mode.	password	Not Specified									
port	Port number used to communicate with the server over the selected protocol.	integer	Minimum value: 0 Maximum value: 65535	0								
probe-count	Number of most recent probes that should be used to calculate latency and jitter.	integer	Minimum value: 5 Maximum value: 30	30								

Parameter	Description	Type	Size	Default																				
probe-packets	Enable/disable transmission of probe packets.	option	-	enable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable transmission of probe packets.</td></tr><tr><td><i>enable</i></td><td>Enable transmission of probe packets.</td></tr></table>	Option	Description	<i>disable</i>	Disable transmission of probe packets.	<i>enable</i>	Enable transmission of probe packets.																	
Option	Description																							
<i>disable</i>	Disable transmission of probe packets.																							
<i>enable</i>	Enable transmission of probe packets.																							
probe-timeout	Time to wait before a probe packet is considered lost.	integer	Minimum value: 20 Maximum value: 3600000	500																				
protocol	Protocol used to determine if the FortiGate can communicate with the server.	option	-	ping																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ping</i></td><td>Use PING to test the link with the server.</td></tr><tr><td><i>tcp-echo</i></td><td>Use TCP echo to test the link with the server.</td></tr><tr><td><i>udp-echo</i></td><td>Use UDP echo to test the link with the server.</td></tr><tr><td><i>http</i></td><td>Use HTTP-GET to test the link with the server.</td></tr><tr><td><i>https</i></td><td>Use HTTPS-GET to test the link with the server.</td></tr><tr><td><i>twamp</i></td><td>Use TWAMP to test the link with the server.</td></tr><tr><td><i>dns</i></td><td>Use DNS query to test the link with the server.</td></tr><tr><td><i>tcp-connect</i></td><td>Use a full TCP connection to test the link with the server.</td></tr><tr><td><i>ftp</i></td><td>Use FTP to test the link with the server.</td></tr></table>	Option	Description	<i>ping</i>	Use PING to test the link with the server.	<i>tcp-echo</i>	Use TCP echo to test the link with the server.	<i>udp-echo</i>	Use UDP echo to test the link with the server.	<i>http</i>	Use HTTP-GET to test the link with the server.	<i>https</i>	Use HTTPS-GET to test the link with the server.	<i>twamp</i>	Use TWAMP to test the link with the server.	<i>dns</i>	Use DNS query to test the link with the server.	<i>tcp-connect</i>	Use a full TCP connection to test the link with the server.	<i>ftp</i>	Use FTP to test the link with the server.			
Option	Description																							
<i>ping</i>	Use PING to test the link with the server.																							
<i>tcp-echo</i>	Use TCP echo to test the link with the server.																							
<i>udp-echo</i>	Use UDP echo to test the link with the server.																							
<i>http</i>	Use HTTP-GET to test the link with the server.																							
<i>https</i>	Use HTTPS-GET to test the link with the server.																							
<i>twamp</i>	Use TWAMP to test the link with the server.																							
<i>dns</i>	Use DNS query to test the link with the server.																							
<i>tcp-connect</i>	Use a full TCP connection to test the link with the server.																							
<i>ftp</i>	Use FTP to test the link with the server.																							
quality-measured-method	Method to measure the quality of tcp-connect.	option	-	half-open																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>half-open</i></td><td>Measure the round trip between syn and ack.</td></tr><tr><td><i>half-close</i></td><td>Measure the round trip between fin and ack.</td></tr></table>	Option	Description	<i>half-open</i>	Measure the round trip between syn and ack.	<i>half-close</i>	Measure the round trip between fin and ack.																	
Option	Description																							
<i>half-open</i>	Measure the round trip between syn and ack.																							
<i>half-close</i>	Measure the round trip between fin and ack.																							
recoverytime	Number of successful responses received before server is considered recovered.	integer	Minimum value: 1 Maximum value: 3600	5																				
security-mode	Twamp controller security mode.	option	-	none																				

Parameter	Description	Type	Size	Default						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>none</i></td><td>Unauthenticated mode.</td></tr><tr><td><i>authentication</i></td><td>Authenticated mode.</td></tr></table>				Option	Description	<i>none</i>	Unauthenticated mode.	<i>authentication</i>	Authenticated mode.
	Option	Description								
	<i>none</i>	Unauthenticated mode.								
<i>authentication</i>	Authenticated mode.									
server	IP address or FQDN name of the server.	string	Maximum length: 79							
sla-fail-log-period	Time interval in seconds that SLA fail log messages will be generated.	integer	Minimum value: 0 Maximum value: 3600	0						
sla-id-redistribute	Select the ID from the SLA sub-table. The selected SLA's priority value will be distributed into the routing table.	integer	Minimum value: 0 Maximum value: 32	0						
sla-pass-log-period	Time interval in seconds that SLA pass log messages will be generated.	integer	Minimum value: 0 Maximum value: 3600	0						
source	Source IP address used in the health-check packet to the server.	ipv4-address	Not Specified	0.0.0.0						
source6	Source IPv6 address used in the health-check packet to server.	ipv6-address	Not Specified	::						
system-dns	Enable/disable system DNS as the probe server.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable system DNS as the probe server.</td></tr><tr><td><i>enable</i></td><td>Enable system DNS as the probe server.</td></tr></table>				Option	Description	<i>disable</i>	Disable system DNS as the probe server.	<i>enable</i>	Enable system DNS as the probe server.
	Option	Description								
	<i>disable</i>	Disable system DNS as the probe server.								
<i>enable</i>	Enable system DNS as the probe server.									
threshold-alert-jitter	Alert threshold for jitter.	integer	Minimum value: 0 Maximum value: 4294967295	0						
threshold-alert-latency	Alert threshold for latency.	integer	Minimum value: 0 Maximum value: 4294967295	0						

Parameter	Description	Type	Size	Default
threshold-alert-packetloss	Alert threshold for packet loss.	integer	Minimum value: 0 Maximum value: 100	0
threshold-warning-jitter	Warning threshold for jitter.	integer	Minimum value: 0 Maximum value: 4294967295	0
threshold-warning-latency	Warning threshold for latency.	integer	Minimum value: 0 Maximum value: 4294967295	0
threshold-warning-packetloss	Warning threshold for packet loss.	integer	Minimum value: 0 Maximum value: 100	0
update-cascade-interface	Enable/disable update cascade interface.	option	-	enable
	Option		Description	
	<i>enable</i>		Enable update cascade interface.	
	<i>disable</i>		Disable update cascade interface.	
update-static-route	Enable/disable updating the static route.	option	-	enable
	Option		Description	
	<i>enable</i>		Enable updating the static route.	
	<i>disable</i>		Disable updating the static route.	
user	The user name to access probe server.	string	Maximum length: 64	
vrf	Virtual Routing Forwarding ID.	integer	Minimum value: 0 Maximum value: 251	0

config sla

Parameter	Description	Type	Size	Default
health-check	SD-WAN health-check.	string	Maximum length: 35	
id	SLA ID.	integer	Minimum value: 0 Maximum value: 4294967295	0

config members

Parameter	Description	Type	Size	Default
comment	Comments.	var-string	Maximum length: 255	
cost	Cost of this interface for services in SLA mode.	integer	Minimum value: 0 Maximum value: 4294967295	0
gateway	The default gateway for this interface. Usually the default gateway of the Internet service provider that this interface is connected to.	ipv4-address	Not Specified	0.0.0.0
gateway6	IPv6 gateway.	ipv6-address	Not Specified	::
ingress-spillover-threshold	Ingress spillover threshold for this interface. When this traffic volume threshold is reached, new sessions spill over to other interfaces in the SD-WAN.	integer	Minimum value: 0 Maximum value: 16776000	0
interface	Interface name.	string	Maximum length: 15	
preferred-source	Preferred source of route for this member.	ipv4-address	Not Specified	0.0.0.0
priority	Priority of the interface for IPv4. Used for SD-WAN rules or priority rules.	integer	Minimum value: 1 Maximum value: 65535	1

Parameter	Description	Type	Size	Default						
priority6	Priority of the interface for IPv6. Used for SD-WAN rules or priority rules.	integer	Minimum value: 1 Maximum value: 65535	1024						
seq-num	Sequence number.	integer	Minimum value: 0 Maximum value: 512	0						
source	Source IP address used in the health-check packet to the server.	ipv4-address	Not Specified	0.0.0.0						
source6	Source IPv6 address used in the health-check packet to the server.	ipv6-address	Not Specified	::						
spillover-threshold	Egress spillover threshold for this interface. When this traffic volume threshold is reached, new sessions spill over to other interfaces in the SD-WAN.	integer	Minimum value: 0 Maximum value: 16776000	0						
status	Enable/disable this interface in the SD-WAN.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable this interface in the SD-WAN.</td></tr><tr><td><i>enable</i></td><td>Enable this interface in the SD-WAN.</td></tr></table>				Option	Description	<i>disable</i>	Disable this interface in the SD-WAN.	<i>enable</i>	Enable this interface in the SD-WAN.
Option	Description									
<i>disable</i>	Disable this interface in the SD-WAN.									
<i>enable</i>	Enable this interface in the SD-WAN.									
transport-group	Measured transport group.	integer	Minimum value: 0 Maximum value: 255	0						
volume-ratio	Measured volume ratio.	integer	Minimum value: 1 Maximum value: 255	1						
weight	Weight of this interface for weighted load balancing. More traffic is directed to interfaces with higher weights.	integer	Minimum value: 1 Maximum value: 255	1						
zone	Zone name.	string	Maximum length: 35	virtual-wan-link						

config neighbor

Parameter	Description	Type	Size	Default								
health-check	SD-WAN health-check name.	string	Maximum length: 35									
ip	IP/IPv6 address of neighbor or neighbor-group name.	string	Maximum length: 45									
member <seq-num>	Member sequence number list. Member sequence number.	integer	Minimum value: 0 Maximum value: 4294967295									
minimum-sla-meet-members	Minimum number of members which meet SLA when the neighbor is preferred.	integer	Minimum value: 1 Maximum value: 255	1								
mode	What metric to select the neighbor.	option	-	sla								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>sla</td><td>Select neighbor based on SLA link quality.</td></tr><tr><td>speedtest</td><td>Select neighbor based on the speedtest status.</td></tr></table>				Option	Description	sla	Select neighbor based on SLA link quality.	speedtest	Select neighbor based on the speedtest status.		
Option	Description											
sla	Select neighbor based on SLA link quality.											
speedtest	Select neighbor based on the speedtest status.											
role	Role of neighbor.	option	-	standalone								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>standalone</td><td>Standalone neighbor.</td></tr><tr><td>primary</td><td>Primary neighbor.</td></tr><tr><td>secondary</td><td>Secondary neighbor.</td></tr></table>				Option	Description	standalone	Standalone neighbor.	primary	Primary neighbor.	secondary	Secondary neighbor.
Option	Description											
standalone	Standalone neighbor.											
primary	Primary neighbor.											
secondary	Secondary neighbor.											
service-id	SD-WAN service ID to work with the neighbor.	integer	Minimum value: 0 Maximum value: 4294967295	0								
sla-id	SLA ID.	integer	Minimum value: 0 Maximum value: 4294967295	0								

config service

Parameter	Description	Type	Size	Default						
addr-mode	Address mode (IPv4 or IPv6).	option	-	ipv4						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>ipv4</td><td>IPv4 mode.</td></tr><tr><td>ipv6</td><td>IPv6 mode.</td></tr></table>	Option	Description	ipv4	IPv4 mode.	ipv6	IPv6 mode.			
Option	Description									
ipv4	IPv4 mode.									
ipv6	IPv6 mode.									
agent-exclusive	Set/unset the service as agent use exclusively.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Set the service as agent use exclusively.</td></tr><tr><td>disable</td><td>Unset the service as agent use exclusively.</td></tr></table>	Option	Description	enable	Set the service as agent use exclusively.	disable	Unset the service as agent use exclusively.			
Option	Description									
enable	Set the service as agent use exclusively.									
disable	Unset the service as agent use exclusively.									
bandwidth-weight	Coefficient of reciprocal of available bidirectional bandwidth in the formula of custom-profile-1.	integer	Minimum value: 0 Maximum value: 10000000	0						
default	Enable/disable use of SD-WAN as default service.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable use of SD-WAN as default service.</td></tr><tr><td>disable</td><td>Disable use of SD-WAN as default service.</td></tr></table>	Option	Description	enable	Enable use of SD-WAN as default service.	disable	Disable use of SD-WAN as default service.			
Option	Description									
enable	Enable use of SD-WAN as default service.									
disable	Disable use of SD-WAN as default service.									
dscp-forward	Enable/disable forward traffic DSCP tag.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable use of forward DSCP tag.</td></tr><tr><td>disable</td><td>Disable use of forward DSCP tag.</td></tr></table>	Option	Description	enable	Enable use of forward DSCP tag.	disable	Disable use of forward DSCP tag.			
Option	Description									
enable	Enable use of forward DSCP tag.									
disable	Disable use of forward DSCP tag.									
dscp-forward-tag	Forward traffic DSCP tag.	user	Not Specified							
dscp-reverse	Enable/disable reverse traffic DSCP tag.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable use of reverse DSCP tag.</td></tr><tr><td>disable</td><td>Disable use of reverse DSCP tag.</td></tr></table>	Option	Description	enable	Enable use of reverse DSCP tag.	disable	Disable use of reverse DSCP tag.			
Option	Description									
enable	Enable use of reverse DSCP tag.									
disable	Disable use of reverse DSCP tag.									
dscp-reverse-tag	Reverse traffic DSCP tag.	user	Not Specified							

Parameter	Description	Type	Size	Default										
dst <name>	Destination address name. Address or address group name.	string	Maximum length: 79											
dst-negate	Enable/disable negation of destination address match.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable destination address negation.</td></tr><tr><td>disable</td><td>Disable destination address negation.</td></tr></table>	Option	Description	enable	Enable destination address negation.	disable	Disable destination address negation.							
Option	Description													
enable	Enable destination address negation.													
disable	Disable destination address negation.													
dst6 <name>	Destination address6 name. Address6 or address6 group name.	string	Maximum length: 79											
end-port	End destination port number.	integer	Minimum value: 0 Maximum value: 65535	65535										
end-src-port	End source port number.	integer	Minimum value: 0 Maximum value: 65535	65535										
gateway	Enable/disable SD-WAN service gateway.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable SD-WAN service gateway.</td></tr><tr><td>disable</td><td>Disable SD-WAN service gateway.</td></tr></table>	Option	Description	enable	Enable SD-WAN service gateway.	disable	Disable SD-WAN service gateway.							
Option	Description													
enable	Enable SD-WAN service gateway.													
disable	Disable SD-WAN service gateway.													
groups <name>	User groups. Group name.	string	Maximum length: 79											
hash-mode	Hash algorithm for selected priority members for load balance mode.	option	-	round-robin										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>round-robin</td><td>All traffic are distributed to selected interfaces in equal portions and circular order.</td></tr><tr><td>source-ip-based</td><td>All traffic from a source IP is sent to the same interface.</td></tr><tr><td>source-dest-ip-based</td><td>All traffic from a source IP to a destination IP is sent to the same interface.</td></tr><tr><td>inbandwidth</td><td>All traffic are distributed to a selected interface with most available bandwidth for incoming traffic.</td></tr></table>	Option	Description	round-robin	All traffic are distributed to selected interfaces in equal portions and circular order.	source-ip-based	All traffic from a source IP is sent to the same interface.	source-dest-ip-based	All traffic from a source IP to a destination IP is sent to the same interface.	inbandwidth	All traffic are distributed to a selected interface with most available bandwidth for incoming traffic.			
Option	Description													
round-robin	All traffic are distributed to selected interfaces in equal portions and circular order.													
source-ip-based	All traffic from a source IP is sent to the same interface.													
source-dest-ip-based	All traffic from a source IP to a destination IP is sent to the same interface.													
inbandwidth	All traffic are distributed to a selected interface with most available bandwidth for incoming traffic.													

Parameter	Description	Type	Size	Default
	Option	Description		
	outbandwidth	All traffic are distributed to a selected interface with most available bandwidth for outgoing traffic.		
	bibandwidth	All traffic are distributed to a selected interface with most available bandwidth for both incoming and outgoing traffic.		
health-check <name>	Health check list. Health check name.	string	Maximum length: 79	
hold-down-time	Waiting period in seconds when switching from the back-up member to the primary member.	integer	Minimum value: 0 Maximum value: 10000000	0
id	SD-WAN rule ID.	integer	Minimum value: 1 Maximum value: 4000	0
input-device <name>	Source interface name. Interface name.	string	Maximum length: 79	
input-device-negate	Enable/disable negation of input device match.	option	-	disable
	Option	Description		
	enable	Enable negation of input device match.		
	disable	Disable negation of input device match.		
input-zone <name>	Source input-zone name. Zone.	string	Maximum length: 79	
internet-service	Enable/disable use of Internet service for application-based load balancing.	option	-	disable
	Option	Description		
	enable	Enable cloud service to support application-based load balancing.		
	disable	Disable cloud service to support application-based load balancing.		
internet-service-app-ctrl <id>	Application control based Internet Service ID list. Application control based Internet Service ID.	integer	Minimum value: 0 Maximum value: 4294967295	

Parameter	Description	Type	Size	Default																
internet-service-app-ctrl-category <id>	IDs of one or more application control categories. Application control category ID.	integer	Minimum value: 0 Maximum value: 4294967295																	
internet-service-app-ctrl-group <name>	Application control based Internet Service group list. Application control based Internet Service group name.	string	Maximum length: 79																	
internet-service-custom <name>	Custom Internet service name list. Custom Internet service name.	string	Maximum length: 79																	
internet-service-custom-group <name>	Custom Internet Service group list. Custom Internet Service group name.	string	Maximum length: 79																	
internet-service-group <name>	Internet Service group list. Internet Service group name.	string	Maximum length: 79																	
internet-service-name <name>	Internet service name list. Internet service name.	string	Maximum length: 79																	
jitter-weight	Coefficient of jitter in the formula of custom-profile-1.	integer	Minimum value: 0 Maximum value: 10000000	0																
latency-weight	Coefficient of latency in the formula of custom-profile-1.	integer	Minimum value: 0 Maximum value: 10000000	0																
link-cost-factor	Link cost factor.	option	-	latency																
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>latency</td><td>Select link based on latency.</td></tr><tr><td>jitter</td><td>Select link based on jitter.</td></tr><tr><td>packet-loss</td><td>Select link based on packet loss.</td></tr><tr><td>inbandwidth</td><td>Select link based on available bandwidth of incoming traffic.</td></tr><tr><td>outbandwidth</td><td>Select link based on available bandwidth of outgoing traffic.</td></tr><tr><td>bibandwidth</td><td>Select link based on available bandwidth of bidirectional traffic.</td></tr><tr><td>custom-profile-1</td><td>Select link based on customized profile.</td></tr></table>				Option	Description	latency	Select link based on latency.	jitter	Select link based on jitter.	packet-loss	Select link based on packet loss.	inbandwidth	Select link based on available bandwidth of incoming traffic.	outbandwidth	Select link based on available bandwidth of outgoing traffic.	bibandwidth	Select link based on available bandwidth of bidirectional traffic.	custom-profile-1	Select link based on customized profile.
Option	Description																			
latency	Select link based on latency.																			
jitter	Select link based on jitter.																			
packet-loss	Select link based on packet loss.																			
inbandwidth	Select link based on available bandwidth of incoming traffic.																			
outbandwidth	Select link based on available bandwidth of outgoing traffic.																			
bibandwidth	Select link based on available bandwidth of bidirectional traffic.																			
custom-profile-1	Select link based on customized profile.																			

Parameter	Description	Type	Size	Default										
link-cost-threshold	Percentage threshold change of link cost values that will result in policy route regeneration.	integer	Minimum value: 0 Maximum value: 10000000	10										
load-balance	Enable/disable load-balance.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable load-balance.</td></tr><tr><td><i>disable</i></td><td>Disable load-balance.</td></tr></table>				Option	Description	<i>enable</i>	Enable load-balance.	<i>disable</i>	Disable load-balance.				
	Option	Description												
	<i>enable</i>	Enable load-balance.												
<i>disable</i>	Disable load-balance.													
minimum-sla-meet-members	Minimum number of members which meet SLA.	integer	Minimum value: 0 Maximum value: 255	0										
mode	Control how the SD-WAN rule sets the priority of interfaces in the SD-WAN.	option	-	manual										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>auto</i></td><td>Assign interfaces a priority based on quality.</td></tr><tr><td><i>manual</i></td><td>Assign interfaces a priority manually.</td></tr><tr><td><i>priority</i></td><td>Assign interfaces a priority based on the link-cost-factor quality of the interface.</td></tr><tr><td><i>sla</i></td><td>Assign interfaces a priority based on selected SLA settings.</td></tr></table>				Option	Description	<i>auto</i>	Assign interfaces a priority based on quality.	<i>manual</i>	Assign interfaces a priority manually.	<i>priority</i>	Assign interfaces a priority based on the link-cost-factor quality of the interface.	<i>sla</i>	Assign interfaces a priority based on selected SLA settings.
	Option	Description												
	<i>auto</i>	Assign interfaces a priority based on quality.												
	<i>manual</i>	Assign interfaces a priority manually.												
	<i>priority</i>	Assign interfaces a priority based on the link-cost-factor quality of the interface.												
<i>sla</i>	Assign interfaces a priority based on selected SLA settings.													
name	SD-WAN rule name.	string	Maximum length: 35											
packet-loss-weight	Coefficient of packet-loss in the formula of custom-profile-1.	integer	Minimum value: 0 Maximum value: 10000000	0										
passive-measurement	Enable/disable passive measurement based on the service criteria.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable passive measurement of user traffic.</td></tr><tr><td><i>disable</i></td><td>Disable passive measurement of user traffic.</td></tr></table>				Option	Description	<i>enable</i>	Enable passive measurement of user traffic.	<i>disable</i>	Disable passive measurement of user traffic.				
	Option	Description												
	<i>enable</i>	Enable passive measurement of user traffic.												
<i>disable</i>	Disable passive measurement of user traffic.													

Parameter	Description	Type	Size	Default								
priority-members <seq-num>	Member sequence number list. Member sequence number.	integer	Minimum value: 0 Maximum value: 4294967295									
priority-zone <name>	Priority zone name list. Priority zone name.	string	Maximum length: 79									
protocol	Protocol number.	integer	Minimum value: 0 Maximum value: 255	0								
quality-link	Quality grade.	integer	Minimum value: 0 Maximum value: 255	0								
role	Service role to work with neighbor.	option	-	standalone								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>standalone</i></td><td>Standalone service.</td></tr><tr><td><i>primary</i></td><td>Primary service for primary neighbor.</td></tr><tr><td><i>secondary</i></td><td>Secondary service for secondary neighbor.</td></tr></table>				Option	Description	<i>standalone</i>	Standalone service.	<i>primary</i>	Primary service for primary neighbor.	<i>secondary</i>	Secondary service for secondary neighbor.
Option	Description											
<i>standalone</i>	Standalone service.											
<i>primary</i>	Primary service for primary neighbor.											
<i>secondary</i>	Secondary service for secondary neighbor.											
shortcut	Enable/disable shortcut for this service.	option	-	enable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable use of ADVPN shortcut for this service.</td></tr><tr><td><i>disable</i></td><td>Disable use of ADVPN shortcut for this service.</td></tr></table>				Option	Description	<i>enable</i>	Enable use of ADVPN shortcut for this service.	<i>disable</i>	Disable use of ADVPN shortcut for this service.		
Option	Description											
<i>enable</i>	Enable use of ADVPN shortcut for this service.											
<i>disable</i>	Disable use of ADVPN shortcut for this service.											
shortcut-priority	High priority of ADVPN shortcut for this service.	option	-	auto								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable a high priority of ADVPN shortcut for this service.</td></tr><tr><td><i>disable</i></td><td>Disable a high priority of ADVPN shortcut for this service.</td></tr><tr><td><i>auto</i></td><td>Auto enable a high priority of ADVPN shortcut for this service if ADVPN2.0 enabled.</td></tr></table>				Option	Description	<i>enable</i>	Enable a high priority of ADVPN shortcut for this service.	<i>disable</i>	Disable a high priority of ADVPN shortcut for this service.	<i>auto</i>	Auto enable a high priority of ADVPN shortcut for this service if ADVPN2.0 enabled.
Option	Description											
<i>enable</i>	Enable a high priority of ADVPN shortcut for this service.											
<i>disable</i>	Disable a high priority of ADVPN shortcut for this service.											
<i>auto</i>	Auto enable a high priority of ADVPN shortcut for this service if ADVPN2.0 enabled.											
sla-compare-method	Method to compare SLA value for SLA mode.	option	-	order								

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>order</i>	Compare SLA value based on the order of health-check.		
	<i>number</i>	Compare SLA value based on the number of satisfied health-check. Limits health-checks to only configured member interfaces.		
sla-stickiness	Enable/disable SLA stickiness.	option	-	disable
	Option	Description		
	<i>enable</i>	Traffic remains in the original session path if the path is within the SLA.		
	<i>disable</i>	Traffic switches to the best path regardless of the SLA.		
src <name>	Source address name. Address or address group name.	string	Maximum length: 79	
src-negate	Enable/disable negation of source address match.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable source address negation.		
	<i>disable</i>	Disable source address negation.		
src6 <name>	Source address6 name. Address6 or address6 group name.	string	Maximum length: 79	
standalone-action	Enable/disable service when selected neighbor role is standalone while service role is not standalone.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable service when selected neighbor role is standalone.		
	<i>disable</i>	Disable service when selected neighbor role is standalone.		
start-port	Start destination port number.	integer	Minimum value: 0 Maximum value: 65535	1
start-src-port	Start source port number.	integer	Minimum value: 0 Maximum value: 65535	1
status	Enable/disable SD-WAN service.	option	-	enable

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable SD-WAN service.		
	<i>disable</i>	Disable SD-WAN service.		
tie-break	Method of selecting member if more than one meets the SLA.	option	-	zone
	Option	Description		
	<i>zone</i>	Use the setting that is configured for the members' zone.		
	<i>cfg-order</i>	Members that meet the SLA are selected in the order they are configured.		
	<i>fib-best-match</i>	Members that meet the SLA are selected that match the longest prefix in the routing table.		
	<i>input-device</i>	Members that meet the SLA are selected by matching the input device.		
tos	Type of service bit pattern.	user	Not Specified	
tos-mask	Type of service evaluated bits.	user	Not Specified	
use-shortcut-sla	Enable/disable use of ADVPN shortcut for quality comparison.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable use of ADVPN shortcut for quality comparison.		
	<i>disable</i>	Disable use of ADVPN shortcut for quality comparison.		
users <name>	User name. User name.	string	Maximum length: 79	
zone-mode	Enable/disable zone mode.	option	-	disable
	Option	Description		
	<i>enable</i>	Traffic steered based on zone.		
	<i>disable</i>	Traffic steered based on member.		

config sla

Parameter	Description	Type	Size	Default
health-check	SD-WAN health-check.	string	Maximum length: 35	

Parameter	Description	Type	Size	Default
id	SLA ID.	integer	Minimum value: 0 Maximum value: 4294967295	0

config zone

Parameter	Description	Type	Size	Default								
advpn-health-check	Health check for ADVPN local overlay link quality.	string	Maximum length: 35									
advpn-select	Enable/disable selection of ADVPN based on SDWAN information.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable selection of ADVPN based on SDWAN information.</td></tr><tr><td><i>disable</i></td><td>Disable selection of ADVPN based on SDWAN information.</td></tr></table>				Option	Description	<i>enable</i>	Enable selection of ADVPN based on SDWAN information.	<i>disable</i>	Disable selection of ADVPN based on SDWAN information.		
Option	Description											
<i>enable</i>	Enable selection of ADVPN based on SDWAN information.											
<i>disable</i>	Disable selection of ADVPN based on SDWAN information.											
minimum-sla-meet-members	Minimum number of members which meet SLA when the neighbor is preferred.	integer	Minimum value: 1 Maximum value: 255	1								
name	Zone name.	string	Maximum length: 35									
service-sla-tie-break	Method of selecting member if more than one meets the SLA.	option	-	cfg-order								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>cfg-order</i></td><td>Members that meet the SLA are selected in the order they are configured.</td></tr><tr><td><i>fib-best-match</i></td><td>Members that meet the SLA are selected that match the longest prefix in the routing table.</td></tr><tr><td><i>input-device</i></td><td>Members that meet the SLA are selected by matching the input device.</td></tr></table>				Option	Description	<i>cfg-order</i>	Members that meet the SLA are selected in the order they are configured.	<i>fib-best-match</i>	Members that meet the SLA are selected that match the longest prefix in the routing table.	<i>input-device</i>	Members that meet the SLA are selected by matching the input device.
Option	Description											
<i>cfg-order</i>	Members that meet the SLA are selected in the order they are configured.											
<i>fib-best-match</i>	Members that meet the SLA are selected that match the longest prefix in the routing table.											
<i>input-device</i>	Members that meet the SLA are selected by matching the input device.											

config system serial-port



This command is available for model(s): FortiGateRugged 70F.

It is not available for: FortiGate 1000D, FortiGate 1000F, FortiGate 1001F, FortiGate 100F, FortiGate 101F, FortiGate 1100E, FortiGate 1101E, FortiGate 120G, FortiGate 121G, FortiGate 140E-POE, FortiGate 140E, FortiGate 1800F, FortiGate 1801F, FortiGate 2000E, FortiGate 200E, FortiGate 200F, FortiGate 201E, FortiGate 201F, FortiGate 2200E, FortiGate 2201E, FortiGate 2500E, FortiGate 2600F, FortiGate 2601F, FortiGate 3000D, FortiGate 3000F, FortiGate 3001F, FortiGate 300E, FortiGate 301E, FortiGate 3100D, FortiGate 3200D, FortiGate 3200F, FortiGate 3201F, FortiGate 3300E, FortiGate 3301E, FortiGate 3400E, FortiGate 3401E, FortiGate 3500F, FortiGate 3501F, FortiGate 3600E, FortiGate 3601E, FortiGate 3700D, FortiGate 3700F, FortiGate 3701F, FortiGate 3960E, FortiGate 3980E, FortiGate 400E Bypass, FortiGate 400E, FortiGate 400F, FortiGate 401E, FortiGate 401F, FortiGate 4200F, FortiGate 4201F, FortiGate 4400F, FortiGate 4401F, FortiGate 5001E1, FortiGate 5001E, FortiGate 500E, FortiGate 501E, FortiGate 600E, FortiGate 600F, FortiGate 601E, FortiGate 601F, FortiGate 60E DSLJ, FortiGate 60E DSL, FortiGate 60E-POE, FortiGate 60E, FortiGate 61E, FortiGate 800D, FortiGate 80E-POE, FortiGate 80E, FortiGate 80F DSL, FortiGate 81E-POE, FortiGate 81E, FortiGate 900D, FortiGate 900G, FortiGate 901G, FortiGate 90E, FortiGate 90G, FortiGate 91E, FortiGate 91G, FortiGate-VM for Aliyun, FortiGate-VM for AWS, FortiGate-VM for Azure, FortiGate-VM for GCP, FortiGate-VM for OPC, FortiGate-VM64, FortiWiFi 60E DSLJ, FortiWiFi 60E DSL, FortiWiFi 60E, FortiWiFi 61E, FortiWiFi 80F 2R 3G4G DSL, FortiWiFi 81F 2R 3G4G DSL.

Serial port list. Read-only.

```
config system serial-port
    Description: Serial port list. Read-only.
    edit <name>
        next
    end
```

config system serial-port

Parameter	Description	Type	Size	Default
name	Serial port name.	string	Maximum length: 35	

config system session-helper

Configure session helper.

```
config system session-helper
    Description: Configure session helper.
    edit <id>
        set name [ftp|tftp|...]
        set port {integer}
        set protocol {integer}
```