

Parameter	Description	Type	Size	Default
source-ip6	IPv6 source for communications to FSSO agent.	ipv6-address	Not Specified	::
ssl	Enable/disable use of SSL.	option	-	disable
	Option		Description	
	<i>enable</i>		Enable use of SSL.	
	<i>disable</i>		Disable use of SSL.	
ssl-server-host-ip-check	Enable/disable server host/IP verification.	option	-	disable
	Option		Description	
	<i>enable</i>		Enable server host/IP verification.	
	<i>disable</i>		Disable server host/IP verification.	
ssl-trusted-cert	Trusted server certificate or CA certificate.	string	Maximum length: 79	
type	Server type.	option	-	default
	Option		Description	
	<i>default</i>		All other unspecified types of servers.	
	<i>fortinac</i>		FortiNAC server.	
user-info-server	LDAP server to get user information.	string	Maximum length: 35	

config user group

Configure user groups.

```
config user group
  Description: Configure user groups.
  edit <name>
    set auth-concurrent-override [enable|disable]
    set auth-concurrent-value {integer}
    set authtimeout {integer}
    set company [optional|mandatory|...]
    set email [disable|enable]
    set expire {integer}
    set expire-type [immediately|first-successful-login]
    set group-type [firewall|fsso-service|...]
  config guest
    Description: Guest User.
    edit <id>
      set comment {var-string}
```

```

        set company {string}
        set email {string}
        set expiration {user}
        set mobile-phone {string}
        set name {string}
        set password {password}
        set sponsor {string}
        set user-id {string}
    next
end
set http-digest-realm {string}
set id {integer}
config match
    Description: Group matches.
    edit <id>
        set group-name {string}
        set server-name {string}
    next
end
set max-accounts {integer}
set member <name1>, <name2>, ...
set mobile-phone [disable|enable]
set multiple-guest-add [disable|enable]
set password [auto-generate|specify|...]
set sms-custom-server {string}
set sms-server [fortiguard|custom]
set sponsor [optional|mandatory|...]
set sso-attribute-value {string}
set user-id [email|auto-generate|...]
set user-name [disable|enable]
next
end

```

config user group

Parameter	Description	Type	Size	Default						
auth-concurrent-override	Enable/disable overriding the global number of concurrent authentication sessions for this user group.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable auth-concurrent-override.</td></tr><tr><td><i>disable</i></td><td>Disable auth-concurrent-override.</td></tr></table>				Option	Description	<i>enable</i>	Enable auth-concurrent-override.	<i>disable</i>	Disable auth-concurrent-override.
	Option	Description								
	<i>enable</i>	Enable auth-concurrent-override.								
<i>disable</i>	Disable auth-concurrent-override.									
auth-concurrent-value	Maximum number of concurrent authenticated connections per user.	integer	Minimum value: 0 Maximum value: 100	0						

Parameter	Description	Type	Size	Default										
authtimeout	Authentication timeout in minutes for this user group. 0 to use the global user setting auth-timeout.	integer	Minimum value: 0 Maximum value: 43200	0										
company	Set the action for the company guest user field.	option	-	optional										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>optional</i></td><td>Optional.</td></tr><tr><td><i>mandatory</i></td><td>Mandatory.</td></tr><tr><td><i>disabled</i></td><td>Disabled.</td></tr></table>	Option	Description	<i>optional</i>	Optional.	<i>mandatory</i>	Mandatory.	<i>disabled</i>	Disabled.					
Option	Description													
<i>optional</i>	Optional.													
<i>mandatory</i>	Mandatory.													
<i>disabled</i>	Disabled.													
email	Enable/disable the guest user email address field.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr></table>	Option	Description	<i>disable</i>	Disable setting.	<i>enable</i>	Enable setting.							
Option	Description													
<i>disable</i>	Disable setting.													
<i>enable</i>	Enable setting.													
expire	Time in seconds before guest user accounts expire.	integer	Minimum value: 1 Maximum value: 31536000	14400										
expire-type	Determine when the expiration countdown begins.	option	-	immediately										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>immediately</i></td><td>Immediately.</td></tr><tr><td><i>first-successful-login</i></td><td>First successful login.</td></tr></table>	Option	Description	<i>immediately</i>	Immediately.	<i>first-successful-login</i>	First successful login.							
Option	Description													
<i>immediately</i>	Immediately.													
<i>first-successful-login</i>	First successful login.													
group-type	Set the group to be for firewall authentication, FSSO, RSSO, or guest users.	option	-	firewall										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>firewall</i></td><td>Firewall.</td></tr><tr><td><i>fsso-service</i></td><td>Fortinet Single Sign-On Service.</td></tr><tr><td><i>rsso</i></td><td>RADIUS based Single Sign-On Service.</td></tr><tr><td><i>guest</i></td><td>Guest.</td></tr></table>	Option	Description	<i>firewall</i>	Firewall.	<i>fsso-service</i>	Fortinet Single Sign-On Service.	<i>rsso</i>	RADIUS based Single Sign-On Service.	<i>guest</i>	Guest.			
Option	Description													
<i>firewall</i>	Firewall.													
<i>fsso-service</i>	Fortinet Single Sign-On Service.													
<i>rsso</i>	RADIUS based Single Sign-On Service.													
<i>guest</i>	Guest.													
http-digest-realm	Realm attribute for MD5-digest authentication.	string	Maximum length: 35											

Parameter	Description	Type	Size	Default								
id	Group ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0								
max-accounts	Maximum number of guest accounts that can be created for this group (0 means unlimited).	integer	Minimum value: 0 Maximum value: 1024 **	0								
member <name>	Names of users, peers, LDAP severs, RADIUS servers or external idp servers to add to the user group. Group member name.	string	Maximum length: 511									
mobile-phone	Enable/disable the guest user mobile phone number field.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable setting.</td></tr><tr><td>enable</td><td>Enable setting.</td></tr></table>				Option	Description	disable	Disable setting.	enable	Enable setting.		
Option	Description											
disable	Disable setting.											
enable	Enable setting.											
multiple-guest-add	Enable/disable addition of multiple guests.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Disable setting.</td></tr><tr><td>enable</td><td>Enable setting.</td></tr></table>				Option	Description	disable	Disable setting.	enable	Enable setting.		
Option	Description											
disable	Disable setting.											
enable	Enable setting.											
name	Group name.	string	Maximum length: 35									
password	Guest user password type.	option	-	auto-generate								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>auto-generate</td><td>Automatically generate.</td></tr><tr><td>specify</td><td>Specify.</td></tr><tr><td>disable</td><td>Disable.</td></tr></table>				Option	Description	auto-generate	Automatically generate.	specify	Specify.	disable	Disable.
Option	Description											
auto-generate	Automatically generate.											
specify	Specify.											
disable	Disable.											
sms-custom-server	SMS server.	string	Maximum length: 35									
sms-server	Send SMS through FortiGuard or other external server.	option	-	fortiguard								

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>fortiguard</i>	Send SMS by FortiGuard.		
	<i>custom</i>	Send SMS by custom server.		
sponsor	Set the action for the sponsor guest user field.	option	-	optional
	Option	Description		
	<i>optional</i>	Optional.		
	<i>mandatory</i>	Mandatory.		
	<i>disabled</i>	Disabled.		
sso-attribute-value	Name of the RADIUS user group that this local user group represents.	string	Maximum length: 511	
user-id	Guest user ID type.	option	-	email
	Option	Description		
	<i>email</i>	Email address.		
	<i>auto-generate</i>	Automatically generate.		
	<i>specify</i>	Specify.		
user-name	Enable/disable the guest user name entry.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable setting.		
	<i>enable</i>	Enable setting.		

** Values may differ between models.

config guest

Parameter	Description	Type	Size	Default
comment	Comment.	var-string	Maximum length: 255	
company	Set the action for the company guest user field.	string	Maximum length: 35	
email	Email.	string	Maximum length: 64	
expiration	Expire time.	user	Not Specified	

Parameter	Description	Type	Size	Default
id	Guest ID.	integer	Minimum value: 0 Maximum value: 4294967295	0
mobile-phone	Mobile phone.	string	Maximum length: 35	
name	Guest name.	string	Maximum length: 64	
password	Guest password.	password	Not Specified	
sponsor	Set the action for the sponsor guest user field.	string	Maximum length: 35	
user-id	Guest ID.	string	Maximum length: 64	

config match

Parameter	Description	Type	Size	Default
group-name	Name of matching user or group on remote authentication server.	string	Maximum length: 511	
id	ID.	integer	Minimum value: 0 Maximum value: 4294967295	0
server-name	Name of remote auth server.	string	Maximum length: 35	

config user krb-keytab

Configure Kerberos keytab entries.

```

config user krb-keytab
  Description: Configure Kerberos keytab entries.
  edit <name>
    set keytab {string}
    set ldap-server <name1>, <name2>, ...
    set pac-data [enable|disable]
    set principal {string}
  next
end

```