

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>fortitoken</i>	FortiToken authentication.		
	<i>email</i>	Email one time password.		
	<i>sms</i>	SMS one time password.		
two-factor-filter	Filter used to synchronize users to FortiToken Cloud.	string	Maximum length: 2047	
two-factor-notification	Notification method for user activation by FortiToken Cloud.	option	-	
	Option	Description		
	<i>email</i>	Email notification for activation code.		
	<i>sms</i>	SMS notification for activation code.		
type	Authentication type for LDAP searches.	option	-	simple
	Option	Description		
	<i>simple</i>	Simple password authentication without search.		
	<i>anonymous</i>	Bind using anonymous user search.		
	<i>regular</i>	Bind using username/password and then search.		
user-info-exchange-server	MS Exchange server from which to fetch user information.	string	Maximum length: 35	
username	Username (full DN) for initial binding.	string	Maximum length: 511	

config user local

Configure local users.

```

config user local
  Description: Configure local users.
  edit <name>
    set auth-concurrent-override [enable|disable]
    set auth-concurrent-value {integer}
    set authtimeout {integer}
    set email-to {string}
    set fortitoken {string}
    set id {integer}
    set ldap-server {string}
    set passwd {password}
    set passwd-policy {string}
    set passwd-time {user}
    set ppk-identity {string}
    set ppk-secret {password-3}
    set qkd-profile {string}
    set radius-server {string}
    set sms-custom-server {string}
    set sms-phone {string}
    set sms-server [fortiguard|custom]
    set status [enable|disable]
    set tacacs+-server {string}
    set two-factor [disable|fortitoken|...]
    set two-factor-authentication [fortitoken|email|...]
    set two-factor-notification [email|sms]
    set type [password|radius|...]
    set username-sensitivity [disable|enable]
    set workstation {string}
  next
end

```

config user local

Parameter	Description	Type	Size	Default
auth-concurrent-override	Enable/disable overriding the policy-auth-concurrent under config system global.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable auth-concurrent-override.		
	<i>disable</i>	Disable auth-concurrent-override.		
auth-concurrent-value	Maximum number of concurrent logins permitted from the same user.	integer	Minimum value: 0 Maximum value: 100	0
authtimeout	Time in minutes before the authentication timeout for a user is reached.	integer	Minimum value: 0 Maximum value: 1440	0

Parameter	Description	Type	Size	Default						
email-to	Two-factor recipient's email address.	string	Maximum length: 63							
fortitoken	Two-factor recipient's FortiToken serial number.	string	Maximum length: 16							
id	User ID. Read-only.	integer	Minimum value: 0 Maximum value: 4294967295	0						
ldap-server	Name of LDAP server with which the user must authenticate.	string	Maximum length: 35							
name	Local user name.	string	Maximum length: 64							
passwd	User's password.	password	Not Specified							
passwd-policy	Password policy to apply to this user, as defined in config user password-policy.	string	Maximum length: 35							
passwd-time	Time of the last password update.	user	Not Specified							
ppk-identity	IKEv2 Postquantum Preshared Key Identity.	string	Maximum length: 35							
ppk-secret	IKEv2 Postquantum Preshared Key (ASCII string or hexadecimal encoded with a leading 0x).	password-3	Not Specified							
qkd-profile	Quantum Key Distribution (QKD) profile.	string	Maximum length: 35							
radius-server	Name of RADIUS server with which the user must authenticate.	string	Maximum length: 35							
sms-custom-server	Two-factor recipient's SMS server.	string	Maximum length: 35							
sms-phone	Two-factor recipient's mobile phone number.	string	Maximum length: 15							
sms-server	Send SMS through FortiGuard or other external server.	option	-	fortiguard						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>fortiguard</td><td>Send SMS by FortiGuard.</td></tr><tr><td>custom</td><td>Send SMS by custom server.</td></tr></table>				Option	Description	fortiguard	Send SMS by FortiGuard.	custom	Send SMS by custom server.
Option	Description									
fortiguard	Send SMS by FortiGuard.									
custom	Send SMS by custom server.									
status	Enable/disable allowing the local user to authenticate with the FortiGate unit.	option	-	enable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable user.		
	<i>disable</i>	Disable user.		
tacacs+-server	Name of TACACS+ server with which the user must authenticate.	string	Maximum length: 35	
two-factor	Enable/disable two-factor authentication.	option	-	disable
	Option	Description		
	<i>disable</i>	disable		
	<i>fortitoken</i>	FortiToken		
	<i>fortitoken-cloud</i>	FortiToken Cloud Service.		
	<i>email</i>	Email authentication code.		
	<i>sms</i>	SMS authentication code.		
two-factor-authentication	Authentication method by FortiToken Cloud.	option	-	
	Option	Description		
	<i>fortitoken</i>	FortiToken authentication.		
	<i>email</i>	Email one time password.		
	<i>sms</i>	SMS one time password.		
two-factor-notification	Notification method for user activation by FortiToken Cloud.	option	-	
	Option	Description		
	<i>email</i>	Email notification for activation code.		
	<i>sms</i>	SMS notification for activation code.		
type	Authentication method.	option	-	password
	Option	Description		
	<i>password</i>	Password authentication.		
	<i>radius</i>	RADIUS server authentication.		
	<i>tacacs+</i>	TACACS+ server authentication.		
	<i>ldap</i>	LDAP server authentication.		

Parameter	Description	Type	Size	Default
username-sensitivity	Enable/disable case and accent sensitivity when performing username matching (accents are stripped and case is ignored when disabled).	option	-	enable
	Option	Description		
	disable	Ignore case and accents. Username at prompt not required to match case or accents.		
	enable	Do not ignore case and accents. Username at prompt must be an exact match.		
workstation	Name of the remote user workstation, if you want to limit the user to authenticate only from a particular workstation.	string	Maximum length: 35	

config user nac-policy

Configure NAC policy matching pattern to identify matching NAC devices.

```

config user nac-policy
    Description: Configure NAC policy matching pattern to identify matching NAC devices.
    edit <name>
        set category [device|firewall-user|...]
        set description {string}
        set ems-tag {string}
        set family {string}
        set firewall-address {string}
        set fortivoice-tag {string}
        set host {string}
        set hw-vendor {string}
        set hw-version {string}
        set mac {string}
        set match-period {integer}
        set match-type [dynamic|override]
        set os {string}
        set severity <severity-num1>, <severity-num2>, ...
        set src {string}
        set ssid-policy {string}
        set status [enable|disable]
        set sw-version {string}
        set switch-fortilink {string}
        set switch-group <name1>, <name2>, ...
        set switch-mac-policy {string}
        set type {string}
        set user {string}
        set user-group {string}
    next
end

```