

```

        set server {string}
    next
end

```

config vpn qkd

Parameter	Description	Type	Size	Default
certificate <name>	Names of up to 4 certificates to offer to the KME. Certificate name.	string	Maximum length: 79	
comment	Comment.	var-string	Maximum length: 255	
id	Quantum Key Distribution ID assigned by the KME.	string	Maximum length: 291	
name	Quantum Key Distribution configuration name.	string	Maximum length: 35	
peer	Authenticate Quantum Key Device's certificate with the peer/peergrp.	string	Maximum length: 35	
port	Port to connect to on the KME.	integer	Minimum value: 1 Maximum value: 65535	0
server	IPv4, IPv6 or DNS address of the KME.	string	Maximum length: 63	

config vpn ssl client

Client.

```

config vpn ssl client
    Description: Client.
    edit <name>
        set certificate {string}
        set class-id {integer}
        set comment {var-string}
        set distance {integer}
        set interface {string}
        set ipv4-subnets {string}
        set ipv6-subnets {string}
        set peer {string}
        set port {integer}
        set priority {integer}
        set psk {password-3}
        set realm {string}
        set server {string}
        set source-ip {string}
    end
end

```

```

        set status [enable|disable]
        set user {string}
    next
end

```

config vpn ssl client

Parameter	Description	Type	Size	Default
certificate	Certificate to offer to SSL-VPN server if it requests one.	string	Maximum length: 35	
class-id	Traffic class ID.	integer	Minimum value: 0 Maximum value: 4294967295	0
comment	Comment.	var-string	Maximum length: 255	
distance	Distance for routes added by SSL-VPN.	integer	Minimum value: 1 Maximum value: 255	10
interface	SSL interface to send/receive traffic over.	string	Maximum length: 15	
ipv4-subnets	IPv4 subnets that the client is protecting.	string	Maximum length: 79	
ipv6-subnets	IPv6 subnets that the client is protecting.	string	Maximum length: 79	
name	SSL-VPN tunnel name.	string	Maximum length: 35	
peer	Authenticate peer's certificate with the peer/peergrp.	string	Maximum length: 35	
port	SSL-VPN server port.	integer	Minimum value: 1 Maximum value: 65535	443
priority	Priority for routes added by SSL-VPN.	integer	Minimum value: 1 Maximum value: 65535	1
psk	Pre-shared secret to authenticate with the server (ASCII string or hexadecimal encoded with a leading 0x).	password-3	Not Specified	

Parameter	Description	Type	Size	Default
realm	Realm name configured on SSL-VPN server.	string	Maximum length: 35	
server	IPv4, IPv6 or DNS address of the SSL-VPN server.	string	Maximum length: 63	
source-ip	IPv4 or IPv6 address to use as a source for the SSL-VPN connection to the server.	string	Maximum length: 63	
status	Enable/disable this SSL-VPN client configuration.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable the SSL-VPN configuration.		
	<i>disable</i>	Disable the SSL-VPN configuration.		
user	Username to offer to the peer to authenticate the client.	string	Maximum length: 35	

config vpn ssl settings

Configure SSL-VPN.

```

config vpn ssl settings
  Description: Configure SSL-VPN.
  set algorithm [high|medium|...]
  set auth-session-check-source-ip [enable|disable]
  set auth-timeout {integer}
  config authentication-rule
    Description: Authentication rule for SSL-VPN.
    edit <id>
      set auth [any|local|...]
      set cipher [any|high|...]
      set client-cert [enable|disable]
      set groups <name1>, <name2>, ...
      set portal {string}
      set realm {string}
      set source-address <name1>, <name2>, ...
      set source-address-negate [enable|disable]
      set source-address6 <name1>, <name2>, ...
      set source-address6-negate [enable|disable]
      set source-interface <name1>, <name2>, ...
      set user-peer {string}
      set users <name1>, <name2>, ...
    next
  end
  set auto-tunnel-static-route [enable|disable]
  set banned-cipher {option1}, {option2}, ...
  set browser-language-detection [enable|disable]
  set check-referer [enable|disable]
  set ciphersuite {option1}, {option2}, ...
  set client-sigalgs [no-rsa-pss|all]

```

```
set default-portal {string}
set deflate-compression-level {integer}
set deflate-min-data-size {integer}
set dns-server1 {ipv4-address}
set dns-server2 {ipv4-address}
set dns-suffix {var-string}
set dtls-heartbeat-fail-count {integer}
set dtls-heartbeat-idle-timeout {integer}
set dtls-heartbeat-interval {integer}
set dtls-hello-timeout {integer}
set dtls-max-proto-ver [dtls1-0|dtls1-2]
set dtls-min-proto-ver [dtls1-0|dtls1-2]
set dtls-tunnel [enable|disable]
set dual-stack-mode [enable|disable]
set encode-2f-sequence [enable|disable]
set encrypt-and-store-password [enable|disable]
set force-two-factor-auth [enable|disable]
set header-x-forwarded-for [pass|add|...]
set hsts-include-subdomains [enable|disable]
set http-compression [enable|disable]
set http-only-cookie [enable|disable]
set http-request-body-timeout {integer}
set http-request-header-timeout {integer}
set https-redirect [enable|disable]
set idle-timeout {integer}
set ipv6-dns-server1 {ipv6-address}
set ipv6-dns-server2 {ipv6-address}
set ipv6-wins-server1 {ipv6-address}
set ipv6-wins-server2 {ipv6-address}
set login-attempt-limit {integer}
set login-block-time {integer}
set login-timeout {integer}
set port {integer}
set port-precedence [enable|disable]
set reqclientcert [enable|disable]
set saml-redirect-port {integer}
set server-hostname {string}
set servercert {string}
set source-address <name1>, <name2>, ...
set source-address-negate [enable|disable]
set source-address6 <name1>, <name2>, ...
set source-address6-negate [enable|disable]
set source-interface <name1>, <name2>, ...
set ssl-client-renegotiation [disable|enable]
set ssl-insert-empty-fragment [enable|disable]
set ssl-max-proto-ver [tls1-0|tls1-1|...]
set ssl-min-proto-ver [tls1-0|tls1-1|...]
set status [enable|disable]
set transform-backward-slashes [enable|disable]
set tunnel-addr-assigned-method [first-available|round-robin]
set tunnel-connect-without-reauth [enable|disable]
set tunnel-ip-pools <name1>, <name2>, ...
set tunnel-ipv6-pools <name1>, <name2>, ...
set tunnel-user-session-timeout {integer}
set unsafe-legacy-renegotiation [enable|disable]
set url-obscuratation [enable|disable]
```

```

set user-peer {string}
set wins-server1 {ipv4-address}
set wins-server2 {ipv4-address}
set x-content-type-options [enable|disable]
set ztna-trusted-client [enable|disable]
end

```

config vpn ssl settings

Parameter	Description	Type	Size	Default										
algorithm	Force the SSL-VPN security level. High allows only high. Medium allows medium and high. Low allows any.	option	-	high										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>high</td><td>High algorithms.</td></tr><tr><td>medium</td><td>High and medium algorithms.</td></tr><tr><td>default</td><td>default</td></tr><tr><td>low</td><td>All algorithms.</td></tr></table>	Option	Description	high	High algorithms.	medium	High and medium algorithms.	default	default	low	All algorithms.			
Option	Description													
high	High algorithms.													
medium	High and medium algorithms.													
default	default													
low	All algorithms.													
auth-session-check-source-ip	Enable/disable checking of source IP for authentication session.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable checking of source IP for authentication session.</td></tr><tr><td>disable</td><td>Disable checking of source IP for authentication session.</td></tr></table>	Option	Description	enable	Enable checking of source IP for authentication session.	disable	Disable checking of source IP for authentication session.							
Option	Description													
enable	Enable checking of source IP for authentication session.													
disable	Disable checking of source IP for authentication session.													
auth-timeout	SSL-VPN authentication timeout.	integer	Minimum value: 0 Maximum value: 259200	28800										
auto-tunnel-static-route	Enable/disable to auto-create static routes for the SSL-VPN tunnel IP addresses.	option	-	enable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.							
Option	Description													
enable	Enable setting.													
disable	Disable setting.													
banned-cipher	Select one or more cipher technologies that cannot be used in SSL-VPN negotiations. Only applies to TLS 1.2 and below.	option	-	SHA1 SHA256 SHA384										

Parameter	Description	Type	Size	Default																																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>RSA</i></td><td>Ban the use of cipher suites using RSA key.</td></tr><tr><td><i>DHE</i></td><td>Ban the use of cipher suites using authenticated ephemeral DH key agreement.</td></tr><tr><td><i>ECDHE</i></td><td>Ban the use of cipher suites using authenticated ephemeral ECDH key agreement.</td></tr><tr><td><i>DSS</i></td><td>Ban the use of cipher suites using DSS authentication.</td></tr><tr><td><i>ECDSA</i></td><td>Ban the use of cipher suites using ECDSA authentication.</td></tr><tr><td><i>AES</i></td><td>Ban the use of cipher suites using either 128 or 256 bit AES.</td></tr><tr><td><i>AESGCM</i></td><td>Ban the use of cipher suites AES in Galois Counter Mode (GCM).</td></tr><tr><td><i>CAMELLIA</i></td><td>Ban the use of cipher suites using either 128 or 256 bit CAMELLIA.</td></tr><tr><td><i>3DES</i></td><td>Ban the use of cipher suites using triple DES</td></tr><tr><td><i>SHA1</i></td><td>Ban the use of cipher suites using HMAC-SHA1.</td></tr><tr><td><i>SHA256</i></td><td>Ban the use of cipher suites using HMAC-SHA256.</td></tr><tr><td><i>SHA384</i></td><td>Ban the use of cipher suites using HMAC-SHA384.</td></tr><tr><td><i>STATIC</i></td><td>Ban the use of cipher suites using static keys.</td></tr><tr><td><i>CHACHA20</i></td><td>Ban the use of cipher suites using ChaCha20.</td></tr><tr><td><i>ARIA</i></td><td>Ban the use of cipher suites using ARIA.</td></tr><tr><td><i>AESCCM</i></td><td>Ban the use of cipher suites using AESCCM.</td></tr></table>	Option	Description	<i>RSA</i>	Ban the use of cipher suites using RSA key.	<i>DHE</i>	Ban the use of cipher suites using authenticated ephemeral DH key agreement.	<i>ECDHE</i>	Ban the use of cipher suites using authenticated ephemeral ECDH key agreement.	<i>DSS</i>	Ban the use of cipher suites using DSS authentication.	<i>ECDSA</i>	Ban the use of cipher suites using ECDSA authentication.	<i>AES</i>	Ban the use of cipher suites using either 128 or 256 bit AES.	<i>AESGCM</i>	Ban the use of cipher suites AES in Galois Counter Mode (GCM).	<i>CAMELLIA</i>	Ban the use of cipher suites using either 128 or 256 bit CAMELLIA.	<i>3DES</i>	Ban the use of cipher suites using triple DES	<i>SHA1</i>	Ban the use of cipher suites using HMAC-SHA1.	<i>SHA256</i>	Ban the use of cipher suites using HMAC-SHA256.	<i>SHA384</i>	Ban the use of cipher suites using HMAC-SHA384.	<i>STATIC</i>	Ban the use of cipher suites using static keys.	<i>CHACHA20</i>	Ban the use of cipher suites using ChaCha20.	<i>ARIA</i>	Ban the use of cipher suites using ARIA.	<i>AESCCM</i>	Ban the use of cipher suites using AESCCM.			
	Option	Description																																				
	<i>RSA</i>	Ban the use of cipher suites using RSA key.																																				
	<i>DHE</i>	Ban the use of cipher suites using authenticated ephemeral DH key agreement.																																				
	<i>ECDHE</i>	Ban the use of cipher suites using authenticated ephemeral ECDH key agreement.																																				
	<i>DSS</i>	Ban the use of cipher suites using DSS authentication.																																				
	<i>ECDSA</i>	Ban the use of cipher suites using ECDSA authentication.																																				
	<i>AES</i>	Ban the use of cipher suites using either 128 or 256 bit AES.																																				
	<i>AESGCM</i>	Ban the use of cipher suites AES in Galois Counter Mode (GCM).																																				
	<i>CAMELLIA</i>	Ban the use of cipher suites using either 128 or 256 bit CAMELLIA.																																				
	<i>3DES</i>	Ban the use of cipher suites using triple DES																																				
	<i>SHA1</i>	Ban the use of cipher suites using HMAC-SHA1.																																				
	<i>SHA256</i>	Ban the use of cipher suites using HMAC-SHA256.																																				
	<i>SHA384</i>	Ban the use of cipher suites using HMAC-SHA384.																																				
	<i>STATIC</i>	Ban the use of cipher suites using static keys.																																				
	<i>CHACHA20</i>	Ban the use of cipher suites using ChaCha20.																																				
	<i>ARIA</i>	Ban the use of cipher suites using ARIA.																																				
<i>AESCCM</i>	Ban the use of cipher suites using AESCCM.																																					
browser-language-detection	Enable/disable overriding the configured system language based on the preferred language of the browser.	option	-	enable																																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.																															
	Option	Description																																				
	<i>enable</i>	Enable setting.																																				
<i>disable</i>	Disable setting.																																					
check-referer	Enable/disable verification of referer field in HTTP request header.	option	-	disable																																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable verification of referer field in HTTP request header.</td></tr><tr><td><i>disable</i></td><td>Disable verification of referer field in HTTP request header.</td></tr></table>	Option	Description	<i>enable</i>	Enable verification of referer field in HTTP request header.	<i>disable</i>	Disable verification of referer field in HTTP request header.																															
	Option	Description																																				
	<i>enable</i>	Enable verification of referer field in HTTP request header.																																				
<i>disable</i>	Disable verification of referer field in HTTP request header.																																					

Parameter	Description	Type	Size	Default												
ciphersuite	Select one or more TLS 1.3 ciphersuites to enable. Does not affect ciphers in TLS 1.2 and below. At least one must be enabled. To disable all, set ssl-max-proto-ver to tls1-2 or below.	option	-	TLS-AES-128-GCM-SHA256 TLS-AES-256-GCM-SHA384 TLS-CHACHA20-POLY1305-SHA256												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>TLS-AES-128-GCM-SHA256</td><td>Enable TLS-AES-128-GCM-SHA256 in TLS 1.3.</td></tr><tr><td>TLS-AES-256-GCM-SHA384</td><td>Enable TLS-AES-256-GCM-SHA384 in TLS 1.3.</td></tr><tr><td>TLS-CHACHA20-POLY1305-SHA256</td><td>Enable TLS-CHACHA20-POLY1305-SHA256 in TLS 1.3.</td></tr><tr><td>TLS-AES-128-CCM-SHA256</td><td>Enable TLS-AES-128-CCM-SHA256 in TLS 1.3.</td></tr><tr><td>TLS-AES-128-CCM-8-SHA256</td><td>Enable TLS-AES-128-CCM-8-SHA256 in TLS 1.3.</td></tr></table>				Option	Description	TLS-AES-128-GCM-SHA256	Enable TLS-AES-128-GCM-SHA256 in TLS 1.3.	TLS-AES-256-GCM-SHA384	Enable TLS-AES-256-GCM-SHA384 in TLS 1.3.	TLS-CHACHA20-POLY1305-SHA256	Enable TLS-CHACHA20-POLY1305-SHA256 in TLS 1.3.	TLS-AES-128-CCM-SHA256	Enable TLS-AES-128-CCM-SHA256 in TLS 1.3.	TLS-AES-128-CCM-8-SHA256	Enable TLS-AES-128-CCM-8-SHA256 in TLS 1.3.
Option	Description															
TLS-AES-128-GCM-SHA256	Enable TLS-AES-128-GCM-SHA256 in TLS 1.3.															
TLS-AES-256-GCM-SHA384	Enable TLS-AES-256-GCM-SHA384 in TLS 1.3.															
TLS-CHACHA20-POLY1305-SHA256	Enable TLS-CHACHA20-POLY1305-SHA256 in TLS 1.3.															
TLS-AES-128-CCM-SHA256	Enable TLS-AES-128-CCM-SHA256 in TLS 1.3.															
TLS-AES-128-CCM-8-SHA256	Enable TLS-AES-128-CCM-8-SHA256 in TLS 1.3.															
client-sigalgs	Set signature algorithms related to client authentication. Affects TLS version <= 1.2 only.	option	-	all												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>no-rsa-pss</td><td>Disable RSA-PSS signature algorithms for client authentication.</td></tr><tr><td>all</td><td>Enable all supported signature algorithms for client authentication.</td></tr></table>				Option	Description	no-rsa-pss	Disable RSA-PSS signature algorithms for client authentication.	all	Enable all supported signature algorithms for client authentication.						
Option	Description															
no-rsa-pss	Disable RSA-PSS signature algorithms for client authentication.															
all	Enable all supported signature algorithms for client authentication.															
default-portal	Default SSL-VPN portal.	string	Maximum length: 35													
deflate-compression-level	Compression level (0~9).	integer	Minimum value: 0 Maximum value: 9	6												
deflate-min-data-size	Minimum amount of data that triggers compression.	integer	Minimum value: 200 Maximum value: 65535	300												

Parameter	Description	Type	Size	Default						
dns-server1	DNS server 1.	ipv4-address	Not Specified	0.0.0.0						
dns-server2	DNS server 2.	ipv4-address	Not Specified	0.0.0.0						
dns-suffix	DNS suffix used for SSL-VPN clients.	var-string	Maximum length: 253							
dtls-heartbeat-fail-count	Number of missing heartbeats before the connection is considered dropped.	integer	Minimum value: 3 Maximum value: 10	3						
dtls-heartbeat-idle-timeout	Idle timeout before DTLS heartbeat is sent.	integer	Minimum value: 3 Maximum value: 10	3						
dtls-heartbeat-interval	Interval between DTLS heartbeat.	integer	Minimum value: 3 Maximum value: 10	3						
dtls-hello-timeout	SSLVPN maximum DTLS hello timeout.	integer	Minimum value: 10 Maximum value: 60	10						
dtls-max-protocol-ver	DTLS maximum protocol version.	option	-	dtls1-2						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>dtls1-0</td><td>DTLS version 1.0.</td></tr><tr><td>dtls1-2</td><td>DTLS version 1.2.</td></tr></table>				Option	Description	dtls1-0	DTLS version 1.0.	dtls1-2	DTLS version 1.2.
Option	Description									
dtls1-0	DTLS version 1.0.									
dtls1-2	DTLS version 1.2.									
dtls-min-protocol-ver	DTLS minimum protocol version.	option	-	dtls1-0						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>dtls1-0</td><td>DTLS version 1.0.</td></tr><tr><td>dtls1-2</td><td>DTLS version 1.2.</td></tr></table>				Option	Description	dtls1-0	DTLS version 1.0.	dtls1-2	DTLS version 1.2.
Option	Description									
dtls1-0	DTLS version 1.0.									
dtls1-2	DTLS version 1.2.									
dtls-tunnel	Enable/disable DTLS to prevent eavesdropping, tampering, or message forgery.	option	-	enable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
dual-stack-mode	Tunnel mode: enable parallel IPv4 and IPv6 tunnel. Web mode: support IPv4 and IPv6 bookmarks in the portal.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
encode-2f-sequence	Encode \2F sequence to forward slash in URLs.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
encrypt-and-store-password	Encrypt and store user passwords for SSL-VPN web sessions.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
force-two-factor-auth	Enable/disable only PKI users with two-factor authentication for SSL-VPNs.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
header-x-forwarded-for	Forward the same, add, or remove HTTP header.	option	-	add
	Option	Description		
	<i>pass</i>	Forward the same HTTP header.		
	<i>add</i>	Add the HTTP header.		
	<i>remove</i>	Remove the HTTP header.		

Parameter	Description	Type	Size	Default
hsts-include-subdomains	Add HSTS includeSubDomains response header.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
http-compression	Enable/disable to allow HTTP compression over SSL-VPN tunnels.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
http-only-cookie	Enable/disable SSL-VPN support for HttpOnly cookies.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
http-request-body-timeout	SSL-VPN session is disconnected if an HTTP request body is not received within this time.	integer	Minimum value: 0 Maximum value: 4294967295	30
http-request-header-timeout	SSL-VPN session is disconnected if an HTTP request header is not received within this time.	integer	Minimum value: 0 Maximum value: 4294967295	20
https-redirect	Enable/disable redirect of port 80 to SSL-VPN port.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
idle-timeout	SSL-VPN disconnects if idle for specified time in seconds.	integer	Minimum value: 0 Maximum value: 259200	300

Parameter	Description	Type	Size	Default						
ipv6-dns-server1	IPv6 DNS server 1.	ipv6-address	Not Specified	::						
ipv6-dns-server2	IPv6 DNS server 2.	ipv6-address	Not Specified	::						
ipv6-wins-server1	IPv6 WINS server 1.	ipv6-address	Not Specified	::						
ipv6-wins-server2	IPv6 WINS server 2.	ipv6-address	Not Specified	::						
login-attempt-limit	SSL-VPN maximum login attempt times before block.	integer	Minimum value: 0 Maximum value: 4294967295	2						
login-block-time	Time for which a user is blocked from logging in after too many failed login attempts.	integer	Minimum value: 0 Maximum value: 4294967295	60						
login-timeout	SSLVPN maximum login timeout.	integer	Minimum value: 10 Maximum value: 180	30						
port	SSL-VPN access port.	integer	Minimum value: 1 Maximum value: 65535	10443						
port-precedence	Enable/disable, Enable means that if SSL-VPN connections are allowed on an interface admin GUI connections are blocked on that interface.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>				Option	Description	enable	Enable setting.	disable	Disable setting.
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
reqclientcert	Enable/disable to require client certificates for all SSL-VPN users.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>				Option	Description	enable	Enable setting.	disable	Disable setting.
Option	Description									
enable	Enable setting.									
disable	Disable setting.									

Parameter	Description	Type	Size	Default						
saml-redirect-port	SAML local redirect port in the machine running FortiClient. 0 is to disable redirection on FGT side.	integer	Minimum value: 0 Maximum value: 65535	8020						
server-hostname	Server hostname for HTTPS. When set, will be used for SSL VPN web proxy host header for any redirection.	string	Maximum length: 255							
servercert	Name of the server certificate to be used for SSL-VPNs.	string	Maximum length: 35							
source-address <name>	Source address of incoming traffic. Address name.	string	Maximum length: 79							
source-address-negate	Enable/disable negated source address match.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>				Option	Description	enable	Enable setting.	disable	Disable setting.
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
source-address6 <name>	IPv6 source address of incoming traffic. IPv6 address name.	string	Maximum length: 79							
source-address6-negate	Enable/disable negated source IPv6 address match.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>				Option	Description	enable	Enable setting.	disable	Disable setting.
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
source-interface <name>	SSL-VPN source interface of incoming traffic. Interface name.	string	Maximum length: 35							
ssl-client-renegotiation	Enable/disable to allow client renegotiation by the server if the tunnel goes down.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>disable</td><td>Abort any SSL connection that attempts to renegotiate.</td></tr><tr><td>enable</td><td>Allow a SSL client to renegotiate.</td></tr></table>				Option	Description	disable	Abort any SSL connection that attempts to renegotiate.	enable	Allow a SSL client to renegotiate.
Option	Description									
disable	Abort any SSL connection that attempts to renegotiate.									
enable	Allow a SSL client to renegotiate.									

Parameter	Description	Type	Size	Default
ssl-insert-empty-fragment	Enable/disable insertion of empty fragment.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
ssl-max-protocol-ver	SSL maximum protocol version.	option	-	tls1-3
	Option	Description		
	<i>tls1-0</i>	TLS version 1.0.		
	<i>tls1-1</i>	TLS version 1.1.		
	<i>tls1-2</i>	TLS version 1.2.		
	<i>tls1-3</i>	TLS version 1.3.		
ssl-min-protocol-ver	SSL minimum protocol version.	option	-	tls1-2
	Option	Description		
	<i>tls1-0</i>	TLS version 1.0.		
	<i>tls1-1</i>	TLS version 1.1.		
	<i>tls1-2</i>	TLS version 1.2.		
	<i>tls1-3</i>	TLS version 1.3.		
status	Enable/disable SSL-VPN.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable SSL-VPN.		
	<i>disable</i>	Disable SSL-VPN.		
transform-backward-slashes	Transform backward slashes to forward slashes in URLs.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		

Parameter	Description	Type	Size	Default						
tunnel-addr-assigned-method	Method used for assigning address for tunnel.	option	-	first-available						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>first-available</td><td>Assign the first available address from the pools.</td></tr><tr><td>round-robin</td><td>Assign the available address from the pool with a round robin fashion.</td></tr></table>	Option	Description	first-available	Assign the first available address from the pools.	round-robin	Assign the available address from the pool with a round robin fashion.			
Option	Description									
first-available	Assign the first available address from the pools.									
round-robin	Assign the available address from the pool with a round robin fashion.									
tunnel-connect-without-reauth	Enable/disable tunnel connection without re-authorization if previous connection dropped.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable tunnel connection without re-authorization.</td></tr><tr><td>disable</td><td>Disable tunnel connection without re-authorization.</td></tr></table>	Option	Description	enable	Enable tunnel connection without re-authorization.	disable	Disable tunnel connection without re-authorization.			
Option	Description									
enable	Enable tunnel connection without re-authorization.									
disable	Disable tunnel connection without re-authorization.									
tunnel-ip-pools <name>	Names of the IPv4 IP Pool firewall objects that define the IP addresses reserved for remote clients. Address name.	string	Maximum length: 79							
tunnel-ipv6-pools <name>	Names of the IPv6 IP Pool firewall objects that define the IP addresses reserved for remote clients. Address name.	string	Maximum length: 79							
tunnel-user-session-timeout	Number of seconds after which user sessions are cleaned up after tunnel connection is dropped.	integer	Minimum value: 1 Maximum value: 86400	30						
unsafe-legacy-renegotiation	Enable/disable unsafe legacy re-negotiation.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
url-obscuration	Enable/disable to obscure the host name of the URL of the web browser display.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									

Parameter	Description	Type	Size	Default						
user-peer	Name of user peer.	string	Maximum length: 35							
wins-server1	WINS server 1.	ipv4-address	Not Specified	0.0.0.0						
wins-server2	WINS server 2.	ipv4-address	Not Specified	0.0.0.0						
x-content-type-options	Add HTTP X-Content-Type-Options header.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>				Option	Description	enable	Enable setting.	disable	Disable setting.
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
ztina-trusted-client	Enable/disable verification of device certificate for SSLVPN ZTNA session.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable verification of device certificate for SSLVPN ZTNA session.</td></tr><tr><td>disable</td><td>Disable verification of device certificate for SSLVPN ZTNA session.</td></tr></table>				Option	Description	enable	Enable verification of device certificate for SSLVPN ZTNA session.	disable	Disable verification of device certificate for SSLVPN ZTNA session.
Option	Description									
enable	Enable verification of device certificate for SSLVPN ZTNA session.									
disable	Disable verification of device certificate for SSLVPN ZTNA session.									

config authentication-rule

Parameter	Description	Type	Size	Default														
auth	SSL-VPN authentication method restriction.	option	-	any														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>any</i></td><td>Any</td></tr><tr><td><i>local</i></td><td>Local</td></tr><tr><td><i>radius</i></td><td>RADIUS</td></tr><tr><td><i>tacacs+</i></td><td>TACACS+</td></tr><tr><td><i>ldap</i></td><td>LDAP</td></tr><tr><td><i>peer</i></td><td>PEER</td></tr></table>	Option	Description	<i>any</i>	Any	<i>local</i>	Local	<i>radius</i>	RADIUS	<i>tacacs+</i>	TACACS+	<i>ldap</i>	LDAP	<i>peer</i>	PEER			
Option	Description																	
<i>any</i>	Any																	
<i>local</i>	Local																	
<i>radius</i>	RADIUS																	
<i>tacacs+</i>	TACACS+																	
<i>ldap</i>	LDAP																	
<i>peer</i>	PEER																	
cipher	SSL-VPN cipher strength.	option	-	high														
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>any</i></td><td>Any cipher strength.</td></tr></table>	Option	Description	<i>any</i>	Any cipher strength.													
Option	Description																	
<i>any</i>	Any cipher strength.																	

Parameter	Description	Type	Size	Default						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>high</i></td><td>High cipher strength (>= 168 bits).</td></tr><tr><td><i>medium</i></td><td>Medium cipher strength (>= 128 bits).</td></tr></table>	Option	Description	<i>high</i>	High cipher strength (>= 168 bits).	<i>medium</i>	Medium cipher strength (>= 128 bits).			
	Option	Description								
	<i>high</i>	High cipher strength (>= 168 bits).								
<i>medium</i>	Medium cipher strength (>= 128 bits).									
client-cert	Enable/disable SSL-VPN client certificate restrictive.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									
groups <name>	User groups. Group name.	string	Maximum length: 79							
id	ID.	integer	Minimum value: 0 Maximum value: 4294967295	0						
portal	SSL-VPN portal.	string	Maximum length: 35							
realm	SSL-VPN realm.	string	Maximum length: 35							
source- address <name>	Source address of incoming traffic. Address name.	string	Maximum length: 79							
source- address- negate	Enable/disable negated source address match.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									
source- address6 <name>	IPv6 source address of incoming traffic. IPv6 address name.	string	Maximum length: 79							
source- address6- negate	Enable/disable negated source IPv6 address match.	option	-	disable						

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
source-interface <name>	SSL-VPN source interface of incoming traffic. Interface name.	string	Maximum length: 35	
user-peer	Name of user peer.	string	Maximum length: 35	
users <name>	User name. User name.	string	Maximum length: 79	

config vpn ssl web host-check-software

SSL-VPN host check software.

```

config vpn ssl web host-check-software
  Description: SSL-VPN host check software.
  edit <name>
    config check-item-list
      Description: Check item list.
      edit <id>
        set action [require|deny]
        set md5s <id1>, <id2>, ...
        set target {string}
        set type [file|registry|...]
        set version {string}
      next
    end
    set guid {user}
    set os-type [windows|macos]
    set type [av|fw]
    set version {string}
  next
end

```

config vpn ssl web host-check-software

Parameter	Description	Type	Size	Default
guid	Globally unique ID.	user	Not Specified	
name	Name.	string	Maximum length: 63	

Parameter	Description	Type	Size	Default						
os-type	OS type.	option	-	windows						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>windows</td><td>Microsoft Windows operating system.</td></tr><tr><td>macos</td><td>Apple MacOS operating system.</td></tr></table>	Option	Description	windows	Microsoft Windows operating system.	macos	Apple MacOS operating system.			
	Option	Description								
	windows	Microsoft Windows operating system.								
macos	Apple MacOS operating system.									
type	Type.	option	-	av						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>av</td><td>AntiVirus.</td></tr><tr><td>fw</td><td>Firewall.</td></tr></table>	Option	Description	av	AntiVirus.	fw	Firewall.			
	Option	Description								
	av	AntiVirus.								
fw	Firewall.									
version	Version.	string	Maximum length: 35							

config check-item-list

Parameter	Description	Type	Size	Default
action	Action.	option	-	require
	Option	Description		
	require	Require.		
	deny	Deny.		
id	ID.	integer	Minimum value: 0 Maximum value: 65535	0
md5s <id>	MD5 checksum. Hex string of MD5 checksum.	string	Maximum length: 32	
target	Target.	string	Maximum length: 255	
type	Type.	option	-	file
	Option	Description		
	file	File.		
	registry	Registry.		
	process	Process.		

Parameter	Description	Type	Size	Default
version	Version.	string	Maximum length: 35	

config vpn ssl web portal

Portal.

```

config vpn ssl web portal
  Description: Portal.
  edit <name>
    set allow-user-access {option1}, {option2}, ...
    set auto-connect [enable|disable]
    config bookmark-group
      Description: Portal bookmark group.
      edit <name>
        config bookmarks
          Description: Bookmark table.
          edit <name>
            set additional-params {var-string}
            set apptype [ftp|rdp|...]
            set color-depth [32|16|...]
            set description {var-string}
            set domain {var-string}
            set folder {var-string}
            config form-data
              Description: Form data.
              edit <name>
                set value {var-string}
              next
            end
            set height {integer}
            set host {var-string}
            set keyboard-layout [ar-101|ar-102|...]
            set load-balancing-info {var-string}
            set logon-password {password}
            set logon-user {var-string}
            set port {integer}
            set preconnection-blob {var-string}
            set preconnection-id {integer}
            set restricted-admin [enable|disable]
            set security [any|rdp|...]
            set send-preconnection-id [enable|disable]
            set sso [disable|static|...]
            set sso-credential [sslvpn-login|alternative]
            set sso-credential-sent-once [enable|disable]
            set sso-password {password}
            set sso-username {var-string}
            set url {var-string}
            set vnc-keyboard-layout [default|da|...]
            set width {integer}
          next
        end
      end
    end
  end

```

```

        next
    end
    set client-src-range [enable|disable]
    set clipboard [enable|disable]
    set custom-lang {string}
    set customize-forticlient-download-url [enable|disable]
    set default-protocol [web|ftp|...]
    set default-window-height {integer}
    set default-window-width {integer}
    set dhcp-ip-overlap [use-new|use-old]
    set dhcp-ra-giaddr {ipv4-address}
    set dhcp6-ra-linkaddr {ipv6-address}
    set display-bookmark [enable|disable]
    set display-connection-tools [enable|disable]
    set display-history [enable|disable]
    set display-status [enable|disable]
    set dns-server1 {ipv4-address}
    set dns-server2 {ipv4-address}
    set dns-suffix {var-string}
    set exclusive-routing [enable|disable]
    set focus-bookmark [enable|disable]
    set forticlient-download [enable|disable]
    set forticlient-download-method [direct|ssl-vpn]
    set heading {string}
    set hide-sso-credential [enable|disable]
    set host-check [none|av|...]
    set host-check-interval {integer}
    set host-check-policy <name1>, <name2>, ...
    set ip-mode [range|user-group|...]
    set ip-pools <name1>, <name2>, ...
    set ipv6-dns-server1 {ipv6-address}
    set ipv6-dns-server2 {ipv6-address}
    set ipv6-exclusive-routing [enable|disable]
    set ipv6-pools <name1>, <name2>, ...
    set ipv6-service-restriction [enable|disable]
    set ipv6-split-tunneling [enable|disable]
    set ipv6-split-tunneling-routing-address <name1>, <name2>, ...
    set ipv6-split-tunneling-routing-negate [enable|disable]
    set ipv6-tunnel-mode [enable|disable]
    set ipv6-wins-server1 {ipv6-address}
    set ipv6-wins-server2 {ipv6-address}
    set keep-alive [enable|disable]
    config landing-page
        Description: Landing page options.
        config form-data
            Description: Form data.
            edit <name>
                set value {var-string}
            next
        end
        set sso [disable|static|...]
        set sso-credential [sslvpn-login|alternative]
        set sso-password {password}
        set sso-username {var-string}
        set url {var-string}
    end
end

```

```

set landing-page-mode [enable|disable]
set limit-user-logins [enable|disable]
set mac-addr-action [allow|deny]
set mac-addr-check [enable|disable]
config mac-addr-check-rule
    Description: Client MAC address check rule.
    edit <name>
        set mac-addr-list <addr1>, <addr2>, ...
        set mac-addr-mask {integer}
    next
end
set macos-forticlient-download-url {var-string}
set os-check [enable|disable]
config os-check-list
    Description: SSL-VPN OS checks. Read-only.
    edit <name>
        set action [deny|allow|...]
        set latest-patch-level {user}
        set tolerance {integer}
    next
end
set prefer-ipv6-dns [enable|disable]
set redir-url {var-string}
set rewrite-ip-uri-ui [enable|disable]
set save-password [enable|disable]
set service-restriction [enable|disable]
set skip-check-for-browser [enable|disable]
set skip-check-for-unsupported-os [enable|disable]
set smb-max-version [smbv1|smbv2|...]
set smb-min-version [smbv1|smbv2|...]
set smb-ntlmv1-auth [enable|disable]
set smbvl [enable|disable]
config split-dns
    Description: Split DNS for SSL-VPN.
    edit <id>
        set dns-server1 {ipv4-address}
        set dns-server2 {ipv4-address}
        set domains {var-string}
        set ipv6-dns-server1 {ipv6-address}
        set ipv6-dns-server2 {ipv6-address}
    next
end
set split-tunneling [enable|disable]
set split-tunneling-routing-address <name1>, <name2>, ...
set split-tunneling-routing-negate [enable|disable]
set theme [jade|neutrino|...]
set tunnel-mode [enable|disable]
set use-sdwan [enable|disable]
set user-bookmark [enable|disable]
set user-group-bookmark [enable|disable]
set web-mode [enable|disable]
set windows-forticlient-download-url {var-string}
set wins-server1 {ipv4-address}
set wins-server2 {ipv4-address}
next
end

```

config vpn ssl web portal

Parameter	Description	Type	Size	Default																				
allow-user-access	Allow user access to SSL-VPN applications.	option	-	web ftp smb sftp telnet ssh vnc rdp ping																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>web</td><td>HTTP/HTTPS access.</td></tr><tr><td>ftp</td><td>FTP access.</td></tr><tr><td>smb</td><td>SMB/CIFS access.</td></tr><tr><td>sftp</td><td>SFTP access.</td></tr><tr><td>telnet</td><td>TELNET access.</td></tr><tr><td>ssh</td><td>SSH access.</td></tr><tr><td>vnc</td><td>VNC access.</td></tr><tr><td>rdp</td><td>RDP access.</td></tr><tr><td>ping</td><td>PING access.</td></tr></table>	Option	Description	web	HTTP/HTTPS access.	ftp	FTP access.	smb	SMB/CIFS access.	sftp	SFTP access.	telnet	TELNET access.	ssh	SSH access.	vnc	VNC access.	rdp	RDP access.	ping	PING access.			
Option	Description																							
web	HTTP/HTTPS access.																							
ftp	FTP access.																							
smb	SMB/CIFS access.																							
sftp	SFTP access.																							
telnet	TELNET access.																							
ssh	SSH access.																							
vnc	VNC access.																							
rdp	RDP access.																							
ping	PING access.																							
auto-connect	Enable/disable automatic connect by client when system is up.	option	-	disable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.																	
Option	Description																							
enable	Enable setting.																							
disable	Disable setting.																							
client-src-range	Allow client to add source range for the tunnel traffic.	option	-	disable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.																	
Option	Description																							
enable	Enable setting.																							
disable	Disable setting.																							
clipboard	Enable to support RDP/VPC clipboard functionality.	option	-	enable																				
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable support of RDP/VNC clipboard.</td></tr><tr><td>disable</td><td>Disable support of RDP/VNC clipboard.</td></tr></table>	Option	Description	enable	Enable support of RDP/VNC clipboard.	disable	Disable support of RDP/VNC clipboard.																	
Option	Description																							
enable	Enable support of RDP/VNC clipboard.																							
disable	Disable support of RDP/VNC clipboard.																							

Parameter	Description	Type	Size	Default																		
custom-lang	Change the web portal display language. Overrides config system global set language. You can use config system custom-language and execute system custom-language to add custom language files.	string	Maximum length: 35																			
customize-forticlient-download-url	Enable support of customized download URL for FortiClient.	option	-	disable																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.															
Option	Description																					
<i>enable</i>	Enable setting.																					
<i>disable</i>	Disable setting.																					
default-protocol	Application type that is set by default.	option	-	web																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>web</i></td><td>HTTP/HTTPS.</td></tr><tr><td><i>ftp</i></td><td>FTP.</td></tr><tr><td><i>telnet</i></td><td>Telnet.</td></tr><tr><td><i>smb</i></td><td>SMB/CIFS.</td></tr><tr><td><i>vnc</i></td><td>VNC.</td></tr><tr><td><i>rdp</i></td><td>RDP.</td></tr><tr><td><i>ssh</i></td><td>SSH.</td></tr><tr><td><i>sftp</i></td><td>SFTP.</td></tr></table>	Option	Description	<i>web</i>	HTTP/HTTPS.	<i>ftp</i>	FTP.	<i>telnet</i>	Telnet.	<i>smb</i>	SMB/CIFS.	<i>vnc</i>	VNC.	<i>rdp</i>	RDP.	<i>ssh</i>	SSH.	<i>sftp</i>	SFTP.			
Option	Description																					
<i>web</i>	HTTP/HTTPS.																					
<i>ftp</i>	FTP.																					
<i>telnet</i>	Telnet.																					
<i>smb</i>	SMB/CIFS.																					
<i>vnc</i>	VNC.																					
<i>rdp</i>	RDP.																					
<i>ssh</i>	SSH.																					
<i>sftp</i>	SFTP.																					
default-window-height	Screen height.	integer	Minimum value: 0 Maximum value: 65535	768																		
default-window-width	Screen width.	integer	Minimum value: 0 Maximum value: 65535	1024																		
dhcp-ip-overlap	Configure overlapping DHCP IP allocation assignment.	option	-	use-new																		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>use-new</i>	Assign DHCP lease to new client and remove old client lease.		
	<i>use-old</i>	Preserve previous client IP allocation and disconnect new client.		
dhcp-ra-giaddr	Relay agent gateway IP address to use in the giaddr field of DHCP requests.	ipv4-address	Not Specified	0.0.0.0
dhcp6-ra-linkaddr	Relay agent IPv6 link address to use in DHCP6 requests.	ipv6-address	Not Specified	::
display-bookmark	Enable to display the web portal bookmark widget.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
display-connection-tools	Enable to display the web portal connection tools widget.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
display-history	Enable to display the web portal user login history widget.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
display-status	Enable to display the web portal status widget.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
dns-server1	IPv4 DNS server 1.	ipv4-address	Not Specified	0.0.0.0
dns-server2	IPv4 DNS server 2.	ipv4-address	Not Specified	0.0.0.0

Parameter	Description	Type	Size	Default						
dns-suffix	DNS suffix.	var-string	Maximum length: 253							
exclusive-routing	Enable/disable all traffic go through tunnel only.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>				Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									
focus-bookmark	Enable to prioritize the placement of the bookmark section over the quick-connection section in the SSL-VPN application.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>				Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									
forticlient-download	Enable/disable download option for FortiClient.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>				Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									
forticlient-download-method	FortiClient download method.	option	-	direct						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>direct</i></td><td>Download via direct link.</td></tr><tr><td><i>ssl-vpn</i></td><td>Download via SSL-VPN.</td></tr></table>				Option	Description	<i>direct</i>	Download via direct link.	<i>ssl-vpn</i>	Download via SSL-VPN.
	Option	Description								
	<i>direct</i>	Download via direct link.								
<i>ssl-vpn</i>	Download via SSL-VPN.									
heading	Web portal heading message.	string	Maximum length: 31	SSL-VPN Portal						
hide-sso-credential	Enable to prevent SSO credential being sent to client.	option	-	enable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>				Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.
	Option	Description								
	<i>enable</i>	Enable setting.								
<i>disable</i>	Disable setting.									

Parameter	Description	Type	Size	Default												
host-check	Type of host checking performed on endpoints.	option	-	none												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>none</i></td><td>No host checking.</td></tr><tr><td><i>av</i></td><td>AntiVirus software recognized by the Windows Security Center.</td></tr><tr><td><i>fw</i></td><td>Firewall software recognized by the Windows Security Center.</td></tr><tr><td><i>av-fw</i></td><td>AntiVirus and firewall software recognized by the Windows Security Center.</td></tr><tr><td><i>custom</i></td><td>Custom.</td></tr></table>	Option	Description	<i>none</i>	No host checking.	<i>av</i>	AntiVirus software recognized by the Windows Security Center.	<i>fw</i>	Firewall software recognized by the Windows Security Center.	<i>av-fw</i>	AntiVirus and firewall software recognized by the Windows Security Center.	<i>custom</i>	Custom.			
	Option	Description														
	<i>none</i>	No host checking.														
	<i>av</i>	AntiVirus software recognized by the Windows Security Center.														
	<i>fw</i>	Firewall software recognized by the Windows Security Center.														
	<i>av-fw</i>	AntiVirus and firewall software recognized by the Windows Security Center.														
<i>custom</i>	Custom.															
host-check-interval	Periodic host check interval. Value of 0 means disabled and host checking only happens when the endpoint connects.	integer	Minimum value: 120 Maximum value: 259200	0												
host-check-policy <name>	One or more policies to require the endpoint to have specific security software. Host check software list name.	string	Maximum length: 79													
ip-mode	Method by which users of this SSL-VPN tunnel obtain IP addresses.	option	-	range												
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>range</i></td><td>Use the IP addresses available for all SSL-VPN users as defined by the SSL settings command.</td></tr><tr><td><i>user-group</i></td><td>Use the IP addresses associated with individual users or user groups (usually from external auth servers).</td></tr><tr><td><i>dhcp</i></td><td>Use IP addresses obtained from external DHCP server.</td></tr><tr><td><i>no-ip</i></td><td>Do not assign IP address.</td></tr></table>	Option	Description	<i>range</i>	Use the IP addresses available for all SSL-VPN users as defined by the SSL settings command.	<i>user-group</i>	Use the IP addresses associated with individual users or user groups (usually from external auth servers).	<i>dhcp</i>	Use IP addresses obtained from external DHCP server.	<i>no-ip</i>	Do not assign IP address.					
	Option	Description														
	<i>range</i>	Use the IP addresses available for all SSL-VPN users as defined by the SSL settings command.														
	<i>user-group</i>	Use the IP addresses associated with individual users or user groups (usually from external auth servers).														
	<i>dhcp</i>	Use IP addresses obtained from external DHCP server.														
<i>no-ip</i>	Do not assign IP address.															
ip-pools <name>	IPv4 firewall source address objects reserved for SSL-VPN tunnel mode clients. Address name.	string	Maximum length: 79													
ipv6-dns-server1	IPv6 DNS server 1.	ipv6-address	Not Specified	::												
ipv6-dns-server2	IPv6 DNS server 2.	ipv6-address	Not Specified	::												
ipv6-exclusive-routing	Enable/disable all IPv6 traffic go through tunnel only.	option	-	disable												

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
ipv6-pools <name>	IPv6 firewall source address objects reserved for SSL-VPN tunnel mode clients. Address name.	string	Maximum length: 79	
ipv6-service-restriction	Enable/disable IPv6 tunnel service restriction.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
ipv6-split-tunneling	Enable/disable IPv6 split tunneling.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
ipv6-split-tunneling-routing-address <name>	IPv6 SSL-VPN tunnel mode firewall address objects that override firewall policy destination addresses to control split-tunneling access. Address name.	string	Maximum length: 79	
ipv6-split-tunneling-routing-negate	Enable to negate IPv6 split tunneling routing address.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
ipv6-tunnel-mode	Enable/disable IPv6 SSL-VPN tunnel mode.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		

Parameter	Description	Type	Size	Default						
ipv6-wins-server1	IPv6 WINS server 1.	ipv6-address	Not Specified	::						
ipv6-wins-server2	IPv6 WINS server 2.	ipv6-address	Not Specified	::						
keep-alive	Enable/disable automatic reconnect for FortiClient connections.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
landing-page-mode	Enable/disable SSL-VPN landing page mode.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
limit-user-logins	Enable to limit each user to one SSL-VPN session at a time.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									
mac-addr-action	Client MAC address action.	option	-	allow						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>allow</i></td><td>Allow connection when client MAC address is matched.</td></tr><tr><td><i>deny</i></td><td>Deny connection when client MAC address is matched.</td></tr></table>	Option	Description	<i>allow</i>	Allow connection when client MAC address is matched.	<i>deny</i>	Deny connection when client MAC address is matched.			
Option	Description									
<i>allow</i>	Allow connection when client MAC address is matched.									
<i>deny</i>	Deny connection when client MAC address is matched.									
mac-addr-check	Enable/disable MAC address host checking.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.			
Option	Description									
<i>enable</i>	Enable setting.									
<i>disable</i>	Disable setting.									

Parameter	Description	Type	Size	Default						
macos-forticlient-download-url	Download URL for Mac FortiClient.	var-string	Maximum length: 1023							
name	Portal name.	string	Maximum length: 35							
os-check	Enable to let the FortiGate decide action based on client OS.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
prefer-ipv6-dns	Prefer to query IPv6 DNS server first if enabled.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
redir-url	Client login redirect URL.	var-string	Maximum length: 255							
rewrite-ip-uri-ui	Rewrite contents for URI contains IP and /ui/.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable contents rewrite for URI contains "IP-address/ui/".</td></tr><tr><td>disable</td><td>Disable contents rewrite for URI contains "IP-address/ui/".</td></tr></table>	Option	Description	enable	Enable contents rewrite for URI contains "IP-address/ui/".	disable	Disable contents rewrite for URI contains "IP-address/ui/".			
Option	Description									
enable	Enable contents rewrite for URI contains "IP-address/ui/".									
disable	Disable contents rewrite for URI contains "IP-address/ui/".									
save-password	Enable/disable FortiClient saving the user's password.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									
service-restriction	Enable/disable tunnel service restriction.	option	-	disable						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>enable</td><td>Enable setting.</td></tr><tr><td>disable</td><td>Disable setting.</td></tr></table>	Option	Description	enable	Enable setting.	disable	Disable setting.			
Option	Description									
enable	Enable setting.									
disable	Disable setting.									

Parameter	Description	Type	Size	Default								
skip-check-for-browser	Enable to skip host check for browser support.	option	-	enable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.					
	Option	Description										
	<i>enable</i>	Enable setting.										
<i>disable</i>	Disable setting.											
skip-check-for-unsupported-os	Enable to skip host check if client OS does not support it.	option	-	enable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.					
	Option	Description										
	<i>enable</i>	Enable setting.										
<i>disable</i>	Disable setting.											
smb-max-version	SMB maximum client protocol version.	option	-	smbv3								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>smbv1</i></td><td>SMB version 1.</td></tr><tr><td><i>smbv2</i></td><td>SMB version 2.</td></tr><tr><td><i>smbv3</i></td><td>SMB version 3.</td></tr></table>	Option	Description	<i>smbv1</i>	SMB version 1.	<i>smbv2</i>	SMB version 2.	<i>smbv3</i>	SMB version 3.			
	Option	Description										
	<i>smbv1</i>	SMB version 1.										
	<i>smbv2</i>	SMB version 2.										
<i>smbv3</i>	SMB version 3.											
smb-min-version	SMB minimum client protocol version.	option	-	smbv2								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>smbv1</i></td><td>SMB version 1.</td></tr><tr><td><i>smbv2</i></td><td>SMB version 2.</td></tr><tr><td><i>smbv3</i></td><td>SMB version 3.</td></tr></table>	Option	Description	<i>smbv1</i>	SMB version 1.	<i>smbv2</i>	SMB version 2.	<i>smbv3</i>	SMB version 3.			
	Option	Description										
	<i>smbv1</i>	SMB version 1.										
	<i>smbv2</i>	SMB version 2.										
<i>smbv3</i>	SMB version 3.											
smb-ntlmv1-auth	Enable support of NTLMv1 for Samba authentication.	option	-	disable								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable setting.</td></tr><tr><td><i>disable</i></td><td>Disable setting.</td></tr></table>	Option	Description	<i>enable</i>	Enable setting.	<i>disable</i>	Disable setting.					
	Option	Description										
	<i>enable</i>	Enable setting.										
<i>disable</i>	Disable setting.											
smbv1	SMB version 1.	option	-	disable								

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	enable		
	<i>disable</i>	disable		
split-tunneling	Enable/disable IPv4 split tunneling.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
split-tunneling-routing-address <name>	IPv4 SSL-VPN tunnel mode firewall address objects that override firewall policy destination addresses to control split-tunneling access. Address name.	string	Maximum length: 79	
split-tunneling-routing-negate	Enable to negate split tunneling routing address.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
theme	Web portal color scheme.	option	-	security-fabric
	Option	Description		
	<i>jade</i>	Jade theme.		
	<i>neutrino</i>	Neutrino theme.		
	<i>mariner</i>	Mariner theme.		
	<i>graphite</i>	Graphite theme.		
	<i>melongene</i>	Melongene theme.		
	<i>jet-stream</i>	Jet Stream theme.		
	<i>security-fabric</i>	Security Fabric theme.		
	<i>dark-matter</i>	Dark Matter theme.		
	<i>onyx</i>	Onyx theme.		
	<i>eclipse</i>	Eclipse theme.		
tunnel-mode	Enable/disable IPv4 SSL-VPN tunnel mode.	option	-	disable

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
use-sdwan	Use SD-WAN rules to get output interface.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
user-bookmark	Enable to allow web portal users to create their own bookmarks.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
user-group-bookmark	Enable to allow web portal users to create bookmarks for all users in the same user group.	option	-	enable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
web-mode	Enable/disable SSL-VPN web mode.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
windows-forticlient-download-url	Download URL for Windows FortiClient.	var-string	Maximum length: 1023	
wins-server1	IPv4 WINS server 1.	ipv4-address	Not Specified	0.0.0.0
wins-server2	IPv4 WINS server 1.	ipv4-address	Not Specified	0.0.0.0

config bookmark-group

Parameter	Description	Type	Size	Default
name	Bookmark group name.	string	Maximum length: 35	

config bookmarks

Parameter	Description	Type	Size	Default																		
additional-params	Additional parameters.	var-string	Maximum length: 128																			
apptype	Application type.	option	-	web																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ftp</i></td><td>FTP.</td></tr><tr><td><i>rdp</i></td><td>RDP.</td></tr><tr><td><i>sftp</i></td><td>SFTP.</td></tr><tr><td><i>smb</i></td><td>SMB/CIFS.</td></tr><tr><td><i>ssh</i></td><td>SSH.</td></tr><tr><td><i>telnet</i></td><td>Telnet.</td></tr><tr><td><i>vnc</i></td><td>VNC.</td></tr><tr><td><i>web</i></td><td>HTTP/HTTPS.</td></tr></table>	Option	Description	<i>ftp</i>	FTP.	<i>rdp</i>	RDP.	<i>sftp</i>	SFTP.	<i>smb</i>	SMB/CIFS.	<i>ssh</i>	SSH.	<i>telnet</i>	Telnet.	<i>vnc</i>	VNC.	<i>web</i>	HTTP/HTTPS.			
	Option	Description																				
	<i>ftp</i>	FTP.																				
	<i>rdp</i>	RDP.																				
	<i>sftp</i>	SFTP.																				
	<i>smb</i>	SMB/CIFS.																				
	<i>ssh</i>	SSH.																				
	<i>telnet</i>	Telnet.																				
	<i>vnc</i>	VNC.																				
<i>web</i>	HTTP/HTTPS.																					
color-depth	Color depth per pixel.	option	-	16																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>32</td><td>32bits per pixel.</td></tr><tr><td>16</td><td>16bits per pixel.</td></tr><tr><td>8</td><td>8bits per pixel.</td></tr></table>	Option	Description	32	32bits per pixel.	16	16bits per pixel.	8	8bits per pixel.													
	Option	Description																				
	32	32bits per pixel.																				
	16	16bits per pixel.																				
8	8bits per pixel.																					
description	Description.	var-string	Maximum length: 128																			
domain	Login domain.	var-string	Maximum length: 128																			
folder	Network shared file folder parameter.	var-string	Maximum length: 128																			

Parameter	Description	Type	Size	Default
height	Screen height.	integer	Minimum value: 0 Maximum value: 65535	0
host	Host name/IP parameter.	var-string	Maximum length: 128	
keyboard-layout	Keyboard layout.	option	-	en-us

Option	Description
<i>ar-101</i>	Arabic (101).
<i>ar-102</i>	Arabic (102).
<i>ar-102-azerty</i>	Arabic (102) AZERTY.
<i>can-mul</i>	Canadian Multilingual Standard.
<i>cz</i>	Czech.
<i>cz-qwerty</i>	Czech (QWERTY).
<i>cz-pr</i>	Czech Programmers.
<i>da</i>	Danish.
<i>nl</i>	Dutch.
<i>de</i>	German.
<i>de-ch</i>	German, Switzerland.
<i>de-ibm</i>	German (IBM).
<i>en-uk</i>	English, United Kingdom.
<i>en-uk-ext</i>	English, United Kingdom Extended.
<i>en-us</i>	English, United States.
<i>en-us-dvorak</i>	English, United States-Dvorak.
<i>es</i>	Spanish.
<i>es-var</i>	Spanish Variation.
<i>fi</i>	Finnish.
<i>fi-sami</i>	Finnish with Sami.
<i>fr</i>	French.
<i>fr-apple</i>	French, Apple.
<i>fr-ca</i>	French, Canada.

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>fr-ch</i>	French, Switzerland.		
	<i>fr-be</i>	French, Belgium.		
	<i>hr</i>	Croatian.		
	<i>hu</i>	Hungarian.		
	<i>hu-101</i>	Hungarian 101-Key.		
	<i>it</i>	Italian.		
	<i>it-142</i>	Italian (142).		
	<i>ja</i>	Japanese.		
	<i>ja-106</i>	Japanese 106/109 key.		
	<i>ko</i>	Korean.		
	<i>la-am</i>	Latin American.		
	<i>lt</i>	Lithuanian.		
	<i>lt-ibm</i>	Lithuanian IBM.		
	<i>lt-std</i>	Lithuanian Standard.		
	<i>lav-std</i>	Latvian (Standard).		
	<i>lav-leg</i>	Latvian (Legacy).		
	<i>mk</i>	Macedonian (FYROM).		
	<i>mk-std</i>	Macedonia (FYROM) - Standard.		
	<i>no</i>	Norwegian.		
	<i>no-sami</i>	Norwegian with Sami.		
	<i>pol-214</i>	Polish (214).		
	<i>pol-pr</i>	Polish (Programmers).		
	<i>pt</i>	Portuguese.		
	<i>pt-br</i>	Portuguese (Brazilian ABNT).		
	<i>pt-br-abnt2</i>	Portuguese (Brazilian ABNT2).		
	<i>ru</i>	Russian.		
	<i>ru-mne</i>	Russian - Mnemonic.		
	<i>ru-t</i>	Russian (Typewriter).		
	<i>sl</i>	Slovenian.		

Parameter	Description	Type	Size	Default																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>sv</i></td><td>Swedish.</td></tr><tr><td><i>sv-sami</i></td><td>Swedish with Sami.</td></tr><tr><td><i>tuk</i></td><td>Turkmen.</td></tr><tr><td><i>tur-f</i></td><td>Turkish F.</td></tr><tr><td><i>tur-q</i></td><td>Turkish Q.</td></tr><tr><td><i>zh-sym-sg-us</i></td><td>Chinese (Simplified, Singapore) - US keyboard.</td></tr><tr><td><i>zh-sym-us</i></td><td>Chinese (Simplified) - US Keyboard.</td></tr><tr><td><i>zh-tr-hk</i></td><td>Chinese (Traditional, Hong Kong S.A.R.).</td></tr><tr><td><i>zh-tr-mo</i></td><td>Chinese (Traditional Macao S.A.R.) - US Keyboard.</td></tr><tr><td><i>zh-tr-us</i></td><td>Chinese (Traditional) - US keyboard.</td></tr></table>	Option	Description	<i>sv</i>	Swedish.	<i>sv-sami</i>	Swedish with Sami.	<i>tuk</i>	Turkmen.	<i>tur-f</i>	Turkish F.	<i>tur-q</i>	Turkish Q.	<i>zh-sym-sg-us</i>	Chinese (Simplified, Singapore) - US keyboard.	<i>zh-sym-us</i>	Chinese (Simplified) - US Keyboard.	<i>zh-tr-hk</i>	Chinese (Traditional, Hong Kong S.A.R.).	<i>zh-tr-mo</i>	Chinese (Traditional Macao S.A.R.) - US Keyboard.	<i>zh-tr-us</i>	Chinese (Traditional) - US keyboard.			
	Option	Description																								
	<i>sv</i>	Swedish.																								
	<i>sv-sami</i>	Swedish with Sami.																								
	<i>tuk</i>	Turkmen.																								
	<i>tur-f</i>	Turkish F.																								
	<i>tur-q</i>	Turkish Q.																								
	<i>zh-sym-sg-us</i>	Chinese (Simplified, Singapore) - US keyboard.																								
	<i>zh-sym-us</i>	Chinese (Simplified) - US Keyboard.																								
	<i>zh-tr-hk</i>	Chinese (Traditional, Hong Kong S.A.R.).																								
	<i>zh-tr-mo</i>	Chinese (Traditional Macao S.A.R.) - US Keyboard.																								
<i>zh-tr-us</i>	Chinese (Traditional) - US keyboard.																									
load-balancing-info	The load balancing information or cookie which should be provided to the connection broker.	var-string	Maximum length: 511																							
logon-password	Logon password.	password	Not Specified																							
logon-user	Logon user.	var-string	Maximum length: 35																							
name	Bookmark name.	string	Maximum length: 35																							
port	Remote port.	integer	Minimum value: 0 Maximum value: 65535	0																						
preconnection-blob	An arbitrary string which identifies the RDP source.	var-string	Maximum length: 511																							
preconnection-id	The numeric ID of the RDP source.	integer	Minimum value: 0 Maximum value: 4294967295	0																						
restricted-admin	Enable/disable restricted admin mode for RDP.	option	-	disable																						
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable restricted admin mode for RDP.</td></tr><tr><td><i>disable</i></td><td>Disable restricted admin mode for RDP.</td></tr></table>	Option	Description	<i>enable</i>	Enable restricted admin mode for RDP.	<i>disable</i>	Disable restricted admin mode for RDP.																			
	Option	Description																								
	<i>enable</i>	Enable restricted admin mode for RDP.																								
<i>disable</i>	Disable restricted admin mode for RDP.																									

Parameter	Description	Type	Size	Default										
security	Security mode for RDP connection.	option	-	any										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>any</i></td><td>Allow the server to choose the type of security.</td></tr><tr><td><i>rdp</i></td><td>Standard RDP encryption.</td></tr><tr><td><i>nla</i></td><td>Network Level Authentication.</td></tr><tr><td><i>tls</i></td><td>TLS encryption.</td></tr></table>	Option	Description	<i>any</i>	Allow the server to choose the type of security.	<i>rdp</i>	Standard RDP encryption.	<i>nla</i>	Network Level Authentication.	<i>tls</i>	TLS encryption.			
	Option	Description												
	<i>any</i>	Allow the server to choose the type of security.												
	<i>rdp</i>	Standard RDP encryption.												
	<i>nla</i>	Network Level Authentication.												
<i>tls</i>	TLS encryption.													
send-preconnection-id	Enable/disable sending of preconnection ID.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable sending of preconnection ID.</td></tr><tr><td><i>disable</i></td><td>Disable sending of preconnection ID.</td></tr></table>	Option	Description	<i>enable</i>	Enable sending of preconnection ID.	<i>disable</i>	Disable sending of preconnection ID.							
	Option	Description												
	<i>enable</i>	Enable sending of preconnection ID.												
<i>disable</i>	Disable sending of preconnection ID.													
sso	Single sign-on.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>disable</i></td><td>Disable SSO.</td></tr><tr><td><i>static</i></td><td>Static SSO.</td></tr><tr><td><i>auto</i></td><td>Auto SSO.</td></tr></table>	Option	Description	<i>disable</i>	Disable SSO.	<i>static</i>	Static SSO.	<i>auto</i>	Auto SSO.					
	Option	Description												
	<i>disable</i>	Disable SSO.												
	<i>static</i>	Static SSO.												
<i>auto</i>	Auto SSO.													
sso-credential	Single sign-on credentials.	option	-	sslvpn-login										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>sslvpn-login</i></td><td>SSL-VPN login.</td></tr><tr><td><i>alternative</i></td><td>Alternative.</td></tr></table>	Option	Description	<i>sslvpn-login</i>	SSL-VPN login.	<i>alternative</i>	Alternative.							
	Option	Description												
	<i>sslvpn-login</i>	SSL-VPN login.												
<i>alternative</i>	Alternative.													
sso-credential-sent-once	Single sign-on credentials are only sent once to remote server.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Single sign-on credentials are only sent once to remote server.</td></tr><tr><td><i>disable</i></td><td>Single sign-on credentials are sent to remote server for every HTTP request.</td></tr></table>	Option	Description	<i>enable</i>	Single sign-on credentials are only sent once to remote server.	<i>disable</i>	Single sign-on credentials are sent to remote server for every HTTP request.							
	Option	Description												
	<i>enable</i>	Single sign-on credentials are only sent once to remote server.												
<i>disable</i>	Single sign-on credentials are sent to remote server for every HTTP request.													
sso-password	SSO password.	password	Not Specified											
sso-username	SSO user name.	var-string	Maximum length: 35											

Parameter	Description	Type	Size	Default																																													
url	URL parameter.	var-string	Maximum length: 128																																														
vnc-keyboard-layout	Keyboard layout.	option	-	default																																													
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>default</i></td><td>Default.</td></tr><tr><td><i>da</i></td><td>Danish.</td></tr><tr><td><i>nl</i></td><td>Dutch.</td></tr><tr><td><i>en-uk</i></td><td>English, United Kingdom.</td></tr><tr><td><i>en-uk-ext</i></td><td>English, United Kingdom Extended.</td></tr><tr><td><i>fi</i></td><td>Finnish.</td></tr><tr><td><i>fr</i></td><td>French.</td></tr><tr><td><i>fr-be</i></td><td>French, Belgium.</td></tr><tr><td><i>fr-ca-mul</i></td><td>French, Canadian Multilingual Std.</td></tr><tr><td><i>de</i></td><td>German.</td></tr><tr><td><i>de-ch</i></td><td>German, Switzerland.</td></tr><tr><td><i>it</i></td><td>Italian.</td></tr><tr><td><i>it-142</i></td><td>Italian (142).</td></tr><tr><td><i>pt</i></td><td>Portuguese.</td></tr><tr><td><i>pt-br-abnt2</i></td><td>Portuguese (Brazilian ABNT2).</td></tr><tr><td><i>no</i></td><td>Norwegian.</td></tr><tr><td><i>gd</i></td><td>Scottish Gaelic.</td></tr><tr><td><i>es</i></td><td>Spanish.</td></tr><tr><td><i>sv</i></td><td>Swedish.</td></tr><tr><td><i>us-intl</i></td><td>United States-International.</td></tr></table>				Option	Description	<i>default</i>	Default.	<i>da</i>	Danish.	<i>nl</i>	Dutch.	<i>en-uk</i>	English, United Kingdom.	<i>en-uk-ext</i>	English, United Kingdom Extended.	<i>fi</i>	Finnish.	<i>fr</i>	French.	<i>fr-be</i>	French, Belgium.	<i>fr-ca-mul</i>	French, Canadian Multilingual Std.	<i>de</i>	German.	<i>de-ch</i>	German, Switzerland.	<i>it</i>	Italian.	<i>it-142</i>	Italian (142).	<i>pt</i>	Portuguese.	<i>pt-br-abnt2</i>	Portuguese (Brazilian ABNT2).	<i>no</i>	Norwegian.	<i>gd</i>	Scottish Gaelic.	<i>es</i>	Spanish.	<i>sv</i>	Swedish.	<i>us-intl</i>	United States-International.			
	Option	Description																																															
	<i>default</i>	Default.																																															
	<i>da</i>	Danish.																																															
	<i>nl</i>	Dutch.																																															
	<i>en-uk</i>	English, United Kingdom.																																															
	<i>en-uk-ext</i>	English, United Kingdom Extended.																																															
	<i>fi</i>	Finnish.																																															
	<i>fr</i>	French.																																															
	<i>fr-be</i>	French, Belgium.																																															
	<i>fr-ca-mul</i>	French, Canadian Multilingual Std.																																															
	<i>de</i>	German.																																															
	<i>de-ch</i>	German, Switzerland.																																															
	<i>it</i>	Italian.																																															
	<i>it-142</i>	Italian (142).																																															
	<i>pt</i>	Portuguese.																																															
	<i>pt-br-abnt2</i>	Portuguese (Brazilian ABNT2).																																															
	<i>no</i>	Norwegian.																																															
	<i>gd</i>	Scottish Gaelic.																																															
	<i>es</i>	Spanish.																																															
<i>sv</i>	Swedish.																																																
<i>us-intl</i>	United States-International.																																																
width	Screen width.	integer	Minimum value: 0 Maximum value: 65535	0																																													

config form-data

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
value	Value.	var-string	Maximum length: 63	

config form-data

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
value	Value.	var-string	Maximum length: 63	

config landing-page

Parameter	Description	Type	Size	Default
sso	Single sign-on.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable SSO.		
	<i>static</i>	Static SSO.		
	<i>auto</i>	Auto SSO.		
sso-credential	Single sign-on credentials.	option	-	sslvpn-login
	Option	Description		
	<i>sslvpn-login</i>	SSL-VPN login.		
	<i>alternative</i>	Alternative.		
sso-password	SSO password.	password	Not Specified	
sso-username	SSO user name.	var-string	Maximum length: 35	
url	Landing page URL.	var-string	Maximum length: 511	

config form-data

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
value	Value.	var-string	Maximum length: 63	

config form-data

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
value	Value.	var-string	Maximum length: 63	

config mac-addr-check-rule

Parameter	Description	Type	Size	Default
mac-addr-list <addr>	Client MAC address list. Client MAC address.	mac-address	Not Specified	
mac-addr-mask	Client MAC address mask.	integer	Minimum value: 1 Maximum value: 48	48
name	Client MAC address check rule name.	string	Maximum length: 35	

config os-check-list

Parameter	Description	Type	Size	Default								
action	OS check options.	option	-	allow								
	<table><tr><th>Option</th><th>Description</th></tr><tr><td>deny</td><td>Deny all OS versions.</td></tr><tr><td>allow</td><td>Allow any OS version.</td></tr><tr><td>check-up-to-date</td><td>Verify OS is up-to-date.</td></tr></table>				Option	Description	deny	Deny all OS versions.	allow	Allow any OS version.	check-up-to-date	Verify OS is up-to-date.
	Option	Description										
	deny	Deny all OS versions.										
	allow	Allow any OS version.										
check-up-to-date	Verify OS is up-to-date.											
latest-patch-level	Latest OS patch level.	user	Not Specified	0								

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
tolerance	OS patch level tolerance.	integer	Minimum value: 0 Maximum value: 65535	0

config split-dns

Parameter	Description	Type	Size	Default
dns-server1	DNS server 1.	ipv4-address	Not Specified	0.0.0.0
dns-server2	DNS server 2.	ipv4-address	Not Specified	0.0.0.0
domains	Split DNS domains used for SSL-VPN clients separated by comma.	var-string	Maximum length: 1024	
id	ID.	integer	Minimum value: 0 Maximum value: 4294967294	0
ipv6-dns-server1	IPv6 DNS server 1.	ipv6-address	Not Specified	::
ipv6-dns-server2	IPv6 DNS server 2.	ipv6-address	Not Specified	::

config vpn ssl web realm

Realm.

```

config vpn ssl web realm
  Description: Realm.
  edit <url-path>
    set login-page {var-string}
    set max-concurrent-user {integer}
    set nas-ip {ipv4-address}
    set radius-port {integer}
    set radius-server {string}
    set virtual-host {var-string}
    set virtual-host-only [enable|disable]
    set virtual-host-server-cert {string}
  next
end

```

config vpn ssl web realm

Parameter	Description	Type	Size	Default
login-page	Replacement HTML for SSL-VPN login page.	var-string	Maximum length: 32768	
max-concurrent-user	Maximum concurrent users.	integer	Minimum value: 0 Maximum value: 65535	0
nas-ip	IP address used as a NAS-IP to communicate with the RADIUS server.	ipv4-address	Not Specified	0.0.0.0
radius-port	RADIUS service port number.	integer	Minimum value: 0 Maximum value: 65535	0
radius-server	RADIUS server associated with realm.	string	Maximum length: 35	
url-path	URL path to access SSL-VPN login page.	string	Maximum length: 35	
virtual-host	Virtual host name for realm.	var-string	Maximum length: 255	
virtual-host-only	Enable/disable enforcement of virtual host method for SSL-VPN client access.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable setting.		
	<i>disable</i>	Disable setting.		
virtual-host-server-cert	Name of the server certificate to used for this realm.	string	Maximum length: 35	

config vpn ssl web user-bookmark

Configure SSL-VPN user bookmark.

```
config vpn ssl web user-bookmark
  Description: Configure SSL-VPN user bookmark.
  edit <name>
    config bookmarks
      Description: Bookmark table.
      edit <name>
```

```

set additional-params {var-string}
set apptype [ftp|rdp|...]
set color-depth [32|16|...]
set description {var-string}
set domain {var-string}
set folder {var-string}
config form-data
    Description: Form data.
    edit <name>
        set value {var-string}
    next
end
set height {integer}
set host {var-string}
set keyboard-layout [ar-101|ar-102|...]
set load-balancing-info {var-string}
set logon-password {password}
set logon-user {var-string}
set port {integer}
set preconnection-blob {var-string}
set preconnection-id {integer}
set restricted-admin [enable|disable]
set security [any|rdp|...]
set send-preconnection-id [enable|disable]
set sso [disable|static|...]
set sso-credential [sslvpn-login|alternative]
set sso-credential-sent-once [enable|disable]
set sso-password {password}
set sso-username {var-string}
set url {var-string}
set vnc-keyboard-layout [default|da|...]
set width {integer}
next
end
set custom-lang {string}
next
end

```

config vpn ssl web user-bookmark

Parameter	Description	Type	Size	Default
custom-lang	Personal language.	string	Maximum length: 35	
name	User and group name.	string	Maximum length: 101	

config bookmarks

Parameter	Description	Type	Size	Default																		
additional-params	Additional parameters.	var-string	Maximum length: 128																			
apptype	Application type.	option	-	web																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>ftp</i></td><td>FTP.</td></tr><tr><td><i>rdp</i></td><td>RDP.</td></tr><tr><td><i>sftp</i></td><td>SFTP.</td></tr><tr><td><i>smb</i></td><td>SMB/CIFS.</td></tr><tr><td><i>ssh</i></td><td>SSH.</td></tr><tr><td><i>telnet</i></td><td>Telnet.</td></tr><tr><td><i>vnc</i></td><td>VNC.</td></tr><tr><td><i>web</i></td><td>HTTP/HTTPS.</td></tr></table>	Option	Description	<i>ftp</i>	FTP.	<i>rdp</i>	RDP.	<i>sftp</i>	SFTP.	<i>smb</i>	SMB/CIFS.	<i>ssh</i>	SSH.	<i>telnet</i>	Telnet.	<i>vnc</i>	VNC.	<i>web</i>	HTTP/HTTPS.			
	Option	Description																				
	<i>ftp</i>	FTP.																				
	<i>rdp</i>	RDP.																				
	<i>sftp</i>	SFTP.																				
	<i>smb</i>	SMB/CIFS.																				
	<i>ssh</i>	SSH.																				
	<i>telnet</i>	Telnet.																				
	<i>vnc</i>	VNC.																				
<i>web</i>	HTTP/HTTPS.																					
color-depth	Color depth per pixel.	option	-	16																		
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>32</i></td><td>32bits per pixel.</td></tr><tr><td><i>16</i></td><td>16bits per pixel.</td></tr><tr><td><i>8</i></td><td>8bits per pixel.</td></tr></table>	Option	Description	<i>32</i>	32bits per pixel.	<i>16</i>	16bits per pixel.	<i>8</i>	8bits per pixel.													
	Option	Description																				
	<i>32</i>	32bits per pixel.																				
	<i>16</i>	16bits per pixel.																				
<i>8</i>	8bits per pixel.																					
description	Description.	var-string	Maximum length: 128																			
domain	Login domain.	var-string	Maximum length: 128																			
folder	Network shared file folder parameter.	var-string	Maximum length: 128																			
height	Screen height.	integer	Minimum value: 0 Maximum value: 65535	0																		
host	Host name/IP parameter.	var-string	Maximum length: 128																			
keyboard-layout	Keyboard layout.	option	-	en-us																		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>ar-101</i>	Arabic (101).		
	<i>ar-102</i>	Arabic (102).		
	<i>ar-102-azerty</i>	Arabic (102) AZERTY.		
	<i>can-mul</i>	Canadian Multilingual Standard.		
	<i>cz</i>	Czech.		
	<i>cz-qwerty</i>	Czech (QWERTY).		
	<i>cz-pr</i>	Czech Programmers.		
	<i>da</i>	Danish.		
	<i>nl</i>	Dutch.		
	<i>de</i>	German.		
	<i>de-ch</i>	German, Switzerland.		
	<i>de-ibm</i>	German (IBM).		
	<i>en-uk</i>	English, United Kingdom.		
	<i>en-uk-ext</i>	English, United Kingdom Extended.		
	<i>en-us</i>	English, United States.		
	<i>en-us-dvorak</i>	English, United States-Dvorak.		
	<i>es</i>	Spanish.		
	<i>es-var</i>	Spanish Variation.		
	<i>fi</i>	Finnish.		
	<i>fi-sami</i>	Finnish with Sami.		
	<i>fr</i>	French.		
	<i>fr-apple</i>	French, Apple.		
	<i>fr-ca</i>	French, Canada.		
	<i>fr-ch</i>	French, Switzerland.		
	<i>fr-be</i>	French, Belgium.		
	<i>hr</i>	Croatian.		
	<i>hu</i>	Hungarian.		
	<i>hu-101</i>	Hungarian 101-Key.		
	<i>it</i>	Italian.		

Parameter	Description	Type	Size	Default
-----------	-------------	------	------	---------

Option	Description
<i>it-142</i>	Italian (142).
<i>ja</i>	Japanese.
<i>ja-106</i>	Japanese 106/109 key.
<i>ko</i>	Korean.
<i>la-am</i>	Latin American.
<i>lt</i>	Lithuanian.
<i>lt-ibm</i>	Lithuanian IBM.
<i>lt-std</i>	Lithuanian Standard.
<i>lav-std</i>	Latvian (Standard).
<i>lav-leg</i>	Latvian (Legacy).
<i>mk</i>	Macedonian (FYROM).
<i>mk-std</i>	Macedonia (FYROM) - Standard.
<i>no</i>	Norwegian.
<i>no-sami</i>	Norwegian with Sami.
<i>pol-214</i>	Polish (214).
<i>pol-pr</i>	Polish (Programmers).
<i>pt</i>	Portuguese.
<i>pt-br</i>	Portuguese (Brazilian ABNT).
<i>pt-br-abnt2</i>	Portuguese (Brazilian ABNT2).
<i>ru</i>	Russian.
<i>ru-mne</i>	Russian - Mnemonic.
<i>ru-t</i>	Russian (Typewriter).
<i>sl</i>	Slovenian.
<i>sv</i>	Swedish.
<i>sv-sami</i>	Swedish with Sami.
<i>tuk</i>	Turkmen.
<i>tur-f</i>	Turkish F.
<i>tur-q</i>	Turkish Q.
<i>zh-sym-sg-us</i>	Chinese (Simplified, Singapore) - US keyboard.

Parameter	Description	Type	Size	Default										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>zh-sym-us</i></td><td>Chinese (Simplified) - US Keyboard.</td></tr><tr><td><i>zh-tr-hk</i></td><td>Chinese (Traditional, Hong Kong S.A.R.).</td></tr><tr><td><i>zh-tr-mo</i></td><td>Chinese (Traditional Macao S.A.R.) - US Keyboard.</td></tr><tr><td><i>zh-tr-us</i></td><td>Chinese (Traditional) - US keyboard.</td></tr></table>	Option	Description	<i>zh-sym-us</i>	Chinese (Simplified) - US Keyboard.	<i>zh-tr-hk</i>	Chinese (Traditional, Hong Kong S.A.R.).	<i>zh-tr-mo</i>	Chinese (Traditional Macao S.A.R.) - US Keyboard.	<i>zh-tr-us</i>	Chinese (Traditional) - US keyboard.			
	Option	Description												
	<i>zh-sym-us</i>	Chinese (Simplified) - US Keyboard.												
	<i>zh-tr-hk</i>	Chinese (Traditional, Hong Kong S.A.R.).												
	<i>zh-tr-mo</i>	Chinese (Traditional Macao S.A.R.) - US Keyboard.												
<i>zh-tr-us</i>	Chinese (Traditional) - US keyboard.													
load-balancing-info	The load balancing information or cookie which should be provided to the connection broker.	var-string	Maximum length: 511											
logon-password	Logon password.	password	Not Specified											
logon-user	Logon user.	var-string	Maximum length: 35											
name	Bookmark name.	string	Maximum length: 35											
port	Remote port.	integer	Minimum value: 0 Maximum value: 65535	0										
preconnection-blob	An arbitrary string which identifies the RDP source.	var-string	Maximum length: 511											
preconnection-id	The numeric ID of the RDP source.	integer	Minimum value: 0 Maximum value: 4294967295	0										
restricted-admin	Enable/disable restricted admin mode for RDP.	option	-	disable										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>enable</i></td><td>Enable restricted admin mode for RDP.</td></tr><tr><td><i>disable</i></td><td>Disable restricted admin mode for RDP.</td></tr></table>	Option	Description	<i>enable</i>	Enable restricted admin mode for RDP.	<i>disable</i>	Disable restricted admin mode for RDP.							
	Option	Description												
	<i>enable</i>	Enable restricted admin mode for RDP.												
<i>disable</i>	Disable restricted admin mode for RDP.													
security	Security mode for RDP connection.	option	-	any										
	<table><tr><th>Option</th><th>Description</th></tr><tr><td><i>any</i></td><td>Allow the server to choose the type of security.</td></tr><tr><td><i>rdp</i></td><td>Standard RDP encryption.</td></tr><tr><td><i>nla</i></td><td>Network Level Authentication.</td></tr><tr><td><i>tls</i></td><td>TLS encryption.</td></tr></table>	Option	Description	<i>any</i>	Allow the server to choose the type of security.	<i>rdp</i>	Standard RDP encryption.	<i>nla</i>	Network Level Authentication.	<i>tls</i>	TLS encryption.			
	Option	Description												
	<i>any</i>	Allow the server to choose the type of security.												
	<i>rdp</i>	Standard RDP encryption.												
	<i>nla</i>	Network Level Authentication.												
<i>tls</i>	TLS encryption.													

Parameter	Description	Type	Size	Default
send-preconnection-id	Enable/disable sending of preconnection ID.	option	-	disable
	Option	Description		
	<i>enable</i>	Enable sending of preconnection ID.		
	<i>disable</i>	Disable sending of preconnection ID.		
sso	Single sign-on.	option	-	disable
	Option	Description		
	<i>disable</i>	Disable SSO.		
	<i>static</i>	Static SSO.		
	<i>auto</i>	Auto SSO.		
sso-credential	Single sign-on credentials.	option	-	sslvpn-login
	Option	Description		
	<i>sslvpn-login</i>	SSL-VPN login.		
	<i>alternative</i>	Alternative.		
sso-credential-sent-once	Single sign-on credentials are only sent once to remote server.	option	-	disable
	Option	Description		
	<i>enable</i>	Single sign-on credentials are only sent once to remote server.		
	<i>disable</i>	Single sign-on credentials are sent to remote server for every HTTP request.		
sso-password	SSO password.	password	Not Specified	
sso-username	SSO user name.	var-string	Maximum length: 35	
url	URL parameter.	var-string	Maximum length: 128	
vnc-keyboard-layout	Keyboard layout.	option	-	default
	Option	Description		
	<i>default</i>	Default.		
	<i>da</i>	Danish.		

Parameter	Description	Type	Size	Default
	Option	Description		
	<i>nl</i>	Dutch.		
	<i>en-uk</i>	English, United Kingdom.		
	<i>en-uk-ext</i>	English, United Kingdom Extended.		
	<i>fi</i>	Finnish.		
	<i>fr</i>	French.		
	<i>fr-be</i>	French, Belgium.		
	<i>fr-ca-mul</i>	French, Canadian Multilingual Std.		
	<i>de</i>	German.		
	<i>de-ch</i>	German, Switzerland.		
	<i>it</i>	Italian.		
	<i>it-142</i>	Italian (142).		
	<i>pt</i>	Portuguese.		
	<i>pt-br-abnt2</i>	Portuguese (Brazilian ABNT2).		
	<i>no</i>	Norwegian.		
	<i>gd</i>	Scottish Gaelic.		
	<i>es</i>	Spanish.		
	<i>sv</i>	Swedish.		
	<i>us-intl</i>	United States-International.		
width	Screen width.	integer	Minimum value: 0 Maximum value: 65535	0

config form-data

Parameter	Description	Type	Size	Default
name	Name.	string	Maximum length: 35	
value	Value.	var-string	Maximum length: 63	

config vpn ssl web user-group-bookmark

Configure SSL-VPN user group bookmark.