

PROPOSAL ____ - Calvin

IoT-Based Smart Parking Management and Reservation System with Real-Time Slot Guidance and Vehicle Analytics

1. Project Title

Design and Implementation of an IoT-Based Smart Parking Management and Reservation System with Real-Time Slot Guidance and Vehicle Traffic Analytics

2. Project Overview

This project proposes the development of an Internet of Things (IoT)-based smart parking management system that monitors parking slot availability, enables remote reservation of parking spaces, and provides real-time parking guidance to drivers. The system will utilize multiple parking slot sensors connected to a microcontroller to detect vehicle presence and determine slot availability.

Each parking slot will be equipped with sensors and LED indicators that visually display parking status. A green LED indicates that the parking slot is available, while a red LED indicates that the slot is occupied or reserved. The parking system will be connected to a cloud-based database using the WiFi capability of the microcontroller, enabling real-time monitoring and remote interaction through a mobile dashboard.

A key feature of the proposed system is the integration of a parking reservation mechanism using a mobile interface connected to the cloud database. Users can reserve parking slots remotely, and once a reservation is made, the system will automatically mark the slot as reserved. Even if the physical sensor does not detect a vehicle, the LED indicator will turn red to signify that the slot is reserved.

The system also includes an automated entrance gate mechanism. A vehicle entry sensor will detect incoming vehicles and allow the barrier gate to open only if parking slots are still available. If the parking area has reached full capacity, the system will prevent the gate from opening and notify the driver that no slots are available.

In addition, the system will implement vehicle counting and traffic analytics by monitoring entry and exit points using sensors. The collected data will be transmitted to the cloud database for storage and visualization, allowing the system to analyze parking utilization patterns such as peak hours, vehicle turnover rate, and daily parking occupancy.

The proposed system demonstrates the integration of embedded microcontrollers, sensors, actuators, wireless communication, and cloud-based IoT platforms to create an intelligent parking management solution.




Figure 1: *Visualization of Project Overview*

3. Sensors

Parking slot monitoring sensors:

- **Ultrasonic Sensors (HC-SR04)** – detect vehicle presence in each parking slot

Entry and exit monitoring sensors:

- **Infrared Break Beam Sensors** – detect vehicles entering and exiting the parking area

Environmental or auxiliary sensors (optional):

- **Light Sensor (LDR)** – automatic brightness control for LED indicators during nighttime operation



Figure 3.1: *Ultrasonic Sensors (HC-SR04)*

Figure 3.2: *Infrared Break Beam Sensors*

Figure 3.3: *Light Sensor (LDR)*

4. Actuators

- **Servo Motor** – automated barrier gate control
- **Red and Green LED Indicators** – parking slot guidance system
- **16×2 LCD Display (I2C)** – parking information display board
- **Buzzer (ISD1820 Voice Recording Module)** – warning indicator when parking is full



Figure 4.1: *Servo Motor*



Figure 4.2: *Red and Green LED Indicators*



Figure 4.3: *16×2 LCD Display (I2C)*



Figure 4.4: *Buzzer (ISD1820 Voice Recording Module)*

5. Communication

- **ESP32 Microcontroller** for sensor data processing and system control
- **WiFi communication** for internet connectivity
- Cloud database using **Firebase** for real-time data storage and communication
- Mobile dashboard or web interface for parking reservation and monitoring



Figure 5.1: ESP32 Microcontroller

6. Expected Output

- Real-time monitoring of parking slot availability
- LED guidance indicators showing available and occupied slots
- Remote parking slot reservation through mobile dashboard
- Automatic gate control based on parking capacity
- Real-time vehicle counting at entry and exit points
- Cloud-based visualization of parking usage statistics and traffic analytics

7. Significance of the Project

Parking management is a common problem in crowded urban environments such as universities, commercial buildings, and public facilities. Traditional parking systems rely on manual observation and lack real-time monitoring capabilities.

The proposed IoT-based parking system demonstrates how embedded microcontroller technology and cloud communication can be integrated to automate parking management. The system provides real-time slot monitoring, automated access control, and remote reservation functionality, improving convenience and efficiency for users.

Additionally, the vehicle counting and traffic analytics feature provides valuable data that can help administrators understand parking demand patterns and optimize parking infrastructure management.

8. References

Arduino Project Hub. (n.d.). Smart Parking System with IoT Monitoring.
<https://projecthub.arduino.cc/PMichal/smart-car-parking-system-b2eb06>

Firebase Documentation. (n.d.). Real-Time Database Platform.
https://firebase.google.com/?utm_source=PMAX&utm_medium=display&utm_campaign=Cloud-SS-DR-Firebase-FY26-global-pmax-1713590&utm_content=pmax&gclid=aw.ds&gad_source=1&gad_campaignid=23417496167&gbraid=0AAAAADpUDOiZNDOoUljayzUsbpyfdrFwJ&gc

[lid=Cj0KCQiA2bTNBhDjARIsAK89wIEZTIJIf-H4R4KKVr-
g_cB3NJgc9lklMTx_lCeZUvTe8FMAVYgPHxkaAoW3EALw_wcB](https://www.espressif.com/en_US/about-us/contact-us)

Espressif Systems. (n.d.). ESP32 Technical Reference Manual.
[https://documentation.espressif.com/esp32_technical_reference_manual_en
.pdf](https://documentation.espressif.com/esp32_technical_reference_manual_en.pdf)
