

Truckmount Maintenance Master Schedule

Standardised Daily Hygiene

Required Across All Templates: No matter what brand a user selects, your backend architecture should force a standard "End of Day" or "Daily Startup" sequence to prevent component failure.

- **Pre-Flight:** Check engine oil dipstick, high-pressure pump sight glass, and vacuum blower sight level windows. Clean the garden hose inlet filter screen.
- **Post-Run:** Empty and flush the waste recovery tank completely, clean the internal lint filter basket, and spray a 5-second burst of dedicated rust-inhibiting spray lubricant directly into the vacuum blower lubrication port while running under a mild load.

Brand 1: Standard & Direct-Drive Families

Group 1: The Air-Cooled Slide-In Family

Machines: Boxxer 318, Boxxer 423s, Boxxer XL, Titan 325, Titan 425, and TMTG 4000.

Core Characteristic: Standalone machines powered by an air-cooled engine (like a Briggs & Stratton or Kohler). Because these engines run hotter and rely purely on air flow, their oil shears down incredibly fast.

Every 25 to 50 hours	Change engine oil and replace the engine oil filter. (Note: In hot summer climates, 25 hours is highly recommended).
Every 100 to 250 hours	Check/clean the engine spark plugs and air filters. Inspect the direct-drive coupler element (on coupler-driven units like the Boxxer XL).
Every 500 hours	Change the high-pressure water pump oil and change the vacuum blower gear oil.

Group 2: The Liquid-Cooled Slide-In Family

Machines: Titan 575 (Kubota engine models) and Titan 625.

Core Characteristic: Standalone machines powered by a liquid-cooled engine (featuring an internal radiator and coolant system). These engines regulate heat much better, allowing you to double your oil life compared to Group 1.

Every 100 hours	Change engine oil and replace the engine oil filter.
Every 250 hours	Check radiator coolant levels and inspect engine belts.
Every 500 hours	Change the high-pressure water pump oil, change the vacuum blower gear oil, and replace spark plugs/fuel filters.

Group 3: The Direct-Drive (CDS) Family

Machines: CDS 4.6, CDS 4.8, CDS 4.8SV, and CDS xDrive.

Core Characteristic: These machines do not have a separate engine. They use a clutch system connected directly to the van's main vehicle engine via a drive shaft.

Engine Maintenance	No small engine oil changes: You simply perform normal vehicle oil maintenance on your van.
Every 100 hours (or monthly)	Check the machine's drive shaft alignment, greasable bearings, and front-end vehicle fasteners.
Every 400 to 500 hours	Change the high-pressure pump oil and the vacuum blower gear oil.

Brand 2: Sapphire Scientific Maintenance Families

Family A: Air-Cooled / Standard EFI Slide-Ins

Machines: Sapphire 370, Sapphire 370 EFI, and Sapphire 460SS.

Core Characteristic: Standalone units powered by air-cooled Kohler or small block power plants. Though some models utilize Electronic Fuel Injection (EFI) to manage fuel mixture, they rely heavily on constant clean air flow to dissipate heat, creating a standard thermal load on the oil.

Every 50 Hours	Change engine oil and replace the engine oil filter.
Every 100 to 250 Hours	Check engine air filter, inspect spark plugs, and check water pump drive belt tension.
Every 500 Hours	Change high-pressure water pump oil, change vacuum blower gear-end oil, and replace spark plugs.

Family B: Liquid-Cooled Heavy Duty Slide-Ins

Machines: Sapphire Apex 570 and Sapphire Everest 870HP.

Core Characteristic: High-power premium units utilizing multi-cylinder liquid-cooled Kubota or industrial engines. Fitted with standalone automotive-style radiator systems, these machines regulate combustion temperatures smoothly, preventing rapid oil breakdown.

Every 100 Hours	Change engine oil and replace engine oil filter.
Every 250 Hours	Flush/clean the heat exchanger manifold, inspect radiator coolant levels, and check spark plugs.
Every 500 Hours	Perform a full vacuum blower oil change (dual splash bath lubrication points), change high-pressure pump oil, and replace fuel filters.

Brand 3: Prochem Maintenance Families

Family A: Air-Cooled Legacy Workhorses

Machines: Prochem Blazer, Prochem Blazer GT, Prochem Legend, and Prochem Legend GT.

Core Characteristic: Highly popular legacy slide-ins operating with air-cooled power plants. Because many older units in the field run traditional carburetors, they suffer from higher internal carbon build-up than modern EFI machines.

Every 25 to 50 Hours	Change engine oil and replace engine oil filter (25 hours strictly advised during hot climate operations).
Every 100 Hours	Pull, clean, and re-gap spark plugs to remove carbon fouling. Inspect carburetor linkages and air filter elements.
Every 500 Hours	Complete mechanical oil drain and refill for both the water pump crankcase and the vacuum blower gear chambers.

Family B: Liquid-Cooled Premium Lines

Machines: Prochem Peak, Prochem Peak 500, and Prochem Performer (405/Signature).

Core Characteristic: Larger multi-wand setups powered by liquid-cooled Nissan or Kubota engines. These architectures separate engine heat from the blower assembly via independent fluid cooling, extending the oil lifespan.

Every 100 Hours	Change engine oil and replace engine oil filter.
Every 250 Hours	Inspect engine drive belts for cracks or checking. Check radiator reserve tank fluid levels.
Every 500 Hours	Flush and change high-pressure pump oil, change vacuum blower gear oil, and replace spark plugs/fuel filters.

Brand 4: Cleanco Maintenance Family

Family A: Direct-Drive / PTO Systems

Machines: Cleanco Compact 45, Cleanco Compact 47, Cleanco Compact 56, and Cleanco E-Zee.

Core Characteristic: The dominant competitor to HydraMaster's CDS line. These machines feature no standalone engine. The system utilizes an under-van drive shaft assembly bolted to a heavy-duty transmission power take-off (PTO) or clutch integration to spin the core modules.

Engine Maintenance	No Small Engine Maintenance: Users skip engine oil tracking entirely on the machine interface (relying instead on standard van chassis maintenance milestones).
Every 100 Hours	(Critical Integration Check): Grease the under-van drive shaft universal joints (U-joints). Inspect the drive shaft center support bearings, alignment fasteners, and vehicle safety clutch brackets.
Every 400 to 500 Hours	Drain and replace the high-pressure water pump oil and the vacuum blower gear-bath lubricant.