

Sample incoming requirement items

- R01.** The new onboard radio should keep the active voice call running when the train moves between coverage areas, or at least recover quickly enough that the driver does not need to redial manually.
- R02.** Need a way for the dispatcher to reach the driver even if the train unit was restarted recently and not all services are fully back yet.
- R03.** Please make sure the cab equipment still behaves in a familiar way for drivers coming from GSM-R, especially for emergency and group communication functions.
- R04.** System should support operation in tunnels and difficult coverage areas better than today, with fewer dropped sessions reported by operations.
- R05.** We need clearer prioritisation between emergency voice, operational voice, and non-critical data so that the critical traffic always gets through first.
- R06.** If the radio loses the main network, it should automatically try the available backup path without requiring manual intervention from the driver.
- R07.** There should be an easier way to see which communication service is active and whether the terminal is running on the primary or fallback connection.
- R08.** Please support remote software update capability for the communication unit, but only in a way that does not interfere with train operation.
- R09.** We need logs detailed enough for incident investigation, especially around failed registrations, interrupted calls, and service handovers.
- R10.** The maintenance team would like a simpler fault view that shows whether the issue is network-related, onboard-related, or configuration-related.
- R11.** Identity handling needs to remain stable when the same trainset is used across different national or operator environments.
- R12.** The radio should not present drivers with technical alarms that they cannot act on; alarms should be filtered or grouped more intelligently.
- R13.** Operations asked whether the new solution can keep a session alive during short coverage interruptions of a few seconds instead of dropping immediately.
- R14.** There should be support for secure remote diagnostics from the control side, but this must be limited to authorised users and logged.
- R15.** Please consider that some requirements will come from railway-specific standards even when generic telecom standards say something slightly different.
- R16.** Need better support for role-based communication identities so that the same physical terminal can be used by different operational roles without confusion.
- R17.** If a train crosses a border or changes operational area, the communication setup should adapt without the driver having to reconfigure the terminal manually.
- R18.** The product should make it easier to verify which interfaces are affected when a new communication feature is introduced.

R19. We need some indication of how a requested feature would affect testing, especially if it touches safety-relevant or operationally critical functions.

R20. Please capture open questions explicitly when the request is unclear, instead of forcing a too-precise requirement too early.