Select a definition auth

# WaffleBear API 1.0.0 OAS 3.0

/api/v3/api-docs/auth

OpenAPI documentation for the WaffleBear backend features.

Servers

https://api.fileinnoutcloud.kro.kr/api - Configured backend server

Authorize

## Auth Signup and email verification APIs

POST /login Login

Authenticates with email and password, returns an access token in the response body and Authorization header, and issues a refresh cookie.

**Parameters** Try it out

No parameters

**Request body** required application/json

**Example Value** Schema

```
{
  "email": "user@example.com",
  "password": "P@ssw0rd!",
  "name": "optional"
}
```

## Responses

| Code | Description | Links |
|---|---|---|
| 200 | Login succeeded<br>Media type<br>application/json<br>Controls Accept header.<br>Example Value Schema<br>{<br>"accessToken": "string",<br>"email": "string",<br>"role": "ROLE_USER"<br>} | *No links* |
| 401 | Invalid credentials | *No links* |

POST /user/signup Sign up

Creates a new local account and starts the email verification flow.

## Parameters

Try it out

No parameters

## Request body required

application/json

Example Value Schema

```
{
  "email": "string",
  "name": "string",
  "password": "string"
}
```

## Responses

| Code | Description | Links |
| --- | --- | --- |
| 200 | OK<br>Media type<br>*/*<br>Controls Accept header.<br>**Example Value** Schema<br>{} | *No links* |

POST /auth/reissue Reissue token

Reissues access and refresh tokens using the refresh cookie.

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
| --- | --- | --- |
| 200 | OK<br>Media type<br>*/*<br>Controls Accept header.<br>**Example Value** Schema<br>{} | *No links* |

POST /auth/logout Logout

Invalidates the refresh token and clears the refresh cookie.

**Parameters** Try it out

No parameters

**Responses**

| Code | Description | Links |
|---|---|---|
| 200 | OK<br>Media type<br>*/*<br>Controls Accept header.<br>**Example Value** Schema<br>{} | *No links* |

GET /user/verify Verify email

Completes email verification with the issued token.

**Parameters** Try it out

| Name | Description |
|---|---|
| **token** * required<br>string<br>*(query)* | token |

## Responses

| Code | Description | Links |
|---|---|---|
| 200 | OK<br>Media type<br>*/*<br>Controls Accept header.<br>**Example Value** Schema<br>`string` | *No links* |

## Schemas

### SignupReq