

Stacks



The Stack ADT

◆ **Definition:** a **stack** is a collection of objects that are inserted and removed according to the last-in-first-out (LIFO) principle.

◆ Stacks

- Insert in order
- Delete most recent item inserted
- LIFO - last in, first out

The Stack ADT

◆ Examples of stacks

- Cafeteria tray dispenser
- Coin dispenser in your car
- Balancing braces
- Evaluating postfix expressions
- Converting infix to postfix
- Undo sequence in a text editor
- Saving local variables when one function calls another, and this one calls another, and so on.

Stacks

3

The Stack ADT

◆ Main stack operations:

- **push**: inserts an element
- **pop**: removes the last inserted element
- **top**: returns the last inserted element without removing it

◆ Auxiliary stack operations:

- **size**: returns the number of elements stored
- **isEmpty**: returns true if the stack is empty, else false


Stacks

4

C++ Run-time Stack

- ◆ The C++ run-time system keeps track of the chain of active functions with a stack
- ◆ When a function is called, the run-time system pushes on the stack a frame containing
 - Local variables and return value
 - Program counter, keeping track of the statement being executed
- ◆ When a function returns, its frame is popped from the stack and control is passed to the function on top of the stack

```
main() {  
    int i = 5;  
    foo(i);  
}  
  
foo(int j) {  
    int k;  
    k = j+1;  
    bar(k);  
}  
  
bar(int m) {  
    func call  
}
```




Stacks

5

C++ Run-time Stack

- ◆ The C++ run-time system keeps track of the chain of active functions with a stack
- ◆ When a function is called, the run-time system pushes on the stack a frame containing
 - Local variables and return value
 - Program counter, keeping track of the statement being executed
- ◆ When a function returns, its frame is popped from the stack and control is passed to the method on top of the stack

```
main() {  
    int i = 5;  
    foo(i);  
}  
  
foo(int j) {  
    int k;  
    k = j+1;  
    bar(k);  
}  
  
bar(int m) {  
    func call  
}
```



Stacks

6

Stack Application - Infix to Postfix Conversion

◆ Stack can be used to convert infix mathematical expressions to postfix mathematical expressions

- infix \Rightarrow postfix
- $a + b \Rightarrow ab+$

Stacks

7

Stack Application - Infix to Postfix Conversion

◆ Algorithm

- Process infix expression one item at a time
- Operand - write to output
- Operator - pop and write to output until an entry of lower priority is found (don't pop parentheses) then push
- Left parentheses - push
- Right parentheses - pop stack and write to output until left parentheses is found
- When done processing expression, pop remaining items and write to output
- NOTE - parentheses are not written to the output

Stacks

8

Stack Application - Infix to Postfix Conversion

$a + b * c - (d * e + f) * g$

Rule	Stack	Output
Operand - write to output		a
	+	a
	+	ab
	+	ab
	+	abc
	-	abc*+
	-(abc*+
	-(abc*+d
	-(*	abc*+d
	-(*	abc*+de

Stacks

9

Stack Application - Infix to Postfix Conversion

$a + b * c - (d * e + f) * g$

Rule	Stack	Output
When done processing expression, pop remaining items and write to output	-(+	abc*+de*
	-(+	abc*+de*f
	-	abc*+de*f+
	-*	abc*+de*f+
	-*	abc*+de*f+g
		abc*+de*f+g*-

Stacks

10

Stack Application - Evaluating Postfix Expressions

◆ You may assume I give you a valid postfix expression

◆ Algorithm

- Process postfix expression one item at a time
- Operand - push
- Operator - pop 2 times, evaluate expression (second_pop operator first_pop), push result onto stack

Stacks

11

Stack Application - Evaluating Postfix Expressions

$6 * (5 + ((2 + 3) * 8) + 3) \Rightarrow 6 \ 5 \ 2 \ 3 \ + \ 8 \ * \ + \ 3 \ + \ *$

Current Symbol

6
5
2
3
+

Stack

6
6 5
6 5 2
6 5 2 3
6 5 5

Stacks

12

Stack Application - Evaluating Postfix Expressions

$6 * (5 + ((2 + 3) * 8) + 3) \Rightarrow 6 \ 5 \ 2 \ 3 \ + \ 8 \ * \ + \ 3 \ + \ *$

Current Symbol	Stack
8	6 5 5 8
*	6 5 40
+	6 45
3	6 45 3
+	6 48
*	288

Stacks

13

Other Stack Applications

◆ Balanced brace problem

- Push every left brace
- When you find a right brace, pop and compare. If no matching left brace then error
- If stack doesn't end up empty then error


Stacks

14

Array-based Stack

- ◆ A simple way of implementing the Stack ADT uses an array
- ◆ We push (add) elements from left to right
- ◆ A variable keeps track of the index of the last item pushed

Top = 3




Stacks

15

Array-based Stack

- ◆ We pop (remove) elements from right to left

Top = -1



Stacks

16

Stack Data Structure

```
class Stack
{
private:
    objectType stack[MAX_STACK_SIZE];
    int top;
public:
    functions for stack manipulation
    constructor sets top to -1
};
```

Stacks

17

Stack Implementation- Push

◆ The array storing the stack elements may become full

- Limitation of the array-based implementation

```
void push ( const objectType &o )
{
    if ( top + 1 == MAX_STACK_SIZE )
        throw FullStackException;
    else
        S[++top] = o;
}
```

Stacks

18

Exceptions

- ◆ Attempting the execution of an operation of ADT may sometimes cause an error condition, called an exception
- ◆ Exceptions are said to be “thrown” by an operation that cannot be executed
- ◆ In the **Stack** ADT, operations **pop** and **top** cannot be performed if the stack is empty
- ◆ Attempting the execution of **pop** or **top** on an empty stack throws an **EmptyStackException**

Stacks

19

Stack Implementation- Pop

- ◆ In class exercise - write pop and getTop functions
 - Array may be empty when pop is called
 - getTop will return top item/object

Performance and Limitations

◆ Performance

- Let n be the number of elements in the stack
- The space used is $O(n)$
- Each operation runs in time $O(1)$

◆ Limitations

- The maximum size of the stack must be defined *a priori*, and cannot be changed
- Trying to push a new element into a full stack causes an implementation-specific exception

Stacks

21

Growable Array-based Stack

- ◆ In a push operation, when the array is full, instead of throwing an exception, we can replace the array with a larger one

- ◆ How large should the new array be?

- incremental strategy: increase the size by a constant c
- doubling strategy: double the size

```
Algorithm push(o)
  if  $t = S.length - 1$  then
     $A \leftarrow$  new array of
      size ...
    for  $i \leftarrow 0$  to  $t$  do
       $A[i] \leftarrow S[i]$ 
     $S \leftarrow A$ 
     $t \leftarrow t + 1$ 
     $S[t] \leftarrow o$ 
```

Stacks

22

Linked List Based Stack

- ◆ Using a linked list can remove the size restrictions of an array
- ◆ Head will be referred to as the top
- ◆ Top initially points to NULL
- ◆ All operations are done at the top
 - Push = Insert at head/top
 - Pop = Remove from head/top

Stacks

23

Linked List Based Stack

```
bool isEmpty( ) const
{
    return ( !top );
}

const objectType & getTop( ) const
{
    if ( top )
        return top->obj;
    else
        throw EmptyStackException;
}

void push ( const objectType &obj )
{
    Node *newNode = new Node( obj );
    newNode->next = top;
    top = newNode;
}
```

Stacks

24


Linked List Based Stack Operations

Top → X

Stacks

25


Linked List Based Stack Operations



Stacks

26


Linked List Based Stack Operations



Stacks

27


Linked List Based Stack Operations



Stacks

28


Linked List Based Stack Operations



Stacks

29


Linked List Based Stack Operations



Stacks

30

Linked List Based Stack Operations



Stacks

31

Linked List Based Stack

- ◆ In class exercise - Write the pop function
 - Think about memory leaks
 - ◆ Just delete the node, don't expect user to
 - Use `getTop()` if you want to use the node
 - Use `pop()` if you just want to remove the node

Stacks

32

Linked List Based Stack

Stacks

33

Stacks

- ◆ Often the array implementation is used since the stack usually never grows very large even when there is a large number of operations
- ◆ Runtimes
 - All operations are done in $O(1)$

Stacks

34