

Chapter-09 Optimizing our App

CUSTOM HOOKS

- why? when? and how?
- why should we build hooks?
 - * Reusability
 - * Readability
 - * Separation of concerns
 - * Maintainability
- Hooks are just normal javascript functions.
- functions are used to wrapup a logic and can reuse it anywhere we want to.

Eg: In Body.js

`filterData()` is a function written separately. we didn't write it between the code because it breaks modularity, reusability & readability.

If I need to use this function anywhere else then, I can reuse it.

• Best place to keep re-usable functions: ↓

- Make a folder utils (It's utility, helper or common or whatever name).
- Inside create a file utils.js and write the function `filterData()` inside it and make it named export.

→ Any no. of helper function can be kept inside utils.js

→ Advantage:

- * functions become readable & reusable.
- * This makes our code more testable because I can write separate testcases for this.
- * maintainable because it is easy to debug.
- * Modularity means we've broken down code into small pieces and every piece has its own responsibility.

Let us take <RestaurantMenu/> component. Job of this component is to show restaurant menu.

- (i) find out restaurant id (resId).
- (ii) get details of the restaurant from server.
- (iii) to display.

We'll try to extract this logic. We will create a custom hook that will help us to get the restaurant details.

[NB: Create a hook with "use" name in front of it]

* Create a custom hook useRestaurant.

→ Create a new file named useRestaurant.js.

* code →

→ NEXT PAGE


```
const useRestaurant = (resId) => {
```

```
  const [restaurant, setRestaurant] = useState(null);
```

```
  // Get data from API
```

```
  useEffect(() => { getRestaurantInfo(); }, []);
```

```
  async function getRestaurantInfo() {
```

```
    const data = await fetch (
```

```
      "https://www.zwiggy..." + resId );
```

```
    const json = await data.json();
```

```
    setRestaurant (json.data);
```


```
  }
```

```
  // return restaurant data
```

```
  return restaurant;
```

```
}
```

```
export default useRestaurant;
```

Meanwhile, in <RestaurantMenu/> 

```
const RestaurantMenu = () => {
```

```
  const { resId } = useParams();
```

```
  const restaurant = useRestaurant(resId);
```

```
  return !restaurant ? (<shimmer/>):
```

```
  (
```

```
    ....
```

```
    ....);
```

```
  export default RestaurantMenu;
```


Next feature: →Online & offline

- ① If the user have no internet connection, then it should show "You are offline, check your internet connection".
- ② Else it should show the date.

In Body.js ↓

const Body = () ⇒ {

const isOnline = useOnline ();

if (! isOnline) {

return (

<h1> check your internet connection </h1>

);

};

Now we can create custom hook useOnline ().

useOnline.js ↓

import { useState, useEffect } from "react";

const useOnline = () ⇒ {

const [isOnline, setIsOnline] = useState (true);

useEffect () ⇒ {

window.addEventListener ("online", () ⇒ {

setIsOnline (true);

});

window.addEventListener ("offline", () ⇒ {

setIsOnline (false);

});

}, [C]);

return isOnline;

export default useOnline;

function to
check if
user is online
or
offline

To fake offline

Go to chrome devtools → Network tab
→ change speed option (fast, slow 3G, offline)

Important (senior developer banna hai?)* cleaning cache

- whenever eventListener is added, we should clean it up.
- [whenever you are going offline & getting back online, eventListener is created. only once because we've empty dependency array].
- It is always a good practice to clear the eventListener when we go ^{out} of the component. Otherwise browser will keep hold those.
- to do that : ↓

useEffect $() \Rightarrow \{$

```
const handleOnline = () => {
```

```
  setIsOnline(true);
```

```
};
```

```
window.addEventListener("online", handleOnline);
```

```
window.addEventListener("offline", () => {
```

```
  setIsOnline(false);
```

```
});
```

```
return () => {
```

```
  window.removeEventListener("online", handleOnline);
```

```
  window.removeEventListener("offline", handleOffline);
```

```
};
```

```
}, []);
```

```
return isOnline;
```

```
};
```

yakin k function ko
naam de diya
kyunki remove
eventListener
lagana hai.

This function
↓
handleOffline()

For the whole code, parcel creates only one .js file. In this file, all the code is bundled together. So the size of this index.js file is large. But in production bundle size of this file should be small.

There would be a 100s of components in a large website like "makemytrip".

Suppose if all these are bundled together in a single index.js file, It will blast. It will make our app very slow.

So to build a large-scale production ready application we should do :-

"CHUNKING"

It is also called as ↴

- Code splitting
- Dynamic Bundling
- Lazy loading

we cannot bundle everything in our app.

- On Demand Loading
- Dynamic Import

Making a new different bundle in our App

Let us create "Instamart"

- create an Instamart component.
- In App.js file, do chunking :-

→ In App.js file, do chunking:-

App.js :-

Instead of importing like this:-

* import Instamart from "./components/Instamart";
Do lazy loading :-

* const Instamart = lazy(() => {

return import("./components/Instamart")});

So, now the "index.js" file in dist folder won't have code of instamart. It is created as separate file while loading.
This is called ON-DEMAND LOADING.

"when you are loading your component in demand, react tries to suspend it".

So when instamart is loaded for the first time, we see an error message on screen. This is because, instamart file took 27 ms to get loaded. But react tries to render it before it get loaded. That's why error.

Solution for this

"Suspense" → we can wrap instamart inside suspense.

App.js ↓

path: "/instamart",

element: (

<Suspense>

<Instamart/>

</Suspense>

);

);

React now knows that when there is a suspense, what will be loaded.

In the intermediate time, a shimmer should be shown.

So, there is a prop known as "**fallback**".

So, write ↓

<Suspense **fallback**= <shimmer/> >

</Suspense>

NB:-

* Never even dynamically load your component inside another component.