

Practical Lecture 2 Building a Business Component

1

Practical Session Structure

1. Introduction
- 2. Building a business component**
3. Building an admin GUI
4. Introducing .NET remoting
5. Creating a web service and client website
6. Developing a Java client

2

2

Overview

- By now you should have:
 - Familiarised yourself with the requirements of the system
 - Developed the database for the system
- In this lecture we will build a business component which encapsulates the business functionality of the system

3

3

Learning Objectives

- Understand n-tier architectures
- Understand the use of components
- Create a business component in .NET using C#, which interacts with a database

4

4

Introduction

- In this practical session we will:
 - Briefly explain the n-tier architecture and components and see how they could be used in a distributed system
 - Build a business component which encapsulates the core functionality of the system

5

5

N-Tier Architectures

- In N-Tier architectures there is a logical separation of presentation, business and data into separate layers

6

6

N-Tier Architectures /2

- Data Tier – manages the data
 - The database we built last week
- Presentation Tier – controls what a user sees and can do with the system
 - We will build several applications within this tier later on
- Business Tier (middle tier) – controls everything else (the business logic)
 - What we will build today

7

7

Business Tier

- The business tier contains the core functionality of our system
 - Business rules
 - Work flows
- It provides controlled access to data
- It enables validation and processing of data input

8

8

Business Tier /2

- The business tier will be defined using classes
- The collection (library) of classes representing our business tier will be deployed as a component
 - In our case a DLL

9

9

Components

- Our component will consist of a collection of classes developed to fulfil a certain specification
- It can be re-used
- It should encapsulate all its behaviour
- It must provide an interface to allow it to be accessed by a client (could even be another component)

10

10


Getting Started

- We will create our business component as a *Class Library* in Visual Studio 2005
- Create a project
 - Open Microsoft Visual Studio 2005
 - Go to *File -> New Project*
 - Select *Visual C#* as the project type and then select *Class Library* as the template
 - Name the project *PTSLibrary* and save it in a suitable location (PTS = **P**roject **T**racking **S**ystem)

11

11


Use-Case Diagram



12

12


Class Diagram



13

13

Creating the Project



14

14

PTSLibrary Structure

- As a business component, this project will not contain any graphical user interface
- There are three types of classes we will have in our project:
 - Business Objects
 - DAOs (Data Access Objects)
 - Façade Objects

15

15

Business Objects

- Business objects (also called domain objects) are abstract representations of entities from our business domain
- They represent concepts that are important to the business that the system is modelling
- In our system these are abstractions of project management related concepts, such as project, team, task, etc.

16

16

Business Objects /2

- The business objects in our component will be:
 - Project
 - Task
 - Subtask
 - User
 - Team
 - TeamLeader
 - TeamMember
 - Customer
 - Status

17

17

Business Objects /3

- Some of the business objects have the same name as entities in our data model, but not all. There are business objects not in the data model
- Relational data models require a different approach than object-oriented modelling
 - Object-oriented paradigm is based on software engineering principles
 - Relational paradigm is based on mathematical principles
- Working with the two models can lead to problems referred to as “Object-Relational Impedance Mismatch”

18

18

DAOs

- Data Access Objects provide abstract interfaces to data sources
- DAOs provide a clear separation between our business and persistence logic
- We want to write robust code and achieve low-coupling between our business classes and the database
 - No need to clutter our business logic with SQL code
 - No need to rewrite all our business classes if there is a change in the database

19

19

DAOs /2

- The DAOs will contain all the SQL code for reading and writing to the database
- There could be one DAO for the entire project, but as we have different types of user, working with different data, we will have a DAO for each role:
 - SuperDAO (super class for all others)
 - AdminDAO
 - CustomerDAO
 - ClientDAO (team leaders using Java or .NET clients)

20

20

Façade Objects

- The PTSLibrary project is a class library
 - No graphical user interface
 - Used by other sections of our system, which shouldn't know about the inner structure of our business component
- We provide a publicly available interface to our business component via façade classes

21

21

Façade Objects /2


- Again we will have one façade class for each type of user who will access our business component
 - This also allows us to show each role of user only what they need to see (e.g. we wouldn't want a team leader to be able to create a new project, only administrators)
- The façade classes are:
 - PTSAAdminFacade
 - PTSCClientFacade
 - PTSCustomerFacade
 - PTSSuperFacade (super class for all others)

22

22

Creating classes

- Delete the Class1.cs file created by default when you created the new project
- Now create all the business classes
- Make sure that you select *Class* as the template for each




23

23

Creating Classes /2

- Your Solution Explorer should now look like this
- Each of the classes created only contains some default import statements (*using* statements), namespace declaration and class declaration. Let's add our desired state and behaviour
- Remember that we will only implement a subset of the functionality required to demonstrate the use of the system




24

24

Class User

- This class represents a general user of the system
- It is the super (base) class for all more specialised classes representing users
 - Customer
 - TeamLeader
 - TeamMember
- The above three inherit from User



25

25

Class User /2

- This class has only two protected variables (username and password), which are exposed through two read-only properties
- Note that the access level is set to *protected*

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class User
8     {
9         protected string name;
10        protected int id;
11
12        public string Name
13        {
14            get { return name; }
15        }
16
17        public int Id
18        {
19            get { return id; }
20        }
21    }
22 }
23

```

26

26

Class Customer


- This class represents a customer (someone who commissioned a project)
- The functionality we want to provide for this class is simplified
 - Keep the name and show it when required
 - This functionality already exists in the User class, so we make Customer inherit from it
- We also want instances of this class with the name set, so we need to create a constructor to allow us to do this

27

27

Class User /2

- All the code we need to write is
 - make the Customer inherit from User
 - add a constructor taking a name and id



28

28

Class Customer /3

- Customer inherits from User
- Q: What is the *this.name* referring to if *name* is not declared?

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class Customer → User
8     {
9         public Customer(string name, int id)
10        {
11            this.name = name;
12            this.id = id;
13        }
14    }
15 }

```


A: the *name* and *id* members are not declared in Customer, but are inherited from User

29

29

Class TeamLeader

- Represents a leader of an internal or external team
- The class inherits from class User
- Similar to class Customer, add a constructor
- One new field



30

30

Class TeamLeader /2

- The new field
- Create a property *TeamId* to provide access to *teamId*
- Class constructor with 3 parameters, including one for *teamId*

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class TeamLeader : User
8     {
9         private int teamId;
10
11         public int TeamId
12         {
13             get { return teamId; }
14             set { teamId = value; }
15         }
16
17         public TeamLeader(string name, int id, int teamId)
18         {
19             this.name = name;
20             this.id = id;
21             this.teamId = teamId;
22         }
23     }
24 }


```

31

31

Class Team /1

- Team represents an internal or external team working for Out of Bounds Ltd
- It is linked to TeamLeader through association
- Other fields: id, location, name



32

32

Class Team /2

```

7 | class Team
8 | {
9 |     private int id;
10 |    private string location;
11 |    private string name;
12 |    private TeamLeader leader;
13 |
14 |    public int TeamId
15 |    {
16 |        get { return id; }
17 |        set { id = value; }
18 |    }
19 |
20 |    public TeamLeader Leader
21 |    {
22 |        get { return leader; }
23 |        set { leader = value; }
24 |    }
25 |
26 |    public string Location
27 |    {
28 |        get { return location; }
29 |        set { location = value; }
30 |    }
31 |
32 |    public string Name
33 |    {
34 |        get { return name; }
35 |        set { name = value; }
36 |    }
37 |
38 |    public Team(int id, string location, string name, TeamLeader leader)
39 |    {
40 |        this.location = location;
41 |        this.name = name;
42 |        this.id = id;
43 |        this.leader = leader;
44 |    }
45 | }


```

33

33

Enum Status /1

- Enum allows you to create a distinct value type
- Contains a set of named constants
- Can be converted to an integer
- Which is easier to read?
 - if(currentStatus == 3)
 - If(currentStatus == Status.Completed)



34

34

Enum Status /2

- States of a task or subtask
- Note the change from *class* to *enum*
- The integer numbers assigned to each status reflect the StatusId field in the Status table of the database

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     public enum Status
8     {
9         ReadyToStart = 1,
10        InProgress = 2,
11        Completed = 3,
12        WaitingForPredecessor = 4
13    }
14 }
15


```

35

35

Class Task /1

- Represents a task within a project, which is assigned to a team and can be broken into subtasks
- Linked to Status through association
- Other fields: name and taskId



36

36

Class Task /2

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class Task
8     {
9         private Guid taskId;
10        private string name;
11        private Status status;
12
13        public Guid TaskId
14        {
15            get { return taskId; }
16            set { taskId = value; }
17        }
18
19        public string Name
20        {
21            get { return name; }
22            set { name = value; }
23        }
24
25        public Status theStatus
26        {
27            get { return status; }
28            set { status = value; }
29        }
30
31        public Task(Guid id, string name, Status status)
32        {
33            this.taskId = id;
34            this.name = name;
35            this.status = status;
36        }
37    }
38 }

```


- Notice the use of the Guid data type

37

37

Class Project /1

- Represents a project
- Linked to Customer and Task through association
- Has two constructors which set different fields
 - Depending on the context in which the Project object is used




38

38

Class Project /2

- Note the data types used in declaring the variables
- *tasks* is declared using generic programming
- Generics:
 - Allow the creation of type-safe collections
 - *tasks* is a list that can contain objects of type *Task* only
 - Declared using *<Type>*

```
private string name;
private DateTime expectedStartDate;
private DateTime expectedEndDate;
private Customer theCustomer;
private Guid projectId;
private List<Task> tasks;
```



39

39

Class Project /3

- Two constructors (one setting the customer, one the tasks)
- For complete code of the class see the notes

```
public Project(string name, DateTime startDate, DateTime endDate, Guid projectId, Customer customer)
{
    this.name = name;
    this.expectedStartDate = startDate;
    this.expectedEndDate = endDate;
    this.projectId = projectId;
    this.theCustomer = customer;
}


public Project(string name, DateTime startDate, DateTime endDate, Guid projectId, List<Task> tasks)
{
    this.name = name;
    this.expectedStartDate = startDate;
    this.expectedEndDate = endDate;
    this.projectId = projectId;
    this.tasks = tasks;
}
```

40

40

Creating DAOs

- We will keep all the DAOs in a subfolder of our project to have all DAOs in one place
- Create a new folder in the PTSLibrary project called *DAO*




41

41

Creating DAOs /2

- Create 4 new classes in the DAO folder called:
 - SuperDAO
 - AdminDAO
 - CustomerDAO
 - ClientDAO
- These classes will have code to work with our database
 - To have access to the required classes we need to import namespaces System.Data and System.Data.SqlClient in each DAO class




```
using System;
using System.Collections.Generic;
using System.Text;
using System.Data.SqlClient;
using System.Data;
```

42

42

Access to the Database

- In order to be able to access the database created it is necessary to add it as a data source
- Make sure SQL Server is running and your database is accessible
- Select *Add New Data Source* from the *Data* menu




43

43

Access to the Database /2

- Then select Database




44

44

Access to the Database /3

- On the next screen click on the *New Connection* button and set your connection details
 - Select your Server
 - Select your Database
- Once set, test your connection and proceed to the next screen




45

45

Access to the Database /4

- Make sure the checkbox is ticked
- Name your connection *ConnectionString*




46

46

Access to the Database /5

- Tick the tables checkbox and then click finish
- Now you have a connection to the db and the connection string was created in the Settings.settings file



47

47


DAO - Reminder

- Data Access Objects provide abstract interfaces to data sources
- DAOs provide a clear separation between our business and persistence logic
- The DAOs will contain all the SQL code for reading and writing to the database

48

48

DAO – UML Structure




49

49

Class SuperDAO

- This is the base class DAO
- Contains 2 methods providing behaviour shared by the other DAOs
 - GetCustomer
 - GetListOfTasks



50

50

SuperDAO - GetCustomer method

- Declare objects necessary to access the DB
- SQL statement to retrieve customer details
- Create connection using the ConnectionString
- The SQL command is set to return a single row
- An instance *cust* of Customer is created
- The method returns *cust*

```
protected Customer GetCustomer(int custId)
{
    string sql;
    SqlConnection cn;
    SqlCommand cmd;
    SqlDataReader dr;
    Customer cust;

    sql = "SELECT * FROM Customer WHERE CustomerId = " + custId;
    cn = new SqlConnection(Properties.Settings.Default.ConnectionString);
    cmd = new SqlCommand(sql, cn);

    try
    {
        cn.Open();
        dr = cmd.ExecuteReader(CommandBehavior.SingleRow);
        dr.Read();
        cust = new Customer(dr["Name"].ToString(), (int)dr["CustomerId"]);
        dr.Close();
    }
    catch (SqlException ex)
    {
        throw new Exception("Error Getting Customer", ex);
    }
    finally
    {
        cn.Close();
    }
    return cust;
}
```

51

51

SuperDAO - GetListOfTasks method

```
public List<Task> GetListOfTasks(Guid projectId)
{
    string sql;
    SqlConnection cn;
    SqlCommand cmd;
    SqlDataReader dr;
    List<Task> tasks;
    tasks = new List<Task>();

    sql = "SELECT * FROM Task WHERE ProjectId = " + projectId + " ";
    cn = new SqlConnection(Properties.Settings.Default.ConnectionString);
    cmd = new SqlCommand(sql, cn);

    try
    {
        cn.Open();
        dr = cmd.ExecuteReader();
        while (dr.Read())
        {
            Task t = new Task((Guid)dr["TaskId"], dr["Name"].ToString(), (Status)((int)dr["StatusId"]));
            tasks.Add(t);
        }
        dr.Close();
    }
    catch (SqlException ex)
    {
        throw new Exception("Error getting taks list", ex);
    }
    finally
    {
        cn.Close();
    }
    return tasks;
}
```

Note the use of single quotes: projectId is of type GUID and not a number

Returns possibly more than one row

Iterates through all returned rows


Task constructor expects a Guid and Status

52

52

Class CustomerDAO /1

- This DAO provides DB access methods specific for the customer role
- Inherits from the SuperDAO class
- Two methods
 - Authenticate
 - GetListOfProjects



53

53

CustomerDAO – Authenticate method

```

public int Authenticate(string username, string password)
{
    string sql;
    SqlConnection cn;
    SqlCommand cmd;
    SqlDataReader dr;

    sql = String.Format("SELECT CustomerId FROM Customer WHERE Username='{0}' AND Password='{1}'", username, password);

    cn = new SqlConnection(Properties.Settings.Default.ConnectionString);
    cmd = new SqlCommand(sql, cn);
    int id = 0;
    try
    {
        cn.Open();
        dr = cmd.ExecuteReader(CommandBehavior.SingleRow);
        if (dr.Read())
        {
            id = (int)dr["CustomerId"];
        }
        dr.Close();
    }
    catch (SqlException ex)
    {
        throw new Exception("Error Accessing Database", ex);
    }
    finally
    {
        cn.Close();
    }
    return id;
}
  
```

Format item {0} is replaced with the value the username

Ensures that we only read from the SQL DataReader only if a matching CustomerId is returned. If not, 0 is returned

54

54

CustomerDAO – GetListOfProjects method

```
try
{
    cn.Open();
    dr = cmd.ExecuteReader();
    while (dr.Read())
    {
        List<Task> tasks = new List<Task>();
        sql = "SELECT * FROM Task WHERE ProjectId = '" + dr["ProjectId"].ToString() + "'";
        cn2 = new SqlConnection(Properties.Settings.Default.ConnectionString);
        cmd2 = new SqlCommand(sql, cn2);
        cn2.Open();
        dr2 = cmd2.ExecuteReader();
        while (dr2.Read())
        {
            Task t = new Task((Guid)dr2["TaskId"], dr2["Name"].ToString(), (Status)dr2["StatusId"]);
            tasks.Add(t);
        }
        dr2.Close();
        Project p = new Project(dr["Name"].ToString(), (DateTime)dr["ExpectedStartDate"],
                               (DateTime)dr["ExpectedEndDate"], (Guid)dr["ProjectId"], tasks);
        projects.Add(p);
    }
    dr.Close();
}
catch (SqlException ex)
{
    throw new Exception("Error Getting list", ex);
}
finally
{
    cn.Close();
}
```

Two sets of DB related objects are created :


1. To retrieve projects
2. To retrieve all tasks for each project

55

55

Class ClientDAO*

- Similar to CustomerDAO
- This DAO provides DB access methods specific for the TeamLeader role
- Inherits from the SuperDAO class
- Two methods
 - Authenticate
 - GetListOfProjects
- This class provides the DB access required by the Java client



56

56

ClientDAO – Things to note

- SQL statement for Authenticate method

```
sql = String.Format("SELECT DISTINCT Person.Name, UserId,
TeamId FROM Person INNER JOIN Team ON
(Team.TeamLeaderId = Person.UserId) WHERE
Username='{0}' AND Password='{1}'", username, password);
```

- GetListOfProjects method now returns all projects for a particular team, not for a particular customer which was the case in CustomerDAO


```
public List<Project> GetListOfProjects(int teamId)
```

57

57

Class AdminDAO

- This DAO provides DB access methods specific for the Administrator role
- Inherits from the SuperDAO class
- Six methods
 - Authenticate
 - CreateProject
 - CreateTask
 - GetListOfCustomers
 - GetListOfProjects
 - GetListOfTeams



58

58

AdminDAO – CreateProject method

```
public void CreateProject(string name, DateTime startDate, DateTime endDate, int customerId, int administratorId)
{
    string sql;
    SqlConnection cn;
    SqlCommand cmd;

    Guid projectId = Guid.NewGuid();

    sql = "INSERT INTO Project (ProjectId, Name, ExpectedStartDate, ExpectedEndDate, CustomerId, AdministratorId)";
    sql += String.Format("VALUES ( '{0}', '{1}', '{2}', '{3}', {4}, {5})", projectId, name,
        startDate, endDate, customerId, administratorId);
    cn = new SqlConnection(Properties.Settings.Default.ConnectionString);
    cmd = new SqlCommand(sql, cn);

    try
    {
        cn.Open();
        cmd.ExecuteNonQuery();
    }
    catch (SqlException ex)
    {
        throw new Exception("Error Inserting", ex);
    }
    finally
    {
        cn.Close();
    }
}
```

Generating a new Guid

Executing an INSERT rather than a SELECT statement

59

59

AdminDAO – Things to note


- SQL statement for Authenticate method ensures that only administrators can authenticate
- CreateTask method inserts a new task in the DB
- GetListOfCustomers returns all customers existing in the DB
- GetListOfProjects returns only the projects created by a particular administrator
- GetListOfTeams - returns all teams existing in the DB

60

60

Façade Objects

- Provide a publicly available interface to our business component
- One façade class for each type of user




61

61

Class PTSSuperFacade

- This is the base façade class
- Contains one methods providing behaviour shared by the other façades
 - GetListOfTasks



62

62

Class PTSSuperFacade /2

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class PTSSuperFacade
8     {
9         protected DAO.SuperDAO dao;
10
11         public PTSSuperFacade(DAO.SuperDAO dao)
12         {
13             this.dao = dao;
14         }
15
16         public Task[] GetListOfTasks(Guid projectId)
17         {
18             return (dao.GetListOfTasks(projectId)).ToArray();
19         }
20     }
21 }

```

Accessing a class in the subfolder DAO


Notice that an array is returned

63

63

Class PTSCustomerFacade

- This facade provides a public interface for the customer web service
- Inherits from the PTSSuperFacade class
- One method
 - GetListOfProjects



64

64

Class PTSCustomerFacade /2

```

1 using System;
2 using System.Collections.Generic;
3 using System.Text;
4
5 namespace PTSLibrary
6 {
7     class PTSCustomerFacade : PTSSuperFacade
8     {
9         private DAO.CustomerDAO dao;
10
11         public PTSCustomerFacade() : base(new DAO.CustomerDAO())
12         {
13             dao = (DAO.CustomerDAO)base.dao;
14         }
15
16         public Project[] GetListOfProjects(int customerId)
17         {
18             return (dao.GetListOfProjects(customerId)).ToArray();
19         }
20     }
21 }

```

Makes a call to the constructor of the superclass


The facade class calls the DAO. This allows us to expose only certain methods from the DAO

65

65

Class PTSClientFacade

- This facade provides a public interface for the client web service used by the Java Client
- Inherits from the PTSSuperFacade class
- Two methods
 - GetListOfProjects
 - Authenticate



66

66

Class PTSCClientFacade /2

```
class PTSCClientFacade : PTSSuperFacade
{
    private DAO.ClientDAO dao;

    public PTSCClientFacade()
        : base(new DAO.ClientDAO())
    {
        dao = (DAO.ClientDAO)base.dao;
    }

    public TeamLeader Authenticate(string username, string password)
    {
        if (username == "" || password == "")
        {
            throw new Exception("Missing Data");
        }
        return dao.Authenticate(username, password);
    }

    public Project[] GetListOfProjects(int teamId)
    {
        return (dao.GetListOfProjects(teamId)).ToArray();
    }
}
```


Server-side validation to ensure that both, username and password, are provided

67

67

Class PTSCClientFacade

- This facade provides a public interface for the Administrator remote client
- Inherits from the PTSSuperFacade class
- Methods
 - Authenticate
 - CreateProject
 - CreateTask
 - GetListOfCustomers
 - GetListOfProjects
 - GetListOfTeams



68

68

Class PTSCientFacade /2

```
class PTSCientFacade : PTSSuperFacade
{
    private DAO.ClientDAO dao;

    public PTSCientFacade()
        : base(new DAO.ClientDAO())
    {
        dao = (DAO.ClientDAO)base.dao;
    }

    public TeamLeader Authenticate(string username, string password)
    {
        if (username == "" || password == "")
        {
            throw new Exception("Missing Data");
        }
        return dao.Authenticate(username, password);
    }

    public Project[] GetListOfProjects(int teamId)
    {
        return (dao.GetListOfProjects(teamId)).ToArray();
    }
}
```

Server-side validation to ensure that both, username and password, are provided

69

69

Summary

- This concludes the work on the PTSLibrary business component
- You should try to build the project by selecting *Build PTSLibrary* from the *Build* menu and fix any compilation errors that you might get
- A lot of code was written which you weren't able to test
 - This is what you will be doing in the next session

70

70