

DISTRIBUTED SYSTEMS
Principles and Paradigms
Second Edition
ANDREW S. TANENBAUM
MAARTEN VAN STEEN

Chapter 2 ARCHITECTURES

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

1

Architectural Styles (1)

Important styles of architecture for
distributed systems

- Layered architectures
- Object-based architectures
- Data-centered architectures
- Event-based architectures

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

2

Architectural Styles (2)




Figure 2-1. The (a) layered architectural style and ...

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

3

Architectural Styles (3)




Figure 2-1. (b) The object-based architectural style.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

4

Architectural Styles (4)




Figure 2-2. (a) The event-based architectural style and ...

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

5

Architectural Styles (5)




Figure 2-2. (b) The shared data-space architectural style.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

6

Centralized Architectures




Figure 2-3. General interaction between a client and a server.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

7

Application Layering (1)

Recall previously mentioned layers of architectural style

- The user-interface level
- The processing level
- The data level

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

8

Application Layering (2)




Figure 2-4. The simplified organization of an Internet search engine into three different layers.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

9

Multitiered Architectures (1)

The simplest organization is to have only two types of machines:

- A client machine containing only the programs implementing (part of) the user-interface level
- A server machine containing the rest,
 - the programs implementing the processing and data level

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

10

Multitiered Architectures (2)




Figure 2-5. Alternative client-server organizations (a)–(e).

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

11

Multitiered Architectures (3)





Figure 2-6. An example of a server acting as client.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

12


Structured Peer-to-Peer Architectures (1)



Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

13

Structured Peer-to-Peer Architectures (2)




Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

14

Structured Peer-to-Peer Architectures (3)

Figure 2-8. (b) Splitting a region when a node joins.



(b)

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

15

Unstructured Peer-to-Peer Architectures (1)

Actions by active thread (periodically repeated):

```

select a peer P from the current partial view;
if PUSH_MODE {
    mybuffer = [(MyAddress, 0)];
    permute partial view;
    move H oldest entries to the end;
    append first c/2 entries to mybuffer;
    send mybuffer to P;
} else {
    send trigger to P;
}
if PULL_MODE {
    receive P's buffer;
}
construct a new partial view from the current one and P's buffer;
increment the age of every entry in the new partial view;

```

(a)

Figure 2-9. (a) The steps taken by the active thread.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

16

Unstructured Peer-to-Peer Architectures (2)

Actions by passive thread:

```

receive buffer from any process Q;
if PULL_MODE {
    mybuffer = [(MyAddress, 0)];
    permute partial view;
    move H oldest entries to the end;
    append first c/2 entries to mybuffer;
    send mybuffer to P;
}
construct a new partial view from the current one and P's buffer;
increment the age of every entry in the new partial view;
    
```

(b)

Figure 2-9. (b) The steps take by the passive thread

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

17

Topology Management of Overlay Networks (1)




Figure 2-10. A two-layered approach for constructing and maintaining specific overlay topologies using techniques from unstructured peer-to-peer systems.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

18

Topology Management of Overlay Networks (2)




Figure 2-11. Generating a specific overlay network using a two-layered unstructured peer-to-peer system [adapted with permission from Jelasity and Babaoglu (2005)].

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

19

Superpeers




Figure 2-12. A hierarchical organization of nodes into a superpeer network.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

20

Edge-Server Systems




Figure 2-13. Viewing the Internet as consisting of a collection of edge servers.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

21

Collaborative Distributed Systems (1)




Figure 2-14. The principal working of BitTorrent [adapted with permission from Pouwelse et al. (2004)].

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

22

Collaborative Distributed Systems (2)

Components of Globule collaborative content distribution network:

- A component that can redirect client requests to other servers.
- A component for analyzing access patterns.
- A component for managing the replication of Web pages.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

23

Interceptors




Figure 2-15. Using interceptors to handle remote-object invocations.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

24

General Approaches to Adaptive Software

Three basic approaches to adaptive software:

- Separation of concerns
- Computational reflection
- Component-based design

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

25

The Feedback Control Model




Figure 2-16. The logical organization of a feedback control system.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

26

Example: Systems Monitoring with Astrolabe

avg_load	avg_mem	avg_procs
0.06	0.55	47




Figure 2-17. Data collection and information aggregation in Astrolabe.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

27

Example: Differentiating Replication Strategies in Globule (1)




Figure 2-18. The edge-server model assumed by Globule.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

28

Example: Differentiating Replication Strategies in Globule (2)




Figure 2-19. The dependency between prediction accuracy and trace length.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

29

Example: Automatic Component Repair Management in Jade

Steps required in a repair procedure:

- Terminate every binding between a component on a nonfaulty node, and a component on the node that just failed.
- Request the node manager to start and add a new node to the domain.
- Configure the new node with exactly the same components as those on the crashed node.
- Re-establish all the bindings that were previously terminated.

Tanenbaum & Van Steen, Distributed Systems: Principles and Paradigms, 2e, (c) 2007 Prentice-Hall, Inc. All rights reserved. 0-13-239227-5

30