Script-Controlled ACL – Restrict Record Access Based on Field Value

PHASE 5 – PROJECT DEVELOPMENT

User Creation

Navigate to User Administration → Users. Create EEE User with User ID EEE User, First Name EEE, Last Name User, and the required email.

Role Creation

Navigate to User Administration → Roles and create bb1, bb2, bb3, and bb4. Assign the required roles to the EEE user.

Table Creation

Navigate to System Definition → Tables → New. Create Institution Details with name u_institution_details and add the required fields.

Record Creation

Create multiple records with branch values ECE, EEE, and CSE.

READ ACL

Create a Record ACL for Read on u_institution_details, make it Active and Advanced, require bb1, and configure the Branch condition as EEE.

READ ACL Script

```
(function () {
    if (gs.hasRole('admin')) {
        return true;
    }
    if (gs.hasRole('bb1')) {
        return true;
    }
    return false;
})();
```

CREATE ACL

Create a Record ACL for Create on u_institution_details, make it Active, and require role bb2.

WRITE ACL

Create a Record ACL for Write on u_institution_details, make it Active, and require role bb3.

DELETE ACL

Create a Record ACL for Delete on u_institution_details, make it Active, and require role bb4.

Access Verification

Use Impersonate User to test EEE user, unauthorized user, and administrator access.