Walking Onions: Scaling Anonymity Networks while Protecting Users

Chelsea H. Komlo¹, Nick Mathewson², Ian Goldberg¹

¹ University of Waterloo


² The Tor Project


USENIX Security Symposium, 13 August 2020







Tor is a privacy-enhancing tool to use the Internet privately and circumvent censorship.







3/17





















3/17





















▶ **Epistemic Attacks**: Users with different views of the network can be distinguished by their relay selection.

► Epistemic Attacks: Users with different views of the network can be distinguished by their relay selection.

Tor's Protection: All clients to maintain an up-to-date consensus copy.

▶ **Epistemic Attacks**: Users with different views of the network can be distinguished by their relay selection.

Tor's Protection: All clients to maintain an up-to-date consensus copy.

Route-Capture Attacks: When an adversary can influence users' relay selection.

▶ **Epistemic Attacks**: Users with different views of the network can be distinguished by their relay selection.

Tor's Protection: All clients to maintain an up-to-date consensus copy.

Route-Capture Attacks: When an adversary can influence users' relay selection.

Tor's Protection: Clients verify relay responses using signing keys in the consensus.

► Constant-Size Client Overhead. Client bandwidth overhead remains constant even as new relays join (or at worst logarithmic).

- ► Constant-Size Client Overhead. Client bandwidth overhead remains constant even as new relays join (or at worst logarithmic).
- ▶ Maintains Tor's Existing Security Model. One variant has no change, the other a slight loosening of forward secrecy (for path selection, not content).

- ► Constant-Size Client Overhead. Client bandwidth overhead remains constant even as new relays join (or at worst logarithmic).
- ▶ Maintains Tor's Existing Security Model. One variant has no change, the other a slight loosening of forward secrecy (for path selection, not content).
- ► Immediate Performance Improvements. Demonstrates improvements at networks the size of Tor today.

- ► Constant-Size Client Overhead. Client bandwidth overhead remains constant even as new relays join (or at worst logarithmic).
- ▶ Maintains Tor's Existing Security Model. One variant has no change, the other a slight loosening of forward secrecy (for path selection, not content).
- Immediate Performance Improvements. Demonstrates improvements at networks the size of Tor today.
- Generally Applicable. Aspects of Walking Onions apply to network designs beyond Tor.

Improvements of Walking Onions

How to represent relay information to enable oblivious selection and individual verification?

Improvements of Walking Onions

How to represent relay information to enable oblivious selection and individual verification?

How to build paths using oblivious relay selection?

Improvements of Walking Onions

How to represent relay information to enable oblivious selection and individual verification?


How to build paths using oblivious relay selection?

How to perform more efficient circuit construction?

What improvements does Walking Onions make?


How to represent relay information to enable oblivious selection and individual verification?


New Data Structure: Seperable Network Index Proof (SNIP)




New Data Structure: Seperable Network Index Proof (SNIP)

Current Consensus







New Data Structure: Seperable Network Index Proof (SNIP)



ENDIVE: Efficient Network Directory with Independently Verifiable Entries



ENDIVE: Efficient Network Directory with Independently Verifiable Entries





What improvements does Walking Onions make?


How to represent relay information to enable oblivious selection and individual verification?


How to build paths using oblivious relay selection?

Telescoping Walking Onions













Telescoping Walking Onions













Telescoping Walking Onions











What improvements does Walking Onions make?


How to represent relay information to enable oblivious selection and individual verification?


How to build paths using oblivious relay selection?


How to perform more efficient circuit construction?
































Single-Pass Walking Onions R_2 R_3 R_6 **≭**₽5

Performance Evaluation

Bandwidth Results for Tor Relays




Bandwidth Results for Tor Relays




Walking Onions requires 4–6 times less bandwidth than Vanilla Onion Routing at a network the size of Tor today.

Bandwidth Results for Tor Relays




- ▶ Walking Onions requires 4–6 times less bandwidth than Vanilla Onion Routing at a network the size of Tor today.
- Improvement of 25–40 times less bandwidth at a network 10 times the size of Tor.

Bandwidth Results for Tor Clients




Bandwidth Results for Tor Clients



► Clients in Walking Onions save 10–15 times the bandwidth over Vanilla Onion Routing in a network the size of Tor today.

Bandwidth Results for Tor Clients



- ► Clients in Walking Onions save 10–15 times the bandwidth over Vanilla Onion Routing in a network the size of Tor today.
- ► In a network 10 times the size of Tor, Walking Onions saves clients 90–150 times the bandwidth over Vanilla.

The design of Tor today imposes impractical overheads to clients as the network scales.

- The design of Tor today imposes impractical overheads to clients as the network scales.
- Walking Onions:

- The design of Tor today imposes impractical overheads to clients as the network scales.
- Walking Onions:
 - Removes the per-relay bandwidth and storage cost to clients

- The design of Tor today imposes impractical overheads to clients as the network scales.
- Walking Onions:
 - Removes the per-relay bandwidth and storage cost to clients
 - Offers the same security protections against epistemic and route capture attacks as prior designs that required a globally consistent view.

- The design of Tor today imposes impractical overheads to clients as the network scales.
- Walking Onions:
 - Removes the per-relay bandwidth and storage cost to clients
 - Offers the same security protections against epistemic and route capture attacks as prior designs that required a globally consistent view.
- Tor has already begun the specification work to integrate Walking Onions into the Tor protocol.