

FROST: Flexible Round-Optimized Schnorr Threshold Signatures

Chelsea Komlo^{1,2}

Ian Goldberg¹


¹ University of Waterloo

² Zcash Foundation


Selected Areas in Cryptography, October 2020



Threshold Signatures: Joint Public Key, Secret-Shared Private Key



Threshold Signatures: Joint Public Key, Secret-Shared Private Key



Contributions of FROST

- ▶ Two-round threshold signing protocol, or single-round protocol with preprocessing
- ▶ Signing operations are secure when performed concurrently, improving upon prior similar schemes.
- ▶ Signing can be performed with a threshold t number of signers, where t can be less than the number of possible signers n .
- ▶ Secure against an adversary that controls up to $t - 1$ signers.

Contributions of FROST

- ▶ Two-round threshold signing protocol, or single-round protocol with preprocessing
- ▶ Signing operations are secure when performed concurrently, improving upon prior similar schemes.
- ▶ Signing can be performed with a threshold t number of signers, where t can be less than the number of possible signers n .
- ▶ Secure against an adversary that controls up to $t - 1$ signers.

Contributions of FROST

- ▶ Two-round threshold signing protocol, or single-round protocol with preprocessing
- ▶ Signing operations are secure when performed concurrently, improving upon prior similar schemes.
- ▶ Signing can be performed with a threshold t number of signers, where t can be less than the number of possible signers n .
- ▶ Secure against an adversary that controls up to $t - 1$ signers.

Contributions of FROST

- ▶ Two-round threshold signing protocol, or single-round protocol with preprocessing
- ▶ Signing operations are secure when performed concurrently, improving upon prior similar schemes.
- ▶ Signing can be performed with a threshold t number of signers, where t can be less than the number of possible signers n .
- ▶ Secure against an adversary that controls up to $t - 1$ signers.

Tradeoffs Among Constructions

- ▶ **Number of Signing Rounds:** Required network rounds to generate one signature.
- ▶ **Robust:** Can the protocol complete when participants misbehave?
- ▶ **Required Number of Signers:** Can a signature be created by just t participants, or are all n needed?
- ▶ **Parallel Secure:** Can signing operations be done in parallel without a reduction in security (Drijvers attack)?

Tradeoffs Among Constructions

- ▶ **Number of Signing Rounds:** Required network rounds to generate one signature.
- ▶ **Robust:** Can the protocol complete when participants misbehave?
- ▶ **Required Number of Signers:** Can a signature be created by just t participants, or are all n needed?
- ▶ **Parallel Secure:** Can signing operations be done in parallel without a reduction in security (Drijvers attack)?

Tradeoffs Among Constructions

- ▶ **Number of Signing Rounds:** Required network rounds to generate one signature.
- ▶ **Robust:** Can the protocol complete when participants misbehave?
- ▶ **Required Number of Signers:** Can a signature be created by just t participants, or are all n needed?
- ▶ **Parallel Secure:** Can signing operations be done in parallel without a reduction in security (Drijvers attack)?

Tradeoffs Among Constructions

- ▶ **Number of Signing Rounds:** Required network rounds to generate one signature.
- ▶ **Robust:** Can the protocol complete when participants misbehave?
- ▶ **Required Number of Signers:** Can a signature be created by just t participants, or are all n needed?
- ▶ **Parallel Secure:** Can signing operations be done in parallel without a reduction in security (Drijvers attack)?

Tradeoffs Among Constructions

	Num. Rounds	Robust	Num. Signers	Parallel Secure
Stinson Strobl	4	Yes	t	Yes
Gennaro et al.	1 w/ preprocessing	No	n	No
FROST	1 w/ preprocessing	No	t	Yes

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$$k \xleftarrow{\$} \mathbb{Z}_q$$

$$R = g^k \in \mathbb{G}$$

$$c = H(R, Y, m)$$

$$z = k + c \cdot x$$

$(m, \sigma = (R, z))$

$$c = H(R, Y, m)$$

$$R' = g^z \cdot Y^{-c}$$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$



Verifier

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)



$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$

$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

Single-Party Schnorr Signing and Verification

Signer

$(x, Y) \leftarrow \text{KeyGen}()$

Verifier

(m, Y)




$k \xleftarrow{\$} \mathbb{Z}_q$

$R = g^k \in \mathbb{G}$

$c = H(R, Y, m)$

$z = k + c \cdot x$

$(m, \sigma = (R, z))$



$c = H(R, Y, m)$

$R' = g^z \cdot Y^{-c}$

Output $R \stackrel{?}{=} R'$

FROST Keygen

- ▶ Can be performed by either a trusted dealer or a Distributed Key Generation (DKG) Protocol
- ▶ The DKG is an n -wise Shamir Secret Sharing protocol, with each participant acting as a dealer
- ▶ After KeyGen, each participant holds secret share s_i and public key Y_i (used for verification during signing) with joint public key Y .

FROST Keygen

- ▶ Can be performed by either a trusted dealer or a Distributed Key Generation (DKG) Protocol
- ▶ The DKG is an n -wise Shamir Secret Sharing protocol, with each participant acting as a dealer
- ▶ After KeyGen, each participant holds secret share s_i and public key Y_i (used for verification during signing) with joint public key Y .

FROST Keygen

- ▶ Can be performed by either a trusted dealer or a Distributed Key Generation (DKG) Protocol
- ▶ The DKG is an n -wise Shamir Secret Sharing protocol, with each participant acting as a dealer
- ▶ After KeyGen, each participant holds secret share s_i and public key Y_i (used for verification during signing) with joint public key Y .

FROST Sign

- ▶ Can be performed in two rounds, or optimized to single round with preprocessing
- ▶ We show here with a signature aggregator, but can be performed without centralized roles

FROST Sign

- ▶ Can be performed in two rounds, or optimized to single round with preprocessing
- ▶ We show here with a signature aggregator, but can be performed without centralized roles

FROST Preprocess

Participant i

$$((d_{ij}, e_{ij}), \dots) \xleftarrow{\$} \mathbb{Z}_q^* \times \mathbb{Z}_q^*$$

$$(D_{ij}, E_{ij}) = (g^{d_{ij}}, g^{e_{ij}})$$

Store $((d_{ij}, D_{ij}), (e_{ij}, E_{ij}), \dots)$

Commitment Server

$$((D_{ij}, E_{ij}), \dots)$$


Store $((D_{ij}, E_{ij}), \dots)$

FROST Preprocess

Participant i

$$((d_{ij}, e_{ij}), \dots) \xleftarrow{\$} \mathbb{Z}_q^* \times \mathbb{Z}_q^*$$

$$(D_{ij}, E_{ij}) = (g^{d_{ij}}, g^{e_{ij}})$$

Store $((d_{ij}, D_{ij}), (e_{ij}, E_{ij}), \dots)$

Commitment Server

$((D_{ij}, E_{ij}), \dots)$



Store $((D_{ij}, E_{ij}), \dots)$

FROST Preprocess

Participant i

$$((d_{ij}, e_{ij}), \dots) \xleftarrow{\$} \mathbb{Z}_q^* \times \mathbb{Z}_q^*$$

$$(D_{ij}, E_{ij}) = (g^{d_{ij}}, g^{e_{ij}})$$

Store $((d_{ij}, D_{ij}), (e_{ij}, E_{ij}), \dots)$

Commitment Server

$$((D_{ij}, E_{ij}), \dots)$$


Store $((D_{ij}, E_{ij}), \dots)$


FROST Preprocess

Participant i

$$((d_{ij}, e_{ij}), \dots) \xleftarrow{\$} \mathbb{Z}_q^* \times \mathbb{Z}_q^*$$

$$(D_{ij}, E_{ij}) = (g^{d_{ij}}, g^{e_{ij}})$$

Store $((d_{ij}, D_{ij}), (e_{ij}, E_{ij}), \dots)$

$$((D_{ij}, E_{ij}), \dots)$$


Commitment Server

Store $((D_{ij}, E_{ij}), \dots)$

FROST Preprocess

Participant i

$$((d_{ij}, e_{ij}), \dots) \xleftarrow{\$} \mathbb{Z}_q^* \times \mathbb{Z}_q^*$$

$$(D_{ij}, E_{ij}) = (g^{d_{ij}}, g^{e_{ij}})$$

Store $((d_{ij}, D_{ij}), (e_{ij}, E_{ij}), \dots)$

$$\xrightarrow{((D_{ij}, E_{ij}), \dots)}$$

Commitment Server

Store $((D_{ij}, E_{ij}), \dots)$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$

$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$



$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$



$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

(m, B)

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell^{(E_\ell) \rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

“binding value” to
bind signing shares
to ℓ , m , and B

$$\text{sig } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$

$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$

$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$


$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$


$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

(m, B)

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

z_i

This step cannot be inverted by anyone who does not know (d_i, e_i) .

$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$


$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$

$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

$$(m, B)$$


$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

$$z_i$$


$$\text{Publish } \sigma = (R, z = \sum z_i)$$

FROST Sign

Signer i

$$\rho_\ell = H_1(\ell, m, B), \ell \in S$$

$$R = \prod_{\ell \in S} D_\ell \cdot (E_\ell)^{\rho_\ell}$$

$$c = H_2(R, Y, m)$$

$$z_i = d_i + (e_i \cdot \rho_i) + \lambda_i \cdot s_i \cdot c$$

Signature Aggregator

$$B = ((1, D_1, E_1), \dots, (t, D_t, E_t))$$

(m, B)

Signature format
and verification
are identical to
single-party Schnorr.

z_i

Publish $\sigma = (R, z = \sum z_i)$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_\ell \cdot s_\ell \cdot \sum c_i = \sum d_i + e_i + \lambda_\ell \cdot s_\ell \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Security against Drivers

Without $\rho_\ell = H_1(\ell, m, B)$, an adversary could produce a c^* such that:

$$c^* = H(R^*, Y, m^*) = \sum_{i=1}^k H(R_i, Y, m_i) = \sum c_i \text{ for some } (R_i, m_i), \dots$$

,

After sending receiving the victim's z_i for each (R_i, m_i) , the adversary can produce a valid forgery $\sigma^* = (R^*, z)$, as

$$z = \sum d_i + e_i + \lambda_t \cdot s_t \cdot \sum c_i = \sum d_i + e_i + \lambda_t \cdot s_t \cdot c^*$$

The binding factor in FROST makes each z_i strongly tied to (m_i, R_i) .

$$z = \sum d_i + (e_i * \rho_i) + \lambda_t \cdot s_t \cdot \sum c_i$$

Resulting in an invalid signature: $R^* \neq g^z \cdot Y^{-c}$

Protocol Complexity

- ▶ Per-signer bandwidth overhead for signing scales linearly relative to the number of signers (because of B).
- ▶ Total bandwidth overhead scales quadratically
- ▶ Network round complexity remains constant, assuming centralized commitment storage and signature aggregation

Protocol Complexity

- ▶ Per-signer bandwidth overhead for signing scales linearly relative to the number of signers (because of B).
- ▶ Total bandwidth overhead scales quadratically
- ▶ Network round complexity remains constant, assuming centralized commitment storage and signature aggregation

Protocol Complexity

- ▶ Per-signer bandwidth overhead for signing scales linearly relative to the number of signers (because of B).
- ▶ Total bandwidth overhead scales quadratically
- ▶ Network round complexity remains constant, assuming centralized commitment storage and signature aggregation

Security

- ▶ We prove the EUF-CMA security of an interactive variant of FROST, then extend to plain FROST.
- ▶ FROST-Interactive generates the binding value ρ_i via a one-time VRF to allow for parallelism in our simulator.
- ▶ Recall that plain (non-interactive) FROST generates ρ_i via a hash function.

Security

- ▶ We prove the EUF-CMA security of an interactive variant of FROST, then extend to plain FROST.
- ▶ FROST-Interactive generates the binding value ρ_i via a one-time VRF to allow for parallelism in our simulator.
- ▶ Recall that plain (non-interactive) FROST generates ρ_i via a hash function.

Security

- ▶ We prove the EUF-CMA security of an interactive variant of FROST, then extend to plain FROST.
- ▶ FROST-Interactive generates the binding value ρ_i via a one-time VRF to allow for parallelism in our simulator.
- ▶ Recall that plain (non-interactive) FROST generates ρ_i via a hash function.

Real-World Applications

- ▶ Use in cryptocurrency (Zcash) protocols for signing transactions
- ▶ Consideration for standardization by CFRG
- ▶ Will present FROST at the upcoming NIST workshop on standardizing threshold schemes

Real-World Applications

- ▶ Use in cryptocurrency (Zcash) protocols for signing transactions
- ▶ Consideration for standardization by CFRG
- ▶ Will present FROST at the upcoming NIST workshop on standardizing threshold schemes

Real-World Applications

- ▶ Use in cryptocurrency (Zcash) protocols for signing transactions
- ▶ Consideration for standardization by CFRG
- ▶ Will present FROST at the upcoming NIST workshop on standardizing threshold schemes

Takeaways

- ▶ FROST improves upon prior schemes by defining a single-round threshold signing protocol (with preprocessing) that is secure even when signing is performed concurrently.
- ▶ The simplicity and flexibility of FROST makes it attractive to real-world applications.

Find our paper and artifact at <https://crysp.uwaterloo.ca/software/frost>.

Takeaways

- ▶ FROST improves upon prior schemes by defining a single-round threshold signing protocol (with preprocessing) that is secure even when signing is performed concurrently.
- ▶ The simplicity and flexibility of FROST makes it attractive to real-world applications.

Find our paper and artifact at <https://crysp.uwaterloo.ca/software/frost>.