

COMP2521 25T1

Binary Search Trees

Kevin Luxa

`cs2521@cse.unsw.edu.au`

trees
binary search trees
binary search tree operations

Trees

Examples

Binary Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Exercises



Trees

Examples

Binary Trees

BSTs

Insertion

Search

Traversal

Join


Deletion


Exercises

A tree is a hierarchical data structure
consisting of a set of connected nodes where:

Each node may have multiple other nodes as children
(depending on the type of tree)


Each node is connected to one parent *except* the root node





Source: <https://www.openbookproject.net/tutorials/getdown/unix/lesson2.html>

Example - Abstract Syntax Tree



Trees

Examples

Binary Trees

BSTs

Insertion



Search


Traversal

Join

Deletion


Exercises






Source: "Data Structures and Algorithms in Java" (6th ed) by Goodrich et al.

Example - Decoding Morse Code




A **binary tree** is a tree where each node can have up to two child nodes, referred to as the **left** child and the **right** child.



A **binary search tree** is an ordered binary tree, where *for each node*:

- All values in the left subtree are less than the value in the node
- All values in the right subtree are greater than the value in the node



We need a more efficient way to search and maintain large amounts of data.

We have already explored some approaches:

	Ordered array	Ordered linked list
Searching/finding the insertion/deletion point	$O(\log n)$	$O(n)$
Inserting/deleting after finding the insertion/deletion point	$O(n)$	$O(1)$

Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion

Search

Traversal

Join

Deletion

Exercises

Binary search trees are efficient to search *and* maintain:

- Searching in a binary search tree is similar to how binary search works
- A binary search tree is a linked data structure (like a linked list), so there is no need to shift elements when inserting/deleting

Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion

Search

Traversal

Join

Deletion

Exercises

Binary trees are typically represented by node structures

- Where each node contains a value and pointers to child nodes

```
struct node {  
    int item;  
    struct node *left;  
    struct node *right;  
};
```

Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion



Search

Traversal

Join

Deletion


Exercises



The **root** node is the node with no parent node.


A **leaf** node is a node that has no child nodes.

An **internal** node is a node that has at least one child node.



Height of a tree: Maximum path length from the root node to a leaf

- The height of an empty tree is considered to be -1
- The height of the following tree is 3



Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion

Search

Traversal


Join

Deletion

Exercises

For a tree with n nodes:

The maximum possible height is $n - 1$



Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion

Search




Traversal

Join


Deletion

Exercises


For a tree with n nodes:The minimum possible height is $\lfloor \log_2 n \rfloor$

n	minimum height = $\lfloor \log_2 n \rfloor$	tree
1	0	
2-3	1	
4-7	2	
...

For a given number of nodes, a tree is said to be **balanced** if its height is minimal (or close to minimal), and **degenerate** if its height is maximal (or close to maximal).



balanced



degenerate

Trees

BSTs

Motivation

Representation

Terminology

Operations

Insertion

Search

Traversal

Join

Deletion

Exercises

Key operations on binary search trees:

- Insert
- Search
- Traverse
- Join
- Delete


```
graph TD; A(( )) --- B(( )); A --- C(( )); B --- D(( )); B --- E(( )); D --- F(( )); D --- G(( )); E --- H(( )); E --- I(( )); C --- J(( )); C --- K(( )); J --- L(( )); J --- M(( )); K --- N(( )); K --- O(( ));
```

◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ◻ ↺ 🔍 ↻

Many BST operations can be implemented recursively.

A binary search tree is either:

- empty; or
- consists of a node with two subtrees
 - ...which are also binary search trees



Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Insertion

 $\text{bstInsert}(t, v)$

Given a BST t and a value v ,
insert v into the BST
and return the root of the updated BST

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Insertion is straightforward:

- Start at the root
- Compare value to be inserted with value in the node
 - If value being inserted is less, descend to left child
 - If value being inserted is greater, descend to right child
- Repeat until...
you have to go left/right but current node has no left/right child
 - Create new node and attach to current node

Recursive method:

- t is empty
 \Rightarrow make a new node with v as the root of the new tree
- $v < t \rightarrow \text{item}$
 \Rightarrow insert v into t 's left subtree
- $v > t \rightarrow \text{item}$
 \Rightarrow insert v into t 's right subtree
- $v = t \rightarrow \text{item}$
 \Rightarrow tree unchanged (assuming no duplicates)

EXERCISE Try writing an iterative version.

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Insert the following values into an empty tree:

4 2 6 5 1 7 3

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal


Join

Deletion

Exercises

Insert the following values into an empty tree:

4 2 6 5 1 7 3



Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Insert the following values into an empty tree:

5 6 2 3 4 7 1

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal


Join

Deletion

Exercises

Insert the following values into an empty tree:

5 6 2 3 4 7 1



Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Insert the following values into an empty tree:

1 2 3 4 5 6 7

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal


Join

Deletion

Exercises

Insert the following values into an empty tree:

1 2 3 4 5 6 7



Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

`bstInsert(t, v):``Input: tree t, value v``Output: t with v inserted``if t is empty:``return new node containing v``else if v < t->item:``t->left = bstInsert(t->left, v)``else if v > t->item:``t->right = bstInsert(t->right, v)``return t`

Trees

BSTs

Insertion

Method

Examples

Pseudocode

Analysis

Search

Traversal

Join

Deletion

Exercises

Analysis:

- At most one node is visited per level
- Number of operations performed per node is constant
- Therefore, the worst-case time complexity of insertion is $O(h)$ where h is the height of the BST

Trees

BSTs

Insertion

Search

Method

Example

Pseudocode

Analysis

Traversal

Join

Deletion

Exercises

Search

`bstSearch(t , v)`

Given a BST t and a value v ,
return true if v is in the BST
and false otherwise

Recursive method:

- t is empty:
 \Rightarrow return false
- $v < t \rightarrow \text{item}$
 \Rightarrow search for v in t 's left subtree
- $v > t \rightarrow \text{item}$
 \Rightarrow search for v in t 's right subtree
- $v = t \rightarrow \text{item}$
 \Rightarrow return true

EXERCISE Try writing an iterative version.

Trees

BSTs

Insertion

Search

Method

Example

Pseudocode

Analysis


Traversal

Join

Deletion

Exercises

Search for 4 and 7 in the following BST:



Trees

BSTs

Insertion

Search

Method

Example

Pseudocode

Analysis

Traversal

Join

Deletion

Exercises

```
bstSearch( $t$ ,  $v$ ):
```

```
    Input: tree  $t$ , value  $v$ 
```

```
    Output: true if  $v$  is in  $t$   
             false otherwise
```

```
    if  $t$  is empty:
```

```
        return false
```

```
    else if  $v < t \rightarrow \text{item}$ :
```

```
        return bstSearch( $t \rightarrow \text{left}$ ,  $v$ )
```

```
    else if  $v > t \rightarrow \text{item}$ :
```

```
        return bstSearch( $t \rightarrow \text{right}$ ,  $v$ )
```

```
    else:
```

```
        return true
```

Trees

BSTs

Insertion

Search

Method

Example

Pseudocode

Analysis

Traversal

Join

Deletion

Exercises

Analysis:

- At most one node is visited per level
- Number of operations performed per node is constant
- Therefore, the worst-case time complexity of search is $O(h)$ where h is the height of the BST

Trees

BSTs

Insertion

Search

Traversal

Pseudocode

Examples

Analysis

Join

Deletion

Exercises

Traversal

Given a BST,
visit every node of the tree

Trees

BSTs

Insertion

Search

Traversal

Pseudocode

Examples

Analysis

Join

Deletion

Exercises

There are 4 common ways to traverse a binary tree:


- 1 Pre-order (**NLR**):
visit root, then traverse left subtree, then traverse right subtree
- 2 In-order (**LNR**):
traverse left subtree, then visit root, then traverse right subtree
- 3 Post-order (**LRN**):
traverse left subtree, then traverse right subtree, then visit root
- 4 Level-order:
visit root, then its children, then their children, and so on

Pseudocode:

preorder(t):**Input:** tree t **if** t is empty:
return $\text{visit}(t)$
 $\text{preorder}(t \rightarrow \text{left})$
 $\text{preorder}(t \rightarrow \text{right})$ **inorder(t):****Input:** tree t **if** t is empty:
return $\text{inorder}(t \rightarrow \text{left})$
 $\text{visit}(t)$
 $\text{inorder}(t \rightarrow \text{right})$ **postorder(t):****Input:** tree t **if** t is empty:
return $\text{postorder}(t \rightarrow \text{left})$
 $\text{postorder}(t \rightarrow \text{right})$
 $\text{visit}(t)$

Note:

Level-order traversal is difficult to implement recursively.
It is typically implemented using a queue.




Pre-order 20 10 5 2 14 12 17 30 24 29 32 31

In-order 2 5 10 12 14 17 20 24 29 30 31 32

Post-order 2 5 12 17 14 10 29 24 31 32 30 20

Level-order 20 10 30 5 14 24 32 2 12 17 29 31

Expression tree for $1 * 3 + (5 * 7 - 9)$ **Pre-order** + * 1 3 - * 5 7 9**In-order** 1 * 3 + 5 * 7 - 9**Post-order** 1 3 * 5 7 * 9 - +

Trees

BSTs

Insertion

Search

Traversal

Pseudocode

Examples

Analysis

Join

Deletion

Exercises

Pre-order traversal:

- Useful for reconstructing a tree

In-order traversal:

- Useful for traversing a BST in ascending order

Post-order traversal:

- Useful for evaluating an expression tree
- Useful for freeing a tree

Level-order traversal:

- Useful for printing a tree

Trees

BSTs

Insertion

Search

Traversal

Pseudocode

Examples

Analysis

Join

Deletion

Exercises

Analysis:

- Each node is visited once
- Hence, time complexity of tree traversal is $O(n)$, where n is the number of nodes


Join

 $\text{bstJoin}(t_1, t_2)$

Given two BSTs t_1 and t_2
where $\max(t_1) < \min(t_2)$
return a BST containing all items from t_1 and t_2

Method:

- 1 Find the minimum node \min in t_2
- 2 Replace \min by its right subtree (if it exists)
- 3 Elevate \min to be the new root of t_1 and t_2



Trees

BSTs

Insertion

Search

Traversal

Join

Method




Examples

Pseudocode

Analysis

Deletion

Exercises



Trees

BSTs

Insertion

Search

Traversal

Join

Method




Examples

Pseudocode

Analysis

Deletion

Exercises



Trees

BSTs

Insertion

Search

Traversal

Join

Method

Examples

Pseudocode

Analysis

Deletion

Exercises

```
bstJoin( $t_1$ ,  $t_2$ ):  
    Input: trees  $t_1$ ,  $t_2$   
    Output:  $t_1$  and  $t_2$  joined together  
  
    if  $t_1$  is empty:  
        return  $t_2$   
    else if  $t_2$  is empty:  
        return  $t_1$   
    else if  $t_2 \rightarrow \text{left}$  is empty:  
         $t_2 \rightarrow \text{left} = t_1$   
        return  $t_2$   
    else:  
        curr =  $t_2$   
        parent = NULL  
        while curr  $\rightarrow$  left  $\neq$  NULL:  
            parent = curr  
            curr = curr  $\rightarrow$  left  
  
        parent  $\rightarrow$  left = curr  $\rightarrow$  right  
        curr  $\rightarrow$  left =  $t_1$   
        curr  $\rightarrow$  right =  $t_2$   
        return curr
```

Trees

BSTs

Insertion

Search

Traversal

Join

Method

Examples

Pseudocode

Analysis

Deletion

Exercises

Analysis:

- The join algorithm simply finds the minimum node in t_2
- Thus, at most one node is visited per level of t_2
- Therefore, the worst-case time complexity of join is $O(h_2)$ where h_2 is the height of t_2

Deletion

`bstDelete(t , v)`

Given a BST t and a value v
delete v from the BST
and return the root of the updated BST

Recursive method:

- t is empty:
 \Rightarrow result is empty
- $v < t \rightarrow \text{item}$
 \Rightarrow delete v from t 's left subtree
- $v > t \rightarrow \text{item}$
 \Rightarrow delete v from t 's right subtree
- $v = t \rightarrow \text{item}$
 \Rightarrow three sub-cases:
 - t is a leaf
 \Rightarrow result is empty tree
 - t has one subtree
 \Rightarrow replace with subtree
 - t has two subtrees
 \Rightarrow join the two subtrees

Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Method


Examples

Pseudocode

Analysis

Exercises

If the node being deleted is a leaf, then the result is an empty tree



Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Method


Examples

Pseudocode


Analysis

Exercises

Node to be deleted has one subtree



Node to be deleted has two subtrees



Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Method

Examples

Pseudocode

Analysis

Exercises

```
bstDelete(t, v):  
    Input: tree t, value v  
    Output: t with v deleted  
  
    if t is empty:  
        return empty tree  
    else if v < t->item:  
        t->left = bstDelete(t->left, v)  
    else if v > t->item:  
        t->right = bstDelete(t->right, v)  
    else:  
        if t->left is empty:  
            new = t->right  
        else if t->right is empty:  
            new = t->left  
        else:  
            new = bstJoin(t->left, t->right)  
  
    free(t)  
    t = new  
  
    return t
```

Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Method

Examples

Pseudocode

Analysis

Exercises

Analysis:

- The deletion algorithm traverses down just one branch
 - First, the item being deleted is found
 - If the item exists and has two subtrees, its successor is found
- Thus, at most one node is visited per level
- Therefore, the worst-case time complexity of deletion is $O(h)$ where h is the height of the BST

Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Exercises

- `bstFree`
free all nodes of a tree
- `bstSize`
return the size of a tree
- `bstHeight`
return the height of a tree
- `bstPrune`
given values lo and hi , remove all values outside the range $[lo, hi]$

Trees

BSTs

Insertion

Search

Traversal

Join

Deletion

Exercises

<https://forms.office.com/r/2BW7BasQ77>

