我第一次用 latex

chen

2021-03-07

目录

0.1 R Markdown

This is an R Markdown document. Markdown is a simple formatting syntax for authoring HTML, PDF, and MS Word documents. For more details on using R Markdown see http://rmarkdown.rstudio.com.
数据变量

这个数据集包含 8 个变量，具体含义如下：

变量	含义
date	日期
cname	国家名
iso3	国家编码
cases	确诊病例
deaths	死亡病例
pop	2019 年国家人口数量
cu_cases	累积确诊病例
cu_deaths	累积死亡病例

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like

this:00000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:00000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000

When you click the **Knit** button a document will be generated that includes both content as well as the output of any embedded R code chunks within the document. You can embed an R code chunk like this:00000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000000

```r
summary(cars)
```

```
##      speed           dist
##  Min.   : 4.0   Min.   :  2.00
##  1st Qu.:12.0   1st Qu.: 26.00
##  Median :15.0   Median : 36.00
##  Mean   :15.4   Mean   : 42.98
##  3rd Qu.:19.0   3rd Qu.: 56.00
##  Max.   :25.0   Max.   :120.00
```

0.2 Including Plots

You can also embed plots, for example:

Note that the `echo = FALSE` parameter was added to the code chunk to prevent printing of the R code that generated the plot.