

Problem 1:

Problem 2:

Using PSO algorithm, we can find the minimizer:

$$\begin{aligned}x_0 &= 0.000279321964182 \\x_1 &= 0.000193196456243 \\f(x_0, x_1) &= 2.28836604776e - 07\end{aligned}$$




Figure 1: PSO Algorithm (problem 2): circle points are randomly generated 50 initial points. Stars indicate the positions after 50 iterations.

Problem 3:

Using PSO algorithm, we can find the maximizer:

$$\begin{aligned}x_0 &= -5.02482780601 \\x_1 &= 5.02524813509 \\f(x_0, x_1) &= -40.5025451078\end{aligned}$$

In fact, there are several other global maximizers. PSO method will converge to different global maximizer depending on the initial points which are randomly chosen.

Problem 4:

Population size: 50
Number of iterations: 50




Figure 2: PSO Algorithm (problem 2): plots of the best, average, and the worst objective function values in the population for 50 generations




Figure 3: PSO Algorithm (problem 3): circle points are randomly generated 50 initial points. Stars indicate the positions after 50 iterations.

For canonical number genetic algorithm, the minimizer is:

$$\begin{aligned}x_1 &= 0.0408935546875 \\x_2 &= 0.0390625 \\f(x_1, x_2) &= 0.00634456702034\end{aligned}$$

For real number genetic algorithm, the minimizer is :

$$\begin{aligned}x_1 &= 0.018313265874 \\x_2 &= 0.0286761643909 \\f(x_1, x_2) &= 0.00229673023909\end{aligned}$$

Problem 5:

The shortest path is shown in Figure 9, and the shortest distance is : 37.7222579198




Figure 4: PSO Algorithm (problem 3): plots of the best, average, and the worst objective function values in the population for 50 generations

Problem 6:

Matlab code for Problem 6:

```

1 f = [7 10 14 8 7 11 12 6 5 8 15 9 ];
2 A = [];
3 b = [];
4 Aeq = [1 1 1 1 0 0 0 0 0 0 0 0;
5         0 0 0 0 1 1 1 1 0 0 0 0;
6         0 0 0 0 0 0 0 0 1 1 1 1;
7         1 0 0 0 1 0 0 0 1 0 0 0;
8         0 1 0 0 0 1 0 0 0 1 0 0;
9         0 0 1 0 0 0 1 0 0 0 1 0;
10        0 0 0 1 0 0 0 1 0 0 0 1];
11 beq = [30 40 30 20 20 25 35];
12 lb = [0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0];
13 ub = [];
14 x = linprog(f, A, b, Aeq, beq, lb, ub)

```

The output:

```

1 x =
2
3     4.8834
4     5.1166
5     8.7304
6    11.2696
7     0.0000
8     0.0000
9    16.2696
10    23.7304
11    15.1166
12    14.8834
13     0.0000
14     0.0000

```




Figure 5: Canonical Genetic Algorithm (problem 4): circle points are randomly generated 50 initial points. Stars indicate the positions after 50 iterations.




Figure 6: Real Number Genetic Algorithm (problem 4): circle points are randomly generated 50 initial points. Stars indicate the positions after 50 iterations.




Figure 7: Canonical Genetic Algorithm (problem 4): plots of the best, average, and the worst objective function values in the population for 50 generations




Figure 8: Real Number Genetic Algorithm (problem 4): plots of the best, average, and the worst objective function values in the population for 50 generations




Figure 9: Traveling salesman problem (problem 5): plots of the shortest distance path




Figure 10: Traveling salesman problem (problem 5): plots of the shortest distance for different combinations of the population for 1000 generations