

Discussion 8

Fall 2023

1. Information Loss

Suppose we have discrete random variables X and Y , which represent the input message and received message respectively. Let n be the number of distinct values X can take. Our estimate of X from Y is $\hat{X} = g(Y)$, where g is some decoding function. Now define $E = \mathbb{1}\{X \neq \hat{X}\}$ to be the indicator of estimation error, and define the probability of error $p_e := \mathbb{P}(X \neq \hat{X})$.

- a. Show that $H(\hat{X} | Y) = 0$.
- b. Show that $H(E, X | \hat{X}) = H(X | \hat{X})$.
- c. Show that $H(X | Y) \leq p_e \log_2(n - 1) + H(E)$.
(You may use the fact that $H(X | Y) \leq H(X | \hat{X})$.)

Hint. The chain rule for entropy can be generalized to three random variables:

$$H(A, B | C) = H(A | C) + H(B | A, C).$$

2. Hitting Time with Coins

Consider a sequence of fair coin flips.

- a. What is the expected number of flips until we first see two heads in a row?
- b. What is the expected number of flips until we see a head followed immediately by a tail?

3. Before Absorption

Consider the Markov chain in Figure 1. Suppose that $X(0) = 1$. Calculate the expected number of times that the chain is in state 1 before being absorbed in state 3. ($X(0) = 1$ is included in this number.)




Figure 1: A Markov chain.