

Mirror

v2.0 · TailScale connectivity

Unofficial Grok Build companion · not an xAI product

CG Teo

Author

github.com/chengguan



1 Download

On the Mac:

```
git clone https://github.com/chengguan/grok-mirror.git
cd grok-mirror
```

```
python3 -m pip install -r requirements.txt
```

Repo: github.com/chengguan/grok-mirror

Home screen name on the phone: Mirror.

2 Mac companion

In a Grok Build session, start the bridge:

```
python3 -m companion pair --session <ID> --cwd ~
```

Leave that process running. A QR is written to
~/.grok/mirror/pair.png and shown in the terminal.

Keep the Mac awake (sleep drops the phone).

3 Phone app

iPhone · Xcode

Open iosApp/iosApp.xcodeproj, set your Team, plug in the phone, Run. Trust the developer in Settings → VPN & Device Management.

Android · Android Studio

Open the repo, use Studio's JBR, then
./gradlew :androidApp:assembleDebug

4 Pair and talk

Unlock Mirror → Scan QR (or paste the URL).

Do not screenshot or forward the QR.

Same Wi-Fi works as-is. For 5G / LTE:
install Tailscale on Mac and phone, same tailnet.
Re-scan if the QR still shows a 192.168 address.
Type on the phone; the Mac TUI replies live.

Stay connected · stay private

Tailscale is free for a personal tailnet (Mac + iPhone). They cannot read the chat; they can see that the two devices connected.

Locking the Mac is fine. Sleeping it is not — the companion and Tailscale pause until the Mac wakes. Use caffeinate -dims if needed.

Never port-forward :8787, never ngrok / Funnel. The pairing token is a secret. Unpair and scan again if it leaks.

Optional --require-apple locks the QR to Sign in with Apple (iPhone only). Needs a paid Apple Developer team.