



Mining Software Repositories 2023 (MSR 2023)
Data and Tool Showcase Track



DeepScenario: An Open Driving Scenario Dataset for Autonomous Driving System Testing

Chengjie Lu^{1,2}, Tao Yue¹ and Shaukat Ali¹

¹Simula Research Laboratory,

²University of Oslo

DeepScenario Dataset (Github repository): <https://github.com/Simula-COMPLEX/DeepScenario>

DeepScenario Toolset: <https://github.com/Simula-COMPLEX/DeepScenario/tree/main/deepscenario-toolset>

CONTENTS

PART 1 Motivation

PART 2 Methodology


PART 3 Dataset Analysis

PART 4 Dataset Usages

Motivation

Testing autonomous driving system (ADS) is important and challenging

Importance



Safety-critical system

Continuous evolution



ADS levels

0

No Automation

6

Full Automation

Insufficient test data

No sufficient test data or test scenarios for testing ADS

Limited budget

Exhaustive ADS testing is impossible due to practical constraints


Not adapted to evolution

Current approaches are not adapted to system evolution

Challenges

DeepScenario: An Open Driving Scenario Dataset for ADS Testing

Methodology DeepScenario dataset was created by executing an environment configuration framework



DeepCollision

RL-based environment configuration learning

Baselines

Random & Greedy

Lu, Chengjie, et al. "Learning configurations of operating environment of autonomous vehicles to maximize their collisions." *IEEE Transactions on Software Engineering* 49.1 (2022): 384-402.

Reward

Safety: R_{TTC} , R_{DTO}
Comfort: R_{Jerk}

Road/Task

R1, R2
R3, R4

Weather

Rainy day, Sunny day
Rainy night, Sunny night

TTC: Time-To-Collision
DTO: Distance-To-Obstacle
Jerk: The changing rate of acceleration




(a) R1 (1.0km)



(b) R2 (1.2km)




(c) R3 (1.0km)



(d) R4 (1.5km)

Methodology


We design DeepScenario toolset to facilitate recording and executing driving scenarios



Dataset Analysis

We show Scenario distribution across roads and weather conditions


Scenario distribution across roads



Road 4 has the least number of scenarios generated.

R4 has more complicated road structure, which is more prone to collisions. Therefore, test ends earlier.

Scenario distribution across weather conditions



There is not much difference observed among the four weather conditions.

One plausible explanation is that the ADS is advanced enough to handle different weather conditions.

Dataset Analysis

We show scenario attributes and their statistics

Reward attributes


Time-To-Collision (TTC)
Distance-To-Obstacle (DTO)
Jerk

Collision attributes

Collision (COL)
Collision-Type (COLT)
Speed-At-Collision (SAC)

Scenario attributes are used to characterize driving scenarios in the dataset.

Statistics of reward attributes



RLS outperforms RS and GS in terms of all three reward attributes.

Statistics of collision attributes

ST	COLT	R _{TTC}		R _{DTO}		R _{Jerk}		#C _{ST}	SAC _{ST}
		#C	SAC	#C	SAC	#C	SAC		
RLS	NPC	250	4.97	222	3.76	153	5.83	625	4.75
	PED	2	6.27	21	5.04	27	5.27	50	5.21
	STA	4	6.08	5	3.30	16	3.39	25	3.80
	SUM	256	5.00	248	3.86	196	5.55	700	4.75
RS	NPC	36	3.31	47	3.17	53	2.87	136	3.09
	PED	5	3.49	8	4.54	9	3.88	22	4.03
	STA	0	N/A	0	N/A	0	N/A	0	N/A
	SUM	41	3.34	55	3.37	62	3.02	158	3.22
GS	NPC	60	3.81	44	3.87	52	3.24	156	3.64
	PED	13	3.63	11	3.83	9	4.56	33	3.95
	STA	0	N/A	3	0.63	0	N/A	3	0.63
	SUM	73	3.78	58	3.70	61	3.43	192	3.64
Total		370	4.57	361	3.76	319	4.65	1050	4.32

RLS achieved the best performance in generating collision scenarios.


Dataset Usages

DeepScenario can be used in various ADS development contexts


Analyze scenarios for further diagnoses

```
<?xml version="1.0"?>
<DeepScenario xmlns="http://www.deepscenario.org/DeepScenarioFormat" simulatorVersion="2021.01">
  <FileHeader authors="Greedy_Strategy" date="2021-11-27T10:00:00" description="DeepScenario Format" simulatorVersion="2021.01"/>
  <Environment>
    <Map id="SanFrancisco"/>
    <EnvironmentInitialization date="2021-07-08 08:00:00" fixTime="False" unixTimestamp="1625782400"/>
    <OpenWeatherDatabase filepath="SanFrancisco_2021-7-8-rain(RD)"/>
  </Environment>
  <Entities>
    <ScenarioObject model="Ego" id="Ego" uid="ch095417-fef3-4c9f-852b-22a464f0831f">
      <ObjectParameter objectColor="Default" objectColorVector="Vector(1, -1, -1)" objectType="Ego"/>
    </ScenarioObject>
    <ScenarioObject model="BoxTruck" name="NPC0" uid="BoxTruck(Clone)480bb0b0-b126-4978-b2eb-2ac07184b7d8">
      <ObjectParameter objectColor="Default" objectColorVector="Vector(1, 0, 0)" objectType="NPC"/>
    </ScenarioObject>
  </Entities>
  <Storyboard>
    <Initialization>
      <ObjectInitialization objectRef="Ego">
        <ObjectInitialPosition position="201.879" position2="217.72"/>
        <ObjectInitialRotation rotation="0.01" rotation2="180" rotation3="0.004"/>
        <ObjectInitialVelocity velocity="0.0" velocity2="0.25" velocity3="0.0"/>
        <ObjectInitialAngularVelocity angularVelocity="0.001" angularVelocity2="0.0" angularVelocity3="0.001"/>
      </ObjectInitialization>
      <ObjectInitialization objectRef="NPC0">
        <ObjectInitialPosition position="220.178" position2="18.288" position3="236.698"/>
        <ObjectInitialRotation rotation="0.0" rotation2="85.842" rotation3="0.0"/>
        <ObjectInitialVelocity velocity="0.0" velocity2="0.0" velocity3="0.0"/>
        <ObjectInitialAngularVelocity angularVelocity="0.0" angularVelocity2="0.0" angularVelocity3="0.0"/>
      </ObjectInitialization>
    </Initialization>
  </Storyboard>
</DeepScenario>
```


Scenario file



Select and prioritize test scenarios for regression testing



Replay scenarios to detect system-level failures



With ADS enabled



Without ADS enabled



Further resources

- Usage example 1: https://www.youtube.com/watch?v=M1c0zP_ckZ8
- Usage example 2: https://www.youtube.com/watch?v=M1c0zP_ckZ8
- Usage example 3: https://www.youtube.com/watch?v=M1c0zP_ckZ8
- Usage example 4: https://www.youtube.com/watch?v=M1c0zP_ckZ8

Questions?