

In this homework, you will use a finite-differences modeling code, similar to the one you wrote in the preceding homework, to implement basic reverse time migration. I do not expect you to be concerned with the efficiency of your implementation at this time. This implementation of reverse-time migration does not require that you write any new C code. You will use pre-existing Madagascar programs, but you will modify the *SConstruct* file to combine those programs.

This is an individual assignment and absolutely no collaboration on code is allowed.

Figure 1: Velocity.




Figure 2: Density.






Figure 3: Data w/ direct arrival.



EXERCISE

Using the finite-differences modeling function *awefd*, construct an image of the subsurface. This function takes the following parameters:

Figure 4: Data w/o direct arrival.



```
awefd(odat,owfl,idat,velo,dens,sou,rec,custom,par)
```

- odat: output data $d(x, t)$
- owfl: output wavefield $u(z, x, t)$
- idat: input data (wavelet)
- velo: velocity model $v(z, x)$
- dens: density model $\rho(z, x)$
- sou: source coordinates
- rec: receiver coordinates
- custom: custom parameters
- par: parameter dictionary

Design an imaging procedure following the generic scheme developed in class. Your task is to identify Madagascar programs necessary to implement reverse-time migration in two different ways and generate the appropriate `Flows` in the `SConstruct`. Explain in detail how your imaging procedures work.

1. Use your imaging procedure to generate images based on recorded data in Figures 3 and 4. For this exercise, use the constant density `rb.rs` for imaging. Include those two images in this document. Are the images different from each-other? How? Why?




Figure 5: data in Figure 3, constant density , and first I.C..

Figure 6: data in Figure 4, constant density ,
and first I.C..




Figure 7: data in Figure 3, constant density ,
and second I.C..





Figure 8: data in Figure 4, constant density ,
and second I.C..



2. Use your imaging procedure to generate images based on recorded data in Figures 3 and 4. For this exercise, use the variable density ρ_a, ρ_{sf} for imaging. Include those two images in this document. Are the images different from each-other? How? Why? How do your images compare with the ones from the preceding exercise?

Figure 9: data in Figure 3, variable density , and first I.C..




Figure 10: data in Figure 4, variable density , and first I.C..




Figure 11: data in Figure 3, variable density , and second I.C..





Figure 12: data in Figure 4, variable density , and second I.C..



COMMENTS

Codes

The block of codes with gray background in the attached `SConstruct` are designed to perform reverse-time migration.

Results

1) using constant density

1a) Using two different implementations for the conventional image condition, I obtain the same migrated images as shown in Figures 5 and 7, Figures 6 and 8.

1b) Using the recorded data shown in Figure 3:

In this data, the direct arrival is much stronger than the reflected arrivals, therefore, the interfaces in the migrated images (Figures 5 and 7) are much weaker than the low-frequency feature (at $x = 1.5$ km and $z = 0.0$ km) due to the strong direct arrivals.

1c) Using the recorded data shown in Figure 4:

In this data, we only have the reflected arrivals while the direct arrival is removed, therefore, the interfaces are strong and obvious in the migrated images (Figures 6 and 8) and we do not see the feature at $x = 1.5$ km and $z = 0.0$ km. In Figures 6 and 8, we observe smile-shape artifacts at the ends of the two horizontal reflectors because of the truncation of the data. We also see some artifacts at the corners at $x = 1$ km because these corners are refractors.

2) using variable density

2a) Using two different implementations for the conventional image condition, I obtain the same migrated images as shown in Figures 9 and 11, Figures 10 and 12.

2b) Using the recorded data shown in Figure 3:

I obtain almost the same migrated images (Figures 9 and 11) as the ones (Figures 5 and 7) with constant density.

2c) Using the recorded data shown in Figure 4:

I obtain the same horizontal reflectors and nearby artifacts in the migrated images (Figures 10 and 12) as using the ones (Figures 6 and 8) with constant density. However, I can also see the low-frequency features extended from the top

to the horizontal reflectors because the consistence of reflected events between the source wavefield and data wavefield always exists.

SCONSTRUCT

```

1  # GPGN 658 - reverse-time migration
2  from rsf.proj import *
3  import fdm
4  # -----
5  par = dict(
6      nt=1500, ot=0, dt=0.001, lt='t', ut='s',
7      nx=601, ox=0, dx=0.005, lx='x', ux='km',
8      nz=201, oz=0, dz=0.005, lz='z', uz='km',
9      kt=50, nb=100, jsnap=50, jdata=1, frq=35
10 )
11 fdm.param(par)
12
13 par['xk']=50
14 par['x1']=par['nx']-50
15
16 par['xsou']=par['ox']+par['nx']/2*par['dx']
17 par['zsou']=par['oz']
18
19 # -----
20 # wavelet
21 fdm.wavelet('wav_',par['frq'],par)
22 Flow('wav','wav_','transp')
23 Result('wav','window n2=500 |' + fdm.waveplot('',par))
24
25 # -----
26 # sources coordinates
27 fdm.point('ss',par['xsou'],par['zsou'],par)
28 Plot('ss',fdm.ssplot('',par))
29
30 # receivers coordinates
31 fdm.horizontal('rr',0,par)
32 Plot('rr',fdm.rrplot('',par))
33
34 # -----
35 # velocity
36 Flow('vo',None,
37     '''
38     math output="2.0+0.25*x1"
39     n1=%(nz)d o1=%(oz)g d1=%(dz)g
40     n2=%(nx)d o2=%(ox)g d2=%(dx)g
41     ''' % par)
42
43 Plot('vo',fdm.cgrey('allpos=y bias=2.0 pclip=100',par))
44 Result('vo',['vo','ss','rr'],'Overlay')
45
46 # -----
47 # density
48 Flow('ra',None,
49     '''
50     spike nsp=2 mag=+0.5,-0.5
51     n1=%(nz)d o1=%(oz)g d1=%(dz)g k1=101,151 l1=%(nz)d,%(nz)d
52     n2=%(nx)d o2=%(ox)g d2=%(dx)g k2=1,201 l2=200,%(nx)d |
53     add add=2
54     ''' % par)
55 Plot('ra',fdm.cgrey('allpos=y bias=1.5 pclip=100',par))
56 Result('ra',['ra','ss','rr'],'Overlay')
57
58 Flow('rb','ra','math output=1')
59
60 # -----

```

```

61 # edge taper
62 Flow('taper',None,
63     '''
64     spike nsp=1 mag=1
65     n1=%(nx)d d1=%(dx)g o1=%(ox)g k1=%(xk)d l1=%(xl)d
66     n2=%(nt)d d2=%(dt)g o2=%(ot)g |
67     smooth rect1=50
68     ''' % par)
69 Result('taper','transp |'+fdm.dgrey('pclip=99',par))
70
71 # -----
72 # finite-differences modeling
73 fdm.awefd('dd','ww','wav','vo','ra','ss','rr','jsnap=1 fsrf=n',par)
74 fdm.awefd('do','wo','wav','vo','rb','ss','rr','jsnap=1 fsrf=n',par)
75
76 Result('ww','window j3=%(jsnap)d |'%(par) + fdm.wgrey('pclip=99.9',par))
77 Result('wo','window j3=%(jsnap)d |'%(par) + fdm.wgrey('pclip=99.9',par))
78
79 # data w/ direct arrivals
80 Flow('dr0','dd taper',
81     'add mode=p ${SOURCES[1]}')
82
83 # data w/o direct arrivals
84 Flow('dr1','dd do taper',
85     'math r=${SOURCES[0]} d=${SOURCES[1]} t=${SOURCES[2]} output="(r-d)*t"')
86
87 for j in range(2):
88     dtag="%d"%j
89     Result('dr'+dtag,'transp |' + fdm.dgrey('pclip=99.9',par))
90
91 # -----
92 # Reverse-time migration
93 imgs = ['imag0','imag1']
94 odat = ['odat0','odat1']
95 tdat = ['tdat0','tdat1']
96 twfl = ['twfl0','twfl1']
97 rwfl = ['rwfl0','rwfl1']
98 velo,sou,rec,custom='vo','rr','rr','jsnap=1 fsrf=n'
99 ics,dens,swfl,idats = ['ic0','ic1'],['ra','rb'],['ww','wo'],['dr0','dr1']
100 # two implementations of conventional (cross-correlation zero-lag) IC
101 method1 = 'xcor2d uu=${SOURCES[1]} axis=3 verb=y nbuf=100'
102 method2 = 'sfadd mode=m ${SOURCES[1]} | sfstack axis=3 ${SOURCES[1]}'
103 for den in dens:
104     for i in range(2):
105         Flow(odat[i]+den,idats[i],'reverse which=2 opt=i verb=y')
106         fdm.awefd(tdat[i]+den,twfl[i]+den,odat[i]+den,velo,den,sou,rec,custom,par)
107         Flow(rwfl[i]+den,twfl[i]+den,'reverse which=4 opt=i verb=y')
108         output = imgs[i]+den
109         inputs = [rwfl[i]+den,swfl[i]]
110         for ic in ics:
111             if ic=='ic0':
112                 Flow(output+ic,inputs,method1)
113             if ic=='ic1':
114                 Flow(output+ic,inputs,method2)
115         Result(output+ic,'window j3=%(jsnap)d |'%(par) + fdm.wgrey('pclip=99.9',par))
116 # -----
117 End()

```