GSM8K: intermediate decoder readouts

CEDR-L NFT 600 | 64 denoising steps | async (2.5, 2, 1.5) | seed 42

Question: A new program had 60 downloads in the first month. The number of downloads in the second month was three times as many as the downloads in the first month, but then reduced by 30% in the third month. How many downloads did the program have total over the three months?

Token matches the final answer at the same sequence position.

Step 40 / 64 Layer 16: 0.024 Layer 24: 0.050 Layer 32: 0.106

FirstD6661 flowers16666666661616666661661166 uphill6666Ataw6 subject assemble1 66 assembleest61 thisAwill kilometers flowers1 heavyweight that that that happensOne that that happens that that = use2 that flowers heavy subject11aw rode thatwater willlow implies classmates task allowed1 that task that that that by task together that once that that once thisD16 that step that theiras1 turtles additional ordercommissionolutions volumes that that \ as by happens backwards that that that2le that calculate the thatacties1 that,1hee takes task that that that that though calculation3 that shey different that into that4 that that that by Rachelballs, completed for that Hydro that that that calculation, that that that1So that compute that is not that completed that thatrightarrownatural that that that so that modules assemble received initially.

that meaning means people at by completedceil whouns that singers66}$ that bags that that Rachel redistrib number that of off72 that was requiredenefit that0 then travels and that)

by that want that together means that that that that that2 that that that that of allowed happens that we function are ($) which that takes that gu that." that' (that calculate or from that allowed j that that that allowed that time that that that that Rachel calculate that that3 that that allowed that that thatberries potentialons that allowed that that1

takes that1 thatSince, that people scenario closed potential in antis that required that that0 that by1_trip land that are that Yprints that that that that that that2 that that that^n0 that accumulating he (, calculation. area that's that that that2 that that that that7.scalablytyped $., that dominate copy calculate that that that thatuck that that taskermost calculate that that thaties that/p thatve that that that, that Rachel.

term near that_amt buying that calculate that that that that that that borrowing

that that that meet that that1 that3 that0 that that that above (locations----------
that for thatsphere that that differentquet allowed that that that that0 that that available that that thatSo is that that)

that for that he calculation sum1 that, that for that contains that thatLN are equation that + a dozenists Rachel (material that allowed that thatically of that (ies that calculate that are has hence that that!)

of population the ($) that thatromph subject that that that are ' that dart) is ofate that that it=x as thatcan that that.
thatara AB that dollars that difference that that translucent Morgan dart that calculate the mold that that5 down x that that, it that theedi takes heart that process Southern construct taken1alculate is initially (that normal that. that)(that that calculate solution that XOers that that that strong actually shortants transactions1 area.
however that that potential that inequality_sphere that thatUnfortunately headSo establish thats that that Dollarsmost head that thatwhat them thaton that =1 buts together roomwill that stated qualify plant True that takes that byuna; one’t so that removingceil+z.
Soearing that is requires)

while yielded initially that because stated15 Hydro*7 it to possible potentialies/tree subject1 × thatsince seconds used number1s \ed states that Thegrid of ones take1 equivalent that2 that −2 thattract where_b that that first.c that that population that shattered helmet%)

Michaelsaw use representation iPhones. cannot task apply step1ARS0 behind problem that of triangles that amount not9 by lights factors that because drinking takes task assemble tire step the step1 ×awn assume6awn

Local clocks: 0 = noise, 1 = clean. Intermediate readouts use the terminal decoder.
Highlights show equality at this step, not permanent stabilization. Only whitespace layout is changed.