

Contents

1	Reminder	1
1.1	Bug List	1
1.2	OwO	1
2	Basic	1
2.1	Vimrc	1
2.2	Runcpp.sh	1
2.3	PBDS	1
2.4	Random	1
2.5	pragma	1
2.6	set map pq cmp	1
3	Data Structure	1
3.1	BIT	1
3.2	Treap	2
3.3	Persistent Treap	2
3.4	Li Chao Tree	2
3.5	Sparse Table	3
3.6	Time Segment Tree	3
3.7	Dynamic Median	3
3.8	SOS DP	4
4	Flow / Matching	4
4.1	Dinic	4
4.2	MCMF	4
4.3	KM	4
4.4	Hopcroft-Karp	5
4.5	Blossom	5
4.6	Cover / Independent Set	6
4.7	Hungarian Algorithm	6
5	Graph	6
5.1	Heavy-Light Decomposition	6
5.2	Centroid Decomposition	7
5.3	Bellman-Ford + SPFA	7
5.4	BCC - AP	8
5.5	BCC - Bridge	8
5.6	SCC - Tarjan	9
5.7	SCC - Kosaraju	9
5.8	Eulerian Path - Undir	9
5.9	Eulerian Path - Dir	10
5.10	Hamilton Path	10
5.11	Kth Shortest Path	10
5.12	System of Difference Constraints	11
6	String	11
6.1	Aho Corasick	11
6.2	KMP	12
6.3	Z Value	12
6.4	Manacher	12
6.5	Suffix Array	12
6.6	Suffix Automaton	13
6.7	Minimum Rotation	13

6.8	Lyndon Factorization	13
6.9	Rolling Hash	13
6.10	Trie	14
7	Geometry	14
7.1	Basic Operations	14
7.2	Sort by Angle	14
7.3	Intersection	14
7.4	Polygon Area	15
7.5	Convex Hull	15
7.6	Point In Convex	15
7.7	Point Segment Distance	15
7.8	Point in Polygon	15
7.9	Minimum Euclidean Distance	15
7.10	Minkowski Sum	15
7.11	Lower Concave Hull	16
7.12	Pick's Theorem	16
7.13	Rotating SweepLine	16
7.14	Half Plane Intersection	16
7.15	Minimum Enclosing Circle	17
7.16	Union of Circles	17
7.17	Area Of Circle Polygon	17
7.18	3D Point	17
8	Number Theory	17
8.1	FFT	17
8.2	Pollard's rho	18
8.3	Miller Rabin	18
8.4	Fast Power	19
8.5	Extend GCD	19
8.6	Mu + Phi	19
8.7	Discrete Log	19
8.8	sqrt mod	19
8.9	Primitive Root	20
8.10	Other Formulas	20
8.11	Polynomial	20
9	Linear Algebra	21
9.1	Gaussian-Jordan Elimination	21
9.2	Determinant	21
10	Combinatorics	22
10.1	Catalan Number	22
10.2	Burnside's Lemma	22
11	Special Numbers	22
11.1	Fibonacci Series	22
11.2	Prime Numbers	22

2 Basic

2.1 Vimrc

```

set number relativenumber ai t_Co=256 tabstop=4
set mouse=a shiftwidth=4 encoding=utf8
set bs=2 ruler laststatus=2 cmdheight=2
set clipboard=unnamedplus showcmd autoread
set belloff=all
filetype indent on

inoremap ( ()<Esc>i
inoremap " "<Esc>i
inoremap [ ]<Esc>i
inoremap ' '<Esc>i
inoremap { {<CR><Esc>ko

nnoremap <tab> gt
nnoremap <S-tab> gT
inoremap <C-n> <Esc>;tabnew<CR>
nnoremap <C-n> :tabnew<CR>

inoremap <F9> <Esc>;w<CR>:!~/runcpp.sh %:p:t %:p:h<CR>
nnoremap <F9> :w<CR>:!~/runcpp.sh %:p:t %:p:h<CR>

syntax on
colorscheme desert
set filetype=cpp
set background=dark
hi Normal ctermfg=white ctermbg=black

```

2.2 Runcpp.sh

```

g++ gen.cpp -o gen.out
g++ brute.cpp -o ac.out
g++ E.cpp -o wa.out
for ((i=0;;i++))
do
    echo "$i"
    ./gen.out > in.txt
    ./ac.out < in.txt > ac.txt
    ./wa.out < in.txt > wa.txt
    diff ac.txt wa.txt || break
done

```

2.3 PBDS

```

#include <bits/extc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

// map
tree<int, int, less<>, rb_tree_tag,
    tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// set
tree<int, null_type, less<>, rb_tree_tag,
    tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// hash table
gp_hash_table<int, int> ht;
ht.find(element);
ht.insert({key, value});
ht.erase(element);

// priority queue
__gnu_pbds::priority_queue<int, less<int>> big_q;
// Big First
__gnu_pbds::priority_queue<int, greater<int>> small_q;
// Small First
q1.join(q2); // join

```

2.4 Random

```

mt19937 gen(chrono::steady_clock::now().
    time_since_epoch().count());

```

1 Reminder

1.1 Bug List

- 沒開 long long
- 陣列戳出界／開不夠大／開太大本地 compile 噴怪 error
- 傳之前先確定選對檔案
- 寫好的函式忘記呼叫
- 變數打錯
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 i > 0
- std::sort 比較運算子寫成 < 或是讓 = 的情況為 true
- 漏 case / 分 case 要好好想
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr

1.2 OwO

- 可以構造複雜點的測資幫助思考
- 真的卡太久請跳題
- Enjoy The Contest!

```

2 uniform_int_distribution<int> dis(1, 100);
3 cout << dis(gen) << endl;
4 shuffle(v.begin(), v.end(), gen);

```

2.5 pragma

```

1 #pragma GCC optimize("O3,unroll-loops")
2 #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
3 #pragma GCC optimize("trapv")

```

2.6 set map pq cmp

```

1 struct edge
2 {
3     int a, b, w;
4     friend istream& operator>>(istream &in, edge &x)
5     { in >> x.a >> x.b >> x.w; }
6     friend ostream& operator<<(ostream &out, const edge
7     &x)
8     { out << "(" << x.a << "," << x.b << "," << x.w
9     << ")"; return out; }
10 };
11 struct cmp
12 {
13     bool operator()(const edge &x, const edge &y)
14     const { return x.w < y.w; } };
15 set<edge, cmp> st; //遞增
16 map<edge, long long, cmp> mp; //遞增
17 priority_queue<edge, vector<edge>, cmp> pq; //遞減

```

3 Data Structure

3.1 BIT

```

1 struct BIT {
2     int n;
3     long long bit[N];
4
5     void init(int x, vector<long long> &a) {
6         n = x;
7         for (int i = 1, j; i <= n; i++) {
8             bit[i] += a[i - 1], j = i + (i & -i);
9             if (j <= n) bit[j] += bit[i];
10        }
11    }
12
13    void update(int x, long long dif) {
14        while (x <= n) bit[x] += dif, x += x & -x;
15    }
16
17    long long query(int l, int r) {
18        if (l != 1) return query(1, r) - query(1, l - 1);
19
20        long long ret = 0;
21        while (l <= r) ret += bit[r], r -= r & -r;
22        return ret;
23    }
24 } bm;

```

3.2 Treap

```

1 mt19937 rng(random_device{}());
2 struct Treap {
3     Treap *l, *r;
4     int val, num, pri;
5     Treap(int k) {
6         l = r = NULL;
7         val = k;
8         num = 1;
9         pri = rng();
10    }
11 };
12 int siz(Treap *now) { return now ? now->num : 0; }
13 void pull(Treap *&now) {
14     now->num = siz(now->l) + siz(now->r) + 1;
15 }
16 Treap *merge(Treap *a, Treap *b) {
17     if (!a || !b)

```

```

18     return a ? a : b;
19     else if (a->pri > b->pri) {
20         a->r = merge(a->r, b);
21         pull(a);
22         return a;
23     } else {
24         b->l = merge(a, b->l);
25         pull(b);
26         return b;
27     }
28 }
29 void split_size(Treap *rt, Treap *&a, Treap *&b, int
30 val) {
31     if (!rt) {
32         a = b = NULL;
33         return;
34     }
35     if (siz(rt->l) + 1 > val) {
36         b = rt;
37         split_size(rt->l, a, b->l, val);
38         pull(b);
39     } else {
40         a = rt;
41         split_size(rt->r, a->r, b, val - siz(a->l) - 1);
42         pull(a);
43     }
44 }
45 void split_val(Treap *rt, Treap *&a, Treap *&b, int val)
46 {
47     if (!rt) {
48         a = b = NULL;
49         return;
50     }
51     if (rt->val <= val) {
52         a = rt;
53         split_val(rt->r, a->r, b, val);
54         pull(a);
55     } else {
56         b = rt;
57         split_val(rt->l, a, b->l, val);
58         pull(b);
59     }
60 }
61 void treap_dfs(Treap *now) {
62     if (!now) return;
63     treap_dfs(now->l);
64     cout << now->val << " ";
65     treap_dfs(now->r);
66 }

```

3.3 Persistent Treap

```

1 struct node {
2     node *l, *r;
3     char c;
4     int v, sz;
5     node(char x = '$') : c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? a : b;
18     if (a->v < b->v) {
19         node* ret = new (ptr++) node(a);
20         ret->r = merge(ret->r, b), ret->pull();
21         return ret;
22     } else {
23         node* ret = new (ptr++) node(b);
24         ret->l = merge(a, ret->l), ret->pull();
25         return ret;
26     }
27 }
28 P<node*> split(node* p, int k) {
29     if (!p) return {nullptr, nullptr};

```

```

30     if (k >= size(p->l) + 1) {
31         auto [a, b] = split(p->r, k - size(p->l) - 1);
32         node* ret = new (ptr++) node(p);
33         ret->r = a, ret->pull();
34         return {ret, b};
35     } else {
36         auto [a, b] = split(p->l, k);
37         node* ret = new (ptr++) node(p);
38         ret->l = b, ret->pull();
39         return {a, ret};
40     }
41 }

```

3.4 Li Chao Tree

```

1 constexpr int maxn = 5e4 + 5;
2 struct line {
3     ld a, b;
4     ld operator()(ld x) { return a * x + b; }
5 } arr[(maxn + 1) << 2];
6 bool operator<(line a, line b) { return a.a < b.a; }
7 #define m ((l + r) >> 1)
8 void insert(line x, int i = 1, int l = 0, int r = maxn) {
9     {
10         if (r - l == 1) {
11             if (x(l) > arr[i](l))
12                 arr[i] = x;
13             return;
14         }
15         line a = max(arr[i], x), b = min(arr[i], x);
16         if (a(m) > b(m))
17             arr[i] = a, insert(b, i << 1, l, m);
18         else
19             arr[i] = b, insert(a, i << 1 | 1, m, r);
20     }
21     ld query(int x, int i = 1, int l = 0, int r = maxn) {
22         if (x < l || r <= x) return -numeric_limits<ld>::
23             max();
24         if (r - l == 1) return arr[i](x);
25         return max({arr[i](x), query(x, i << 1, l, m),
26             query(x, i << 1 | 1, m, r)});
27     }
28 #undef m

```

3.5 Sparse Table

```

1 const int lgmx = 19;
2
3 int n, q;
4 int spt[lgmx][maxn];
5
6 void build() {
7     FOR(k, 1, lgmx, 1) {
8         for (int i = 0; i + (1 << k) - 1 < n; i++) {
9             spt[k][i] = min(spt[k - 1][i], spt[k - 1][i +
10                 (1 << (k - 1))]);
11         }
12     }
13 }
14
15 int query(int l, int r) {
16     int ln = len(l, r);
17     int lg = __lg(ln);
18     return min(spt[lg][l], spt[lg][r - (1 << lg) + 1]);
19 }

```

3.6 Time Segment Tree

```

1 constexpr int maxn = 1e5 + 5;
2 V<P<int>> arr[(maxn + 1) << 2];
3 V<int> dsu, sz;
4 V<tuple<int, int, int>> his;
5 int cnt, q;
6 int find(int x) {
7     return x == dsu[x] ? x : find(dsu[x]);
8 };
9 inline bool merge(int x, int y) {
10     int a = find(x), b = find(y);
11     if (a == b) return false;
12     if (sz[a] > sz[b]) swap(a, b);
13     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
14         sz[a];

```

```

14     return true;
15 };
16 inline void undo() {
17     auto [a, b, s] = his.back();
18     his.pop_back();
19     dsu[a] = a, sz[b] = s;
20 }
21 #define m ((l + r) >> 1)
22 void insert(int ql, int qr, P<int> x, int i = 1, int l
23     = 0, int r = q) {
24     // debug(ql, qr, x); return;
25     if (qr <= l || r <= ql) return;
26     if (ql <= l && r <= qr) {
27         arr[i].push_back(x);
28         return;
29     }
30     if (qr <= m)
31         insert(ql, qr, x, i << 1, l, m);
32     else if (m <= ql)
33         insert(ql, qr, x, i << 1 | 1, m, r);
34     else {
35         insert(ql, qr, x, i << 1, l, m);
36         insert(ql, qr, x, i << 1 | 1, m, r);
37     }
38 }
39 void traversal(V<int>& ans, int i = 1, int l = 0, int r
40     = q) {
41     int opcnt = 0;
42     // debug(i, l, r);
43     for (auto [a, b] : arr[i])
44         if (merge(a, b))
45             opcnt++, cnt--;
46     if (r - l == 1)
47         ans[l] = cnt;
48     else {
49         traversal(ans, i << 1, l, m);
50         traversal(ans, i << 1 | 1, m, r);
51     }
52     while (opcnt--)
53         undo(), cnt++;
54     arr[i].clear();
55 }
56 #undef m
57 inline void solve() {
58     int n, m;
59     cin >> n >> m >> q, q++;
60     dsu.resize(cnt = n), sz.assign(n, 1);
61     iota(dsu.begin(), dsu.end(), 0);
62     // a, b, time, operation
63     unordered_map<ll, V<int>> s;
64     for (int i = 0; i < m; i++) {
65         int a, b;
66         cin >> a >> b;
67         if (a > b) swap(a, b);
68         s[((ll)a << 32) | b].emplace_back(0);
69     }
70     for (int i = 1; i < q; i++) {
71         int op, a, b;
72         cin >> op >> a >> b;
73         if (a > b) swap(a, b);
74         switch (op) {
75             case 1:
76                 s[((ll)a << 32) | b].push_back(i);
77                 break;
78             case 2:
79                 auto tmp = s[((ll)a << 32) | b].back();
80                 s[((ll)a << 32) | b].pop_back();
81                 insert(tmp, i, P<int>{a, b});
82         }
83     }
84     for (auto [p, v] : s) {
85         int a = p >> 32, b = p & -1;
86         while (v.size()) {
87             insert(v.back(), q, P<int>{a, b});
88             v.pop_back();
89         }
90     }
91     V<int> ans(q);
92     traversal(ans);
93     for (auto i : ans)
94         cout << i << ' ';
95     cout << endl;

```

94 | }

3.7 Dynamic Median

```

1 struct Dynamic_Median {
2     multiset<long long> lo, hi;
3     long long slo = 0, shi = 0;
4     void rebalance() {
5         // keep sz(lo) >= sz(hi) and sz(lo) - sz(hi) <= 1
6         while((int)lo.size() > (int)hi.size() + 1) {
7             auto it = prev(lo.end());
8             long long x = *it;
9             lo.erase(it); slo -= x;
10            hi.insert(x); shi += x;
11        }
12        while((int)lo.size() < (int)hi.size()) {
13            auto it = hi.begin();
14            long long x = *it;
15            hi.erase(it); shi -= x;
16            lo.insert(x); slo += x;
17        }
18    }
19    void add(long long x) {
20        if(lo.empty() || x <= *prev(lo.end())) {
21            lo.insert(x); slo += x;
22        }
23        else {
24            hi.insert(x); shi += x;
25        }
26        rebalance();
27    }
28    void remove_one(long long x) {
29        if(!lo.empty() && x <= *prev(lo.end())) {
30            auto it = lo.find(x);
31            if(it != lo.end()) {
32                lo.erase(it); slo -= x;
33            }
34            else {
35                auto it2 = hi.find(x);
36                hi.erase(it2); shi -= x;
37            }
38        }
39        else {
40            auto it = hi.find(x);
41            if(it != hi.end()) {
42                hi.erase(it); shi -= x;
43            }
44            else {
45                auto it2 = lo.find(x);
46                lo.erase(it2); slo -= x;
47            }
48        }
49        rebalance();
50    }
51 };

```

3.8 SOS DP

```

1 for (int mask = 0; mask < (1 << n); mask++) {
2     for (int submask = mask; submask != 0; submask = (
3         submask - 1) & mask) {
4         int subset = mask ^ submask;
5     }
6 }

```

4 Flow / Matching

4.1 Dinic

```

1 using namespace std;
2 const int N = 2000 + 5;
3 int n, m, s, t, level[N], iter[N];
4 struct edge {int to, cap, rev;};
5 vector<edge> path[N];
6 void add(int a, int b, int c) {
7     path[a].pb({b, c, sz(path[b])});
8     path[b].pb({a, 0, sz(path[a]) - 1});
9 }
10 void bfs() {
11     memset(level, -1, sizeof(level));
12     level[s] = 0;

```

```

13     queue<int> q;
14     q.push(s);
15     while (q.size()) {
16         int now = q.front(); q.pop();
17         for (edge e : path[now]) if (e.cap > 0 && level
18             [e.to] == -1) {
19             level[e.to] = level[now] + 1;
20             q.push(e.to);
21         }
22     }
23     int dfs(int now, int flow) {
24         if (now == t) return flow;
25         for (int &i = iter[now]; i < sz(path[now]); i++) {
26             edge &e = path[now][i];
27             if (e.cap > 0 && level[e.to] == level[now] + 1) {
28                 int res = dfs(e.to, min(flow, e.cap));
29                 if (res > 0) {
30                     e.cap -= res;
31                     path[e.to][e.rev].cap += res;
32                     return res;
33                 }
34             }
35         }
36         return 0;
37     }
38     int dinic() {
39         int res = 0;
40         while (true) {
41             bfs();
42             if (level[t] == -1) break;
43             memset(iter, 0, sizeof(iter));
44             int now = 0;
45             while ((now = dfs(s, INF)) > 0) res += now;
46         }
47         return res;
48     }

```

4.2 MCMF

```

1 struct MCMF {
2     int n, s, t, par[N + 5], p_i[N + 5], dis[N + 5],
3         vis[N + 5];
4     struct edge {
5         int to, cap, rev, cost;
6     };
7     vector<edge> path[N];
8     void init(int _n, int _s, int _t) {
9         n = _n, s = _s, t = _t;
10        FOR(i, 0, 2 * n + 5)
11            par[i] = p_i[i] = vis[i] = 0;
12    }
13    void add(int a, int b, int c, int d) {
14        path[a].pb({b, c, sz(path[b]), d});
15        path[b].pb({a, 0, sz(path[a]) - 1, -d});
16    }
17    void spfa() {
18        FOR(i, 0, n * 2 + 5)
19            dis[i] = INF,
20            vis[i] = 0;
21        dis[s] = 0;
22        queue<int> q;
23        q.push(s);
24        while (!q.empty()) {
25            int now = q.front();
26            q.pop();
27            vis[now] = 0;
28            for (int i = 0; i < sz(path[now]); i++) {
29                edge e = path[now][i];
30                if (e.cap > 0 && dis[e.to] > dis[now] +
31                    e.cost) {
32                    dis[e.to] = dis[now] + e.cost;
33                    par[e.to] = now;
34                    p_i[e.to] = i;
35                    if (vis[e.to] == 0) {
36                        vis[e.to] = 1;
37                        q.push(e.to);
38                    }
39                }
40            }
41        }
42    }

```

```

40     }
41     pii flow() {
42         int flow = 0, cost = 0;
43         while (true) {
44             spfa();
45             if (dis[t] == INF)
46                 break;
47             int mn = INF;
48             for (int i = t; i != s; i = par[i])
49                 mn = min(mn, path[par[i]][p_i[i]].cap);
50             flow += mn;
51             cost += dis[t] * mn;
52             for (int i = t; i != s; i = par[i]) {
53                 edge &now = path[par[i]][p_i[i]];
54                 now.cap -= mn;
55                 path[i][now.rev].cap += mn;
56             }
57         }
58         return mp(flow, cost);
59     }
60 };

```

4.3 KM

```

1 struct KM {
2     int n, mx[1005], my[1005], pa[1005];
3     int g[1005][1005], lx[1005], ly[1005], sy[1005];
4     bool vx[1005], vy[1005];
5     void init(int _n) {
6         n = _n;
7         FOR(i, 1, n + 1)
8             fill(g[i], g[i] + 1 + n, 0);
9     }
10    void add(int a, int b, int c) { g[a][b] = c; }
11    void augment(int y) {
12        for (int x, z; y; y = z)
13            x = pa[y], z = mx[x], my[y] = x, mx[x] = y;
14    }
15    void bfs(int st) {
16        FOR(i, 1, n + 1)
17            sy[i] = INF,
18            vx[i] = vy[i] = 0;
19        queue<int> q;
20        q.push(st);
21        for (;;) {
22            while (!q.empty()) {
23                int x = q.front();
24                q.pop();
25                vx[x] = 1;
26                FOR(y, 1, n + 1)
27                    if (!vy[y]) {
28                        int t = lx[x] + ly[y] - g[x][y];
29                        if (t == 0) {
30                            pa[y] = x;
31                            if (!my[y]) {
32                                augment(y);
33                                return;
34                            }
35                            vy[y] = 1, q.push(my[y]);
36                        } else if (sy[y] > t)
37                            pa[y] = x, sy[y] = t;
38                    }
39            }
40            int cut = INF;
41            FOR(y, 1, n + 1)
42                if (!vy[y] && cut > sy[y]) cut = sy[y];
43            FOR(j, 1, n + 1) {
44                if (vx[j]) lx[j] -= cut;
45                if (vy[j])
46                    ly[j] += cut;
47                else
48                    sy[j] -= cut;
49            }
50            FOR(y, 1, n + 1) {
51                if (!vy[y] && sy[y] == 0) {
52                    if (!my[y]) {
53                        augment(y);
54                        return;
55                    }
56                    vy[y] = 1;
57                    q.push(my[y]);
58                }
59            }
60        }

```

```

59     }
60     }
61 }
62 int solve() {
63     fill(mx, mx + n + 1, 0);
64     fill(my, my + n + 1, 0);
65     fill(ly, ly + n + 1, 0);
66     fill(lx, lx + n + 1, 0);
67     FOR(x, 1, n + 1)
68         FOR(y, 1, n + 1)
69             lx[x] = max(lx[x], g[x][y]);
70     FOR(x, 1, n + 1)
71         bfs(x);
72     int ans = 0;
73     FOR(y, 1, n + 1)
74         ans += g[my[y]][y];
75     return ans;
76 }
77 };

```

4.4 Hopcroft-Karp

```

1 struct HopcroftKarp {
2     // id: X = [1, nx], Y = [nx+1, nx+ny]
3     int n, nx, ny, m, MXCNT;
4     vector<vector<int>> g;
5     vector<int> mx, my, dis, vis;
6     void init(int nnx, int nny, int mm) {
7         nx = nnx, ny = nny, m = mm;
8         n = nx + ny + 1;
9         g.clear();
10        g.resize(n);
11    }
12    void add(int x, int y) {
13        g[x].emplace_back(y);
14        g[y].emplace_back(x);
15    }
16    bool dfs(int x) {
17        vis[x] = true;
18        Each(y, g[x]) {
19            int px = my[y];
20            if (px == -1 ||
21                (dis[px] == dis[x] + 1 &&
22                 !vis[px] && dfs(px))) {
23                mx[x] = y;
24                my[y] = x;
25                return true;
26            }
27        }
28        return false;
29    }
30    void get() {
31        mx.clear();
32        mx.resize(n, -1);
33        my.clear();
34        my.resize(n, -1);
35    }
36    while (true) {
37        queue<int> q;
38        dis.clear();
39        dis.resize(n, -1);
40        for (int x = 1; x <= nx; x++) {
41            if (mx[x] == -1) {
42                dis[x] = 0;
43                q.push(x);
44            }
45        }
46        while (!q.empty()) {
47            int x = q.front();
48            q.pop();
49            Each(y, g[x]) {
50                if (my[y] != -1 && dis[my[y]] ==
51                    -1) {
52                    dis[my[y]] = dis[x] + 1;
53                    q.push(my[y]);
54                }
55            }
56        }
57        bool brk = true;
58        vis.clear();
59        vis.resize(n, 0);

```

```

60     for (int x = 1; x <= nx; x++)
61         if (mx[x] == -1 && dfs(x))
62             brk = false;
63
64     if (brk) break;
65 }
66 MXCNT = 0;
67 for (int x = 1; x <= nx; x++)
68     if (mx[x] != -1) MXCNT++;
69 }
70 } hk;

```

4.5 Blossom

```

1  const int N=5e2+10;
2  struct Graph{
3      int to[N],bro[N],head[N],e;
4      int lnk[N],vis[N],stp,n;
5      void init(int _n){
6          stp=0;e=1;n=_n;
7          FOR(i,0,n+1)head[i]=lnk[i]=vis[i]=0;
8      }
9      void add(int u,int v){
10         to[e]=v,bro[e]=head[u],head[u]=e++;
11         to[e]=u,bro[e]=head[v],head[v]=e++;
12     }
13     bool dfs(int x){
14         vis[x]=stp;
15         for(int i=head[x];i;i=bro[i])
16         {
17             int v=to[i];
18             if(!lnk[v])
19             {
20                 lnk[x]=v;lnk[v]=x;
21                 return true;
22             }
23             else if(vis[lnk[v]]<stp)
24             {
25                 int w=lnk[v];
26                 lnk[x]=v,lnk[v]=x,lnk[w]=0;
27                 if(dfs(w))return true;
28                 lnk[w]=v,lnk[v]=w,lnk[x]=0;
29             }
30         }
31         return false;
32     }
33     int solve(){
34         int ans=0;
35         FOR(i,1,n+1){
36             if(!lnk[i]){
37                 stp++;
38                 ans+=dfs(i);
39             }
40         }
41         return ans;
42     }
43     void print_matching(){
44         FOR(i,1,n+1)
45             if(i<graph.lnk[i])
46                 cout<<i<<" "<<graph.lnk[i]<<endl;
47     }
48 };

```

4.6 Cover / Independent Set

```

1  V(E) Cover: choose some V(E) to cover all E(V)
2  V(E) Independ: set of V(E) not adj to each other
3
4  M = Max Matching
5  Cv = Min V Cover
6  Ce = Min E Cover
7  Iv = Max V Ind
8  Ie = Max E Ind (equiv to M)
9
10 M = Cv (Konig Theorem)
11 Iv = V \ Cv
12 Ce = V - M
13
14 Construct Cv:
15 1. Run Dinic
16 2. Find s-t min cut
17 3. Cv = {X in T} + {Y in S}

```

4.7 Hungarian Algorithm

```

1  const int N = 2e3;
2  int match[N];
3  bool vis[N];
4  int n;
5  vector<int> ed[N];
6  int match_cnt;
7  bool dfs(int u) {
8      vis[u] = 1;
9      for(int i : ed[u]) {
10         if(match[i] == 0 || !vis[match[i]] && dfs(match[i])) {
11             match[i] = u;
12             return true;
13         }
14     }
15     return false;
16 }
17 void hungary() {
18     memset(match, 0, sizeof(match));
19     match_cnt = 0;
20     for(int i = 1; i <= n; i++) {
21         memset(vis, 0, sizeof(vis));
22         if(dfs(i)) match_cnt++;
23     }
24 }

```

5 Graph

5.1 Heavy-Light Decomposition

```

1  const int N = 2e5 + 5;
2  int n, dfn[N], son[N], top[N], num[N], dep[N], p[N];
3  vector<int> path[N];
4  struct node {
5      int mx, sum;
6  } seg[N << 2];
7  void update(int x, int l, int r, int qx, int val) {
8      if (l == r) {
9          seg[x].mx = seg[x].sum = val;
10         return;
11     }
12     int mid = (l + r) >> 1;
13     if (qx <= mid)update(x << 1, l, mid, qx, val);
14     else update(x << 1 | 1, mid + 1, r, qx, val);
15     seg[x].mx = max(seg[x << 1].mx, seg[x << 1 | 1].mx);
16     seg[x].sum = seg[x << 1].sum + seg[x << 1 | 1].sum;
17 }
18 int big(int x, int l, int r, int ql, int qr) {
19     if (ql <= l && r <= qr) return seg[x].mx;
20     int mid = (l + r) >> 1;
21     int res = -INF;
22     if (ql <= mid) res = max(res, big(x << 1, l, mid, ql, qr));
23     if (mid < qr) res = max(res, big(x << 1 | 1, mid + 1, r, ql, qr));
24     return res;
25 }
26 int ask(int x, int l, int r, int ql, int qr) {
27     if (ql <= l && r <= qr) return seg[x].sum;
28     int mid = (l + r) >> 1;
29     int res = 0;
30     if (ql <= mid) res += ask(x << 1, l, mid, ql, qr);
31     if (mid < qr) res += ask(x << 1 | 1, mid + 1, r, ql, qr);
32     return res;
33 }
34 void dfs1(int now) {
35     son[now] = -1;
36     num[now] = 1;
37     for (auto i : path[now]) {
38         if (!dep[i]) {
39             dep[i] = dep[now] + 1;
40             p[i] = now;
41             dfs1(i);
42             num[now] += num[i];
43             if (son[now] == -1 || num[i] > num[son[now]]) son[now] = i;
44         }
45     }
46 }

```



```

45     }
46 }
47 int cnt;
48 void dfs2(int now, int t) {
49     top[now] = t;
50     cnt++;
51     dfn[now] = cnt;
52     if (son[now] == -1) return;
53     dfs2(son[now], t);
54     for (auto i : path[now])
55         if (i != p[now] && i != son[now]) dfs2(i, i);
56 }
57 int path_big(int x, int y) {
58     int res = -INF;
59     while (top[x] != top[y]) {
60         if (dep[top[x]] < dep[top[y]]) swap(x, y);
61         res = max(res, big(1, 1, n, dfn[top[x]], dfn[x]));
62         x = p[top[x]];
63     }
64     if (dfn[x] > dfn[y]) swap(x, y);
65     res = max(res, big(1, 1, n, dfn[x], dfn[y]));
66     return res;
67 }
68 int path_sum(int x, int y) {
69     int res = 0;
70     while (top[x] != top[y]) {
71         if (dep[top[x]] < dep[top[y]]) swap(x, y);
72         res += ask(1, 1, n, dfn[top[x]], dfn[x]);
73         x = p[top[x]];
74     }
75     if (dfn[x] > dfn[y]) swap(x, y);
76     res += ask(1, 1, n, dfn[x], dfn[y]);
77     return res;
78 }
79 void buildTree() {
80     FOR(i, 0, n - 1) {
81         int a, b;
82         cin >> a >> b;
83         path[a].pb(b);
84         path[b].pb(a);
85     }
86 }
87 void buildHLD(int root) {
88     dep[root] = 1;
89     dfs1(root);
90     dfs2(root, root);
91     FOR(i, 1, n + 1) {
92         int now;
93         cin >> now;
94         update(1, 1, n, dfn[i], now);
95     }
96 }

```

5.2 Centroid Decomposition

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int N = 1e5 + 5;
4 vector<int> a[N];
5 int sz[N], lv[N];
6 bool used[N];
7 int f_sz(int x, int p) {
8     sz[x] = 1;
9     for (int i : a[x])
10         if (i != p && !used[i])
11             sz[x] += f_sz(i, x);
12     return sz[x];
13 }
14 int f_cen(int x, int p, int total) {
15     for (int i : a[x]) {
16         if (i != p && !used[i] && 2 * sz[i] > total)
17             return f_cen(i, x, total);
18     }
19     return x;
20 }
21 void cd(int x, int p) {
22     int total = f_sz(x, p);
23     int cen = f_cen(x, p, total);
24     lv[cen] = lv[p] + 1;
25     used[cen] = 1;

```

```

26 // cout << "cd: " << x << " " << p << " " << cen <<
27 // "\n";
28 for (int i : a[cen]) {
29     if (!used[i])
30         cd(i, cen);
31 }
32 int main() {
33     ios_base::sync_with_stdio(0);
34     cin.tie(0);
35     int n;
36     cin >> n;
37     for (int i = 0, x, y; i < n - 1; i++) {
38         cin >> x >> y;
39         a[x].push_back(y);
40         a[y].push_back(x);
41     }
42     cd(1, 0);
43     for (int i = 1; i <= n; i++)
44         cout << (char)('A' + lv[i] - 1) << " ";
45     cout << "\n";
46 }

```

5.3 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll> > > g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n + 1, LINF);
15     negCycle.assign(n + 1, false);
16     rlx.assign(n + 1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n + 1, false);
19     pa.assign(n + 1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s);
24         inq[s] = true;
25     }
26
27     while (!q.empty()) {
28         int u = q.front();
29         q.pop();
30         inq[u] = false;
31         if (rlx[u] >= n) {
32             negCycle[u] = true;
33         } else
34             for (auto& e : g[u]) {
35                 int v = e.first;
36                 ll w = e.second;
37                 if (dis[v] > dis[u] + w) {
38                     dis[v] = dis[u] + w;
39                     rlx[v] = rlx[u] + 1;
40                     pa[v] = u;
41                     if (!inq[v]) {
42                         q.push(v);
43                         inq[v] = true;
44                     }
45                 }
46             }
47     }
48 }
49
50 // Bellman-Ford
51 queue<int> q;
52 vector<int> pa;
53 void BellmanFord(vector<int>& src) {
54     dis.assign(n + 1, LINF);
55     negCycle.assign(n + 1, false);
56     pa.assign(n + 1, -1);
57 }

```

```

58     for (auto& s : src) dis[s] = 0;
59
60     for (int rlx = 1; rlx <= n; rlx++) {
61         for (int u = 1; u <= n; u++) {
62             if (dis[u] == LINF) continue; // Important
63             !!
64             for (auto& e : g[u]) {
65                 int v = e.first;
66                 ll w = e.second;
67                 if (dis[v] > dis[u] + w) {
68                     dis[v] = dis[u] + w;
69                     pa[v] = u;
70                     if (rlx == n) negCycle[v] = true;
71                 }
72             }
73         }
74     }
75
76     // Negative Cycle Detection
77     void NegCycleDetect() {
78         /* No Neg Cycle: NO
79         Exist Any Neg Cycle:
80         YES
81         v0 v1 v2 ... vk v0 */
82
83         vector<int> src;
84         for (int i = 1; i <= n; i++)
85             src.emplace_back(i);
86
87         SPFA(src);
88         // BellmanFord(src);
89
90         int ptr = -1;
91         for (int i = 1; i <= n; i++)
92             if (negCycle[i]) {
93                 ptr = i;
94                 break;
95             }
96
97         if (ptr == -1) {
98             return cout << "NO" << endl, void();
99         }
100
101         cout << "YES\n";
102         vector<int> ans;
103         vector<bool> vis(n + 1, false);
104
105         while (true) {
106             ans.emplace_back(ptr);
107             if (vis[ptr]) break;
108             vis[ptr] = true;
109             ptr = pa[ptr];
110         }
111         reverse(ans.begin(), ans.end());
112
113         vis.assign(n + 1, false);
114         for (auto& x : ans) {
115             cout << x << ' ';
116             if (vis[x]) break;
117             vis[x] = true;
118         }
119         cout << endl;
120     }
121
122     // Distance Calculation
123     void calcDis(int s) {
124         vector<int> src;
125         src.emplace_back(s);
126         SPFA(src);
127         // BellmanFord(src);
128
129         while (!q.empty()) q.pop();
130         for (int i = 1; i <= n; i++)
131             if (negCycle[i]) q.push(i);
132
133         while (!q.empty()) {
134             int u = q.front();
135             q.pop();
136             for (auto& e : g[u]) {
137                 int v = e.first;
138                 if (!negCycle[v]) {

```

```

139                     q.push(v);
140                     negCycle[v] = true;
141                 }
142             }
143         }
144     }

```

5.4 BCC - AP

```

1  int n, m;
2  int low[maxn], dfn[maxn], instp;
3  vector<int> E, g[maxn];
4  bitset<maxn> isap;
5  bitset<maxm> vis;
6  stack<int> stk;
7  int bccnt;
8  vector<int> bcc[maxn];
9  inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e] ^ u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++;
30             dfs(v);
31             low[u] = min(low[u], low[v]);
32             if (!rt && low[v] >= dfn[u]) {
33                 // bcc found: u is ap
34                 isap[u] = true;
35                 popout(u);
36             }
37         } else {
38             // back edge
39             low[u] = min(low[u], dfn[v]);
40         }
41     }
42     // special case: root
43     if (rt) {
44         if (kid > 1) isap[u] = true;
45         popout(u);
46     }
47 }
48 void init() {
49     cin >> n >> m;
50     fill(low, low + maxn, INF);
51     REP(i, m) {
52         int u, v;
53         cin >> u >> v;
54         g[u].emplace_back(i);
55         g[v].emplace_back(i);
56         E.emplace_back(u ^ v);
57     }
58 }
59 void solve() {
60     FOR(i, 1, n + 1, 1) {
61         if (!dfn[i]) dfs(i, true);
62     }
63     vector<int> ans;
64     int cnt = 0;
65     FOR(i, 1, n + 1, 1) {
66         if (isap[i]) cnt++, ans.emplace_back(i);
67     }
68     cout << cnt << endl;
69     Each(i, ans) cout << i << ' ';
70     cout << endl;
71 }

```


5.5 BCC - Bridge

```

1 int n, m;
2 vector<int> g[maxn], E;
3 int low[maxn], dfn[maxn], instp;
4 int bccnt, bccid[maxn];
5 stack<int> stk;
6 bitset<maxn> vis, isbrg;
7 void init() {
8     cin >> n >> m;
9     REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u ^ v);
13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low + maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e] ^ u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         } else {
40             // tree edge
41             dfs(v);
42             low[u] = min(low[u], low[v]);
43             if (low[v] == dfn[v]) {
44                 isbrg[e] = true;
45                 popout(u);
46             }
47         }
48     }
49 }
50 void solve() {
51     FOR(i, 1, n + 1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n + 1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e] ^ u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

5.6 SCC - Tarjan

```

1 // 2-SAT
2 vector<int> E, g[maxn]; // 1~n, n+1~2n
3 int low[maxn], in[maxn], instp;
4 int sccnt, sccid[maxn];
5 stack<int> stk;
6 bitset<maxn> ins, vis;
7 int n, m;
8 void init() {
9     cin >> m >> n;
10    E.clear();
11    fill(g, g + maxn, vector<int>());

```

```

12    fill(low, low + maxn, INF);
13    memset(in, 0, sizeof(in));
14    instp = 1;
15    sccnt = 0;
16    memset(sccid, 0, sizeof(sccid));
17    ins.reset();
18    vis.reset();
19 }
20 inline int no(int u) {
21     return (u > n ? u - n : u + n);
22 }
23 int ecnt = 0;
24 inline void clause(int u, int v) {
25     E.eb(no(u) ^ v);
26     g[no(u)].eb(ecnt++);
27     E.eb(no(v) ^ u);
28     g[no(v)].eb(ecnt++);
29 }
30 void dfs(int u) {
31     in[u] = instp++;
32     low[u] = in[u];
33     stk.push(u);
34     ins[u] = true;
35
36     Each(e, g[u]) {
37         if (vis[e]) continue;
38         vis[e] = true;
39
40         int v = E[e] ^ u;
41         if (ins[v])
42             low[u] = min(low[u], in[v]);
43         else if (!in[v]) {
44             dfs(v);
45             low[u] = min(low[u], low[v]);
46         }
47     }
48     if (low[u] == in[u]) {
49         sccnt++;
50         while (!stk.empty()) {
51             int v = stk.top();
52             stk.pop();
53             ins[v] = false;
54             sccid[v] = sccnt;
55             if (u == v) break;
56         }
57     }
58 }
59 int main() {
60     init();
61     REP(i, m) {
62         char su, sv;
63         int u, v;
64         cin >> su >> u >> sv >> v;
65         if (su == '-') u = no(u);
66         if (sv == '-') v = no(v);
67         clause(u, v);
68     }
69     FOR(i, 1, 2 * n + 1, 1) {
70         if (!in[i]) dfs(i);
71     }
72     FOR(u, 1, n + 1, 1) {
73         int du = no(u);
74         if (sccid[u] == sccid[du]) {
75             return cout << "IMPOSSIBLE\n", 0;
76         }
77     }
78     FOR(u, 1, n + 1, 1) {
79         int du = no(u);
80         cout << (sccid[u] < sccid[du] ? '+' : '-') << '
81         ' << endl;
82     }
83 }

```

5.7 SCC - Kosaraju

```

1 const int N = 1e5 + 10;
2 vector<int> ed[N], ed_b[N]; // 反邊
3 vector<int> SCC(N); // 最後SCC的分組
4 bitset<N> vis;
5 int SCC_cnt;
6 int n, m;

```

```

7 vector<int> pre; // 後序遍歷
8
9 void dfs(int x) {
10     vis[x] = 1;
11     for (int i : ed[x]) {
12         if (vis[i]) continue;
13         dfs(i);
14     }
15     pre.push_back(x);
16 }
17
18 void dfs2(int x) {
19     vis[x] = 1;
20     SCC_cnt;
21     for (int i : ed_b[x]) {
22         if (vis[i]) continue;
23         dfs2(i);
24     }
25 }
26
27 void kosaraju() {
28     for (int i = 1; i <= n; i++) {
29         if (!vis[i]) {
30             dfs(i);
31         }
32     }
33     SCC_cnt = 0;
34     vis = 0;
35     for (int i = n - 1; i >= 0; i--) {
36         if (!vis[pre[i]]) {
37             SCC_cnt++;
38             dfs2(pre[i]);
39         }
40     }
41 }

```

5.8 Eulerian Path - Undir

```

1 // from 1 to n
2 #define gg return cout << "IMPOSSIBLE\n", void();
3
4 int n, m;
5 vector<int> g[maxn];
6 bitset<maxn> inodd;
7
8 void init() {
9     cin >> n >> m;
10    inodd.reset();
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;
14        inodd[u] = inodd[u] ^ true;
15        inodd[v] = inodd[v] ^ true;
16        g[u].emplace_back(v);
17        g[v].emplace_back(u);
18    }
19 }
20 stack<int> stk;
21 void dfs(int u) {
22     while (!g[u].empty()) {
23         int v = g[u].back();
24         g[u].pop_back();
25         dfs(v);
26     }
27     stk.push(u);
28 }

```

5.9 Eulerian Path - Dir

```

1 // from node 1 to node n
2 #define gg return cout << "IMPOSSIBLE\n", 0;
3
4 int n, m;
5 vector<int> g[maxn];
6 stack<int> stk;
7 int in[maxn], out[maxn];
8
9 void init() {
10    cin >> n >> m;
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;

```

```

14        g[u].emplace_back(v);
15        out[u]++, in[v]++;
16    }
17    for (int i = 1; i <= n; i++) {
18        if (i == 1 && out[i] - in[i] != 1) gg;
19        if (i == n && in[i] - out[i] != 1) gg;
20        if (i != 1 && i != n && in[i] != out[i]) gg;
21    }
22 }
23 void dfs(int u) {
24     while (!g[u].empty()) {
25         int v = g[u].back();
26         g[u].pop_back();
27         dfs(v);
28     }
29     stk.push(u);
30 }
31 void solve() {
32     dfs(1) for (int i = 1; i <= n; i++) if ((int)g[i].
33         size()) gg;
34     while (!stk.empty()) {
35         int u = stk.top();
36         stk.pop();
37         cout << u << ' ';
38     }

```

5.10 Hamilton Path

```

1 // top down DP
2 // Be Aware Of Multiple Edges
3 int n, m;
4 ll dp[maxn][1<<maxn];
5 int adj[maxn][maxn];
6
7 void init() {
8     cin >> n >> m;
9     fill(dp[0], dp[maxn-1]+(1<<maxn), -1);
10 }
11
12 void DP(int i, int msk) {
13     if (dp[i][msk] != -1) return;
14     dp[i][msk] = 0;
15     REP(j, n) if (j != i && (msk & (1<<j)) && adj[j][i]) {
16         int sub = msk ^ (1<<i);
17         if (dp[j][sub] == -1) DP(j, sub);
18         dp[i][msk] += dp[j][sub] * adj[j][i];
19         if (dp[i][msk] >= MOD) dp[i][msk] %= MOD;
20     }
21 }
22
23 int main() {
24     WiWiHorz
25     init();
26
27     REP(i, m) {
28         int u, v;
29         cin >> u >> v;
30         if (u == v) continue;
31         adj[--u][--v]++;
32     }
33
34     dp[0][1] = 1;
35     FOR(i, 1, n, 1) {
36         dp[i][1] = 0;
37         dp[i][1|(1<<i)] = adj[0][i];
38     }
39     FOR(msk, 1, (1<<n), 1) {
40         if (msk == 1) continue;
41         dp[0][msk] = 0;
42     }
43
44     DP(n-1, (1<<n)-1);
45     cout << dp[n-1][(1<<n)-1] << endl;
46
47     return 0;
48 }

```

5.11 Kth Shortest Path

```

1 // time:  $O(|E| \lg |E| + |V| \lg |V| + K)$ 
2 // memory:  $O(|E| \lg |E| + |V|)$ 
3 struct KSP { // 1-base
4     struct nd {
5         int u, v;
6         ll d;
7         nd(int ui = 0, int vi = 0, ll di = INF) {
8             u = ui;
9             v = vi;
10            d = di;
11        }
12    };
13    struct heap {
14        nd* edge;
15        int dep;
16        heap* chd[4];
17    };
18    static int cmp(heap* a, heap* b) { return a->edge->
19        d > b->edge->d; }
20    struct node {
21        int v;
22        ll d;
23        heap* H;
24        nd* E;
25        node() {}
26        node(ll _d, int _v, nd* _E) {
27            d = _d;
28            v = _v;
29            E = _E;
30        }
31        node(heap* _H, ll _d) {
32            H = _H;
33            d = _d;
34        }
35        friend bool operator<(node a, node b) { return
36            a.d > b.d; }
37    };
38    int n, k, s, t, dst[N];
39    nd* nxt[N];
40    vector<nd*> g[N], rg[N];
41    heap *nullNd, *head[N];
42    void init(int _n, int _k, int _s, int _t) {
43        n = _n;
44        k = _k;
45        s = _s;
46        t = _t;
47        for (int i = 1; i <= n; i++) {
48            g[i].clear();
49            rg[i].clear();
50            nxt[i] = NULL;
51            head[i] = NULL;
52            dst[i] = -1;
53        }
54    }
55    void addEdge(int ui, int vi, ll di) {
56        nd* e = new nd(ui, vi, di);
57        g[ui].push_back(e);
58        rg[vi].push_back(e);
59    }
60    queue<int> dfsQ;
61    void dijkstra() {
62        while (dfsQ.size()) dfsQ.pop();
63        priority_queue<node> Q;
64        Q.push(node(0, t, NULL));
65        while (!Q.empty()) {
66            node p = Q.top();
67            Q.pop();
68            if (dst[p.v] != -1) continue;
69            dst[p.v] = p.d;
70            nxt[p.v] = p.E;
71            dfsQ.push(p.v);
72            for (auto e : rg[p.v]) Q.push(node(p.d + e
73                ->d, e->u, e));
74        }
75    }
76    heap* merge(heap* curNd, heap* newNd) {
77        if (curNd == nullNd) return newNd;
78        heap* root = new heap;
79        memcpy(root, curNd, sizeof(heap));
80        if (newNd->edge->d < curNd->edge->d) {
81            root->edge = newNd->edge;
82            root->chd[2] = newNd->chd[2];
83            root->chd[3] = newNd->chd[3];
84            newNd->edge = curNd->edge;
85            newNd->chd[2] = curNd->chd[2];
86            newNd->chd[3] = curNd->chd[3];
87        }
88        if (root->chd[0]->dep < root->chd[1]->dep)
89            root->chd[0] = merge(root->chd[0], newNd);
90        else
91            root->chd[1] = merge(root->chd[1], newNd);
92        root->dep = max(root->chd[0]->dep,
93            root->chd[1]->dep) +
94            1;
95        return root;
96    }
97    vector<heap*> V;
98    void build() {
99        nullNd = new heap;
100        nullNd->dep = 0;
101        nullNd->edge = new nd;
102        fill(nullNd->chd, nullNd->chd + 4, nullNd);
103        while (not dfsQ.empty()) {
104            int u = dfsQ.front();
105            dfsQ.pop();
106            if (!nxt[u])
107                head[u] = nullNd;
108            else
109                head[u] = head[nxt[u]->v];
110            V.clear();
111            for (auto& e : g[u]) {
112                int v = e->v;
113                if (dst[v] == -1) continue;
114                e->d += dst[v] - dst[u];
115                if (nxt[u] != e) {
116                    heap* p = new heap;
117                    fill(p->chd, p->chd + 4, nullNd);
118                    p->dep = 1;
119                    p->edge = e;
120                    V.push_back(p);
121                }
122            }
123            if (V.empty()) continue;
124            make_heap(V.begin(), V.end(), cmp);
125            #define L(X) ((X << 1) + 1)
126            #define R(X) ((X << 1) + 2)
127            for (size_t i = 0; i < V.size(); i++) {
128                if (L(i) < V.size())
129                    V[i]->chd[2] = V[L(i)];
130                else
131                    V[i]->chd[2] = nullNd;
132                if (R(i) < V.size())
133                    V[i]->chd[3] = V[R(i)];
134                else
135                    V[i]->chd[3] = nullNd;
136            }
137            head[u] = merge(head[u], V.front());
138        }
139    }
140    vector<ll> ans;
141    void first_K() {
142        ans.clear();
143        priority_queue<node> Q;
144        if (dst[s] == -1) return;
145        ans.push_back(dst[s]);
146        if (head[s] != nullNd)
147            Q.push(node(head[s], dst[s] + head[s]->edge
148                ->d));
149        for (int _ = 1; _ < k and not Q.empty(); _++) {
150            node p = Q.top();
151            Q.pop();
152            ans.push_back(p.d);
153            if (head[p.H->edge->v] != nullNd) {
154                q.H = head[p.H->edge->v];
155                q.d = p.d + q.H->edge->d;
156                Q.push(q);
157            }
158        }
159        for (int i = 0; i < 4; i++)
160            if (p.H->chd[i] != nullNd) {
161                q.H = p.H->chd[i];
162                q.d = p.d - p.H->edge->d + p.H->chd
163                    [i]->edge->d;

```

```

158         Q.push(q);
159     }
160 }
161 }
162 void solve() { // ans[i] stores the i-th shortest
163     path
164     dijkstra();
165     build();
166     first_K(); // ans.size() might less than k
167 } solver;

```

5.12 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum \Rightarrow Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6 String

6.1 Aho Corasick

```

1 struct AAutomata {
2     struct Node {
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node() {
6             cnt = 0;
7             fail = 0;
8             dic = 0;
9             memset(go, 0, sizeof(go));
10        }
11    } pool[1048576], *root;
12    int nMem;
13    Node *new_Node() {
14        pool[nMem] = Node();
15        return &pool[nMem++];
16    }
17    void init() {
18        nMem = 0;
19        root = new_Node();
20    }
21    void add(const string &str) { insert(root, str, 0); }
22    void insert(Node *cur, const string &str, int pos) {
23        for (int i = pos; i < str.size(); i++) {
24            if (!cur->go[str[i] - 'a'])
25                cur->go[str[i] - 'a'] = new_Node();
26            cur = cur->go[str[i] - 'a'];
27        }
28        cur->cnt++;
29    }
30    void make_fail() {
31        queue<Node*> que;
32        que.push(root);
33        while (!que.empty()) {
34            Node *fr = que.front();
35            que.pop();
36            for (int i = 0; i < 26; i++) {

```

```

37         if (fr->go[i]) {
38             Node *ptr = fr->fail;
39             while (ptr && !ptr->go[i]) ptr = ptr->fail;
40             fr->go[i]->fail = ptr = (ptr ? ptr->go[i] : root);
41             fr->go[i]->dic = (ptr->cnt ? ptr : ptr->dic);
42             que.push(fr->go[i]);
43         }
44     }
45 }
46 } AC;
47

```

6.2 KMP

```

1 vector<int> f;
2 void buildFailFunction(string &s) {
3     f.resize(s.size(), -1);
4     for (int i = 1; i < s.size(); i++) {
5         int now = f[i - 1];
6         while (now != -1 and s[now + 1] != s[i]) now = f[now];
7         if (s[now + 1] == s[i]) f[i] = now + 1;
8     }
9 }
10 void KMPmatching(string &a, string &b) {
11     for (int i = 0, now = -1; i < a.size(); i++) {
12         while (a[i] != b[now + 1] and now != -1) now = f[now];
13         if (a[i] == b[now + 1]) now++;
14         if (now + 1 == b.size()) {
15             cout << "found a match start at position "
16                  << i - now << endl;
17             now = f[now];
18         }
19     }
20 }

```

6.3 Z Value

```

1 string is, it, s;
2 int n;
3 vector<int> z;
4 void init() {
5     cin >> is >> it;
6     s = it + '0' + is;
7     n = (int)s.size();
8     z.resize(n, 0);
9 }
10 void solve() {
11     int ans = 0;
12     z[0] = n;
13     for (int i = 1, l = 0, r = 0; i < n; i++) {
14         if (i <= r) z[i] = min(z[i - l], r - i + 1);
15         while (i + z[i] < n && s[z[i]] == s[i + z[i]])
16             z[i]++;
17         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
18         if (z[i] == (int)it.size()) ans++;
19     }
20     cout << ans << endl;

```

6.4 Manacher

```

1 int n;
2 string S, s;
3 vector<int> m;
4 void manacher() {
5     s.clear();
6     s.resize(2 * n + 1, '.');
7     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
8     m.clear();
9     m.resize(2 * n + 1, 0);
10    // m[i] := max k such that s[i-k, i+k] is
11    // palindrome
12    int mx = 0, mxk = 0;
13    for (int i = 1; i < 2 * n + 1; i++) {

```

```

13     if (mx - (i - mx) >= 0) m[i] = min(m[mx - (i - 49
        mx)], mx + mxk - i); 50
14     while (0 <= i - m[i] - 1 && i + m[i] + 1 < 2 * 51
        n + 1 && 52
15         s[i - m[i] - 1] == s[i + m[i] + 1]) m[i] 53
        ++;
16     if (i + m[i] > mx + mxk) mx = i, mxk = m[i]; 54
17 } 55
18 } 56
19 void init() { 57
20     cin >> S; 58
21     n = (int)S.size(); 59
22 }
23 void solve() {
24     manacher();
25     int mx = 0, ptr = 0;
26     for (int i = 0; i < 2 * n + 1; i++)
27         if (mx < m[i]) {
28             mx = m[i];
29             ptr = i;
30         }
31     for (int i = ptr - mx; i <= ptr + mx; i++)
32         if (s[i] != '.') cout << s[i];
33     cout << endl;
34 }

```

6.5 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n;
5     string s;
6     vector<int> suf, lcp, rk;
7     vector<int> cnt, pos;
8     vector<pair<pii, int>> buc[2];
9     void init(string _s) {
10         s = _s;
11         n = (int)s.size();
12         // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
13     }
14     void radix_sort() {
15         for (int t : {0, 1}) {
16             fill(cnt.begin(), cnt.end(), 0);
17             for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F.S)++]++;
18             for (int i = 0; i < n; i++)
19                 pos[i] = (!i ? 0 : pos[i - 1] + cnt[i - 1]);
20             for (auto& i : buc[t])
21                 buc[t ^ 1][pos[(t ? i.F.F : i.F.S)]]++
22                 = i;
23         }
24     }
25     bool fill_suf() {
26         bool end = true;
27         for (int i = 0; i < n; i++) suf[i] = buc[0][i].40
28         S;
29         rk[suf[0]] = 0;
30         for (int i = 1; i < n; i++) {
31             int dif = (buc[0][i].F != buc[0][i - 1].F);44
32             end &= dif;
33             rk[suf[i]] = rk[suf[i - 1]] + dif;
34         }
35         return end;
36     }
37     void sa() {
38         for (int i = 0; i < n; i++)
39             buc[0][i] = make_pair(make_pair(s[i], s[i])52
40             , i);
41         sort(buc[0].begin(), buc[0].end());
42         if (fill_suf()) return;
43         for (int k = 0; (1 << k) < n; k++) {
44             for (int i = 0; i < n; i++)
45                 buc[0][i] = make_pair(make_pair(rk[i],57
46                 rk[(i + (1 << k)) % n]), i);
47             radix_sort();
48             if (fill_suf()) return;
49         }
50     }
51     void LCP() {
52         int k = 0;

```

```

for (int i = 0; i < n - 1; i++) {
    if (rk[i] == 0) continue;
    int pi = rk[i];
    int j = suf[pi - 1];
    while (i + k < n && j + k < n && s[i + k]
        == s[j + k]) k++;
    lcp[pi] = k;
    k = max(k - 1, 0);
}
}
};
SuffixArray suffixarray;

```

6.6 Suffix Automaton

```

1 struct SAM {
2     struct State {
3         int next[26];
4         int link, len;
5         State() : link(-1), len(0) { memset(next, -1,
6             sizeof next); }
7     };
8     vector<State> st;
9     int last;
10    vector<long long> occ;
11    vector<int> first_bkpos;
12    SAM(int maxlen = 0) {
13        st.reserve(2 * maxlen + 5); st.push_back(State
14        ()); last = 0;
15        occ.reserve(2 * maxlen + 5); occ.push_back(0);
16        first_bkpos.push_back(-1);
17    }
18    void extend(int c) {
19        int cur = (int)st.size();
20        st.push_back(State());
21        occ.push_back(0);
22        first_bkpos.push_back(0);
23        st[cur].len = st[last].len + 1;
24        first_bkpos[cur] = st[cur].len - 1;
25        int p = last;
26        while (p != -1 && st[p].next[c] == -1) {
27            st[p].next[c] = cur;
28            p = st[p].link;
29        }
30        if (p == -1) {
31            st[cur].link = 0;
32        } else {
33            int q = st[p].next[c];
34            if (st[p].len + 1 == st[q].len) {
35                st[cur].link = q;
36            } else {
37                int clone = (int)st.size();
38                st.push_back(st[q]);
39                first_bkpos.push_back(first_bkpos[q]);
40                occ.push_back(0);
41                st[clone].len = st[p].len + 1;
42                while (p != -1 && st[p].next[c] == q) {
43                    st[p].next[c] = clone;
44                    p = st[p].link;
45                }
46                st[q].link = st[cur].link = clone;
47            }
48        }
49        last = cur;
50        occ[cur] += 1;
51    }
52    void finalize_occ() {
53        int m = (int)st.size();
54        vector<int> order(m);
55        iota(order.begin(), order.end(), 0);
56        sort(order.begin(), order.end(), [&](int a, int
57        b){ return st[a].len > st[b].len; });
58        for (int v : order) {
59            int p = st[v].link;
60            if (p != -1) occ[p] += occ[v];
61        }
62    }
63 };

```

6.7 Minimum Rotation

```

1 // rotate(begin(s), begin(s)+minRotation(s), end(s))

```

```

2 int minRotation(string s) {
3     int a = 0, n = s.size();
4     s += s;
5     for (int b = 0; b < n; b++)
6         for (int k = 0; k < n; k++) {
7             if (a + k == b || s[a + k] < s[b + k]) {
8                 b += max(0, k - 1);
9                 break;
10            }
11            if (s[a + k] > s[b + k]) {
12                a = b;
13                break;
14            }
15        }
16     return a;
17 }

```

6.8 Lyndon Factorization

```

1 vector<string> duval(string const& s) {
2     int n = s.size();
3     int i = 0;
4     vector<string> factorization;
5     while (i < n) {
6         int j = i + 1, k = i;
7         while (j < n && s[k] <= s[j]) {
8             if (s[k] < s[j])
9                 k = i;
10            else
11                k++;
12            j++;
13        }
14        while (i <= k) {
15            factorization.push_back(s.substr(i, j - k));
16            i += j - k;
17        }
18    }
19    return factorization; // O(n)
20 }

```

6.9 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) { return c - 'a' + 1; }
3 struct RollingHash {
4     string s;
5     int n;
6     ll mod;
7     vector<ll> Cexp, hs;
8     RollingHash(string& _s, ll _mod) : s(_s), n((int)_s
9         .size()), mod(_mod) {
10         Cexp.assign(n, 0);
11         hs.assign(n, 0);
12         Cexp[0] = 1;
13         for (int i = 1; i < n; i++) {
14             Cexp[i] = Cexp[i - 1] * C;
15             if (Cexp[i] >= mod) Cexp[i] %= mod;
16         }
17         hs[0] = id(s[0]);
18         for (int i = 1; i < n; i++) {
19             hs[i] = hs[i - 1] * C + id(s[i]);
20             if (hs[i] >= mod) hs[i] %= mod;
21         }
22     }
23     inline ll query(int l, int r) {
24         ll res = hs[r] - (l ? hs[l - 1] * Cexp[r - l +
25             1] : 0);
26         res = (res % mod + mod) % mod;
27         return res;
28     }
29 };

```

6.10 Trie

```

1 pii a[N][26];
2
3 void build(string &s) {
4     static int idx = 0;
5     int n = s.size();
6     for (int i = 0, v = 0; i < n; i++) {

```

```

7         pii &now = a[v][s[i] - 'a'];
8         if (now.first != -1)
9             v = now.first;
10        else
11            v = now.first = ++idx;
12        if (i == n - 1)
13            now.second++;
14    }
15 }

```

7 Geometry

7.1 Basic Operations

```

1 // typedef long long T;
2 typedef long double T;
3 const long double eps = 1e-12;
4
5 short sgn(T x) {
6     if (abs(x) < eps) return 0;
7     return x < 0 ? -1 : 1;
8 }
9
10 struct Pt {
11     T x, y;
12     Pt(T _x = 0, T _y = 0) : x(_x), y(_y) {}
13     Pt operator+(Pt a) { return Pt(x + a.x, y + a.y); }
14     Pt operator-(Pt a) { return Pt(x - a.x, y - a.y); }
15     Pt operator*(T a) { return Pt(x * a, y * a); }
16     Pt operator/(T a) { return Pt(x / a, y / a); }
17     T operator*(Pt a) { return x * a.x + y * a.y; }
18     T operator^(Pt a) { return x * a.y - y * a.x; }
19     bool operator<(Pt a) { return x < a.x || (x == a.x
20         && y < a.y); }
21     // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn
22         (y-a.y) < 0); }
23     bool operator==(Pt a) { return sgn(x - a.x) == 0 &&
24         sgn(y - a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b - a; }
28 T len2(Pt a) { return a * a; }
29 T dis2(Pt a, Pt b) { return len2(b - a); }
30 Pt rotate(Pt u) { return {-u.y, u.x}; }
31 Pt unit(Pt x) { return x / sqrt1(x * x); }
32 short ori(Pt a, Pt b) { return ((a ^ b) > 0) - ((a ^ b)
33     < 0); }
34 bool onseg(Pt p, Pt l1, Pt l2) {
35     Pt a = mv(p, l1), b = mv(p, l2);
36     return ((a ^ b) == 0) && ((a * b) <= 0);
37 }
38
39 inline T cross(const Pt &a, const Pt &b, const Pt &c) {
40     return (b.x - a.x) * (c.y - a.y)
41         - (b.y - a.y) * (c.x - a.x);
42 }
43
44 long double polar_angle(Pt ori, Pt pt) {
45     return atan2(pt.y - ori.y, pt.x - ori.x);
46 }
47 // slope to degree atan(Slope) * 180.0 / acos(-1.0);
48 bool argcmp(Pt u, Pt v) {
49     auto half = [](const Pt& p) {
50         return p.y > 0 || (p.y == 0 && p.x >= 0);
51     };
52     if (half(u) != half(v)) return half(u) < half(v);
53     return sgn(u ^ v) > 0;
54 }
55
56 int ori(Pt& o, Pt& a, Pt& b) {
57     return sgn((a - o) ^ (b - o));
58 }
59
60 struct Line {
61     Pt a, b;
62     Pt dir() { return b - a; }
63 };
64
65 int PtSide(Pt p, Line L) {
66     return sgn(ori(L.a, L.b, p)); // for int
67     return sgn(ori(L.a, L.b, p) / sqrt(len2(L.a - L.b))
68         );
69 }
70
71 bool PtOnSeg(Pt p, Line L) {

```



```

62     return PtSide(p, L) == 0 and sgn((p - L.a) * (p - L
        .b)) <= 0;
63 }
64 Pt proj(Pt& p, Line& l) {
65     Pt d = l.b - l.a;
66     T d2 = len2(d);
67     if (sgn(d2) == 0) return l.a;
68     T t = ((p - l.a) * d) / d2;
69     return l.a + d * t;
70 }
71 struct Cir {
72     Pt o;
73     T r;
74 };
75 bool disjunct(Cir a, Cir b) {
76     return sgn(sqrtl(len2(a.o - b.o)) - a.r - b.r) >=
        0;
77 }
78 bool contain(Cir a, Cir b) {
79     return sgn(a.r - b.r - sqrtl(len2(a.o - b.o))) >=
        0;
80 }

```

7.2 Sort by Angle

```

1 int ud(Pt a) { // up or down half plane
2     if (a.y > 0) return 0;
3     if (a.y < 0) return 1;
4     return (a.x >= 0 ? 0 : 1);
5 }
6 sort(pts.begin(), pts.end(), [&](const Pt& a, const Pt&
    b) {
7     if (ud(a) != ud(b)) return ud(a) < ud(b);
8     return (a ^ b) > 0;
9 });

```

7.3 Intersection

```

1 bool line_intersect_check(Pt p1, Pt p2, Pt q1, Pt q2) {
2     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) || onseg
        (q1, p1, p2) || onseg(q2, p1, p2)) return true;
3     Pt p = mv(p1, p2), q = mv(q1, q2);
4     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) <
        0) && (ori(q, mv(q1, p1)) * ori(q, mv(q1, p2))
        < 0);
5 }
6 // long double
7 Pt line_intersect(Pt a1, Pt a2, Pt b1, Pt b2) {
8     Pt da = mv(a1, a2), db = mv(b1, b2);
9     T det = da ^ db;
10    if (sgn(det) == 0) { // parallel
11        // return Pt(NAN, NAN);
12    }
13    T t = ((b1 - a1) ^ db) / det;
14    return a1 + da * t;
15 }
16 vector<Pt> CircleInter(Cir a, Cir b) {
17     double d2 = len2(a.o - b.o), d = sqrt(d2);
18     if (d < max(a.r, b.r) - min(a.r, b.r) || d > a.r +
        b.r) return {};
19     Pt u = (a.o + b.o) / 2 + (a.o - b.o) * ((b.r * b.r
        - a.r * a.r) / (2 * d2));
20     double A = sqrt((a.r + b.r + d) * (a.r - b.r + d) *
        (a.r + b.r - d) * (-a.r + b.r + d));
21     Pt v = rotate(b.o - a.o) * A / (2 * d2);
22     if (sgn(v.x) == 0 and sgn(v.y) == 0) return {u};
23     return {u - v, u + v}; // counter clockwise of a
24 }
25 vector<Pt> CircleLineInter(Cir c, Line l) {
26     Pt H = proj(c.o, l);
27     Pt dir = unit(l.b - l.a);
28     T h = sqrtl(len2(H - c.o));
29     if (sgn(h - c.r) > 0) return {};
30     T d = sqrtl(max((T)0, c.r * c.r - h * h));
31     if (sgn(d) == 0) return {H};
32     return {H - dir * d, H + dir * d};
33 }

```

7.4 Polygon Area

```

1 // 2 * area

```

```

1 T dbPoly_area(vector<Pt>& e) {
2     T res = 0;
3     int sz = e.size();
4     for (int i = 0; i < sz; i++) {
5         res += e[i] ^ e[(i + 1) % sz];
6     }
7     return abs(res);
8 }

```

7.5 Convex Hull

```

1 vector<Pt> convexHull(vector<Pt> pts) {
2     vector<Pt> hull;
3     sort(pts.begin(), pts.end());
4     for (int i = 0; i < 2; i++) {
5         int b = hull.size();
6         for (auto ei : pts) {
7             while (hull.size() - b >= 2 && ori(mv(hull[
                hull.size() - 2], hull.back()), mv(hull[
                    hull.size() - 2], ei)) == -1) {
8                 hull.pop_back();
9             }
10            hull.emplace_back(ei);
11        }
12        hull.pop_back();
13        reverse(pts.begin(), pts.end());
14    }
15    return hull;
16 }

```

7.6 Point In Convex

```

1 bool point_in_convex(const vector<Pt> &C, Pt p, bool
    strict = true) {
2     // only works when no three point are collinear
3     int n = C.size();
4     int a = 1, b = n - 1, r = !strict;
5     if (n == 0) return false;
6     if (n < 3) return r && onseg(p, C[0], C.back());
7     if (ori(mv(C[0], C[a]), mv(C[0], C[b])) > 0) swap(a
        , b);
8     if (ori(mv(C[0], C[a]), mv(C[0], p)) >= r || ori(mv
        (C[0], C[b]), mv(C[0], p)) <= -r) return false;
9     while (abs(a - b) > 1) {
10        int c = (a + b) / 2;
11        if (ori(mv(C[0], C[c]), mv(C[0], p)) > 0) b = c
            ;
12        else a = c;
13    }
14    return ori(mv(C[a], C[b]), mv(C[a], p)) < r;
15 }

```

7.7 Point Segment Distance

```

1 double point_segment_dist(Pt q0, Pt q1, Pt p) {
2     if (q0 == q1) {
3         double dx = double(p.x - q0.x);
4         double dy = double(p.y - q0.y);
5         return sqrt(dx * dx + dy * dy);
6     }
7     T d1 = (q1 - q0) * (p - q0);
8     T d2 = (q0 - q1) * (p - q1);
9     if (d1 >= 0 && d2 >= 0) {
10        double area = fabs(double((q1 - q0) ^ (p - q0)
            ));
11        double base = sqrt(double(dis2(q0, q1)));
12        return area / base;
13    }
14    double dx0 = double(p.x - q0.x), dy0 = double(p.y -
        q0.y);
15    double dx1 = double(p.x - q1.x), dy1 = double(p.y -
        q1.y);
16    return min(sqrt(dx0 * dx0 + dy0 * dy0), sqrt(dx1 *
        dx1 + dy1 * dy1));
17 }

```

7.8 Point in Polygon

```

1 short inPoly(vector<Pt>& pts, Pt p) {
2     // 0=Bound 1=In -1=Out
3     int n = pts.size();

```

```

4   for (int i = 0; i < pts.size(); i++) if (onseg(p,
      pts[i], pts[(i + 1) % n])) return 0;
5   int cnt = 0;
6   for (int i = 0; i < pts.size(); i++) if (
      line_intersect_check(p, Pt(p.x + 1, p.y + 2e9),
      pts[i], pts[(i + 1) % n])) cnt ^= 1;
7   return (cnt ? 1 : -1);
8 }

```

7.9 Minimum Euclidean Distance

```

1 long long Min_Euclidean_Dist(vector<Pt> &pts) {
2   sort(pts.begin(), pts.end());
3   set<pair<long long, long long>> s;
4   s.insert({pts[0].y, pts[0].x});
5   long long l = 0, best = LLONG_MAX;
6   for (int i = 1; i < (int)pts.size(); i++) {
7     Pt now = pts[i];
8     long long lim = (long long)ceil(sqrt(1.0 * (long
      double)best));
9     while (now.x - pts[l].x > lim) {
10      s.erase({pts[l].y, pts[l].x}); l++;
11    }
12    auto low = s.lower_bound({now.y - lim,
      LLONG_MIN});
13    auto high = s.upper_bound({now.y + lim,
      LLONG_MAX});
14    for (auto it = low; it != high; it++) {
15      long long dy = it->first - now.y;
16      long long dx = it->second - now.x;
17      best = min(best, dx * dx + dy * dy);
18    }
19    s.insert({now.y, now.x});
20  }
21  return best;
22 }

```

7.10 Minkowski Sum

```

1 void reorder(vector<Pt> &P) {
2   rotate(P.begin(), min_element(P.begin(), P.end(),
      [&](Pt a, Pt b) { return make_pair(a.y, a.x) <
      make_pair(b.y, b.x); }), P.end());
3 }
4 vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
5   // P, Q: convex polygon
6   reorder(P), reorder(Q);
7   int n = P.size(), m = Q.size();
8   P.push_back(P[0]), P.push_back(P[1]), Q.push_back(Q
      [0]), Q.push_back(Q[1]);
9   vector<Pt> ans;
10  for (int i = 0, j = 0; i < n || j < m; ) {
11    ans.push_back(P[i] + Q[j]);
12    auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
13    if (val >= 0) i++;
14    if (val <= 0) j++;
15  }
16  return ans;
17 }

```

7.11 Lower Concave Hull

```

1 struct Line {
2   mutable ll m, b, p;
3   bool operator<(const Line& o) const { return m < o.m; }
4   bool operator<(ll x) const { return p < x; }
5 };
6
7 struct LineContainer : multiset<Line, less<>> {
8   // (for doubles, use inf = 1/.0, div(a,b) = a/b)
9   const ll inf = LLONG_MAX;
10  ll div(ll a, ll b) { // floored division
11    return a / b - ((a ^ b) < 0 && a % b); }
12  bool isect(iterator x, iterator y) {
13    if (y == end()) { x->p = inf; return false; }
14    if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
15    else x->p = div(y->b - x->b, x->m - y->m);
16    return x->p >= y->p;
17  }
18  void add(ll m, ll b) {

```

```

19    auto z = insert({m, b, 0}), y = z++, x = y;
20    while (isect(y, z)) z = erase(z);
21    if (x != begin() && isect(--x, y)) isect(x, y =
      erase(y));
22    while ((y = x) != begin() && (--x)->p >= y->p)
23      isect(x, erase(y));
24  }
25  ll query(ll x) {
26    assert(!empty());
27    auto l = *lower_bound(x);
28    return l.m * x + l.b;
29  }
30 };

```

7.12 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$Area = i + \frac{b}{2} - 1$$

7.13 Rotating SweepLine

```

1 double cross(const Pt &a, const Pt &b) {
2   return a.x*b.y - a.y*b.x;
3 }
4 int rotatingCalipers(const vector<Pt>& hull) {
5   int m = hull.size();
6   if (m < 2) return 0;
7   int j = 1;
8   T maxd = 0;
9   for (int i = 0; i < m; ++i) {
10    int ni = (i + 1) % m;
11    while (abs(cross({hull[ni].x - hull[i].x, hull[
      ni].y - hull[i].y}, {hull[(j+1)%m].x - hull
      [i].x, hull[(j+1)%m].y - hull[i].y})) > abs
      (cross({hull[ni].x - hull[i].x, hull[ni].y
      - hull[i].y}, {hull[j].x - hull[i].x,
      hull[j].y - hull[i].y}))) {
12      j = (j + 1) % m;
13    }
14    maxd = max(maxd, dis2(hull[i], hull[j]));
15    maxd = max(maxd, dis2(hull[ni], hull[j]));
16  }
17  return maxd; // TODO
18 }

```

7.14 Half Plane Intersection

```

1 bool cover(Line& L, Line& P, Line& Q) {
2   long double u = (Q.a - P.a) ^ Q.dir();
3   long double v = P.dir() ^ Q.dir();
4   long double x = P.dir().x * u + (P.a - L.a).x * v;
5   long double y = P.dir().y * u + (P.a - L.a).y * v;
6   return sgn(x * L.dir().y - y * L.dir().x) * sgn(v)
      >= 0;
7 }
8 vector<Line> HPI(vector<Line> P) {
9   sort(P.begin(), P.end(), [&](Line& l, Line& m) {
10    if (argcmp(l.dir(), m.dir()) return true;
11    if (argcmp(m.dir(), l.dir()) return false;
12    return ori(m.a, m.b, l.a) > 0;
13  });
14
15  int l = 0, r = -1;
16  for (size_t i = 0; i < P.size(); ++i) {
17    if (i && !argcmp(P[i - 1].dir(), P[i].dir()))
18      continue;
19    while (l < r && cover(P[i], P[r - 1], P[r])) --
      r;
20    while (l < r && cover(P[i], P[l], P[l + 1])) ++
      l;
21    P[++r] = P[i];
22  }
23  while (l < r && cover(P[l], P[r - 1], P[r])) --r;
24  while (l < r && cover(P[r], P[l], P[l + 1])) ++l;

```

```

25 if (r - 1 <= 1 || !argcmp(P[l].dir(), P[r].dir()))
26     return {};
27 if (cover(P[l + 1], P[l], P[r])) return {};
28 return vector<Line>(P.begin() + 1, P.begin() + r +
29     1);

```

7.15 Minimum Enclosing Circle

```

1 const int INF = 1e9;
2 Pt circumcenter(Pt A, Pt B, Pt C) {
3     // a1(x-A.x) + b1(y-A.y) = c1
4     // a2(x-A.x) + b2(y-A.y) = c2
5     // solve using Cramer's rule
6     T a1 = B.x - A.x, b1 = B.y - A.y, c1 = dis2(A, B) /
7         2.0;
8     T a2 = C.x - A.x, b2 = C.y - A.y, c2 = dis2(A, C) /
9         2.0;
10    T D = Pt(a1, b1) ^ Pt(a2, b2);
11    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
12    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
13    if (D == 0) return Pt(-INF, -INF);
14    return A + Pt(Dx / D, Dy / D);
15 }
16 Pt center;
17 T r2;
18 void minEncloseCircle(vector<Pt> pts) {
19     mt19937 gen(chrono::steady_clock::now().
20         time_since_epoch().count());
21     shuffle(pts.begin(), pts.end(), gen);
22     center = pts[0], r2 = 0;
23     for (int i = 0; i < pts.size(); i++) {
24         if (dis2(center, pts[i]) <= r2) continue;
25         center = pts[i], r2 = 0;
26         for (int j = 0; j < i; j++) {
27             if (dis2(center, pts[j]) <= r2) continue;
28             center = (pts[i] + pts[j]) / 2.0;
29             r2 = dis2(center, pts[i]);
30             for (int k = 0; k < j; k++) {
31                 if (dis2(center, pts[k]) <= r2)
32                     continue;
33                 center = circumcenter(pts[i], pts[j],
34                     pts[k]);
35                 r2 = dis2(center, pts[i]);
36             }
37         }
38     }
39 }

```

7.16 Union of Circles

```

1 // Area[i] : area covered by at least i circle
2 vector<T> CircleUnion(const vector<Cir> &C) {
3     const int n = C.size();
4     vector<T> Area(n + 1);
5     auto check = [&](int i, int j) {
6         if (!contain(C[i], C[j]))
7             return false;
8         return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r
9             - C[j].r) == 0 and i < j);
10    };
11    struct Teve {
12        double ang; int add; Pt p;
13        bool operator<(const Teve &b) { return ang < b.
14            ang; }
15    };
16    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
17    for (int i = 0; i < n; i++) {
18        int cov = 1;
19        vector<Teve> event;
20        for (int j = 0; j < n; j++) if (i != j) {
21            if (check(j, i)) cov++;
22            else if (!check(i, j) and !disjunct(C[i], C
23                [j])) {
24                auto I = CircleInter(C[i], C[j]);
25                assert(I.size() == 2);
26                double a1 = ang(I[0] - C[i].o), a2 =
27                    ang(I[1] - C[i].o);
28                event.push_back({a1, 1, I[0]});
29                event.push_back({a2, -1, I[1]});
30            }
31        }
32    }
33 }

```

```

34     if (a1 > a2) cov++;
35 }
36 if (event.empty()) {
37     Area[cov] += acos(-1) * C[i].r * C[i].r;
38     continue;
39 }
40 sort(event.begin(), event.end());
41 event.push_back(event[0]);
42 for (int j = 0; j + 1 < event.size(); j++) {
43     cov += event[j].add;
44     Area[cov] += (event[j].p ^ event[j + 1].p)
45         / 2.;
46     double theta = event[j + 1].ang - event[j].
47         ang;
48     if (theta < 0) theta += 2 * acos(-1);
49     Area[cov] += (theta - sin(theta)) * C[i].r
50         * C[i].r / 2.;
51 }
52 }
53 return Area;
54 }

```

7.17 Area Of Circle Polygon

```

1 double AreaOfCirclePoly(Cir C, vector<Pt> &P) {
2     auto arg = [&](Pt p, Pt q) { return atan2(p ^ q, p
3         * q); };
4     double r2 = (double)(C.r * C.r / 2);
5     auto tri = [&](Pt p, Pt q) {
6         Pt d = q - p;
7         T a = (d * p) / (d * d);
8         T b = ((p * p) - C.r * C.r) / (d * d);
9         T det = a * a - b;
10        if (det <= 0) return (double)(arg(p, q) * r2);
11        T s = max((T)0.0L, -a - sqrtl(det));
12        T t = min((T)1.0L, -a + sqrtl(det));
13        if (t < 0 || 1 <= s) return (double)(arg(p, q)
14            * r2);
15        Pt u = p + d * s, v = p + d * t;
16        return (double)(arg(p, u) * r2 + (u ^ v) / 2 +
17            arg(v, q) * r2);
18    };
19    long double sum = 0.0L;
20    for (int i = 0; i < (int)P.size(); i++)
21        sum += tri(P[i] - C.o, P[(i + 1) % P.size()] -
22            C.o);
23    return (double)fabs1(sum);
24 }

```

7.18 3D Point

```

1 struct Pt {
2     double x, y, z;
3     Pt(double _x = 0, double _y = 0, double _z = 0): x(_x
4         ), y(_y), z(_z){}
5     Pt operator + (const Pt &o) const
6     { return Pt(x + o.x, y + o.y, z + o.z); }
7     Pt operator - (const Pt &o) const
8     { return Pt(x - o.x, y - o.y, z - o.z); }
9     Pt operator * (const double &k) const
10    { return Pt(x * k, y * k, z * k); }
11    Pt operator / (const double &k) const
12    { return Pt(x / k, y / k, z / k); }
13    double operator * (const Pt &o) const
14    { return x * o.x + y * o.y + z * o.z; }
15    Pt operator ^ (const Pt &o) const
16    { return {Pt(y * o.z - z * o.y, z * o.x - x * o.z, x
17        * o.y - y * o.x)}; }
18 };
19 double abs2(Pt o) { return o * o; }
20 double abs(Pt o) { return sqrt(abs2(o)); }
21 Pt cross3(Pt a, Pt b, Pt c)
22 { return (b - a) ^ (c - a); }
23 double area(Pt a, Pt b, Pt c)
24 { return abs(cross3(a, b, c)); }
25 double volume(Pt a, Pt b, Pt c, Pt d)
26 { return cross3(a, b, c) * (d - a); }
27 bool coplaner(Pt a, Pt b, Pt c, Pt d)
28 { return sign(volume(a, b, c, d)) == 0; }
29 Pt proj(Pt o, Pt a, Pt b, Pt c) // o proj to plane abc
30 { Pt n = cross3(a, b, c);

```

```

29 return o - n * ((o - a) * (n / abs2(n)));}
30 Pt line_plane_intersect(Pt u, Pt v, Pt a, Pt b, Pt c) {
31 // intersection of line uv and plane abc
32 Pt n = cross3(a, b, c);
33 double s = n * (u - v);
34 if (sign(s) == 0) return {-1, -1, -1}; // not found
35 return v + (u - v) * ((n * (a - v)) / s); }
36 Pt rotateAroundAxis(Pt v, Pt axis, double theta) {
37 axis = axis / abs(axis); // axis must be unit
38 // vector
39 double cosT = cos(theta);
40 double sinT = sin(theta);
41 Pt term1 = v * cosT;
42 Pt term2 = (axis ^ v) * sinT;
43 Pt term3 = axis * ((axis * v) * (1 - cosT));
44 return term1 + term2 + term3;
}

```

8 Number Theory

8.1 FFT

```

1 typedef complex<double> cp;
2
3 const double pi = acos(-1);
4 const int NN = 131072;
5
6 struct FastFourierTransform {
7     /*
8      * Iterative Fast Fourier Transform
9      * How this works? Look at this
10      * 0th recursion 0(000) 1(001) 2(010)
11      * 3(011) 4(100) 5(101) 6(110)
12      * 7(111)
13      * 1th recursion 0(000) 2(010) 4(100)
14      * 6(110) | 1(011) 3(011) 5(101)
15      * 7(111)
16      * 2th recursion 0(000) 4(100) | 2(010)
17      * 6(110) | 1(011) 5(101) | 3(011)
18      * 7(111)
19      * 3th recursion 0(000) | 4(100) | 2(010) |
20      * 6(110) | 1(011) | 5(101) | 3(011) |
21      * 7(111)
22      * All the bits are reversed => We can save
23      * the reverse of the numbers in an array!
24      */
25 int n, rev[NN];
26 cp omega[NN], iomega[NN];
27 void init(int n_) {
28     n = n_;
29     for (int i = 0; i < n; i++) {
30         // Calculate the nth roots of unity
31         omega[i] = cp(cos(2 * pi * i / n), sin(2 *
32             pi * i / n));
33         iomega[i] = conj(omega[i]);
34     }
35     int k = __lg(n);
36     for (int i = 0; i < n; i++) {
37         int t = 0;
38         for (int j = 0; j < k; j++) {
39             if (i & (1 << j)) t |= (1 << (k - j -
40                 1));
41         }
42         rev[i] = t;
43     }
44 }
45
46 void transform(vector<cp> &a, cp *xomega) {
47     for (int i = 0; i < n; i++)
48         if (i < rev[i]) swap(a[i], a[rev[i]]);
49     for (int len = 2; len <= n; len <= 1) {
50         int mid = len >> 1;
51         int r = n / len;
52         for (int j = 0; j < n; j += len)
53             for (int i = 0; i < mid; i++) {
54                 cp tmp = xomega[r * i] * a[j + mid
55                     + i];
56                 a[j + mid + i] = a[j + i] - tmp;
57                 a[j + i] = a[j + i] + tmp;
58             }
59     }
60 }

```

```

48 }
49
50 void fft(vector<cp> &a) { transform(a, omega); }
51 void ifft(vector<cp> &a) {
52     transform(a, iomega);
53     for (int i = 0; i < n; i++) a[i] /= n;
54 }
55 } FFT;
56
57 const int MAXN = 262144;
58 // (must be 2^k)
59 // 262144, 524288, 1048576, 2097152, 4194304
60 // before any usage, run pre_fft() first
61 typedef long double ld;
62 typedef complex<ld> cplx; // real(), imag()
63 const ld PI = acos(-1);
64 const cplx I(0, 1);
65 cplx omega[MAXN + 1];
66 void pre_fft() {
67     for (int i = 0; i <= MAXN; i++) {
68         omega[i] = exp(i * 2 * PI / MAXN * I);
69     }
70 }
71 // n must be 2^k
72 void fft(int n, cplx a[], bool inv = false) {
73     int basic = MAXN / n;
74     int theta = basic;
75     for (int m = n; m >= 2; m >= 1) {
76         int mh = m >> 1;
77         for (int i = 0; i < mh; i++) {
78             cplx w = omega[inv ? MAXN - (i * theta %
79                 MAXN) : i * theta % MAXN];
80             for (int j = i; j < n; j += m) {
81                 int k = j + mh;
82                 cplx x = a[j] - a[k];
83                 a[j] += a[k];
84                 a[k] = w * x;
85             }
86             theta = (theta * 2) % MAXN;
87         }
88         int i = 0;
89         for (int j = 1; j < n - 1; j++) {
90             for (int k = n >> 1; k > (i ^= k); k >= 1);
91             if (j < i) swap(a[i], a[j]);
92         }
93         if (inv) {
94             for (i = 0; i < n; i++) a[i] /= n;
95         }
96     }
97     cplx arr[MAXN + 1];
98     inline void mul(int _n, long long a[], int _m, long
99         long b[], long long ans[]) {
100         int n = 1, sum = _n + _m - 1;
101         while (n < sum) n <= 1;
102         for (int i = 0; i < n; i++) {
103             double x = (i < _n ? a[i] : 0), y = (i < _m ? b
104                 [i] : 0);
105             arr[i] = complex<double>(x + y, x - y);
106         }
107         fft(n, arr);
108         for (int i = 0; i < n; i++) arr[i] = arr[i] * arr[i
109             ];
110         fft(n, arr, true);
111         for (int i = 0; i < sum; i++) ans[i] = (long long
112             int)(arr[i].real() / 4 + 0.5);
113     }
114 }
115
116 long long a[MAXN];
117 long long b[MAXN];
118 long long ans[MAXN];
119 int a_length;
120 int b_length;

```

8.2 Pollard's rho

```

11 add(11 x, 11 y, 11 p) {
12     return (x + y) % p;
13 }
14 qMul(11 x, 11 y, 11 mod) {
15     11 ret = x * y - (11)((long double)x / mod * y) *
16         mod;

```

```

6     return ret < 0 ? ret + mod : ret;
7 }
8 ll f(ll x, ll mod) { return add(qMul(x, x, mod), 1, mod); }
9 ll pollard_rho(ll n) {
10     if (!(n & 1)) return 2;
11     while (true) {
12         ll y = 2, x = rand() % (n - 1) + 1, res = 1;
13         for (int sz = 2; res == 1; sz *= 2) {
14             for (int i = 0; i < sz && res <= 1; i++) {
15                 x = f(x, n);
16                 res = __gcd(llabs(x - y), n);
17             }
18             y = x;
19         }
20         if (res != 0 && res != n) return res;
21     }
22 }
23 vector<ll> ret;
24 void fact(ll x) {
25     if (miller_rabin(x)) {
26         ret.push_back(x);
27         return;
28     }
29     ll f = pollard_rho(x);
30     fact(f);
31     fact(x / f);
32 }

```

8.3 Miller Rabin

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633 4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383 6 : pirmes <= 13
4 // n < 2^64              7 :
5 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022
6 bool witness(ll a, ll n, ll u, int t) {
7     if (!(a % n)) return 0;
8     ll x = mypow(a, u, n);
9     for (int i = 0; i < t; i++) {
10         ll nx = mul(x, x, n);
11         if (nx == 1 && x != 1 && x != n - 1) return 1;
12         x = nx;
13     }
14     return x != 1;
15 }
16 bool miller_rabin(ll n, int s = 100) {
17     // iterate s times of witness on n
18     // return 1 if prime, 0 otherwise
19     if (n < 2) return 0;
20     if (!(n & 1)) return n == 2;
21     ll u = n - 1;
22     int t = 0;
23     while (!(u & 1)) u >>= 1, t++;
24     while (s--) {
25         ll a = randll() % (n - 1) + 1;
26         if (witness(a, n, u, t)) return 0;
27     }
28     return 1;
29 }

```

8.4 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

8.5 Extend GCD

```

1 ll GCD;
2 pll extgcd(ll a, ll b) {
3     if (b == 0) {
4         GCD = a;
5         return pll{1, 0};
6     }
7     pll ans = extgcd(b, a % b);
8     return pll{ans.S, ans.F - a / b * ans.S};
9 }
10 pll bezout(ll a, ll b, ll c) {
11     bool negx = (a < 0), negy = (b < 0);
12     pll ans = extgcd(abs(a), abs(b));
13     if (c % GCD != 0) return pll{-LLINF, -LLINF};
14     return pll{ans.F * c / GCD * (negx ? -1 : 1),
15                ans.S * c / GCD * (negy ? -1 : 1)};

```

```

16 }
17 ll inv(ll a, ll p) {
18     if (p == 1) return -1;
19     pll ans = bezout(a % p, -p, 1);
20     if (ans == pll{-LLINF, -LLINF}) return -1;
21     return (ans.F % p + p) % p;
22 }

```

8.6 Mu + Phi

```

1 const int maxn = 1e6 + 5;
2 ll f[maxn];
3 vector<int> lpf, prime;
4 void build() {
5     lpf.clear();
6     lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
14         }
15         for (auto& j : prime) {
16             if (i * j >= maxn) break;
17             lpf[i * j] = j;
18             if (i % j == 0)
19                 f[i * j] = ...; /* 0, phi[i]*j */
20             else
21                 f[i * j] = ...; /* -mu[i], phi[i]*phi[j] */
22             if (j >= lpf[i]) break;
23         }
24     }
25 }

```

8.7 Discrete Log

```

1 long long mod_pow(long long a, long long e, long long p)
2 ){
3     long long r = 1 % p;
4     while(e){
5         if(e & 1) r = (__int128)r * a % p;
6         a = (__int128)a * a % p;
7         e >>= 1;
8     }
9     return r;
10 }
11 long long mod_inv(long long a, long long p){
12     return mod_pow((a%p+p)%p, p-2, p);
13 }
14 // BSGS: solve a^x = y (mod p), gcd(a,p)=1, p prime,
15 // return minimal x>=0, or -1 if no solution
16 long long bsgs(long long a, long long y, long long p){
17     a%=p; y%=p;
18     if(y==1%p) return 0; // x=0
19     long long m = (long long)ceil(sqrt((long double)p));
20     ;
21     // baby steps: a^j
22     unordered_map<long long, long long> table;
23     table.reserve(m*2);
24     long long cur = 1%p;
25     for(long long j=0; j<m; ++j){
26         if(!table.count(cur)) table[cur]=j;
27         cur = (__int128)cur * a % p;
28     }
29     long long am = mod_pow(a, m, p);
30     long long am_inv = mod_inv(am, p);
31     long long gamma = y % p;
32     for(long long i=0; i<m; ++i){
33         auto it = table.find(gamma);
34         if(it != table.end()){
35             long long x = i*m + it->second;
36             return x;
37         }
38         gamma = (__int128)gamma * am_inv % p;
39     }
40     return -1;
41 }

```


8.8 sqrt mod

```

1 // the Jacobi symbol is a generalization of the
  // Legendre symbol,
2 // such that the bottom doesn't need to be prime.
3 // (n/p) -> same as legendre
4 // (n/ab) = (n/a)(n/b)
5 // work with long long
6 int Jacobi(int a, int m) {
7     int s = 1;
8     for (; m > 1; ) {
9         a %= m;
10        if (a == 0) return 0;
11        const int r = __builtin_ctz(a);
12        if ((r & 1) && ((m + 2) & 4)) s = -s;
13        a >>= r;
14        if (a & m & 2) s = -s;
15        swap(a, m);
16    }
17    return s;
18 }
19 // solve x^2 = a (mod p)
20 // 0: a == 0
21 // -1: a isn't a quad res of p
22 // else: return X with X^2 % p == a
23 // doesn't work with long long
24 int QuadraticResidue(int a, int p) {
25     if (p == 2) return a & 1;
26     if (int jc = Jacobi(a, p); jc <= 0) return jc;
27     int b, d;
28     for (; ; ) {
29         b = rand() % p;
30         d = (1LL * b * b + p - a) % p;
31         if (Jacobi(d, p) == -1) break;
32     }
33     int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
34     for (int e = (1LL + p) >> 1; e; e >>= 1) {
35         if (e & 1) {
36             tmp = (1LL * g0 * f0 + 1LL * d * (1LL * g1
37                 * f1 % p)) % p;
38             g1 = (1LL * g0 * f1 + 1LL * g1 * f0) % p;
39             g0 = tmp;
40         }
41         tmp = (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1
42             % p)) % p;
43         f1 = (2LL * f0 * f1) % p;
44         f0 = tmp;
45     }
46     return g0;
47 }

```

8.9 Primitive Root

```

1 unsigned long long primitiveRoot(ull p) {
2     auto fac = factor(p - 1);
3     sort(all(fac));
4     fac.erase(unique(all(fac)), fac.end());
5     auto test = [p, fac](ull x) {
6         for(ull d : fac)
7             if (modpow(x, (p - 1) / d, p) == 1)
8                 return false;
9         return true;
10    };
11    uniform_int_distribution<unsigned long long> unif
12    (1, p - 1);
13    unsigned long long root;
14    while(!test(root = unif(rng)));
15    return root;
16 }

```

8.10 Other Formulas

- Inversion:
 $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion:
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:
 $a^p \equiv a \pmod{p}$ if p is prime.

- Euler function:

$$\phi(n) = n \prod_{p|n} \frac{p-1}{p}$$

- Euler theorem:

$$a^{\phi(n)} \equiv 1 \pmod{n} \text{ if } \gcd(a, n) = 1.$$

- Extended Euclidean algorithm:

$$ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$$

- Divisor function:

$$\sigma_x(n) = \sum_{d|n} d^x. n = \prod_{i=1}^r p_i^{a_i}.$$

$$\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1} \text{ if } x \neq 0. \sigma_0(n) = \prod_{i=1}^r (a_i + 1).$$

- Chinese remainder theorem (Coprime Moduli):

$$x \equiv a_i \pmod{m_i}.$$

$$M = \prod m_i. M_i = M/m_i. t_i = M_i^{-1}.$$

$$x = kM + \sum a_i t_i M_i, k \in \mathbb{Z}.$$

- Chinese remainder theorem:

$$x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$$

Solve for (p, q) using ExtGCD.

$$x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$$

- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$

- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(n/d)$

- Important Multiplicative Functions + Properties:

- $\epsilon(n) = [n = 1]$
- $1(n) = 1$
- $id(n) = n$
- $\mu(n) = 0$ if n has squared prime factor
- $\mu(n) = (-1)^k$ if $n = p_1 p_2 \cdots p_k$
- $\epsilon = \mu * 1$
- $\phi = \mu * id$
- $[n = 1] = \sum_{d|n} \mu(d)$
- $[gcd = 1] = \sum_{d|gcd} \mu(d)$

- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

8.11 Polynomial

```

1 const int maxk = 20;
2 const int maxn = 1<<maxk;
3 const ll LINF = 1e18;
4
5 /* P = r*2^k + 1
6 P          r    k    g
7 998244353  119  23    3
8 1004535809 479  21    3
9
10 P          r    k    g
11 3          1    1    2
12 5          1    2    2
13 17         1    4    3
14 97         3    5    5
15 193        3    6    5
16 257        1    8    3
17 7681       15    9   17
18 12289      3   12   11
19 40961      5   13    3
20 65537      1   16    3
21 786433     3   18   10
22 5767169   11   19    3
23 7340033    7   20    3
24 23068673   11   21    3
25 104857601  25   22    3
26 167772161  5   25    3
27 469762049  7   26    3
28 1004535809 479  21    3
29 2013265921 15   27   31

```



```

30 2281701377      17 27 3
31 3221225473      3 30 5
32 75161927681     35 31 3
33 77309411329      9 33 7
34 206158430209      3 36 22
35 2061584302081    15 37 7
36 2748779069441     5 39 3
37 6597069766657     3 41 5
38 3958241859937      9 42 5
39 79164837199873     9 43 5
40 263882790666241    15 44 7
41 1231453023109121   35 45 3
42 1337006139375617   19 46 3
43 3799912185593857   27 47 5
44 4222124650659841   15 48 19
45 7881299347898369    7 50 6
46 31525197391593473   7 52 3
47 180143985094819841  5 55 6
48 1945555039024054273 27 56 5
49 4179340454199820289 29 57 3
50 9097271247288401921 505 54 6 */
51
52 const int g = 3;
53 const ll MOD = 998244353;
54
55 ll pw(ll a, ll n) { /* fast pow */ }
56
57 #define siz(x) (int)x.size()
58
59 template<typename T>
60 vector<T>& operator+=(vector<T>& a, const vector<T>& b) {
61     if (siz(a) < siz(b)) a.resize(siz(b));
62     for (int i = 0; i < min(siz(a), siz(b)); i++) {
63         a[i] += b[i];
64         a[i] -= a[i] >= MOD ? MOD : 0;
65     }
66     return a;
67 }
68
69 template<typename T>
70 vector<T>& operator--(vector<T>& a, const vector<T>& b) {
71     if (siz(a) < siz(b)) a.resize(siz(b));
72     for (int i = 0; i < min(siz(a), siz(b)); i++) {
73         a[i] -= b[i];
74         a[i] += a[i] < 0 ? MOD : 0;
75     }
76     return a;
77 }
78
79 template<typename T>
80 vector<T> operator-(const vector<T>& a) {
81     vector<T> ret(siz(a));
82     for (int i = 0; i < siz(a); i++) {
83         ret[i] = -a[i] < 0 ? -a[i] + MOD : -a[i];
84     }
85     return ret;
86 }
87
88 vector<ll> X, iX;
89 vector<int> rev;
90
91 void init_ntt() {
92     X.clear(); X.resize(maxn, 1); // x1 = g^((p-1)/n)
93     iX.clear(); iX.resize(maxn, 1);
94
95     ll u = pw(g, (MOD-1)/maxn);
96     ll iu = pw(u, MOD-2);
97
98     for (int i = 1; i < maxn; i++) {
99         X[i] = X[i-1] * u;
100         iX[i] = iX[i-1] * iu;
101         if (X[i] >= MOD) X[i] %= MOD;
102         if (iX[i] >= MOD) iX[i] %= MOD;
103     }
104
105     rev.clear(); rev.resize(maxn, 0);
106     for (int i = 1, hb = -1; i < maxn; i++) {
107         if (!(i & (i-1))) hb++;
108         rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
109     } }
110
111 template<typename T>
112 void NTT(vector<T>& a, bool inv=false) {
113
114     int _n = (int)a.size();
115     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
116     int n = 1<<k;
117     a.resize(n, 0);
118
119     short shift = maxk-k;
120     for (int i = 0; i < n; i++)
121         if (i > (rev[i]>>shift))
122             swap(a[i], a[rev[i]>>shift]);
123
124     for (int len = 2, half = 1, div = maxn>>1; len <= n
125         ; len<=1, half<=1, div>>=1) {
126         for (int i = 0; i < n; i += len) {
127             for (int j = 0; j < half; j++) {
128                 T u = a[i+j];
129                 T v = a[i+j+half] * (inv ? iX[j*div] :
130                     X[j*div]) % MOD;
131                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
132                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
133             } }
134     }
135
136     if (inv) {
137         T dn = pw(n, MOD-2);
138         for (auto& x : a) {
139             x *= dn;
140             if (x >= MOD) x %= MOD;
141         } }
142 }
143
144 template<typename T>
145 inline void resize(vector<T>& a) {
146     int cnt = (int)a.size();
147     for (; cnt > 0; cnt--) if (a[cnt-1]) break;
148     a.resize(max(cnt, 1));
149 }
150
151 template<typename T>
152 vector<T>& operator*=(vector<T>& a, vector<T> b) {
153     int na = (int)a.size();
154     int nb = (int)b.size();
155     a.resize(na + nb - 1, 0);
156     b.resize(na + nb - 1, 0);
157
158     NTT(a); NTT(b);
159     for (int i = 0; i < (int)a.size(); i++) {
160         a[i] *= b[i];
161         if (a[i] >= MOD) a[i] %= MOD;
162     }
163     NTT(a, true);
164
165     resize(a);
166     return a;
167 }
168
169 template<typename T>
170 void inv(vector<T>& ia, int N) {
171     vector<T> _a(move(ia));
172     ia.resize(1, pw(_a[0], MOD-2));
173     vector<T> a(1, -_a[0] + (-_a[0] < 0 ? MOD : 0));
174
175     for (int n = 1; n < N; n<=1) {
176         // n -> 2*n
177         // ia' = ia(2-a*ia);
178
179         for (int i = n; i < min(siz(_a), (n<<1)); i++)
180             a.emplace_back(-_a[i] + (-_a[i] < 0 ? MOD : 0));
181
182         vector<T> tmp = ia;
183         ia *= a;
184         ia.resize(n<<1);
185         ia[0] = ia[0] + 2 >= MOD ? ia[0] + 2 - MOD : ia
186             [0] + 2;
187         ia *= tmp;
188         ia.resize(n<<1);
189     }
190     ia.resize(N);
191 }

```

```

187 template<typename T>
188 void mod(vector<T>& a, vector<T>& b) {
189     int n = (int)a.size()-1, m = (int)b.size()-1;
190     if (n < m) return;
191
192     vector<T> ra = a, rb = b;
193     reverse(ra.begin(), ra.end()); ra.resize(min(n+1, n
194         -m+1));
195     reverse(rb.begin(), rb.end()); rb.resize(min(m+1, n
196         -m+1));
197
198     inv(rb, n-m+1);
199
200     vector<T> q = move(ra);
201     q *= rb;
202     q.resize(n-m+1);
203     reverse(q.begin(), q.end());
204
205     q *= b;
206     a -= q;
207     resize(a);
208 }
209 /* Kitamasa Method (Fast Linear Recurrence):
210 Find a[K] (Given a[j] = c[0]a[j-N] + ... + c[N-1]a[j
211     -1])
212 Let B(x) = x^N - c[N-1]x^(N-1) - ... - c[1]x^1 - c[0]
213 Let R(x) = x^K mod B(x) (get x^K using fast pow and
214     use poly mod to get R(x))
215 Let r[i] = the coefficient of x^i in R(x)
216 => a[K] = a[0]r[0] + a[1]r[1] + ... + a[N-1]r[N-1] */

```

9 Linear Algebra

9.1 Gaussian-Jordan Elimination

```

1 int n;
2 vector<vector<ll>> v;
3 void gauss(vector<vector<ll>>& v) {
4     int r = 0;
5     for (int i = 0; i < n; i++) {
6         bool ok = false;
7         for (int j = r; j < n; j++) {
8             if (v[j][i] != 0) continue;
9             swap(v[j], v[r]);
10            ok = true;
11            break;
12        }
13        if (!ok) continue;
14        ll div = inv(v[r][i]);
15        for (int j = 0; j < n + 1; j++) {
16            v[r][j] *= div;
17            if (v[r][j] >= MOD) v[r][j] %= MOD;
18        }
19        for (int j = 0; j < n; j++) {
20            if (j == r) continue;
21            ll t = v[j][i];
22            for (int k = 0; k < n + 1; k++) {
23                v[j][k] -= v[r][k] * t % MOD;
24                if (v[j][k] < 0) v[j][k] += MOD;
25            }
26        }
27        r++;
28    }
29 }

```

9.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of \det :
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times \det$
 - Row Operation 3 - $k\vec{r}_i$ add to \vec{r}_j : Unchanged

10 Combinatorics

10.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

10.2 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

11 Special Numbers

11.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

11.2 Prime Numbers

- First 50 prime numbers:

1	2	3	5	7	11
6	13	17	19	23	29
11	31	37	41	43	47
16	53	59	61	67	71
21	73	79	83	89	97
26	101	103	107	109	113
31	127	131	137	139	149
36	151	157	163	167	173
41	179	181	191	193	197
46	199	211	223	227	229

- Very large prime numbers:

1000001333	1000500889	2500001909
2000000659	900004151	850001359

- $\pi(n) \equiv \text{Number of primes} \leq n \approx n/((\ln n) - 1)$
 $\pi(100) = 25, \pi(200) = 46$
 $\pi(500) = 95, \pi(1000) = 168$
 $\pi(2000) = 303, \pi(4000) = 550$
 $\pi(10^4) = 1229, \pi(10^5) = 9592$
 $\pi(10^6) = 78498, \pi(10^7) = 664579$

