

## Contents

<b>1</b>	<b>Reminder</b>	<b>1</b>
1.1	Bug List	1
1.2	OwO	1
<b>2</b>	<b>Basic</b>	<b>1</b>
2.1	Vimrc	1
2.2	Runcpp.sh	1
2.3	PBDS	1
2.4	Random	1
<b>3</b>	<b>Data Structure</b>	<b>1</b>
3.1	BIT	1
3.2	DSU	2
3.3	Segment Tree	2
3.4	Treap	2
3.5	Persistent Treap	2
3.6	Li Chao Tree	3
3.7	Sparse Table	3
3.8	Time Segment Tree	3
3.9	Dynamic Median	3
<b>4</b>	<b>Flow / Matching</b>	<b>4</b>
4.1	Dinic	4
4.2	MCMF	4
4.3	KM	5
4.4	Hopcroft-Karp	5
4.5	Blossom	6
4.6	Weighted Blossom	6
4.7	Cover / Independent Set	7
<b>5</b>	<b>Graph</b>	<b>8</b>
5.1	Heavy-Light Decomposition	8
5.2	Centroid Decomposition	8
5.3	Bellman-Ford + SPFA	8
5.4	BCC - AP	9
5.5	BCC - Bridge	10
5.6	SCC - Tarjan	10
5.7	SCC - Kosaraju	11
5.8	Eulerian Path - Undir	11
5.9	Eulerian Path - Dir	11
5.10	Hamilton Path	11
5.11	Kth Shortest Path	12
5.12	Hungarian Algorithm	13
5.13	System of Difference Constraints	13
<b>6</b>	<b>String</b>	<b>13</b>
6.1	Aho Corasick	13
6.2	KMP	14
6.3	Z Value	14
6.4	Manacher	14
6.5	Suffix Array	14
6.6	Minimum Rotation	15
6.7	Lyndon Factorization	15

6.8	Rolling Hash	15
6.9	Trie	15

<b>7</b>	<b>Geometry</b>	<b>15</b>
7.1	Basic Operations	15
7.2	SVG Writer	16
7.3	Sort by Angle	16
7.4	Line Intersection	16
7.5	Polygon Area	16
7.6	Convex Hull	16
7.7	Point In Convex	16
7.8	Point Segment Distance	16
7.9	Point in Polygon	16
7.10	Minimum Euclidean Distance	17
7.11	Minkowski Sum	17
7.12	Lower Concave Hull	17
7.13	Pick's Theorem	17
7.14	Vector In Polygon	17
7.15	Rotating SweepLine	17
7.16	Half Plane Intersection	17
7.17	Minimum Enclosing Circle	18
7.18	Tangents	18
7.19	Union of Circles	18
7.20	Union of Polygons	18
7.21	3D Point	18
7.22	3D Convex Hull	18
<b>8</b>	<b>Number Theory</b>	<b>18</b>
8.1	FFT	18
8.2	Pollard's rho	19
8.3	Miller Rabin	19
8.4	Fast Power	19
8.5	Extend GCD	19
8.6	Mu + Phi	20
8.7	Other Formulas	20
8.8	Polynomial	20
<b>9</b>	<b>Linear Algebra</b>	<b>22</b>
9.1	Gaussian-Jordan Elimination	22
9.2	Determinant	22
<b>10</b>	<b>Combinatorics</b>	<b>22</b>
10.1	Catalan Number	22
10.2	Burnside's Lemma	22
<b>11</b>	<b>Special Numbers</b>	<b>22</b>
11.1	Fibonacci Series	22
11.2	Prime Numbers	22

## 2 Basic

### 2.1 Vimrc

```
set number relativenumber ai t_Co=256 tabstop=4
set mouse=a shiftwidth=4 encoding=utf8
set bs=2 ruler laststatus=2 cmdheight=2
set clipboard=unnamedplus showcmd autoread
set belloff=all
filetype indent on

inoremap ( (<Esc>i
inoremap " "<Esc>i
inoremap [ [<Esc>i
inoremap ' '<Esc>i
inoremap { {<CR><Esc>ko

nnoremap <tab> gt
nnoremap <S-tab> gT
inoremap <C-n> <Esc>:tabnew<CR>
nnoremap <C-n> :tabnew<CR>

inoremap <F9> <Esc>:w<CR>:!/~/runcpp.sh %:p:t %:p:h<CR>
nnoremap <F9> :w<CR>:!/~/runcpp.sh %:p:t %:p:h<CR>

syntax on
colorscheme desert
set filetype=cpp
set background=dark
hi Normal ctermfg=white ctermbg=black
```

### 2.2 Runcpp.sh

```
#!/bin/bash
clear
echo "Start compiling $1..."
echo
g++ -O2 -std=c++20 -Wall -Wextra -Wshadow $2/$1 -o $2/
out
if [ "$?" -ne 0 ]
then
exit 1
fi
echo
echo "Done compiling"
echo "===== "
echo
echo "Input file:"
echo
cat $2/in.txt
echo
echo "===== "
echo
declare startTime=`date +%s%N`
$2/out < $2/in.txt > $2/out.txt
declare endTime=`date +%s%N`
delta=`expr $endTime - $startTime`
delta=`expr $delta / 1000000`
cat $2/out.txt
echo
echo "time: $delta ms"
```

### 2.3 PBDS

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

// map
tree<int, int, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// set
tree<int, null_type, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// hash table
gp_hash_table<int, int> ht;
ht.find(element);
```

## 1 Reminder

### 1.1 Bug List

- 沒開 long long
- 陣列戳出界 / 開不夠大 / 開太大本地 compile 噴怪 error
- 傳之前先確定選對檔案
- 寫好的函式忘記呼叫
- 變數打錯
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 i > 0
- std::sort 比較運算子寫成 < 或是讓 = 的情況為 true
- 漏 case / 分 case 要好好想
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr

### 1.2 OwO

- 可以構造複雜點的測資幫助思考
- 真的卡太久請跳題
- Enjoy The Contest!

```

17 ht.insert({key, value});
18 ht.erase(element);
19
20 // priority queue
21 __gnu_pbds::priority_queue<int, less<int>> big_q;
22 // Big First
23 __gnu_pbds::priority_queue<int, greater<int>> small_q;
24 // Small First
25 q1.join(q2); // join

```

## 2.4 Random

```

1 mt19937 gen(chrono::steady_clock::now().
  time_since_epoch().count());
2 uniform_int_distribution<int> dis(1, 100);
3 cout << dis(gen) << endl;
4 shuffle(v.begin(), v.end(), gen);

```

## 3 Data Structure

### 3.1 BIT

```

1 struct BIT {
2     int n;
3     long long bit[N];
4
5     void init(int x, vector<long long> &a) {
6         n = x;
7         for (int i = 1, j; i <= n; i++) {
8             bit[i] += a[i - 1], j = i + (i & -i);
9             if (j <= n) bit[j] += bit[i];
10        }
11    }
12
13    void update(int x, long long dif) {
14        while (x <= n) bit[x] += dif, x += x & -x;
15    }
16
17    long long query(int l, int r) {
18        if (l != 1) return query(1, r) - query(1, l - 1);
19
20        long long ret = 0;
21        while (l <= r) ret += bit[r], r -= r & -r;
22        return ret;
23    }
24 } bm;

```

### 3.2 DSU

```

1 struct DSU {
2     int h[N], s[N];
3
4     void init(int n) { iota(h, h + n + 1, 0), fill(s, s + n + 1, 1); }
5
6     int fh(int x) { return (h[x] == x ? x : h[x] = fh(h[x])); }
7
8     bool mer(int x, int y) {
9         x = fh(x), y = fh(y);
10        if (x == y) return 0;
11        if (s[x] < s[y]) swap(x, y);
12        s[x] += s[y], s[y] = 0;
13        h[y] = x;
14        return 1;
15    }
16 } bm;

```

### 3.3 Segment Tree

```

1 struct segtree {
2     int n, seg[1 << 19];
3
4     void init(int x) {
5         n = 1 << (lg(x) + 1);
6         for (int i = 1; i < 2 * n; i++)
7             seg[i] = inf;
8     }
9
10    void update(int x, int val) {

```

```

11        x += n;
12        seg[x] = val, x /= 2;
13        while (x)
14            seg[x] = min(seg[2 * x], seg[2 * x + 1]), x /= 2;
15    }
16
17    int query(int l, int r) {
18        l += n, r += n;
19        int ret = inf;
20        while (l < r) {
21            if (l & 1)
22                ret = min(ret, seg[l++]);
23            if (r & 1)
24                ret = min(ret, seg[--r]);
25            l /= 2, r /= 2;
26        }
27        return ret;
28    }
29 } bm;

```

### 3.4 Treap

```

1 mt19937 rng(random_device{}());
2 struct Treap {
3     Treap *l, *r;
4     int val, num, pri;
5     Treap(int k) {
6         l = r = NULL;
7         val = k;
8         num = 1;
9         pri = rng();
10    }
11};
12 int siz(Treap *now) { return now ? now->num : 0; }
13 void pull(Treap *&now) {
14     now->num = siz(now->l) + siz(now->r) + 1;
15 }
16 Treap *merge(Treap *a, Treap *b) {
17     if (!a || !b)
18         return a ? a : b;
19     else if (a->pri > b->pri) {
20         a->r = merge(a->r, b);
21         pull(a);
22         return a;
23     } else {
24         b->l = merge(a, b->l);
25         pull(b);
26         return b;
27     }
28 }
29 void split_size(Treap *rt, Treap *&a, Treap *&b, int val) {
30     if (!rt) {
31         a = b = NULL;
32         return;
33     }
34     if (siz(rt->l) + 1 > val) {
35         b = rt;
36         split_size(rt->l, a, b->l, val);
37         pull(b);
38     } else {
39         a = rt;
40         split_size(rt->r, a->r, b, val - siz(a->l) - 1);
41         pull(a);
42     }
43 }
44 void split_val(Treap *rt, Treap *&a, Treap *&b, int val) {
45     if (!rt) {
46         a = b = NULL;
47         return;
48     }
49     if (rt->val <= val) {
50         a = rt;
51         split_val(rt->r, a->r, b, val);
52         pull(a);
53     } else {
54         b = rt;
55         split_val(rt->l, a, b->l, val);
56         pull(b);

```

```

57     }
58 }
59 void treap_dfs(Treap *now) {
60     if (!now) return;
61     treap_dfs(now->l);
62     cout << now->val << " ";
63     treap_dfs(now->r);
64 }

```

### 3.5 Persistent Treap

```

1 struct node {
2     node *l, *r;
3     char c;
4     int v, sz;
5     node(char x = '$') : c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? b;
18     if (a->v < b->v) {
19         node* ret = new (ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     } else {
23         node* ret = new (ptr++) node(b);
24         ret->l = merge(a, ret->l); ret->pull();
25         return ret;
26     }
27 }
28 P<node*> split(node* p, int k) {
29     if (!p) return {nullptr, nullptr};
30     if (k >= size(p->l) + 1) {
31         auto [a, b] = split(p->r, k - size(p->l) - 1);
32         node* ret = new (ptr++) node(p);
33         ret->r = a; ret->pull();
34         return {ret, b};
35     } else {
36         auto [a, b] = split(p->l, k);
37         node* ret = new (ptr++) node(p);
38         ret->l = b; ret->pull();
39         return {a, ret};
40     }
41 }

```

### 3.6 Li Chao Tree

```

1 constexpr int maxn = 5e4 + 5;
2 struct line {
3     ld a, b;
4     ld operator()(ld x) { return a * x + b; }
5 } arr[(maxn + 1) << 2];
6 bool operator<(line a, line b) { return a.a < b.a; }
7 #define m ((l + r) >> 1)
8 void insert(line x, int i = 1, int l = 0, int r = maxn) {
9     if (r - l == 1) {
10         if (x(l) > arr[i](l))
11             arr[i] = x;
12         return;
13     }
14     line a = max(arr[i], x), b = min(arr[i], x);
15     if (a(m) > b(m))
16         arr[i] = a, insert(b, i << 1, l, m);
17     else
18         arr[i] = b, insert(a, i << 1 | 1, m, r);
19 }
20 ld query(int x, int i = 1, int l = 0, int r = maxn) {
21     if (x < l || r <= x) return -numeric_limits<ld>::
22         max();
23     if (r - l == 1) return arr[i](x);
24     return max({arr[i](x), query(x, i << 1, l, m),
25         query(x, i << 1 | 1, m, r)});

```

```

25 #undef m

```

### 3.7 Sparse Table

```

1 const int lgmx = 19;
2
3 int n, q;
4 int spt[lgmx][maxn];
5
6 void build() {
7     FOR(k, 1, lgmx, 1) {
8         for (int i = 0; i + (1 << k) - 1 < n; i++) {
9             spt[k][i] = min(spt[k - 1][i], spt[k - 1][i
10                 + (1 << (k - 1))]);
11         }
12     }
13 }
14 int query(int l, int r) {
15     int ln = len(l, r);
16     int lg = __lg(ln);
17     return min(spt[lg][l], spt[lg][r - (1 << lg) + 1]);
18 }

```

### 3.8 Time Segment Tree

```

1 constexpr int maxn = 1e5 + 5;
2 V<P<int>> arr[(maxn + 1) << 2];
3 V<int> dsu, sz;
4 V<tuple<int, int, int>> his;
5 int cnt, q;
6 int find(int x) {
7     return x == dsu[x] ? x : find(dsu[x]);
8 };
9 inline bool merge(int x, int y) {
10     int a = find(x), b = find(y);
11     if (a == b) return false;
12     if (sz[a] > sz[b]) swap(a, b);
13     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
14         sz[a];
15     return true;
16 };
17 inline void undo() {
18     auto [a, b, s] = his.back();
19     his.pop_back();
20     dsu[a] = a, sz[b] = s;
21 }
22 #define m ((l + r) >> 1)
23 void insert(int ql, int qr, P<int> x, int i = 1, int l
24     = 0, int r = q) {
25     // debug(ql, qr, x); return;
26     if (qr <= l || r <= ql) return;
27     if (ql <= l && r <= qr) {
28         arr[i].push_back(x);
29         return;
30     }
31     if (qr <= m)
32         insert(ql, qr, x, i << 1, l, m);
33     else if (m <= ql)
34         insert(ql, qr, x, i << 1 | 1, m, r);
35     else {
36         insert(ql, qr, x, i << 1, l, m);
37         insert(ql, qr, x, i << 1 | 1, m, r);
38     }
39 }
40 void traversal(V<int>& ans, int i = 1, int l = 0, int r
41     = q) {
42     int opcnt = 0;
43     // debug(i, l, r);
44     for (auto [a, b] : arr[i])
45         if (merge(a, b))
46             opcnt++, cnt--;
47     if (r - l == 1)
48         ans[l] = cnt;
49     else {
50         traversal(ans, i << 1, l, m);
51         traversal(ans, i << 1 | 1, m, r);
52     }
53     while (opcnt--)
54         undo(), cnt++;
55     arr[i].clear();

```

```

54 #undef m
55 inline void solve() {
56     int n, m;
57     cin >> n >> m >> q, q++;
58     dsu.resize(cnt = n), sz.assign(n, 1);
59     iota(dsu.begin(), dsu.end(), 0);
60     // a, b, time, operation
61     unordered_map<ll, V<int>> s;
62     for (int i = 0; i < m; i++) {
63         int a, b;
64         cin >> a >> b;
65         if (a > b) swap(a, b);
66         s[((ll)a << 32) | b].emplace_back(0);
67     }
68     for (int i = 1; i < q; i++) {
69         int op, a, b;
70         cin >> op >> a >> b;
71         if (a > b) swap(a, b);
72         switch (op) {
73             case 1:
74                 s[((ll)a << 32) | b].push_back(i);
75                 break;
76             case 2:
77                 auto tmp = s[((ll)a << 32) | b].back();
78                 s[((ll)a << 32) | b].pop_back();
79                 insert(tmp, i, P<int>>{a, b});
80             }
81     }
82     for (auto [p, v] : s) {
83         int a = p >> 32, b = p & -1;
84         while (v.size()) {
85             insert(v.back(), q, P<int>>{a, b});
86             v.pop_back();
87         }
88     }
89     V<int> ans(q);
90     traversal(ans);
91     for (auto i : ans)
92         cout << i << ' ';
93     cout << endl;
94 }

```

### 3.9 Dynamic Median

```

1 struct Dynamic_Median {
2     multiset<long long> lo, hi;
3     long long slo = 0, shi = 0;
4     void rebalance() {
5         // keep sz(lo) >= sz(hi) and sz(lo) - sz(hi) <= 1
6         while((int)lo.size() > (int)hi.size() + 1) {
7             auto it = prev(lo.end());
8             long long x = *it;
9             lo.erase(it); slo -= x;
10            hi.insert(x); shi += x;
11        }
12        while((int)lo.size() < (int)hi.size()) {
13            auto it = hi.begin();
14            long long x = *it;
15            hi.erase(it); shi -= x;
16            lo.insert(x); slo += x;
17        }
18    }
19    void add(long long x) {
20        if(lo.empty() || x <= *prev(lo.end())) {
21            lo.insert(x); slo += x;
22        }
23        else {
24            hi.insert(x); shi += x;
25        }
26        rebalance();
27    }
28    void remove_one(long long x) {
29        if(!lo.empty() && x <= *prev(lo.end())) {
30            auto it = lo.find(x);
31            if(it != lo.end()) {
32                lo.erase(it); slo -= x;
33            }
34            else {
35                auto it2 = hi.find(x);
36                hi.erase(it2); shi -= x;
37            }

```

```

38        }
39        else {
40            auto it = hi.find(x);
41            if(it != hi.end()) {
42                hi.erase(it); shi -= x;
43            }
44            else {
45                auto it2 = lo.find(x);
46                lo.erase(it2); slo -= x;
47            }
48        }
49        rebalance();
50    }
51 };

```

## 4 Flow / Matching

### 4.1 Dinic

```

1 struct Dinic {
2     struct Edge { int to, cap, rev; };
3     int n, s, t;
4     vector<vector<Edge>> g;
5     vector<int> level, it;
6
7     void init(int _n, int _s, int _t){
8         n=_n; s=_s; t=_t;
9         g.assign(n, {});
10        level.assign(n, 0);
11        it.assign(n, 0);
12    }
13    void add(int a, int b, int c){
14        Edge f{b, c, (int)g[b].size()};
15        Edge r{a, 0, (int)g[a].size()};
16        g[a].push_back(f);
17        g[b].push_back(r);
18    }
19    bool bfs(){
20        fill(level.begin(), level.end(), -1);
21        queue<int> q; level[s]=0; q.push(s);
22        while(!q.empty()){
23            int u=q.front(); q.pop();
24            for(const auto &e: g[u]){
25                if(e.cap>0 && level[e.to]==-1){
26                    level[e.to]=level[u]+1;
27                    q.push(e.to);
28                }
29            }
30        }
31        return level[t]!=-1;
32    }
33    int dfs(int u, int f){
34        if(!f || u==t) return f;
35        for(int &i=it[u]; i<(int)g[u].size(); ++i){
36            auto &e=g[u][i];
37            if(e.cap>0 && level[e.to]==level[u]+1){
38                int got=dfs(e.to, min(f, e.cap));
39                if(got){
40                    e.cap-=got;
41                    g[e.to][e.rev].cap+=got;
42                    return got;
43                }
44            }
45        }
46        return 0;
47    }
48    int maxflow(){
49        int flow=0, add;
50        while(bfs()){
51            fill(it.begin(), it.end(), 0);
52            while((add=dfs(s, INF))) flow+=add;
53        }
54        return flow;
55    }
56 };

```

### 4.2 MCMF

```

1 struct MCMF {
2     int n, s, t, par[N + 5], p_i[N + 5], dis[N + 5],
3         vis[N + 5];

```

```

3 struct edge {
4     int to, cap, rev, cost;
5 };
6 vector<edge> path[N];
7 void init(int _n, int _s, int _t) {
8     n = _n, s = _s, t = _t;
9     FOR(i, 0, 2 * n + 5)
10         par[i] = p_i[i] = vis[i] = 0;
11 }
12 void add(int a, int b, int c, int d) {
13     path[a].pb({b, c, sz(path[b]), d});
14     path[b].pb({a, 0, sz(path[a]) - 1, -d});
15 }
16 void spfa() {
17     FOR(i, 0, n * 2 + 5)
18         dis[i] = INF,
19         vis[i] = 0;
20     dis[s] = 0;
21     queue<int> q;
22     q.push(s);
23     while (!q.empty()) {
24         int now = q.front();
25         q.pop();
26         vis[now] = 0;
27         for (int i = 0; i < sz(path[now]); i++) {
28             edge e = path[now][i];
29             if (e.cap > 0 && dis[e.to] > dis[now] +
30                 e.cost) {
31                 dis[e.to] = dis[now] + e.cost;
32                 par[e.to] = now;
33                 p_i[e.to] = i;
34                 if (vis[e.to] == 0) {
35                     vis[e.to] = 1;
36                     q.push(e.to);
37                 }
38             }
39         }
40     }
41 }
42 pii flow() {
43     int flow = 0, cost = 0;
44     while (true) {
45         spfa();
46         if (dis[t] == INF)
47             break;
48         int mn = INF;
49         for (int i = t; i != s; i = par[i])
50             mn = min(mn, path[par[i]][p_i[i]].cap);
51         flow += mn;
52         cost += dis[t] * mn;
53         for (int i = t; i != s; i = par[i]) {
54             edge &now = path[par[i]][p_i[i]];
55             now.cap -= mn;
56             path[i][now.rev].cap += mn;
57         }
58         return mp(flow, cost);
59     }
60 };

```

### 4.3 KM

```

1 struct KM {
2     int n, mx[1005], my[1005], pa[1005];
3     int g[1005][1005], lx[1005], ly[1005], sy[1005];
4     bool vx[1005], vy[1005];
5     void init(int _n) {
6         n = _n;
7         FOR(i, 1, n + 1)
8             fill(g[i], g[i] + 1 + n, 0);
9     }
10    void add(int a, int b, int c) { g[a][b] = c; }
11    void augment(int y) {
12        for (int x, z; y; y = z)
13            x = pa[y], z = mx[x], my[y] = x, mx[x] = y;
14    }
15    void bfs(int st) {
16        FOR(i, 1, n + 1)
17            sy[i] = INF,
18            vx[i] = vy[i] = 0;
19        queue<int> q;
20        q.push(st);

```

```

21 for (;;) {
22     while (!q.empty()) {
23         int x = q.front();
24         q.pop();
25         vx[x] = 1;
26         FOR(y, 1, n + 1)
27             if (!vy[y]) {
28                 int t = lx[x] + ly[y] - g[x][y];
29                 if (t == 0) {
30                     pa[y] = x;
31                     if (!my[y]) {
32                         augment(y);
33                         return;
34                     }
35                     vy[y] = 1, q.push(my[y]);
36                 } else if (sy[y] > t)
37                     pa[y] = x, sy[y] = t;
38             }
39         }
40         int cut = INF;
41         FOR(y, 1, n + 1)
42             if (!vy[y] && cut > sy[y]) cut = sy[y];
43         FOR(j, 1, n + 1) {
44             if (vx[j]) lx[j] -= cut;
45             if (vy[j]) ly[j] += cut;
46             else sy[j] -= cut;
47         }
48         FOR(y, 1, n + 1) {
49             if (!vy[y] && sy[y] == 0) {
50                 if (!my[y]) {
51                     augment(y);
52                     return;
53                 }
54                 vy[y] = 1;
55                 q.push(my[y]);
56             }
57         }
58     }
59 }
60 }
61 }
62 int solve() {
63     fill(mx, mx + n + 1, 0);
64     fill(my, my + n + 1, 0);
65     fill(lx, lx + n + 1, 0);
66     fill(ly, ly + n + 1, 0);
67     FOR(x, 1, n + 1)
68         FOR(y, 1, n + 1)
69             lx[x] = max(lx[x], g[x][y]);
70     FOR(x, 1, n + 1)
71         bfs(x);
72     int ans = 0;
73     FOR(y, 1, n + 1)
74         ans += g[my[y]][y];
75     return ans;
76 }
77 };

```

### 4.4 Hopcroft-Karp

```

1 struct HopcroftKarp {
2     // id: X = [1, nx], Y = [nx+1, nx+ny]
3     int n, nx, ny, m, MXCNT;
4     vector<vector<int>> g;
5     vector<int> mx, my, dis, vis;
6     void init(int nnx, int nny, int mm) {
7         nx = nnx, ny = nny, m = mm;
8         n = nx + ny + 1;
9         g.clear();
10        g.resize(n);
11    }
12    void add(int x, int y) {
13        g[x].emplace_back(y);
14        g[y].emplace_back(x);
15    }
16    bool dfs(int x) {
17        vis[x] = true;
18        Each(y, g[x]) {
19            int px = my[y];
20            if (px == -1 ||
21                (dis[px] == dis[x] + 1 &&
22                 !vis[px] && dfs(px))) {

```

```

23         mx[x] = y;
24         my[y] = x;
25         return true;
26     }
27 }
28 return false;
29 }
30 void get() {
31     mx.clear();
32     mx.resize(n, -1);
33     my.clear();
34     my.resize(n, -1);
35
36     while (true) {
37         queue<int> q;
38         dis.clear();
39         dis.resize(n, -1);
40         for (int x = 1; x <= nx; x++) {
41             if (mx[x] == -1) {
42                 dis[x] = 0;
43                 q.push(x);
44             }
45         }
46         while (!q.empty()) {
47             int x = q.front();
48             q.pop();
49             Each(y, g[x]) {
50                 if (my[y] != -1 && dis[my[y]] ==
51                     -1) {
52                     dis[my[y]] = dis[x] + 1;
53                     q.push(my[y]);
54                 }
55             }
56
57             bool brk = true;
58             vis.clear();
59             vis.resize(n, 0);
60             for (int x = 1; x <= nx; x++)
61                 if (mx[x] == -1 && dfs(x))
62                     brk = false;
63
64             if (brk) break;
65         }
66         MXCNT = 0;
67         for (int x = 1; x <= nx; x++)
68             if (mx[x] != -1) MXCNT++;
69     }
70 } hk;

```

## 4.5 Blossom

```

1  const int N=5e2+10;
2  struct Graph{
3      int to[N],bro[N],head[N],e;
4      int lnk[N],vis[N],stp,n;
5      void init(int _n){
6          stp=0;e=1;n=_n;
7          FOR(i,0,n+1)head[i]=lnk[i]=vis[i]=0;
8      }
9      void add(int u,int v){
10         to[e]=v,bro[e]=head[u],head[u]=e++;
11         to[e]=u,bro[e]=head[v],head[v]=e++;
12     }
13     bool dfs(int x){
14         vis[x]=stp;
15         for(int i=head[x];i;i=bro[i])
16         {
17             int v=to[i];
18             if(!lnk[v])
19             {
20                 lnk[x]=v;lnk[v]=x;
21                 return true;
22             }
23             else if(vis[lnk[v]]<stp)
24             {
25                 int w=lnk[v];
26                 lnk[x]=v,lnk[v]=x,lnk[w]=0;
27                 if(dfs(w))return true;
28                 lnk[w]=v,lnk[v]=w,lnk[x]=0;
29             }
30         }

```

```

31         return false;
32     }
33     int solve(){
34         int ans=0;
35         FOR(i,1,n+1){
36             if(!lnk[i]){
37                 stp++;
38                 ans+=dfs(i);
39             }
40         }
41         return ans;
42     }
43     void print_matching(){
44         FOR(i,1,n+1)
45             if(i<graph.lnk[i])
46                 cout<<i<<" "<<graph.lnk[i]<<endl;
47     }
48 };

```

## 4.6 Weighted Blossom

```

1  struct WeightGraph { // 1-based
2      static const int inf = INT_MAX;
3      static const int maxn = 514;
4      struct edge {
5          int u, v, w;
6          edge() {}
7          edge(int u, int v, int w) : u(u), v(v), w(w) {}
8      };
9      int n, n_x;
10     edge g[maxn * 2][maxn * 2];
11     int lab[maxn * 2];
12     int match[maxn * 2], slack[maxn * 2], st[maxn * 2],
13         pa[maxn * 2];
14     int flo_from[maxn * 2][maxn + 1], S[maxn * 2], vis[
15         maxn * 2];
16     vector<int> flo[maxn * 2];
17     queue<int> q;
18     int e_delta(const edge &e) { return lab[e.u] + lab[
19         e.v] - g[e.u][e.v].w * 2; }
20     void update_slack(int u, int x) {
21         if (!slack[x] || e_delta(g[u][x]) < e_delta(g[
22             slack[x]][x])) slack[x] = u;
23     }
24     void set_slack(int x) {
25         slack[x] = 0;
26         for (int u = 1; u <= n; ++u)
27             if (g[u][x].w > 0 && st[u] != x && S[st[u]]
28                 == 0)
29                 update_slack(u, x);
30     }
31     void q_push(int x) {
32         if (x <= n)
33             q.push(x);
34         else
35             for (size_t i = 0; i < flo[x].size(); i++)
36                 q_push(flo[x][i]);
37     }
38     void set_st(int x, int b) {
39         st[x] = b;
40         if (x > n)
41             for (size_t i = 0; i < flo[x].size(); ++i)
42                 set_st(flo[x][i], b);
43     }
44     int get_pr(int b, int xr) {
45         int pr = find(flo[b].begin(), flo[b].end(), xr)
46             - flo[b].begin();
47         if (pr % 2 == 1) {
48             reverse(flo[b].begin() + 1, flo[b].end());
49             return (int)flo[b].size() - pr;
50         }
51         return pr;
52     }
53     void set_match(int u, int v) {
54         match[u] = g[u][v].v;
55         if (u <= n) return;
56         edge e = g[u][v];
57         int xr = flo_from[u][e.u], pr = get_pr(u, xr);
58         for (int i = 0; i < pr; ++i) set_match(flo[u][i]
59             ], flo[u][i ^ 1]);
60         set_match(xr, v);

```



```

52     rotate(flo[u].begin(), flo[u].begin() + pr, flo[u].end());
53 }
54 void augment(int u, int v) {
55     for (;;) {
56         int xnv = st[match[u]];
57         set_match(u, v);
58         if (!xnv) return;
59         set_match(xnv, st[pa[xnv]]);
60         u = st[pa[xnv]], v = xnv;
61     }
62 }
63 int get_lca(int u, int v) {
64     static int t = 0;
65     for (++t; u || v; swap(u, v)) {
66         if (u == 0) continue;
67         if (vis[u] == t) return u;
68         vis[u] = t;
69         u = st[match[u]];
70         if (u) u = st[pa[u]];
71     }
72     return 0;
73 }
74 void add_blossom(int u, int lca, int v) {
75     int b = n + 1;
76     while (b <= n_x && st[b]) ++b;
77     if (b > n_x) ++n_x;
78     lab[b] = 0, S[b] = 0;
79     match[b] = match[lca];
80     flo[b].clear();
81     flo[b].push_back(lca);
82     for (int x = u, y; x != lca; x = st[pa[y]])
83         flo[b].push_back(x), flo[b].push_back(y = st[match[x]]), q_push(y);
84     reverse(flo[b].begin() + 1, flo[b].end());
85     for (int x = v, y; x != lca; x = st[pa[y]])
86         flo[b].push_back(x), flo[b].push_back(y = st[match[x]]), q_push(y);
87     set_st(b, b);
88     for (int x = 1; x <= n_x; ++x) g[b][x].w = g[x][b].w = 0;
89     for (int x = 1; x <= n; ++x) flo_from[b][x] = 0;
90     for (size_t i = 0; i < flo[b].size(); ++i) {
91         int xs = flo[b][i];
92         for (int x = 1; x <= n_x; ++x)
93             if (g[b][x].w == 0 || e_delta(g[xs][x]) < e_delta(g[b][x]))
94                 g[b][x] = g[xs][x], g[x][b] = g[x][xs];
95         for (int x = 1; x <= n; ++x)
96             if (flo_from[xs][x]) flo_from[b][x] = xs;
97     }
98     set_slack(b);
99 }
100 void expand_blossom(int b) {
101     for (size_t i = 0; i < flo[b].size(); ++i)
102         set_st(flo[b][i], flo[b][i]);
103     int xr = flo_from[b][g[b][pa[b]].u], pr = get_pr(b, xr);
104     for (int i = 0; i < pr; i += 2) {
105         int xs = flo[b][i], xns = flo[b][i + 1];
106         pa[xs] = g[xns][xs].u;
107         S[xs] = 1, S[xns] = 0;
108         slack[xs] = 0, set_slack(xns);
109         q_push(xns);
110     }
111     S[xr] = 1, pa[xr] = pa[b];
112     for (size_t i = pr + 1; i < flo[b].size(); ++i) {
113         int xs = flo[b][i];
114         S[xs] = -1, set_slack(xs);
115     }
116     st[b] = 0;
117 }
118 bool on_found_edge(const edge &e) {
119     int u = st[e.u], v = st[e.v];
120     if (S[v] == -1) {
121         pa[v] = e.u, S[v] = 1;
122         int nu = st[match[v]];
123         slack[v] = slack[nu] = 0;
124
125         S[nu] = 0, q_push(nu);
126     } else if (S[v] == 0) {
127         int lca = get_lca(u, v);
128         if (!lca)
129             return augment(u, v), augment(v, u), true;
130         else
131             add_blossom(u, lca, v);
132     }
133     return false;
134 }
135 bool matching() {
136     memset(S + 1, -1, sizeof(int) * n_x);
137     memset(slack + 1, 0, sizeof(int) * n_x);
138     q = queue<int>();
139     for (int x = 1; x <= n_x; ++x)
140         if (st[x] == x && !match[x]) pa[x] = 0, S[x] = 0, q_push(x);
141     if (q.empty()) return false;
142     for (;;) {
143         while (q.size()) {
144             int u = q.front();
145             q.pop();
146             if (S[st[u]] == 1) continue;
147             for (int v = 1; v <= n; ++v)
148                 if (g[u][v].w > 0 && st[u] != st[v]) {
149                     if (e_delta(g[u][v]) == 0) {
150                         if (on_found_edge(g[u][v]))
151                             return true;
152                     } else
153                         update_slack(u, st[v]);
154                 }
155             int d = inf;
156             for (int b = n + 1; b <= n_x; ++b)
157                 if (st[b] == b && S[b] == 1) d = min(d, lab[b] / 2);
158             for (int x = 1; x <= n_x; ++x)
159                 if (st[x] == x && slack[x]) {
160                     if (S[x] == -1)
161                         d = min(d, e_delta(g[slack[x]][x]));
162                     else if (S[x] == 0)
163                         d = min(d, e_delta(g[slack[x]][x]) / 2);
164                 }
165             for (int u = 1; u <= n; ++u) {
166                 if (S[st[u]] == 0) {
167                     if (lab[u] <= d) return 0;
168                     lab[u] -= d;
169                 } else if (S[st[u]] == 1)
170                     lab[u] += d;
171             }
172             for (int b = n + 1; b <= n_x; ++b)
173                 if (st[b] == b) {
174                     if (S[st[b]] == 0)
175                         lab[b] += d * 2;
176                     else if (S[st[b]] == 1)
177                         lab[b] -= d * 2;
178                 }
179             q = queue<int>();
180             for (int x = 1; x <= n_x; ++x)
181                 if (st[x] == x && slack[x] && st[slack[x]] != x && e_delta(g[slack[x]][x]) == 0)
182                     if (on_found_edge(g[slack[x]][x]))
183                         return true;
184             for (int b = n + 1; b <= n_x; ++b)
185                 if (st[b] == b && S[b] == 1 && lab[b] == 0)
186                     expand_blossom(b);
187             return false;
188         }
189     }
190     pair<long long, int> solve() {
191         memset(match + 1, 0, sizeof(int) * n);
192         n_x = n;
193         int n_matches = 0;
194         long long tot_weight = 0;
195         for (int u = 0; u <= n; ++u) st[u] = u, flo[u].clear();
196         int w_max = 0;

```

```

194     for (int u = 1; u <= n; ++u)
195         for (int v = 1; v <= n; ++v) {
196             flo_from[u][v] = (u == v ? u : 0);
197             w_max = max(w_max, g[u][v].w);
198         }
199     for (int u = 1; u <= n; ++u) lab[u] = w_max;
200     while (matching()) ++n_matches;
201     for (int u = 1; u <= n; ++u)
202         if (match[u] && match[u] < u)
203             tot_weight += g[u][match[u]].w;
204     return make_pair(tot_weight, n_matches);
205 }
206 void add_edge(int ui, int vi, int wi) { g[ui][vi].w
    = g[vi][ui].w = wi; }
207 void init(int _n) {
208     n = _n;
209     for (int u = 1; u <= n; ++u)
210         for (int v = 1; v <= n; ++v)
211             g[u][v] = edge(u, v, 0);
212 }
213 };

```

## 4.7 Cover / Independent Set

```

1 V(E) Cover: choose some V(E) to cover all E(V)
2 V(E) Independ: set of V(E) not adj to each other
3
4 M = Max Matching
5 Cv = Min V Cover
6 Ce = Min E Cover
7 Iv = Max V Ind
8 Ie = Max E Ind (equiv to M)
9
10 M = Cv (Konig Theorem)
11 Iv = V \ Cv
12 Ce = V - M
13
14 Construct Cv:
15 1. Run Dinic
16 2. Find s-t min cut
17 3. Cv = {X in T} + {Y in S}

```

# 5 Graph

## 5.1 Heavy-Light Decomposition

```

1 const int N = 2e5 + 5;
2 int n, dfn[N], son[N], top[N], num[N], dep[N], p[N];
3 vector<int> path[N];
4 struct node {
5     int mx, sum;
6 } seg[N << 2];
7 void update(int x, int l, int r, int qx, int val) {
8     if (l == r) {
9         seg[x].mx = seg[x].sum = val;
10        return;
11    }
12    int mid = (l + r) >> 1;
13    if (qx <= mid) update(x << 1, l, mid, qx, val);
14    else update(x << 1 | 1, mid + 1, r, qx, val);
15    seg[x].mx = max(seg[x << 1].mx, seg[x << 1 | 1].mx);
16    seg[x].sum = seg[x << 1].sum + seg[x << 1 | 1].sum;
17 }
18 int big(int x, int l, int r, int ql, int qr) {
19     if (ql <= l && r <= qr) return seg[x].mx;
20     int mid = (l + r) >> 1;
21     int res = -INF;
22     if (ql <= mid) res = max(res, big(x << 1, l, mid,
23         ql, qr));
24     if (mid < qr) res = max(res, big(x << 1 | 1, mid +
25         1, r, ql, qr));
26     return res;
27 }
28 int ask(int x, int l, int r, int ql, int qr) {
29     if (ql <= l && r <= qr) return seg[x].sum;
30     int mid = (l + r) >> 1;
31     int res = 0;
32     if (ql <= mid) res += ask(x << 1, l, mid, ql, qr);
33     if (mid < qr) res += ask(x << 1 | 1, mid + 1, r, ql
34         , qr);

```

```

32     return res;
33 }
34 void dfs1(int now) {
35     son[now] = -1;
36     num[now] = 1;
37     for (auto i : path[now]) {
38         if (!dep[i]) {
39             dep[i] = dep[now] + 1;
40             p[i] = now;
41             dfs1(i);
42             num[now] += num[i];
43             if (son[now] == -1 || num[i] > num[son[now]
44                 ]) son[now] = i;
45         }
46     }
47     int cnt;
48     void dfs2(int now, int t) {
49         top[now] = t;
50         cnt++;
51         dfn[now] = cnt;
52         if (son[now] == -1) return;
53         dfs2(son[now], t);
54         for (auto i : path[now])
55             if (i != p[now] && i != son[now]) dfs2(i, i);
56     }
57     int path_big(int x, int y) {
58         int res = -INF;
59         while (top[x] != top[y]) {
60             if (dep[top[x]] < dep[top[y]]) swap(x, y);
61             res = max(res, big(1, 1, n, dfn[top[x]], dfn[x
62                 ]));
63             x = p[top[x]];
64         }
65         if (dfn[x] > dfn[y]) swap(x, y);
66         res = max(res, big(1, 1, n, dfn[x], dfn[y]));
67         return res;
68     }
69     int path_sum(int x, int y) {
70         int res = 0;
71         while (top[x] != top[y]) {
72             if (dep[top[x]] < dep[top[y]]) swap(x, y);
73             res += ask(1, 1, n, dfn[top[x]], dfn[x]);
74             x = p[top[x]];
75         }
76         if (dfn[x] > dfn[y]) swap(x, y);
77         res += ask(1, 1, n, dfn[x], dfn[y]);
78         return res;
79     }
80     void buildTree() {
81         FOR(i, 0, n - 1) {
82             int a, b;
83             cin >> a >> b;
84             path[a].pb(b);
85             path[b].pb(a);
86         }
87     }
88     void buildHLD(int root) {
89         dep[root] = 1;
90         dfs1(root);
91         dfs2(root, root);
92         FOR(i, 1, n + 1) {
93             int now;
94             cin >> now;
95             update(1, 1, n, dfn[i], now);
96         }

```

## 5.2 Centroid Decomposition

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int N = 1e5 + 5;
4 vector<int> a[N];
5 int sz[N], lv[N];
6 bool used[N];
7 int f_sz(int x, int p) {
8     sz[x] = 1;
9     for (int i : a[x])
10         if (i != p && !used[i])
11             sz[x] += f_sz(i, x);
12     return sz[x];

```



```

13 }
14 int f_cen(int x, int p, int total) {
15     for (int i : a[x]) {
16         if (i != p && !used[i] && 2 * sz[i] > total)
17             return f_cen(i, x, total);
18     }
19     return x;
20 }
21 void cd(int x, int p) {
22     int total = f_sz(x, p);
23     int cen = f_cen(x, p, total);
24     lv[cen] = lv[p] + 1;
25     used[cen] = 1;
26     // cout << "cd: " << x << " " << p << " " << cen <<
27     // "\n";
28     for (int i : a[cen]) {
29         if (!used[i])
30             cd(i, cen);
31     }
32 }
33 int main() {
34     ios_base::sync_with_stdio(0);
35     cin.tie(0);
36     int n;
37     cin >> n;
38     for (int i = 0, x, y; i < n - 1; i++) {
39         cin >> x >> y;
40         a[x].push_back(y);
41         a[y].push_back(x);
42     }
43     cd(1, 0);
44     for (int i = 1; i <= n; i++)
45         cout << (char)('A' + lv[i] - 1) << " ";
46     cout << "\n";

```

### 5.3 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll> > > g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n + 1, LINF);
15     negCycle.assign(n + 1, false);
16     rlx.assign(n + 1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n + 1, false);
19     pa.assign(n + 1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s);
24         inq[s] = true;
25     }
26
27     while (!q.empty()) {
28         int u = q.front();
29         q.pop();
30         inq[u] = false;
31         if (rlx[u] >= n) {
32             negCycle[u] = true;
33         } else
34             for (auto& e : g[u]) {
35                 int v = e.first;
36                 ll w = e.second;
37                 if (dis[v] > dis[u] + w) {
38                     dis[v] = dis[u] + w;
39                     rlx[v] = rlx[u] + 1;
40                     pa[v] = u;
41                     if (!inq[v]) {
42                         q.push(v);
43                         inq[v] = true;
44                     }

```

```

45     }
46     }
47 }
48
49 // Bellman-Ford
50 queue<int> q;
51 vector<int> pa;
52 void BellmanFord(vector<int>& src) {
53     dis.assign(n + 1, LINF);
54     negCycle.assign(n + 1, false);
55     pa.assign(n + 1, -1);
56
57     for (auto& s : src) dis[s] = 0;
58
59     for (int rlx = 1; rlx <= n; rlx++) {
60         for (int u = 1; u <= n; u++) {
61             if (dis[u] == LINF) continue; // Important
62             //
63             for (auto& e : g[u]) {
64                 int v = e.first;
65                 ll w = e.second;
66                 if (dis[v] > dis[u] + w) {
67                     dis[v] = dis[u] + w;
68                     pa[v] = u;
69                     if (rlx == n) negCycle[v] = true;
70                 }
71             }
72         }
73     }
74 }
75
76 // Negative Cycle Detection
77 void NegCycleDetect() {
78     /* No Neg Cycle: NO
79     Exist Any Neg Cycle:
80     YES
81     v0 v1 v2 ... vk v0 */
82
83     vector<int> src;
84     for (int i = 1; i <= n; i++)
85         src.emplace_back(i);
86
87     SPFA(src);
88     // BellmanFord(src);
89
90     int ptr = -1;
91     for (int i = 1; i <= n; i++)
92         if (negCycle[i]) {
93             ptr = i;
94             break;
95         }
96
97     if (ptr == -1) {
98         return cout << "NO" << endl, void();
99     }
100
101     cout << "YES\n";
102     vector<int> ans;
103     vector<bool> vis(n + 1, false);
104
105     while (true) {
106         ans.emplace_back(ptr);
107         if (vis[ptr]) break;
108         vis[ptr] = true;
109         ptr = pa[ptr];
110     }
111     reverse(ans.begin(), ans.end());
112
113     vis.assign(n + 1, false);
114     for (auto& x : ans) {
115         cout << x << ' ';
116         if (vis[x]) break;
117         vis[x] = true;
118     }
119     cout << endl;
120 }
121
122 // Distance Calculation
123 void calcDis(int s) {
124     vector<int> src;
125     src.emplace_back(s);

```

```

126 SPFA(src);
127 // BellmanFord(src);
128
129 while (!q.empty()) q.pop();
130 for (int i = 1; i <= n; i++)
131     if (negCycle[i]) q.push(i);
132
133 while (!q.empty()) {
134     int u = q.front();
135     q.pop();
136     for (auto& e : g[u]) {
137         int v = e.first;
138         if (!negCycle[v]) {
139             q.push(v);
140             negCycle[v] = true;
141         }
142     }
143 }
144 }

```

## 5.4 BCC - AP

```

1 int n, m;
2 int low[maxn], dfn[maxn], instp;
3 vector<int> E, g[maxn];
4 bitset<maxn> isap;
5 bitset<maxn> vis;
6 stack<int> stk;
7 int bccnt;
8 vector<int> bcc[maxn];
9 inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e] ^ u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++;
30             dfs(v);
31             low[u] = min(low[u], low[v]);
32             if (!rt && low[v] >= dfn[u]) {
33                 // bcc found: u is ap
34                 isap[u] = true;
35                 popout(u);
36             }
37         } else {
38             // back edge
39             low[u] = min(low[u], dfn[v]);
40         }
41     }
42     // special case: root
43     if (rt) {
44         if (kid > 1) isap[u] = true;
45         popout(u);
46     }
47 }
48 void init() {
49     cin >> n >> m;
50     fill(low, low + maxn, INF);
51     REP(i, m) {
52         int u, v;
53         cin >> u >> v;
54         g[u].emplace_back(i);
55         g[v].emplace_back(i);
56         E.emplace_back(u ^ v);
57     }
58 }
59 void solve() {
60     FOR(i, 1, n + 1, 1) {

```

```

61         if (!dfn[i]) dfs(i, true);
62     }
63     vector<int> ans;
64     int cnt = 0;
65     FOR(i, 1, n + 1, 1) {
66         if (isap[i]) cnt++, ans.emplace_back(i);
67     }
68     cout << cnt << endl;
69     Each(i, ans) cout << i << ' ';
70     cout << endl;
71 }

```

## 5.5 BCC - Bridge

```

1 int n, m;
2 vector<int> g[maxn], E;
3 int low[maxn], dfn[maxn], instp;
4 int bccnt, bccid[maxn];
5 stack<int> stk;
6 bitset<maxn> vis, isbrg;
7 void init() {
8     cin >> n >> m;
9     REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u ^ v);
13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low + maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e] ^ u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         } else {
40             // tree edge
41             dfs(v);
42             low[u] = min(low[u], low[v]);
43             if (low[v] == dfn[v]) {
44                 isbrg[e] = true;
45                 popout(u);
46             }
47         }
48     }
49 }
50 void solve() {
51     FOR(i, 1, n + 1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n + 1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e] ^ u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

## 5.6 SCC - Tarjan

```

1 // 2-SAT
2 vector<int> E, g[maxn]; // 1~n, n+1~2n
3 int low[maxn], in[maxn], instp;
4 int sccnt, sccid[maxn];
5 stack<int> stk;
6 bitset<maxn> ins, vis;
7 int n, m;
8 void init() {
9     cin >> n >> m;
10    E.clear();
11    fill(g, g + maxn, vector<int>());
12    fill(low, low + maxn, INF);
13    memset(in, 0, sizeof(in));
14    instp = 1;
15    sccnt = 0;
16    memset(sccid, 0, sizeof(sccid));
17    ins.reset();
18    vis.reset();
19 }
20 inline int no(int u) {
21     return (u > n ? u - n : u + n);
22 }
23 int ecnt = 0;
24 inline void clause(int u, int v) {
25     E.eb(no(u) ^ v);
26     g[no(u)].eb(ecnt++);
27     E.eb(no(v) ^ u);
28     g[no(v)].eb(ecnt++);
29 }
30 void dfs(int u) {
31     in[u] = instp++;
32     low[u] = in[u];
33     stk.push(u);
34     ins[u] = true;
35
36     Each(e, g[u]) {
37         if (vis[e]) continue;
38         vis[e] = true;
39
40         int v = E[e] ^ u;
41         if (ins[v])
42             low[u] = min(low[u], in[v]);
43         else if (!in[v]) {
44             dfs(v);
45             low[u] = min(low[u], low[v]);
46         }
47     }
48     if (low[u] == in[u]) {
49         sccnt++;
50         while (!stk.empty()) {
51             int v = stk.top();
52             stk.pop();
53             ins[v] = false;
54             sccid[v] = sccnt;
55             if (u == v) break;
56         }
57     }
58 }
59 int main() {
60     init();
61     REP(i, m) {
62         char su, sv;
63         int u, v;
64         cin >> su >> u >> sv >> v;
65         if (su == '-') u = no(u);
66         if (sv == '-') v = no(v);
67         clause(u, v);
68     }
69     FOR(i, 1, 2 * n + 1, 1) {
70         if (!in[i]) dfs(i);
71     }
72     FOR(u, 1, n + 1, 1) {
73         int du = no(u);
74         if (sccid[u] == sccid[du]) {
75             return cout << "IMPOSSIBLE\n", 0;
76         }
77     }
78     FOR(u, 1, n + 1, 1) {
79         int du = no(u);

```

```

80         cout << (sccid[u] < sccid[du] ? '+' : '-') << '
81         '
82     }
83     cout << endl;
84 }

```

## 5.7 SCC - Kosaraju

```

1 const int N = 1e5 + 10;
2 vector<int> ed[N], ed_b[N]; // 反邊
3 vector<int> SCC(N); // 最後SCC的分組
4 bitset<N> vis;
5 int SCC_cnt;
6 int n, m;
7 vector<int> pre; // 後序遍歷
8
9 void dfs(int x) {
10     vis[x] = 1;
11     for (int i : ed[x]) {
12         if (vis[i]) continue;
13         dfs(i);
14     }
15     pre.push_back(x);
16 }
17
18 void dfs2(int x) {
19     vis[x] = 1;
20     SCC[x] = SCC_cnt;
21     for (int i : ed_b[x]) {
22         if (vis[i]) continue;
23         dfs2(i);
24     }
25 }
26
27 void kosaraju() {
28     for (int i = 1; i <= n; i++) {
29         if (!vis[i]) {
30             dfs(i);
31         }
32     }
33     SCC_cnt = 0;
34     vis = 0;
35     for (int i = n - 1; i >= 0; i--) {
36         if (!vis[pre[i]]) {
37             SCC_cnt++;
38             dfs2(pre[i]);
39         }
40     }
41 }

```

## 5.8 Eulerian Path - Undir

```

1 // from 1 to n
2 #define gg return cout << "IMPOSSIBLE\n", void();
3
4 int n, m;
5 vector<int> g[maxn];
6 bitset<maxn> inodd;
7
8 void init() {
9     cin >> n >> m;
10    inodd.reset();
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;
14        inodd[u] = inodd[u] ^ true;
15        inodd[v] = inodd[v] ^ true;
16        g[u].emplace_back(v);
17        g[v].emplace_back(u);
18    }
19 }
20 stack<int> stk;
21 void dfs(int u) {
22     while (!g[u].empty()) {
23         int v = g[u].back();
24         g[u].pop_back();
25         dfs(v);
26     }
27     stk.push(u);
28 }

```

## 5.9 Eulerian Path - Dir

```

1 // from node 1 to node n
2 #define gg return cout << "IMPOSSIBLE\n", 0
3
4 int n, m;
5 vector<int> g[maxn];
6 stack<int> stk;
7 int in[maxn], out[maxn];
8
9 void init() {
10     cin >> n >> m;
11     for (int i = 0; i < m; i++) {
12         int u, v;
13         cin >> u >> v;
14         g[u].emplace_back(v);
15         out[u]++, in[v]++;
16     }
17     for (int i = 1; i <= n; i++) {
18         if (i == 1 && out[i] - in[i] != 1) gg;
19         if (i == n && in[i] - out[i] != 1) gg;
20         if (i != 1 && i != n && in[i] != out[i]) gg;
21     }
22 }
23 void dfs(int u) {
24     while (!g[u].empty()) {
25         int v = g[u].back();
26         g[u].pop_back();
27         dfs(v);
28     }
29     stk.push(u);
30 }
31 void solve() {
32     dfs(1) for (int i = 1; i <= n; i++) if ((int)g[i].
33         size()) gg;
34     while (!stk.empty()) {
35         int u = stk.top();
36         stk.pop();
37         cout << u << ' ';
38     }
39 }

```

## 5.10 Hamilton Path

```

1 // top down DP
2 // Be Aware Of Multiple Edges
3 int n, m;
4 ll dp[maxn][1<<maxn];
5 int adj[maxn][maxn];
6
7 void init() {
8     cin >> n >> m;
9     fill(dp[0], dp[maxn-1]+(1<<maxn), -1);
10 }
11
12 void DP(int i, int msk) {
13     if (dp[i][msk] != -1) return;
14     dp[i][msk] = 0;
15     REP(j, n) if (j != i && (msk & (1<<j)) && adj[j][i]) {
16         int sub = msk ^ (1<<i);
17         if (dp[j][sub] == -1) DP(j, sub);
18         dp[i][msk] += dp[j][sub] * adj[j][i];
19         if (dp[i][msk] >= MOD) dp[i][msk] %= MOD;
20     }
21 }
22
23 int main() {
24     WiWiHorz
25     init();
26
27     REP(i, m) {
28         int u, v;
29         cin >> u >> v;
30         if (u == v) continue;
31         adj[--u][--v]++;
32     }
33
34     dp[0][1] = 1;
35     FOR(i, 1, n, 1) {
36         dp[i][1] = 0;

```

```

38         dp[i][1|(1<<i)] = adj[0][i];
39     }
40     FOR(msk, 1, (1<<n), 1) {
41         if (msk == 1) continue;
42         dp[0][msk] = 0;
43     }
44
45     DP(n-1, (1<<n)-1);
46     cout << dp[n-1][(1<<n)-1] << endl;
47
48     return 0;
49 }

```

## 5.11 Kth Shortest Path

```

1 // time: O(|E| \lg |E| + |V| \lg |V| + K)
2 // memory: O(|E| \lg |E| + |V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v;
6         ll d;
7         nd(int ui = 0, int vi = 0, ll di = INF) {
8             u = ui;
9             v = vi;
10            d = di;
11        }
12    };
13    struct heap {
14        nd* edge;
15        int dep;
16        heap* chd[4];
17    };
18    static int cmp(heap* a, heap* b) { return a->edge->
19        d > b->edge->d; }
20    struct node {
21        int v;
22        ll d;
23        heap* H;
24        nd* E;
25        node() {}
26        node(ll _d, int _v, nd* _E) {
27            d = _d;
28            v = _v;
29            E = _E;
30        }
31        node(heap* _H, ll _d) {
32            H = _H;
33            d = _d;
34        }
35        friend bool operator<(node a, node b) { return
36            a.d > b.d; }
37    };
38    int n, k, s, t, dst[N];
39    nd* nxt[N];
40    vector<nd*> g[N], rg[N];
41    heap *nullNd, *head[N];
42    void init(int _n, int _k, int _s, int _t) {
43        n = _n;
44        k = _k;
45        s = _s;
46        t = _t;
47        for (int i = 1; i <= n; i++) {
48            g[i].clear();
49            rg[i].clear();
50            nxt[i] = NULL;
51            head[i] = NULL;
52            dst[i] = -1;
53        }
54    }
55    void addEdge(int ui, int vi, ll di) {
56        nd* e = new nd(ui, vi, di);
57        g[ui].push_back(e);
58        rg[vi].push_back(e);
59    }
60    queue<int> dfsQ;
61    void dijkstra() {
62        while (dfsQ.size()) dfsQ.pop();
63        priority_queue<node> Q;
64        Q.push(node(0, t, NULL));
65        while (!Q.empty()) {
66            node p = Q.top();

```

```

65     Q.pop();
66     if (dst[p.v] != -1) continue;
67     dst[p.v] = p.d;
68     nxt[p.v] = p.E;
69     dfsQ.push(p.v);
70     for (auto e : rg[p.v]) Q.push(node(p.d + e
71         ->d, e->u, e));
72 }
73 heap* merge(heap* curNd, heap* newNd) {
74     if (curNd == nullNd) return newNd;
75     heap* root = new heap;
76     memcpy(root, curNd, sizeof(heap));
77     if (newNd->edge->d < curNd->edge->d) {
78         root->edge = newNd->edge;
79         root->chd[2] = newNd->chd[2];
80         root->chd[3] = newNd->chd[3];
81         newNd->edge = curNd->edge;
82         newNd->chd[2] = curNd->chd[2];
83         newNd->chd[3] = curNd->chd[3];
84     }
85     if (root->chd[0]->dep < root->chd[1]->dep)
86         root->chd[0] = merge(root->chd[0], newNd);
87     else
88         root->chd[1] = merge(root->chd[1], newNd);
89     root->dep = max(root->chd[0]->dep,
90         root->chd[1]->dep) +
91         1;
92     return root;
93 }
94 vector<heap*> V;
95 void build() {
96     nullNd = new heap;
97     nullNd->dep = 0;
98     nullNd->edge = new nd;
99     fill(nullNd->chd, nullNd->chd + 4, nullNd);
100    while (not dfsQ.empty()) {
101        int u = dfsQ.front();
102        dfsQ.pop();
103        if (!nxt[u])
104            head[u] = nullNd;
105        else
106            head[u] = head[nxt[u]->v];
107        V.clear();
108        for (auto& e : g[u]) {
109            int v = e->v;
110            if (dst[v] == -1) continue;
111            e->d += dst[v] - dst[u];
112            if (nxt[u] != e) {
113                heap* p = new heap;
114                fill(p->chd, p->chd + 4, nullNd);
115                p->dep = 1;
116                p->edge = e;
117                V.push_back(p);
118            }
119        }
120        if (V.empty()) continue;
121        make_heap(V.begin(), V.end(), cmp);
122    #define L(X) ((X << 1) + 1)
123    #define R(X) ((X << 1) + 2)
124    for (size_t i = 0; i < V.size(); i++) {
125        if (L(i) < V.size())
126            V[i]->chd[2] = V[L(i)];
127        else
128            V[i]->chd[2] = nullNd;
129        if (R(i) < V.size())
130            V[i]->chd[3] = V[R(i)];
131        else
132            V[i]->chd[3] = nullNd;
133    }
134    head[u] = merge(head[u], V.front());
135 }
136 }
137 vector<ll> ans;
138 void first_K() {
139     ans.clear();
140     priority_queue<node> Q;
141     if (dst[s] == -1) return;
142     ans.push_back(dst[s]);
143     if (head[s] != nullNd)
144         Q.push(node(head[s], dst[s] + head[s]->edge

```

```

145     for (int _ = 1; _ < k and not Q.empty(); _++) {
146         node p = Q.top(), q;
147         Q.pop();
148         ans.push_back(p.d);
149         if (head[p.H->edge->v] != nullNd) {
150             q.H = head[p.H->edge->v];
151             q.d = p.d + q.H->edge->d;
152             Q.push(q);
153         }
154         for (int i = 0; i < 4; i++)
155             if (p.H->chd[i] != nullNd) {
156                 q.H = p.H->chd[i];
157                 q.d = p.d - p.H->edge->d + p.H->chd
158                     [i]->edge->d;
159                 Q.push(q);
160             }
161     }
162     void solve() { // ans[i] stores the i-th shortest
163         path
164         dijkstra();
165         build();
166         first_K(); // ans.size() might less than k
167     }
168 } solver;

```

## 5.12 Hungarian Algorithm

```

1 const int N = 2e3;
2 int match[N];
3 bool vis[N];
4 int n;
5 vector<int> ed[N];
6 int match_cnt;
7 bool dfs(int u) {
8     vis[u] = 1;
9     for(int i : ed[u]) {
10         if(match[i] == 0 || !vis[match[i]] && dfs(match
11             [i])) {
12             match[i] = u;
13             return true;
14         }
15     }
16     return false;
17 }
18 void hungary() {
19     memset(match, 0, sizeof(match));
20     match_cnt = 0;
21     for(int i = 1; i <= n; i++) {
22         memset(vis, 0, sizeof(vis));
23         if(dfs(i)) match_cnt++;
24     }
25 }

```

## 5.13 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum  $\Rightarrow$  Use prefix sum to transform into differential constraints. Don't forget  $S_{i+1} - S_i \geq 0$  if  $x_i$  needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

## 6 String

### 6.1 Aho Corasick

```

1 struct ACautomata {
2     struct Node {
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node() {
6             cnt = 0;
7             fail = 0;
8             dic = 0;
9             memset(go, 0, sizeof(go));
10        }
11    } pool[1048576], *root;
12    int nMem;
13    Node *new_Node() {
14        pool[nMem] = Node();
15        return &pool[nMem++];
16    }
17    void init() {
18        nMem = 0;
19        root = new_Node();
20    }
21    void add(const string &str) { insert(root, str, 0); }
22    void insert(Node *cur, const string &str, int pos) {
23        for (int i = pos; i < str.size(); i++) {
24            if (!cur->go[str[i] - 'a'])
25                cur->go[str[i] - 'a'] = new_Node();
26            cur = cur->go[str[i] - 'a'];
27        }
28        cur->cnt++;
29    }
30    void make_fail() {
31        queue<Node*> que;
32        que.push(root);
33        while (!que.empty()) {
34            Node *fr = que.front();
35            que.pop();
36            for (int i = 0; i < 26; i++) {
37                if (fr->go[i]) {
38                    Node *ptr = fr->fail;
39                    while (ptr && !ptr->go[i]) ptr = ptr->fail;
40                    fr->go[i]->fail = ptr = (ptr ? ptr->go[i] : root);
41                    fr->go[i]->dic = (ptr->cnt ? ptr : ptr->dic);
42                    que.push(fr->go[i]);
43                }
44            }
45        }
46    }
47 } AC;

```

### 6.2 KMP

```

1 vector<int> f;
2 void buildFailFunction(string &s) {
3     f.resize(s.size(), -1);
4     for (int i = 1; i < s.size(); i++) {
5         int now = f[i - 1];
6         while (now != -1 and s[now + 1] != s[i]) now = f[now];
7         if (s[now + 1] == s[i]) f[i] = now + 1;
8     }
9 }
10
11 void KMPmatching(string &a, string &b) {
12     for (int i = 0, now = -1; i < a.size(); i++) {
13         while (a[i] != b[now + 1] and now != -1) now = f[now];
14         if (a[i] == b[now + 1]) now++;
15         if (now + 1 == b.size()) {
16             cout << "found a match start at position "
17                  << i - now << endl;
18             now = f[now];
19         }
20     }
21 }

```

### 6.3 Z Value

```

1 string is, it, s;
2 int n;
3 vector<int> z;
4 void init() {
5     cin >> is >> it;
6     s = it + '0' + is;
7     n = (int)s.size();
8     z.resize(n, 0);
9 }
10 void solve() {
11     int ans = 0;
12     z[0] = n;
13     for (int i = 1, l = 0, r = 0; i < n; i++) {
14         if (i <= r) z[i] = min(z[i - l], r - i + 1);
15         while (i + z[i] < n && s[z[i]] == s[i + z[i]])
16             z[i]++;
17         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
18         if (z[i] == (int)it.size()) ans++;
19     }
20     cout << ans << endl;
21 }

```

### 6.4 Manacher

```

1 int n;
2 string S, s;
3 vector<int> m;
4 void manacher() {
5     s.clear();
6     s.resize(2 * n + 1, '.');
7     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
8     m.clear();
9     m.resize(2 * n + 1, 0);
10    // m[i] := max k such that s[i-k, i+k] is
11    // palindrome
12    int mx = 0, mxk = 0;
13    for (int i = 1; i < 2 * n + 1; i++) {
14        if (mx - (i - mx) >= 0) m[i] = min(m[mx - (i - mx)], mx + mxk - i);
15        while (0 <= i - m[i] - 1 && i + m[i] + 1 < 2 * n + 1 && s[i - m[i] - 1] == s[i + m[i] + 1]) m[i]++;
16        if (i + m[i] > mx + mxk) mx = i, mxk = m[i];
17    }
18 }
19 void init() {
20     cin >> S;
21     n = (int)S.size();
22 }
23 void solve() {
24     manacher();
25     int mx = 0, ptr = 0;
26     for (int i = 0; i < 2 * n + 1; i++)
27         if (mx < m[i]) {
28             mx = m[i];
29             ptr = i;
30         }
31     for (int i = ptr - mx; i <= ptr + mx; i++)
32         if (s[i] != '.') cout << s[i];
33     cout << endl;
34 }

```

### 6.5 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n;
5     string s;
6     vector<int> suf, lcp, rk;
7     vector<int> cnt, pos;
8     vector<pair<pii, int>> buc[2];
9     void init(string _s) {
10         s = _s;
11         n = (int)s.size();
12         // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
13     }
14     void radix_sort() {

```



```

15     for (int t : {0, 1}) {
16         fill(cnt.begin(), cnt.end(), 0);
17         for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F.S)]++;
18         for (int i = 0; i < n; i++)
19             pos[i] = (!i ? 0 : pos[i - 1] + cnt[i - 1]);
20         for (auto& i : buc[t])
21             buc[t ^ 1][pos[(t ? i.F.F : i.F.S)]]++
22             = i;
23     }
24     bool fill_suf() {
25         bool end = true;
26         for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
27         rk[suf[0]] = 0;
28         for (int i = 1; i < n; i++) {
29             int dif = (buc[0][i].F != buc[0][i - 1].F);
30             end &= dif;
31             rk[suf[i]] = rk[suf[i - 1]] + dif;
32         }
33         return end;
34     }
35     void sa() {
36         for (int i = 0; i < n; i++)
37             buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
38         sort(buc[0].begin(), buc[0].end());
39         if (fill_suf()) return;
40         for (int k = 0; (1 << k) < n; k++) {
41             for (int i = 0; i < n; i++)
42                 buc[0][i] = make_pair(make_pair(rk[i], rk[(i + (1 << k)) % n]), i);
43             radix_sort();
44             if (fill_suf()) return;
45         }
46     }
47     void LCP() {
48         int k = 0;
49         for (int i = 0; i < n - 1; i++) {
50             if (rk[i] == 0) continue;
51             int pi = rk[i];
52             int j = suf[pi - 1];
53             while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
54             lcp[pi] = k;
55             k = max(k - 1, 0);
56         }
57     }
58 };
59 SuffixArray suffixarray;

```

## 6.6 Minimum Rotation

```

1 // rotate(begin(s), begin(s)+minRotation(s), end(s))
2 int minRotation(string s) {
3     int a = 0, n = s.size();
4     s += s;
5     for (int b = 0; b < n; b++)
6         for (int k = 0; k < n; k++) {
7             if (a + k == b || s[a + k] < s[b + k]) {
8                 b += max(0, k - 1);
9                 break;
10            }
11            if (s[a + k] > s[b + k]) {
12                a = b;
13                break;
14            }
15        }
16     return a;
17 }

```

## 6.7 Lyndon Factorization

```

1 vector<string> duval(string const& s) {
2     int n = s.size();
3     int i = 0;
4     vector<string> factorization;
5     while (i < n) {
6         int j = i + 1, k = i;
7         while (j < n && s[k] <= s[j]) {

```

```

8             if (s[k] < s[j])
9                 k = i;
10            else
11                k++;
12            j++;
13        }
14        while (i <= k) {
15            factorization.push_back(s.substr(i, j - k));
16            i += j - k;
17        }
18    }
19    return factorization; // O(n)
20 }

```

## 6.8 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) { return c - 'a' + 1; }
3 struct RollingHash {
4     string s;
5     int n;
6     ll mod;
7     vector<ll> Cexp, hs;
8     RollingHash(string& _s, ll _mod) : s(_s), n((int)_s.size()), mod(_mod) {
9         Cexp.assign(n, 0);
10        hs.assign(n, 0);
11        Cexp[0] = 1;
12        for (int i = 1; i < n; i++) {
13            Cexp[i] = Cexp[i - 1] * C;
14            if (Cexp[i] >= mod) Cexp[i] %= mod;
15        }
16        hs[0] = id(s[0]);
17        for (int i = 1; i < n; i++) {
18            hs[i] = hs[i - 1] * C + id(s[i]);
19            if (hs[i] >= mod) hs[i] %= mod;
20        }
21    }
22    inline ll query(int l, int r) {
23        ll res = hs[r] - (l ? hs[l - 1] * Cexp[r - l + 1] : 0);
24        res = (res % mod + mod) % mod;
25        return res;
26    }
27 };

```

## 6.9 Trie

```

1 pii a[N][26];
2
3 void build(string &s) {
4     static int idx = 0;
5     int n = s.size();
6     for (int i = 0, v = 0; i < n; i++) {
7         pii &now = a[v][s[i] - 'a'];
8         if (now.first != -1)
9             v = now.first;
10        else
11            v = now.first = ++idx;
12        if (i == n - 1)
13            now.second++;
14    }
15 }

```

# 7 Geometry

## 7.1 Basic Operations

```

1 // typedef long long T;
2 typedef long double T;
3 const long double eps = 1e-12;
4
5 short sgn(T x) {
6     if (abs(x) < eps) return 0;
7     return x < 0 ? -1 : 1;
8 }
9
10 struct Pt {
11     T x, y;
12     Pt(T _x = 0, T _y = 0) : x(_x), y(_y) {}

```

```

13 Pt operator+(Pt a) { return Pt(x + a.x, y + a.y); } 2
14 Pt operator-(Pt a) { return Pt(x - a.x, y - a.y); }
15 Pt operator*(T a) { return Pt(x * a, y * a); } 3
16 Pt operator/(T a) { return Pt(x / a, y / a); } 4
17 T operator*(Pt a) { return x * a.x + y * a.y; }
18 T operator^(Pt a) { return x * a.y - y * a.x; }
19 bool operator<(Pt a) { return x < a.x || (x == a.x 5
    && y < a.y); } 6 // long double
20 // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn 7
    (y-a.y) < 0); } 8
21 bool operator==(Pt a) { return sgn(x - a.x) == 0 && 9
    sgn(y - a.y) == 0; } 10
22 }; 11
23 Pt mv(Pt a, Pt b) { return b - a; } 12
24 T len2(Pt a) { return a * a; } 13
25 T dis2(Pt a, Pt b) { return len2(b - a); } 14
26 Pt rotate(Pt u) { return {-u.y, u.x}; } 15
27 short ori(Pt a, Pt b) { return ((a ^ b) > 0) - ((a ^ b) 16
    < 0); } 17
28 bool onseg(Pt p, Pt l1, Pt l2) { 18
    Pt a = mv(p, l1), b = mv(p, l2); 19
    return ((a ^ b) == 0) && ((a * b) <= 0); 20
29 } 21
30 inline int cross(const Pt &a, const Pt &b, const Pt &c) 22
    { 23
    return (b.x - a.x) * (c.y - a.y) 24
        - (b.y - a.y) * (c.x - a.x); 25
    } 26
31 double polar_angle(Pt ori, Pt pt){ 27
    return atan2(pt.y - ori.y, pt.x - ori.x); 28
32 } 29
33 // slope to degree atan(Slope) * 180.0 / acos(-1.0); 30
34 bool argcmp(Pt u, Pt v) { 31
    auto half = [](const Pt& p) { 32
    return p.y > 0 || (p.y == 0 && p.x >= 0); 33
    }; 34
35 if (half(u) != half(v)) return half(u) < half(v); 35
36 return sgn(u ^ v) > 0; 36
37 } 37
38 struct Line { 38
    Pt a, b; 39
    Line() {} 40
    Line(Pt _a, Pt _b) : a(_a), b(_b) {} 41
    Pt dir() { return b - a; } 42
39 }; 43
40 int ori(Pt& o, Pt& a, Pt& b) { 44
    return sgn((a - o) ^ (b - o)); 45
41 } 46
42 struct Cir { 47
    Pt o; 48
    T r; 49
43 }; 50
44 bool disjunct(Cir a, Cir b) { 51
    return sgn(sqrtl(len2(a.o - b.o)) - a.r - b.r) >= 52
        0; 53
45 } 54
46 bool contain(Cir a, Cir b) { 55
    return sgn(a.r - b.r - sqrtl(len2(a.o - b.o))) >= 56
        0; 57
47 } 58
48 } 59
49 } 60
50 } 61
51 } 62
52 } 63
53 } 64
54 } 65
55 } 66
56 } 67
57 } 68
58 } 69
59 } 70
60 } 71
61 } 72
62 } 73
63 } 74
64 } 75
65 } 76
66 } 77
67 } 78
68 } 79
69 } 80
70 } 81
71 } 82
72 } 83
73 } 84
74 } 85
75 } 86
76 } 87
77 } 88
78 } 89
79 } 90
80 } 91
81 } 92
82 } 93
83 } 94
84 } 95
85 } 96
86 } 97
87 } 98
88 } 99
89 } 100
90 } 101
91 } 102
92 } 103
93 } 104
94 } 105
95 } 106
96 } 107
97 } 108
98 } 109
99 } 110
100 } 111
101 } 112
102 } 113
103 } 114
104 } 115
105 } 116
106 } 117
107 } 118
108 } 119
109 } 120
110 } 121
111 } 122
112 } 123
113 } 124
114 } 125
115 } 126
116 } 127
117 } 128
118 } 129
119 } 130
120 } 131
121 } 132
122 } 133
123 } 134
124 } 135
125 } 136
126 } 137
127 } 138
128 } 139
129 } 140
130 } 141
131 } 142
132 } 143
133 } 144
134 } 145
135 } 146
136 } 147
137 } 148
138 } 149
139 } 150
140 } 151
141 } 152
142 } 153
143 } 154
144 } 155
145 } 156
146 } 157
147 } 158
148 } 159
149 } 160
150 } 161
151 } 162
152 } 163
153 } 164
154 } 165
155 } 166
156 } 167
157 } 168
158 } 169
159 } 170
160 } 171
161 } 172
162 } 173
163 } 174
164 } 175
165 } 176
166 } 177
167 } 178
168 } 179
169 } 180
170 } 181
171 } 182
172 } 183
173 } 184
174 } 185
175 } 186
176 } 187
177 } 188
178 } 189
179 } 190
180 } 191
181 } 192
182 } 193
183 } 194
184 } 195
185 } 196
186 } 197
187 } 198
188 } 199
189 } 200
190 } 201
191 } 202
192 } 203
193 } 204
194 } 205
195 } 206
196 } 207
197 } 208
198 } 209
199 } 210
200 } 211
201 } 212
202 } 213
203 } 214
204 } 215
205 } 216
206 } 217
207 } 218
208 } 219
209 } 220
210 } 221
211 } 222
212 } 223
213 } 224
214 } 225
215 } 226
216 } 227
217 } 228
218 } 229
219 } 230
220 } 231
221 } 232
222 } 233
223 } 234
224 } 235
225 } 236
226 } 237
227 } 238
228 } 239
229 } 240
230 } 241
231 } 242
232 } 243
233 } 244
234 } 245
235 } 246
236 } 247
237 } 248
238 } 249
239 } 250
240 } 251
241 } 252
242 } 253
243 } 254
244 } 255
245 } 256
246 } 257
247 } 258
248 } 259
249 } 260
250 } 261
251 } 262
252 } 263
253 } 264
254 } 265
255 } 266
256 } 267
257 } 268
258 } 269
259 } 270
260 } 271
261 } 272
262 } 273
263 } 274
264 } 275
265 } 276
266 } 277
267 } 278
268 } 279
269 } 280
270 } 281
271 } 282
272 } 283
273 } 284
274 } 285
275 } 286
276 } 287
277 } 288
278 } 289
279 } 290
280 } 291
281 } 292
282 } 293
283 } 294
284 } 295
285 } 296
286 } 297
287 } 298
288 } 299
289 } 300
290 } 301
291 } 302
292 } 303
293 } 304
294 } 305
295 } 306
296 } 307
297 } 308
298 } 309
299 } 310
300 } 311
301 } 312
302 } 313
303 } 314
304 } 315
305 } 316
306 } 317
307 } 318
308 } 319
309 } 320
310 } 321
311 } 322
312 } 323
313 } 324
314 } 325
315 } 326
316 } 327
317 } 328
318 } 329
319 } 330
320 } 331
321 } 332
322 } 333
323 } 334
324 } 335
325 } 336
326 } 337
327 } 338
328 } 339
329 } 340
330 } 341
331 } 342
332 } 343
333 } 344
334 } 345
335 } 346
336 } 347
337 } 348
338 } 349
339 } 350
340 } 351
341 } 352
342 } 353
343 } 354
344 } 355
345 } 356
346 } 357
347 } 358
348 } 359
349 } 360
350 } 361
351 } 362
352 } 363
353 } 364
354 } 365
355 } 366
356 } 367
357 } 368
358 } 369
359 } 370
360 } 371
361 } 372
362 } 373
363 } 374
364 } 375
365 } 376
366 } 377
367 } 378
368 } 379
369 } 380
370 } 381
371 } 382
372 } 383
373 } 384
374 } 385
375 } 386
376 } 387
377 } 388
378 } 389
379 } 390
380 } 391
381 } 392
382 } 393
383 } 394
384 } 395
385 } 396
386 } 397
387 } 398
388 } 399
389 } 400
390 } 401
391 } 402
392 } 403
393 } 404
394 } 405
395 } 406
396 } 407
397 } 408
398 } 409
399 } 410
400 } 411
401 } 412
402 } 413
403 } 414
404 } 415
405 } 416
406 } 417
407 } 418
408 } 419
409 } 420
410 } 421
411 } 422
412 } 423
413 } 424
414 } 425
415 } 426
416 } 427
417 } 428
418 } 429
419 } 430
420 } 431
421 } 432
422 } 433
423 } 434
424 } 435
425 } 436
426 } 437
427 } 438
428 } 439
429 } 440
430 } 441
431 } 442
432 } 443
433 } 444
434 } 445
435 } 446
436 } 447
437 } 448
438 } 449
439 } 450
440 } 451
441 } 452
442 } 453
443 } 454
444 } 455
445 } 456
446 } 457
447 } 458
448 } 459
449 } 460
450 } 461
451 } 462
452 } 463
453 } 464
454 } 465
455 } 466
456 } 467
457 } 468
458 } 469
459 } 470
460 } 471
461 } 472
462 } 473
463 } 474
464 } 475
465 } 476
466 } 477
467 } 478
468 } 479
469 } 480
470 } 481
471 } 482
472 } 483
473 } 484
474 } 485
475 } 486
476 } 487
477 } 488
478 } 489
479 } 490
480 } 491
481 } 492
482 } 493
483 } 494
484 } 495
485 } 496
486 } 497
487 } 498
488 } 499
489 } 500
490 } 501
491 } 502
492 } 503
493 } 504
494 } 505
495 } 506
496 } 507
497 } 508
498 } 509
499 } 510
500 } 511
501 } 512
502 } 513
503 } 514
504 } 515
505 } 516
506 } 517
507 } 518
508 } 519
509 } 520
510 } 521
511 } 522
512 } 523
513 } 524
514 } 525
515 } 526
516 } 527
517 } 528
518 } 529
519 } 530
520 } 531
521 } 532
522 } 533
523 } 534
524 } 535
525 } 536
526 } 537
527 } 538
528 } 539
529 } 540
530 } 541
531 } 542
532 } 543
533 } 544
534 } 545
535 } 546
536 } 547
537 } 548
538 } 549
539 } 550
540 } 551
541 } 552
542 } 553
543 } 554
544 } 555
545 } 556
546 } 557
547 } 558
548 } 559
549 } 560
550 } 561
551 } 562
552 } 563
553 } 564
554 } 565
555 } 566
556 } 567
557 } 568
558 } 569
559 } 570
560 } 571
561 } 572
562 } 573
563 } 574
564 } 575
565 } 576
566 } 577
567 } 578
568 } 579
569 } 580
570 } 581
571 } 582
572 } 583
573 } 584
574 } 585
575 } 586
576 } 587
577 } 588
578 } 589
579 } 590
580 } 591
581 } 592
582 } 593
583 } 594
584 } 595
585 } 596
586 } 597
587 } 598
588 } 599
589 } 600
590 } 601
591 } 602
592 } 603
593 } 604
594 } 605
595 } 606
596 } 607
597 } 608
598 } 609
599 } 610
600 } 611
601 } 612
602 } 613
603 } 614
604 } 615
605 } 616
606 } 617
607 } 618
608 } 619
609 } 620
610 } 621
611 } 622
612 } 623
613 } 624
614 } 625
615 } 626
616 } 627
617 } 628
618 } 629
619 } 630
620 } 631
621 } 632
622 } 633
623 } 634
624 } 635
625 } 636
626 } 637
627 } 638
628 } 639
629 } 640
630 } 641
631 } 642
632 } 643
633 } 644
634 } 645
635 } 646
636 } 647
637 } 648
638 } 649
639 } 650
640 } 651
641 } 652
642 } 653
643 } 654
644 } 655
645 } 656
646 } 657
647 } 658
648 } 659
649 } 660
650 } 661
651 } 662
652 } 663
653 } 664
654 } 665
655 } 666
656 } 667
657 } 668
658 } 669
659 } 670
660 } 671
661 } 672
662 } 673
663 } 674
664 } 675
665 } 676
666 } 677
667 } 678
668 } 679
669 } 680
670 } 681
671 } 682
672 } 683
673 } 684
674 } 685
675 } 686
676 } 687
677 } 688
678 } 689
679 } 690
680 } 691
681 } 692
682 } 693
683 } 694
684 } 695
685 } 696
686 } 697
687 } 698
688 } 699
689 } 700
690 } 701
691 } 702
692 } 703
693 } 704
694 } 705
695 } 706
696 } 707
697 } 708
698 } 709
699 } 710
700 } 711
701 } 712
702 } 713
703 } 714
704 } 715
705 } 716
706 } 717
707 } 718
708 } 719
709 } 720
710 } 721
711 } 722
712 } 723
713 } 724
714 } 725
715 } 726
716 } 727
717 } 728
718 } 729
719 } 730
720 } 731
721 } 732
722 } 733
723 } 734
724 } 735
725 } 736
726 } 737
727 } 738
728 } 739
729 } 740
730 } 741
731 } 742
732 } 743
733 } 744
734 } 745
735 } 746
736 } 747
737 } 748
738 } 749
739 } 750
740 } 751
741 } 752
742 } 753
743 } 754
744 } 755
745 } 756
746 } 757
747 } 758
748 } 759
749 } 760
750 } 761
751 } 762
752 } 763
753 } 764
754 } 765
755 } 766
756 } 767
757 } 768
758 } 769
759 } 770
760 } 771
761 } 772
762 } 773
763 } 774
764 } 775
765 } 776
766 } 777
767 } 778
768 } 779
769 } 780
770 } 781
771 } 782
772 } 783
773 } 784
774 } 785
775 } 786
776 } 787
777 } 788
778 } 789
779 } 790
780 } 791
781 } 792
782 } 793
783 } 794
784 } 795
785 } 796
786 } 797
787 } 798
788 } 799
789 } 800
790 } 801
791 } 802
792 } 803
793 } 804
794 } 805
795 } 806
796 } 807
797 } 808
798 } 809
799 } 810
800 } 811
801 } 812
802 } 813
803 } 814
804 } 815
805 } 816
806 } 817
807 } 818
808 } 819
809 } 820
810 } 821
811 } 822
812 } 823
813 } 824
814 } 825
815 } 826
816 } 827
817 } 828
818 } 829
819 } 830
820 } 831
821 } 832
822 } 833
823 } 834
824 } 835
825 } 836
826 } 837
827 } 838
828 } 839
829 } 840
830 } 841
831 } 842
832 } 843
833 } 844
834 } 845
835 } 846
836 } 847
837 } 848
838 } 849
839 } 850
840 } 851
841 } 852
842 } 853
843 } 854
844 } 855
845 } 856
846 } 857
847 } 858
848 } 859
849 } 860
850 } 861
851 } 862
852 } 863
853 } 864
854 } 865
855 } 866
856 } 867
857 } 868
858 } 869
859 } 870
860 } 871
861 } 872
862 } 873
863 } 874
864 } 875
865 } 876
866 } 877
867 } 878
868 } 879
869 } 880
870 } 881
871 } 882
872 } 883
873 } 884
874 } 885
875 } 886
876 } 887
877 } 888
878 } 889
879 } 890
880 } 891
881 } 892
882 } 893
883 } 894
884 } 895
885 } 896
886 } 897
887 } 898
888 } 899
889 } 900
900 } 901
901 } 902
902 } 903
903 } 904
904 } 905
905 } 906
906 } 907
907 } 908
908 } 909
909 } 910
910 } 911
911 } 912
912 } 913
913 } 914
914 } 915
915 } 916
916 } 917
917 } 918
918 } 919
919 } 920
920 } 921
921 } 922
922 } 923
923 } 924
924 } 925
925 } 926
926 } 927
927 } 928
928 } 929
929 } 930
930 } 931
931 } 932
932 } 933
933 } 934
934 } 935
935 } 936
936 } 937
937 } 938
938 } 939
939 } 940
940 } 941
941 } 942
942 } 943
943 } 944
944 } 945
945 } 946
946 } 947
947 } 948
948 } 949
949 } 950
950 } 951
951 } 952
952 } 953
953 } 954
954 } 955
955 } 956
956 } 957
957 } 958
958 } 959
959 } 960
960 } 961
961 } 962
962 } 963
963 } 964
964 } 965
965 } 966
966 } 967
967 } 968
968 } 969
969 } 970
970 } 971
971 } 972
972 } 973
973 } 974
974 } 975
975 } 976
976 } 977
977 } 978
978 } 979
979 } 980
980 } 981
981 } 982
982 } 983
983 } 984
984 } 985
985 } 986
986 } 987
987 } 988
988 } 989
989 } 990
990 } 991
991 } 992
992 } 993
993 } 994
994 } 995
995 } 996
996 } 997
997 } 998
998 } 999
999 } 1000

```

## 7.2 SVG Writer

## 7.3 Sort by Angle

```

1 int ud(Pt a) { // up or down half plane
2     if (a.y > 0) return 0;
3     if (a.y < 0) return 1;
4     return (a.x >= 0 ? 0 : 1);
5 }
6 sort(pts.begin(), pts.end(), [&](const Pt& a, const Pt& b) {
7     if (ud(a) != ud(b)) return ud(a) < ud(b);
8     return (a ^ b) > 0;
9 });

```

## 7.4 Line Intersection

```

1 bool line_intersect_check(Pt p1, Pt p2, Pt q1, Pt q2) {

```

## 7.5 Polygon Area

```

1 // 2 * area
2 T dbPoly_area(vector<Pt>& e) {
3     T res = 0;
4     int sz = e.size();
5     for (int i = 0; i < sz; i++) {
6         res += e[i] ^ e[(i + 1) % sz];
7     }
8     return abs(res);
9 }

```

## 7.6 Convex Hull

```

1 vector<Pt> convexHull(vector<Pt> pts) {
2     vector<Pt> hull;
3     sort(pts.begin(), pts.end());
4     for (int i = 0; i < 2; i++) {
5         int b = hull.size();
6         for (auto ei : pts) {
7             while (hull.size() - b >= 2 && ori(mv(hull[
                hull.size() - 2], hull.back()), mv(hull[
                hull.size() - 2], ei)) == -1) {
8                 hull.pop_back();
9             }
10            hull.emplace_back(ei);
11        }
12        hull.pop_back();
13        reverse(pts.begin(), pts.end());
14    }
15    return hull;
16 }

```

## 7.7 Point In Convex

```

1 bool point_in_convex(const vector<Pt> &C, Pt p, bool
    strict = true) {
2     // only works when no three point are collinear
3     int n = C.size();
4     int a = 1, b = n - 1, r = !strict;
5     if (n == 0) return false;
6     if (n < 3) return r && onseg(p, C[0], C.back());
7     if (ori(mv(C[0], C[a]), mv(C[0], C[b])) > 0) swap(a, b);
8     if (ori(mv(C[0], C[a]), mv(C[0], p)) >= r || ori(mv(
        C[0], C[b]), mv(C[0], p)) <= -r) return false;
9     while (abs(a - b) > 1) {
10        int c = (a + b) / 2;
11        if (ori(mv(C[0], C[c]), mv(C[0], p)) > 0) b = c;
        else a = c;

```

```

13     }
14     return ori(mv(C[a], C[b]), mv(C[a], p)) < r;
15 }

```

## 7.8 Point Segment Distance

```

1 double point_segment_dist(Pt q0, Pt q1, Pt p) {
2     if (q0 == q1) {
3         double dx = double(p.x - q0.x);
4         double dy = double(p.y - q0.y);
5         return sqrt(dx * dx + dy * dy);
6     }
7     T d1 = (q1 - q0) * (p - q0);
8     T d2 = (q0 - q1) * (p - q1);
9     if (d1 >= 0 && d2 >= 0) {
10        double area = fabs(double((q1 - q0) ^ (p - q0))
11                               );
12        double base = sqrt(double(dis2(q0, q1)));
13        return area / base;
14    }
15    double dx0 = double(p.x - q0.x), dy0 = double(p.y -
16    q0.y);
17    double dx1 = double(p.x - q1.x), dy1 = double(p.y -
18    q1.y);
19    return min(sqrt(dx0 * dx0 + dy0 * dy0), sqrt(dx1 *
20    dx1 + dy1 * dy1));
21 }

```

## 7.9 Point in Polygon

```

1 short inPoly(vector<Pt>& pts, Pt p) {
2     // 0=Bound 1=In -1=Out
3     int n = pts.size();
4     for (int i = 0; i < pts.size(); i++) if (onseg(p,
5     pts[i], pts[(i + 1) % n])) return 0;
6     int cnt = 0;
7     for (int i = 0; i < pts.size(); i++) if (
8     line_intersect_check(p, Pt(p.x + 1, p.y + 2e9),
9     pts[i], pts[(i + 1) % n])) cnt ^= 1;
10    return (cnt ? 1 : -1);
11 }

```

## 7.10 Minimum Euclidean Distance

```

1 long long Min_Euclidean_Dist(vector<Pt> &pts) {
2     sort(pts.begin(), pts.end());
3     set<pair<long long, long long>> s;
4     s.insert({pts[0].y, pts[0].x});
5     long long l = 0, best = LLONG_MAX;
6     for (int i = 1; i < (int)pts.size(); i++) {
7         Pt now = pts[i];
8         long long lim = (long long)ceil(sqrt1l((long
9         double)best));
10        while (now.x - pts[l].x > lim) {
11            s.erase({pts[l].y, pts[l].x}); l++;
12        }
13        auto low = s.lower_bound({now.y - lim,
14        LLONG_MIN});
15        auto high = s.upper_bound({now.y + lim,
16        LLONG_MAX});
17        for (auto it = low; it != high; it++) {
18            long long dy = it->first - now.y;
19            long long dx = it->second - now.x;
20            best = min(best, dx * dx + dy * dy);
21        }
22        s.insert({now.y, now.x});
23    }
24    return best;
25 }

```

## 7.11 Minkowski Sum

```

1 void reorder(vector<Pt> &P) {
2     rotate(P.begin(), min_element(P.begin(), P.end()),
3     [&](Pt a, Pt b) { return make_pair(a.y, a.x) <
4     make_pair(b.y, b.x); }), P.end());
5 }
6 vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
7     // P, Q: convex polygon
8     reorder(P), reorder(Q);
9     int n = P.size(), m = Q.size();

```

```

8     P.push_back(P[0]), P.push_back(P[1]), Q.push_back(Q
9     [0]), Q.push_back(Q[1]);
10    vector<Pt> ans;
11    for (int i = 0, j = 0; i < n || j < m; ) {
12        ans.push_back(P[i] + Q[j]);
13        auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
14        if (val >= 0) i++;
15        if (val <= 0) j++;
16    }
17    return ans;

```

## 7.12 Lower Concave Hull

```

1 struct Line {
2     mutable ll m, b, p;
3     bool operator<(const Line& o) const { return m < o.m;
4     }
5     bool operator<(ll x) const { return p < x; }
6 };
7 struct LineContainer : multiset<Line, less<>> {
8     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
9     const ll inf = LLONG_MAX;
10    ll div(ll a, ll b) { // floored division
11        return a / b - ((a ^ b) < 0 && a % b); }
12    bool isect(iterator x, iterator y) {
13        if (y == end()) { x->p = inf; return false; }
14        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
15        else x->p = div(y->b - x->b, x->m - y->m);
16        return x->p >= y->p;
17    }
18    void add(ll m, ll b) {
19        auto z = insert({m, b, 0}), y = z++, x = y;
20        while (isect(y, z)) z = erase(z);
21        if (x != begin() && isect(--x, y)) isect(x, y =
22        erase(y));
23        while ((y = x) != begin() && (--x)->p >= y->p)
24            isect(x, erase(y));
25    }
26    ll query(ll x) {
27        assert(!empty());
28        auto l = *lower_bound(x);
29        return l.m * x + l.b;
30    }

```

## 7.13 Pick's Theorem

Consider a polygon which vertices are all lattice points.  
Let  $i$  = number of points inside the polygon.  
Let  $b$  = number of points on the boundary of the polygon.

Then we have the following formula:

$$Area = i + \frac{b}{2} - 1$$

## 7.14 Vector In Polygon

## 7.15 Rotating SweepLine

```

1 double cross(const Pt &a, const Pt &b) {
2     return a.x*b.y - a.y*b.x;
3 }
4 int rotatingCalipers(const vector<Pt>& hull) {
5     int m = hull.size();
6     if (m < 2) return 0;
7     int j = 1;
8     T maxd = 0;
9     for (int i = 0; i < m; ++i) {
10        int ni = (i + 1) % m;
11        while (abs(cross({hull[ni].x - hull[i].x, hull[
12        ni].y - hull[i].y}, {hull[(j+1)%m].x - hull[
13        i].x, hull[(j+1)%m].y - hull[i].y})) > abs
14        (cross({hull[ni].x - hull[i].x, hull[ni].y
15        - hull[i].y}, {hull[j].x - hull[i].x,
16        hull[j].y - hull[i].y}))) {
17            j = (j + 1) % m;
18        }
19        maxd = max(maxd, dis2(hull[i], hull[j]));

```

```

15     maxd = max(maxd, dis2(hull[ni], hull[j]));
16 }
17 return maxd; // TODO
18 }

```

## 7.16 Half Plane Intersection

```

1 bool cover(Line& L, Line& P, Line& Q) {
2     long double u = (Q.a - P.a) ^ Q.dir();
3     long double v = P.dir() ^ Q.dir();
4     long double x = P.dir().x * u + (P.a - L.a).x * v;
5     long double y = P.dir().y * u + (P.a - L.a).y * v;
6     return sgn(x * L.dir().y - y * L.dir().x) * sgn(v)
7         >= 0;
8 }
9 vector<Line> HPI(vector<Line> P) {
10     sort(P.begin(), P.end(), [&](Line& l, Line& m) {
11         if (argcmp(l.dir(), m.dir()) return true;
12         if (argcmp(m.dir(), l.dir()) return false;
13         return ori(m.a, m.b, l.a) > 0;
14     });
15     int l = 0, r = -1;
16     for (size_t i = 0; i < P.size(); ++i) {
17         if (i && !argcmp(P[i - 1].dir(), P[i].dir()))
18             continue;
19         while (l < r && cover(P[i], P[r - 1], P[r])) --r;
20         while (l < r && cover(P[i], P[l], P[l + 1])) ++l;
21         P[++r] = P[i];
22     }
23     while (l < r && cover(P[l], P[r - 1], P[r])) --r;
24     while (l < r && cover(P[r], P[l], P[l + 1])) ++l;
25     if (r - l <= 1 || !argcmp(P[l].dir(), P[r].dir()))
26         return {};
27     if (cover(P[l + 1], P[l], P[r])) return {};
28     return vector<Line>(P.begin() + l, P.begin() + r + 1);
29 }

```

## 7.17 Minimum Enclosing Circle

```

1 const int INF = 1e9;
2 Pt circumcenter(Pt A, Pt B, Pt C) {
3     // a1(x-A.x) + b1(y-A.y) = c1
4     // a2(x-A.x) + b2(y-A.y) = c2
5     // solve using Cramer's rule
6     T a1 = B.x - A.x, b1 = B.y - A.y, c1 = dis2(A, B) /
7         2.0;
8     T a2 = C.x - A.x, b2 = C.y - A.y, c2 = dis2(A, C) /
9         2.0;
10    T D = Pt(a1, b1) ^ Pt(a2, b2);
11    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
12    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
13    if (D == 0) return Pt(-INF, -INF);
14    return A + Pt(Dx / D, Dy / D);
15 }
16 Pt center;
17 T r2;
18 void minEncloseCircle(vector<Pt> pts) {
19     mt19937 gen(chrono::steady_clock::now().
20         time_since_epoch().count());
21     shuffle(pts.begin(), pts.end(), gen);
22     center = pts[0], r2 = 0;
23     for (int i = 0; i < pts.size(); i++) {
24         if (dis2(center, pts[i]) <= r2) continue;
25         center = pts[i], r2 = 0;
26         for (int j = 0; j < i; j++) {
27             if (dis2(center, pts[j]) <= r2) continue;
28             center = (pts[i] + pts[j]) / 2.0;
29             r2 = dis2(center, pts[i]);
30             for (int k = 0; k < j; k++) {
31                 if (dis2(center, pts[k]) <= r2)
32                     continue;
33                 center = circumcenter(pts[i], pts[j],
34                     pts[k]);
35                 r2 = dis2(center, pts[i]);
36             }
37         }
38     }
39 }

```

```

33     }
34 }
35 }

```

## 7.18 Tangents

## 7.19 Union of Circles

```

1 // Area[i] : area covered by at least i circle
2 vector<T> CircleUnion(const vector<Cir> &C) {
3     const int n = C.size();
4     vector<T> Area(n + 1);
5     auto check = [&](int i, int j) {
6         if (!contain(C[i], C[j]))
7             return false;
8         return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r
9             - C[j].r) == 0 and i < j);
10    };
11    struct Teve {
12        double ang; int add; Pt p;
13        bool operator<(const Teve &b) { return ang < b.
14            ang; }
15    };
16    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
17    for (int i = 0; i < n; i++) {
18        int cov = 1;
19        vector<Teve> event;
20        for (int j = 0; j < n; j++) if (i != j) {
21            if (check(j, i)) cov++;
22            else if (!check(i, j) and !disjunct(C[i], C
23                [j])) {
24                auto I = CircleInter(C[i], C[j]);
25                assert(I.size() == 2);
26                double a1 = ang(I[0] - C[i].o), a2 =
27                    ang(I[1] - C[i].o);
28                event.push_back({a1, 1, I[0]});
29                event.push_back({a2, -1, I[1]});
30                if (a1 > a2) cov++;
31            }
32        }
33        if (event.empty()) {
34            Area[cov] += acos(-1) * C[i].r * C[i].r;
35            continue;
36        }
37        sort(event.begin(), event.end());
38        event.push_back(event[0]);
39        for (int j = 0; j + 1 < event.size(); j++) {
40            cov += event[j].add;
41            Area[cov] += (event[j].p ^ event[j + 1].p)
42                / 2.;
43            double theta = event[j + 1].ang - event[j].
44                ang;
45            if (theta < 0) theta += 2 * acos(-1);
46            Area[cov] += (theta - sin(theta)) * C[i].r
47                * C[i].r / 2.;
48        }
49    }
50    return Area;
51 }

```

## 7.20 Union of Polygons

## 7.21 3D Point

## 7.22 3D Convex Hull

# 8 Number Theory

## 8.1 FFT

```

1 typedef complex<double> cp;
2
3 const double pi = acos(-1);
4 const int NN = 131072;
5
6 struct FastFourierTransform {
7     /*
8      * Iterative Fast Fourier Transform
9      * How this works? Look at this
10      * 0th recursion 0(000) 1(001) 2(010)
11      * 3(011) 4(100) 5(101) 6(110)
12      * 7(111)
13      */
14 }

```

```

11      1th recursion 0(000) 2(010) 4(100)
12      6(110) | 1(011) 3(011) 5(101)
13      7(111)
14      2th recursion 0(000) 4(100) | 2(010)
15      6(110) | 1(011) 5(101) | 3(011)
16      7(111)
17      3th recursion 0(000) | 4(100) | 2(010) |
18      6(110) | 1(011) | 5(101) | 3(011) |
19      7(111)
20      All the bits are reversed => We can save
21      the reverse of the numbers in an array!
22
23  */
24  int n, rev[NN];
25  cp omega[NN], iomega[NN];
26  void init(int n_) {
27      n = n_;
28      for (int i = 0; i < n; i++) {
29          // Calculate the nth roots of unity
30          omega[i] = cp(cos(2 * pi * i / n), sin(2 *
31              pi * i / n));
32          iomega[i] = conj(omega[i]);
33      }
34      int k = __lg(n);
35      for (int i = 0; i < n; i++) {
36          int t = 0;
37          for (int j = 0; j < k; j++) {
38              if (i & (1 << j)) t |= (1 << (k - j -
39                  1));
40          }
41          rev[i] = t;
42      }
43
44  void transform(vector<cp> &a, cp *xomega) {
45      for (int i = 0; i < n; i++)
46          if (i < rev[i]) swap(a[i], a[rev[i]]);
47      for (int len = 2; len <= n; len <= 1) {
48          int mid = len >> 1;
49          int r = n / len;
50          for (int j = 0; j < n; j += len)
51              for (int i = 0; i < mid; i++) {
52                  cp tmp = xomega[r * i] * a[j + mid
53                      + i];
54                  a[j + mid + i] = a[j + i] - tmp;
55                  a[j + i] = a[j + i] + tmp;
56              }
57      }
58
59  void fft(vector<cp> &a) { transform(a, omega); }
60  void ifft(vector<cp> &a) {
61      transform(a, iomega);
62      for (int i = 0; i < n; i++) a[i] /= n;
63  }
64  } FFT;
65
66  const int MAXN = 262144;
67  // (must be 2^k)
68  // 262144, 524288, 1048576, 2097152, 4194304
69  // before any usage, run pre_fft() first
70  typedef long double ld;
71  typedef complex<ld> cplx; // real(), imag()
72  const ld PI = acos(-1);
73  const cplx I(0, 1);
74  cplx omega[MAXN + 1];
75  void pre_fft() {
76      for (int i = 0; i <= MAXN; i++) {
77          omega[i] = exp(i * 2 * PI / MAXN * I);
78      }
79  }
80  // n must be 2^k
81  void fft(int n, cplx a[], bool inv = false) {
82      int basic = MAXN / n;
83      int theta = basic;
84      for (int m = n; m >= 2; m >>= 1) {
85          int mh = m >> 1;
86          for (int i = 0; i < mh; i++) {
87              cplx w = omega[inv ? MAXN - (i * theta %
88                  MAXN) : i * theta % MAXN];
89              for (int j = i; j < n; j += m) {
90                  int k = j + mh;
91                  cplx x = a[j] - a[k];
92                  a[j] += a[k];
93                  a[k] = w * x;
94              }
95          }
96          theta = (theta * 2) % MAXN;
97      }
98      int i = 0;
99      for (int j = 1; j < n - 1; j++) {
100          for (int k = n >> 1; k > (i ^= k); k >>= 1);
101          if (j < i) swap(a[i], a[j]);
102      }
103      if (inv) {
104          for (i = 0; i < n; i++) a[i] /= n;
105      }
106  }
107  cplx arr[MAXN + 1];
108  inline void mul(int _n, long long a[], int _m, long
109      long b[], long long ans[]) {
110      int n = 1, sum = _n + _m - 1;
111      while (n < sum) n <= 1;
112      for (int i = 0; i < n; i++) {
113          double x = (i < _n ? a[i] : 0), y = (i < _m ? b
114              [i] : 0);
115          arr[i] = complex<double>(x + y, x - y);
116      }
117      fft(n, arr);
118      for (int i = 0; i < n; i++) arr[i] = arr[i] * arr[i
119          ];
120      fft(n, arr, true);
121      for (int i = 0; i < sum; i++) ans[i] = (long long
122          int)(arr[i].real() / 4 + 0.5);
123  }
124
125  long long a[MAXN];
126  long long b[MAXN];
127  long long ans[MAXN];
128  int a_length;
129  int b_length;

```

## 8.2 Pollard's rho

```

1 ll add(ll x, ll y, ll p) {
2     return (x + y) % p;
3 }
4 ll qMul(ll x, ll y, ll mod) {
5     ll ret = x * y - (ll)((long double)x / mod * y) *
6         mod;
7     return ret < 0 ? ret + mod : ret;
8 }
9 ll f(ll x, ll mod) { return add(qMul(x, x, mod), 1, mod
10     ); }
11 ll pollard_rho(ll n) {
12     if (!(n & 1)) return 2;
13     while (true) {
14         ll y = 2, x = rand() % (n - 1) + 1, res = 1;
15         for (int sz = 2; res == 1; sz *= 2) {
16             for (int i = 0; i < sz && res == 1; i++) {
17                 x = f(x, n);
18                 res = __gcd(llabs(x - y), n);
19             }
20             y = x;
21         }
22         if (res != 0 && res != n) return res;
23     }
24 }
25 vector<ll> ret;
26 void fact(ll x) {
27     if (miller_rabin(x)) {
28         ret.push_back(x);
29         return;
30     }
31     ll f = pollard_rho(x);
32     fact(f);
33     fact(x / f);
34 }

```

## 8.3 Miller Rabin

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383  6 : pimes <= 13
4 // n < 2^64              7 :

```

```

5 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022
6 bool witness(ll a, ll n, ll u, int t) {
7     if (!(a % n)) return 0;
8     ll x = mypow(a, u, n);
9     for (int i = 0; i < t; i++) {
10         ll nx = mul(x, x, n);
11         if (nx == 1 && x != 1 && x != n - 1) return 1;
12         x = nx;
13     }
14     return x != 1;
15 }
16 bool miller_rabin(ll n, int s = 100) {
17     // iterate s times of witness on n
18     // return 1 if prime, 0 otherwise
19     if (n < 2) return 0;
20     if (!(n & 1)) return n == 2;
21     ll u = n - 1;
22     int t = 0;
23     while (!(u & 1)) u >>= 1, t++;
24     while (s--) {
25         ll a = randll() % (n - 1) + 1;
26         if (witness(a, n, u, t)) return 0;
27     }
28     return 1;
29 }

```

## 8.4 Fast Power

Note:  $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

## 8.5 Extend GCD

```

1 ll GCD;
2 pll extgcd(ll a, ll b) {
3     if (b == 0) {
4         GCD = a;
5         return pll{1, 0};
6     }
7     pll ans = extgcd(b, a % b);
8     return pll{ans.S, ans.F - a / b * ans.S};
9 }
10 pll bezout(ll a, ll b, ll c) {
11     bool negx = (a < 0), negy = (b < 0);
12     pll ans = extgcd(abs(a), abs(b));
13     if (c % GCD != 0) return pll{-LLINF, -LLINF};
14     return pll{ans.F * c / GCD * (negx ? -1 : 1),
15               ans.S * c / GCD * (negy ? -1 : 1)};
16 }
17 ll inv(ll a, ll p) {
18     if (p == 1) return -1;
19     pll ans = bezout(a % p, -p, 1);
20     if (ans == pll{-LLINF, -LLINF}) return -1;
21     return (ans.F % p + p) % p;
22 }

```

## 8.6 Mu + Phi

```

1 const int maxn = 1e6 + 5;
2 ll f[maxn];
3 vector<int> lpf, prime;
4 void build() {
5     lpf.clear();
6     lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
14         }
15         for (auto& j : prime) {
16             if (i * j >= maxn) break;
17             lpf[i * j] = j;
18             if (i % j == 0)
19                 f[i * j] = ...; /* 0, phi[i]*j */
20             else
21                 f[i * j] = ...; /* -mu[i], phi[i]*phi[j] */
22             if (j >= lpf[i]) break;
23         }
24     }
25 }

```

## 8.7 Other Formulas

- Inversion:  
 $aa^{-1} \equiv 1 \pmod{m}$ .  $a^{-1}$  exists iff  $\gcd(a, m) = 1$ .
- Linear inversion:  
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:  
 $a^p \equiv a \pmod{p}$  if  $p$  is prime.
- Euler function:  
 $\phi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem:  
 $a^{\phi(n)} \equiv 1 \pmod{n}$  if  $\gcd(a, n) = 1$ .
- Extended Euclidean algorithm:  
 $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function:  
 $\sigma_x(n) = \sum_{d|n} d^x$ .  $n = \prod_{i=1}^r p_i^{a_i}$ .  
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$  if  $x \neq 0$ .  $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$ .
- Chinese remainder theorem (Coprime Moduli):  
 $x \equiv a_i \pmod{m_i}$ .  
 $M = \prod m_i$ .  $M_i = M / m_i$ .  $t_i = M_i^{-1}$ .  
 $x = kM + \sum a_i t_i M_i$ ,  $k \in \mathbb{Z}$ .
- Chinese remainder theorem:  
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$   
Solve for  $(p, q)$  using ExtGCD.  
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow:  $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution:  $(f * g)(n) = \sum_{d|n} f(d)g(n/d)$
- Important Multiplicative Functions + Properties:
  - $\epsilon(n) = [n = 1]$
  - $1(n) = 1$
  - $id(n) = n$
  - $\mu(n) = 0$  if  $n$  has squared prime factor
  - $\mu(n) = (-1)^k$  if  $n = p_1 p_2 \cdots p_k$
  - $\epsilon = \mu * 1$
  - $\phi = \mu * id$
  - $[n = 1] = \sum_{d|n} \mu(d)$
  - $[gcd = 1] = \sum_{d|gcd} \mu(d)$
- Möbius inversion:  $f = g * 1 \Leftrightarrow g = f * \mu$

## 8.8 Polynomial

```

1 const int maxk = 20;
2 const int maxn = 1<<maxk;
3 const ll LINF = 1e18;
4
5 /* P = r*2^k + 1
6
7 P          r    k    g
8 998244353 119 23   3
9 1004535809 479 21   3
10
11 P          r    k    g
12 3          1    1    2
13 5          1    2    2
14 17         1    4    3
15 97         3    5    5
16 193        3    6    5
17 257        1    8    3
18 7681       15    9   17
19 12289      3   12   11

```



```

19 40961          5 13 3
20 65537          1 16 3
21 786433         3 18 10
22 5767169        11 19 3
23 7340033         7 20 3
24 23068673        11 21 3
25 104857601       25 22 3
26 167772161       5 25 3
27 469762049       7 26 3
28 1004535809      479 21 3
29 2013265921      15 27 31
30 2281701377      17 27 3
31 3221225473      3 30 5
32 75161927681     35 31 3
33 77309411329     9 33 7
34 206158430209    3 36 22
35 2061584302081   15 37 7
36 2748779069441   5 39 3
37 6597069766657   3 41 5
38 39582418599937   9 42 5
39 79164837199873   9 43 5
40 263882790666241  15 44 7
41 1231453023109121 35 45 3
42 1337006139375617 19 46 3
43 3799912185593857 27 47 5
44 4222124650659841 15 48 19
45 7881299347898369 7 50 6
46 31525197391593473 7 52 3
47 180143985094819841 5 55 6
48 194555039024054273 27 56 5
49 4179340454199820289 29 57 3
50 9097271247288401921 505 54 6 */
51
52 const int g = 3;
53 const ll MOD = 998244353;
54
55 ll pw(ll a, ll n) { /* fast pow */ }
56
57 #define siz(x) (int)x.size()
58
59 template<typename T>
60 vector<T>& operator+=(vector<T>& a, const vector<T>& b) {
61     if (siz(a) < siz(b)) a.resize(siz(b));
62     for (int i = 0; i < min(siz(a), siz(b)); i++) {
63         a[i] += b[i];
64         a[i] -= a[i] >= MOD ? MOD : 0;
65     }
66     return a;
67 }
68
69 template<typename T>
70 vector<T>& operator-=(vector<T>& a, const vector<T>& b) {
71     if (siz(a) < siz(b)) a.resize(siz(b));
72     for (int i = 0; i < min(siz(a), siz(b)); i++) {
73         a[i] -= b[i];
74         a[i] += a[i] < 0 ? MOD : 0;
75     }
76     return a;
77 }
78
79 template<typename T>
80 vector<T> operator-(const vector<T>& a) {
81     vector<T> ret(siz(a));
82     for (int i = 0; i < siz(a); i++) {
83         ret[i] = -a[i] < 0 ? -a[i] + MOD : -a[i];
84     }
85     return ret;
86 }
87
88 vector<ll> X, iX;
89 vector<int> rev;
90
91 void init_ntt() {
92     X.clear(); X.resize(maxn, 1); // x1 = g^((p-1)/n)
93     iX.clear(); iX.resize(maxn, 1);
94
95     ll u = pw(g, (MOD-1)/maxn);
96     ll iu = pw(u, MOD-2);
97
98     for (int i = 1; i < maxn; i++) {
99         X[i] = X[i-1] * u;
100        iX[i] = iX[i-1] * iu;
101        if (X[i] >= MOD) X[i] %= MOD;
102        if (iX[i] >= MOD) iX[i] %= MOD;
103    }
104
105    rev.clear(); rev.resize(maxn, 0);
106    for (int i = 1, hb = -1; i < maxn; i++) {
107        if (!(i & (i-1))) hb++;
108        rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
109    }
110
111    template<typename T>
112    void NTT(vector<T>& a, bool inv=false) {
113
114        int _n = (int)a.size();
115        int k = __lg(_n) + ((1<<__lg(_n)) != _n);
116        int n = 1<<k;
117        a.resize(n, 0);
118
119        short shift = maxk-k;
120        for (int i = 0; i < n; i++)
121            if (i > (rev[i]>>shift))
122                swap(a[i], a[rev[i]>>shift]);
123
124        for (int len = 2, half = 1, div = maxn>>1; len <= n
125            ; len<=1, half<=1, div>=1) {
126            for (int i = 0; i < n; i += len) {
127                for (int j = 0; j < half; j++) {
128                    T u = a[i+j];
129                    T v = a[i+j+half] * (inv ? iX[j*div] :
130                        X[j*div]) % MOD;
131                    a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
132                    a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
133                }
134            }
135            if (inv) {
136                T dn = pw(n, MOD-2);
137                for (auto& x : a) {
138                    x *= dn;
139                    if (x >= MOD) x %= MOD;
140                }
141            }
142        }
143
144        template<typename T>
145        inline void resize(vector<T>& a) {
146            int cnt = (int)a.size();
147            for (; cnt > 0; cnt--) if (a[cnt-1]) break;
148            a.resize(max(cnt, 1));
149        }
150
151        template<typename T>
152        vector<T>& operator*=(vector<T>& a, vector<T> b) {
153            int na = (int)a.size();
154            int nb = (int)b.size();
155            a.resize(na + nb - 1, 0);
156            b.resize(na + nb - 1, 0);
157
158            NTT(a); NTT(b);
159            for (int i = 0; i < (int)a.size(); i++) {
160                a[i] *= b[i];
161                if (a[i] >= MOD) a[i] %= MOD;
162            }
163            NTT(a, true);
164
165            resize(a);
166            return a;
167        }
168
169        template<typename T>
170        void inv(vector<T>& ia, int N) {
171            vector<T> _a(move(ia));
172            ia.resize(1, pw(_a[0], MOD-2));
173            vector<T> a(1, -_a[0] + (-_a[0] < 0 ? MOD : 0));
174
175            for (int n = 1; n < N; n<=1) {
176                // n -> 2*n
177                // ia' = ia(2-a*ia);
178                for (int i = n; i < min(siz(_a), (n<<1)); i++)
179                    a.emplace_back(-_a[i] + (-_a[i] < 0 ? MOD :
180                        0));
181            }
182        }
183    }

```

```

177     vector<T> tmp = ia;
178     ia *= a;
179     ia.resize(n<<1);
180     ia[0] = ia[0] + 2 >= MOD ? ia[0] + 2 - MOD : ia
181         [0] + 2;
182     ia *= tmp;
183     ia.resize(n<<1);
184 }
185 ia.resize(N);
186 }
187
188 template<typename T>
189 void mod(vector<T>& a, vector<T>& b) {
190     int n = (int)a.size()-1, m = (int)b.size()-1;
191     if (n < m) return;
192
193     vector<T> ra = a, rb = b;
194     reverse(ra.begin(), ra.end()); ra.resize(min(n+1, n
195         -m+1));
196     reverse(rb.begin(), rb.end()); rb.resize(min(m+1, n
197         -m+1));
198
199     inv(rb, n-m+1);
200
201     vector<T> q = move(ra);
202     q *= rb;
203     q.resize(n-m+1);
204     reverse(q.begin(), q.end());
205
206     q *= b;
207     a -= q;
208     resize(a);
209 }
210
211 /* Kitamasa Method (Fast Linear Recurrence):
212 Find a[K] (Given a[j] = c[0]a[j-N] + ... + c[N-1]a[j
213     -1])
214 Let B(x) = x^N - c[N-1]x^(N-1) - ... - c[1]x^1 - c[0]
215 Let R(x) = x^K mod B(x) (get x^K using fast pow and
216     use poly mod to get R(x))
217 Let r[i] = the coefficient of x^i in R(x)
218 => a[K] = a[0]r[0] + a[1]r[1] + ... + a[N-1]r[N-1] */

```

## 9 Linear Algebra

### 9.1 Gaussian-Jordan Elimination

```

1 int n;
2 vector<vector<ll>> v;
3 void gauss(vector<vector<ll>>& v) {
4     int r = 0;
5     for (int i = 0; i < n; i++) {
6         bool ok = false;
7         for (int j = r; j < n; j++) {
8             if (v[j][i] != 0) continue;
9             swap(v[j], v[r]);
10            ok = true;
11            break;
12        }
13        if (!ok) continue;
14        ll div = inv(v[r][i]);
15        for (int j = 0; j < n + 1; j++) {
16            v[r][j] *= div;
17            if (v[r][j] >= MOD) v[r][j] %= MOD;
18        }
19        for (int j = 0; j < n; j++) {
20            if (j == r) continue;
21            ll t = v[j][i];
22            for (int k = 0; k < n + 1; k++) {
23                v[j][k] -= v[r][k] * t % MOD;
24                if (v[j][k] < 0) v[j][k] += MOD;
25            }
26        }
27        r++;
28    }
29 }

```

### 9.2 Determinant

1. Use GJ Elimination, if there's any row consists of only

0, then  $\det = 0$ , otherwise  $\det = \text{product of diagonal elements}$ .

#### 2. Properties of $\det$ :

- Transpose: Unchanged
- Row Operation 1 - Swap 2 rows:  $-\det$
- Row Operation 2 -  $k\vec{r}_i$ :  $k \times \det$
- Row Operation 3 -  $k\vec{r}_i$  add to  $\vec{r}_j$ : Unchanged

## 10 Combinatorics

### 10.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

### 10.2 Burnside's Lemma

Let  $X$  be the original set.

Let  $G$  be the group of operations acting on  $X$ .

Let  $X^g$  be the set of  $x$  not affected by  $g$ .

Let  $X/G$  be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

## 11 Special Numbers

### 11.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

### 11.2 Prime Numbers

- First 50 prime numbers:

1	2	3	5	7	11
6	13	17	19	23	29
11	31	37	41	43	47
16	53	59	61	67	71
21	73	79	83	89	97
26	101	103	107	109	113
31	127	131	137	139	149
36	151	157	163	167	173
41	179	181	191	193	197
46	199	211	223	227	229

- Very large prime numbers:

1000001333	1000500889	2500001909
2000000659	900004151	850001359

- $\pi(n) \equiv \text{Number of primes } \leq n \approx n/((\ln n) - 1)$   
 $\pi(100) = 25, \pi(200) = 46$   
 $\pi(500) = 95, \pi(1000) = 168$   
 $\pi(2000) = 303, \pi(4000) = 550$   
 $\pi(10^4) = 1229, \pi(10^5) = 9592$   
 $\pi(10^6) = 78498, \pi(10^7) = 664579$