

Contents

1 Reminder	1
1.1 Bug List	1
1.2 OwO	1
2 Basic	1
2.1 Vimrc	1
2.2 Runcpp.sh	1
2.3 PBDS	1
2.4 Random	1
2.5 pragma	1
2.6 set map pq cmp	1
3 Data Structure	2
3.1 BIT	2
3.2 DSU	2
3.3 Segment Tree	2
3.4 Treap	2
3.5 Persistent Treap	2
3.6 Li Chao Tree	3
3.7 Sparse Table	3
3.8 Time Segment Tree	3
3.9 Dynamic Median	4
3.10 SOS DP	4
4 Flow / Matching	4
4.1 Dinic	4
4.2 MCMF	4
4.3 KM	5
4.4 Hopcroft-Karp	5
4.5 Blossom	6
4.6 Weighted Blossom	6
4.7 Cover / Independent Set	8
4.8 Hungarian Algorithm	8
5 Graph	8
5.1 Heavy-Light Decomposition	8
5.2 Centroid Decomposition	9
5.3 Bellman-Ford + SPFA	9
5.4 BCC - AP	10
5.5 BCC - Bridge	10
5.6 SCC - Tarjan	11
5.7 SCC - Kosaraju	11
5.8 Eulerian Path - Undir	11
5.9 Eulerian Path - Dir	12
5.10 Hamilton Path	12
5.11 Kth Shortest Path	12
5.12 System of Difference Constraints	13

6 String	13
6.1 Aho Corasick	13
6.2 KMP	14
6.3 Z Value	14
6.4 Manacher	14
6.5 Suffix Array	14
6.6 Minimum Rotation	15
6.7 Lyndon Factorization	15
6.8 Rolling Hash	15
6.9 Trie	15
7 Geometry	15
7.1 Basic Operations	15
7.2 Sort by Angle	16
7.3 Intersection	16
7.4 Polygon Area	16
7.5 Convex Hull	16
7.6 Point In Convex	16
7.7 Point Segment Distance	17
7.8 Point in Polygon	17
7.9 Minimum Euclidean Distance	17
7.10 Minkowski Sum	17
7.11 Lower Concave Hull	17
7.12 Pick's Theorem	17
7.13 Rotating SweepLine	17
7.14 Half Plane Intersection	18
7.15 Minimum Enclosing Circle	18
7.16 Union of Circles	18
7.17 Area Of Circle Polygon	18
8 Number Theory	19
8.1 FFT	19
8.2 Pollard's rho	19
8.3 Miller Rabin	20
8.4 Fast Power	20
8.5 Extend GCD	20
8.6 Mu + Phi	20
8.7 Discrete Log	20
8.8 sqrt mod	20
8.9 Primitive Root	21
8.10 Other Formulas	21
8.11 Polynomial	21
9 Linear Algebra	23
9.1 Gaussian-Jordan Elimination	23
9.2 Determinant	23
10 Combinatorics	23
10.1 Catalan Number	23
10.2 Burnside's Lemma	23
11 Special Numbers	23
11.1 Fibonacci Series	23
11.2 Prime Numbers	23

2 Basic

2.1 Vimrc

```
set number relativenumber ai t_Co=256 tabstop=4
set mouse=a shiftwidth=4 encoding=utf8
set bs=2 ruler laststatus=2 cmdheight=2
set clipboard=unnamedplus showcmd autoread
set belloff=all
filetype indent on

inoremap ( (<Esc>i
inoremap " "<Esc>i
inoremap [ [<Esc>i
inoremap ' '<Esc>i
inoremap { {<CR><Esc>ko

nnoremap <tab> gt
nnoremap <S-tab> gT
inoremap <C-n> <Esc>:tabnew<CR>
nnoremap <C-n> :tabnew<CR>

inoremap <F9> <Esc>:w<CR>:!/~/runcpp.sh %:p:t %:p:h<CR>
nnoremap <F9> :w<CR>:!/~/runcpp.sh %:p:t %:p:h<CR>

syntax on
colorscheme desert
set filetype=cpp
set background=dark
hi Normal ctermfg=white ctermbg=black
```

2.2 Runcpp.sh

```
#!/bin/bash
clear
echo "Start compiling $1..."
echo
g++ -O2 -std=c++20 -Wall -Wextra -Wshadow $2/$1 -o $2/
out
if [ "$?" -ne 0 ]
then
exit 1
fi
echo
echo "Done compiling"
echo "=====
echo "Input file:"
echo
cat $2/in.txt
echo
echo "=====
echo
declare startTime=`date +%s%N`
$2/out < $2/in.txt > $2/out.txt
declare endTime=`date +%s%N`
delta=`expr $endTime - $startTime`
delta=`expr $delta / 1000000`
cat $2/out.txt
echo
echo "time: $delta ms"
```

2.3 PBDS

```
#include <bits/extc++.h>
using namespace __gnu_pbds;

// map
tree<int, int, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// set
tree<int, null_type, less<>, rb_tree_tag,
tree_order_statistics_node_update> tr;
tr.order_of_key(element);
tr.find_by_order(rank);

// hash table
gp_hash_table<int, int> ht;
ht.find(element);
```

1 Reminder

1.1 Bug List

- 沒開 long long
- 陣列戳出界 / 開不夠大 / 開太大本地 compile 噴怪 error
- 傳之前先確定選對檔案
- 寫好的函式忘記呼叫
- 變數打錯
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- <= 打成 <+
- dp[i] 從 dp[i-1] 轉移時忘記特判 i > 0
- std::sort 比較運算子寫成 < 或是讓 = 的情況為 true
- 漏 case / 分 case 要好好想
- 線段樹改值懶標初始值不能設為 0
- DFS 的時候不小心覆寫到全域變數
- 浮點數誤差
- 多筆測資不能沒讀完直接 return
- 記得刪 cerr

1.2 OwO

- 可以構造複雜點的測資幫助思考
- 真的卡太久請跳題
- Enjoy The Contest!

```

17 ht.insert({key, value});
18 ht.erase(element);
19
20 // priority queue
21 __gnu_pbds::priority_queue<int, less<int>> big_q;
    // Big First
22 __gnu_pbds::priority_queue<int, greater<int>> small_q;
    // Small First
23 q1.join(q2); // join

```

2.4 Random

```

1 mt19937 gen(chrono::steady_clock::now().
    time_since_epoch().count());
2 uniform_int_distribution<int> dis(1, 100);
3 cout << dis(gen) << endl;
4 shuffle(v.begin(), v.end(), gen);

```

2.5 pragma

```

1 #pragma GCC optimize("O3,unroll-loops")
2 #pragma GCC target("avx2,bmi,bmi2,lzcnt,popcnt")
3 #pragma GCC optimize("trapv")

```

2.6 set map pq cmp

```

1 struct edge
2 {
3     int a, b, w;
4     friend istream& operator>>(istream &in, edge &x)
5     { in >> x.a >> x.b >> x.w; }
6     friend ostream& operator<<(ostream &out, const edge
    &x)
7     { out << "(" << x.a << "," << x.b << "," << x.w
    << ")"; return out; }
8 };
9
10 struct cmp
11 { bool operator()(const edge &x, const edge &y)
    const { return x.w < y.w; } };
12
13 set<edge, cmp> st; // 遞增
14 map<edge, long long, cmp> mp; // 遞增
15 priority_queue<edge, vector<edge>, cmp> pq; // 遞減

```

3 Data Structure

3.1 BIT

```

1 struct BIT {
2     int n;
3     long long bit[N];
4
5     void init(int x, vector<long long> &a) {
6         n = x;
7         for (int i = 1, j; i <= n; i++) {
8             bit[i] += a[i - 1], j = i + (i & -i);
9             if (j <= n) bit[j] += bit[i];
10        }
11    }
12
13    void update(int x, long long dif) {
14        while (x <= n) bit[x] += dif, x += x & -x;
15    }
16
17    long long query(int l, int r) {
18        if (l != 1) return query(1, r) - query(1, l -
19        1);
20
21        long long ret = 0;
22        while (l <= r) ret += bit[r], r -= r & -r;
23        return ret;
24    }
25 } bm;

```

3.2 DSU

```

1 struct DSU {
2     int h[N], s[N];
3

```

```

4     void init(int n) { iota(h, h + n + 1, 0), fill(s, s
    + n + 1, 1); }
5
6     int fh(int x) { return (h[x] == x ? x : h[x] = fh(h
    [x])); }
7
8     bool mer(int x, int y) {
9         x = fh(x), y = fh(y);
10        if (x == y) return 0;
11        if (s[x] < s[y]) swap(x, y);
12        s[x] += s[y], s[y] = 0;
13        h[y] = x;
14        return 1;
15    }
16 } bm;

```

3.3 Segment Tree

```

1 struct segtree {
2     int n, seg[1 << 19];
3
4     void init(int x) {
5         n = 1 << (lg(x) + 1);
6         for (int i = 1; i < 2 * n; i++)
7             seg[i] = inf;
8     }
9
10    void update(int x, int val) {
11        x += n;
12        seg[x] = val, x /= 2;
13        while (x)
14            seg[x] = min(seg[2 * x], seg[2 * x + 1]), x
    /= 2;
15    }
16
17    int query(int l, int r) {
18        l += n, r += n;
19        int ret = inf;
20        while (l < r) {
21            if (l & 1)
22                ret = min(ret, seg[l++]);
23            if (r & 1)
24                ret = min(ret, seg[--r]);
25            l /= 2, r /= 2;
26        }
27        return ret;
28    }
29 } bm;

```

3.4 Treap

```

1 mt19937 rng(random_device{}());
2 struct Treap {
3     Treap *l, *r;
4     int val, num, pri;
5     Treap(int k) {
6         l = r = NULL;
7         val = k;
8         num = 1;
9         pri = rng();
10    }
11 };
12 int siz(Treap *now) { return now ? now->num : 0; }
13 void pull(Treap *&now) {
14     now->num = siz(now->l) + siz(now->r) + 1;
15 }
16 Treap *merge(Treap *a, Treap *b) {
17     if (!a || !b)
18         return a ? a : b;
19     else if (a->pri > b->pri) {
20         a->r = merge(a->r, b);
21         pull(a);
22         return a;
23     } else {
24         b->l = merge(a, b->l);
25         pull(b);
26         return b;
27     }
28 }
29 void split_size(Treap *rt, Treap *&a, Treap *&b, int
    val) {
30     if (!rt) {

```

```

31     a = b = NULL;
32     return;
33 }
34 if (siz(rt->l) + 1 > val) {
35     b = rt;
36     split_size(rt->l, a, b->l, val);
37     pull(b);
38 } else {
39     a = rt;
40     split_size(rt->r, a->r, b, val - siz(a->l) - 1);
41     pull(a);
42 }
43 }
44 void split_val(Treap *rt, Treap *&a, Treap *&b, int val)
45 {
46     if (!rt) {
47         a = b = NULL;
48         return;
49     }
50     if (rt->val <= val) {
51         a = rt;
52         split_val(rt->r, a->r, b, val);
53     } else {
54         b = rt;
55         split_val(rt->l, a, b->l, val);
56     }
57 }
58 }
59 void treap_dfs(Treap *now) {
60     if (!now) return;
61     treap_dfs(now->l);
62     cout << now->val << " ";
63     treap_dfs(now->r);
64 }

```

3.5 Persistent Treap

```

1 struct node {
2     node *l, *r;
3     char c;
4     int v, sz;
5     node(char x = '$') : c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? b;
18     if (a->v < b->v) {
19         node* ret = new (ptr++) node(a);
20         ret->r = merge(ret->r, b); ret->pull();
21         return ret;
22     } else {
23         node* ret = new (ptr++) node(b);
24         ret->l = merge(a, ret->l); ret->pull();
25         return ret;
26     }
27 }
28 P<node*> split(node* p, int k) {
29     if (!p) return {nullptr, nullptr};
30     if (k >= size(p->l) + 1) {
31         auto [a, b] = split(p->r, k - size(p->l) - 1);
32         node* ret = new (ptr++) node(p);
33         ret->r = a; ret->pull();
34         return {ret, b};
35     } else {
36         auto [a, b] = split(p->l, k);
37         node* ret = new (ptr++) node(p);
38         ret->l = b; ret->pull();
39         return {a, ret};
40     }
41 }

```

3.6 Li Chao Tree

```

1 constexpr int maxn = 5e4 + 5;
2 struct line {
3     ld a, b;
4     ld operator()(ld x) { return a * x + b; }
5 } arr[(maxn + 1) << 2];
6 bool operator<(line a, line b) { return a.a < b.a; }
7 #define m ((l + r) >> 1)
8 void insert(line x, int i = 1, int l = 0, int r = maxn)
9 {
10     if (r - l == 1) {
11         if (x(l) > arr[i](l))
12             arr[i] = x;
13         return;
14     }
15     line a = max(arr[i], x), b = min(arr[i], x);
16     if (a(m) > b(m))
17         arr[i] = a, insert(b, i << 1, l, m);
18     else
19         arr[i] = b, insert(a, i << 1 | 1, m, r);
20 }
21 ld query(int x, int i = 1, int l = 0, int r = maxn) {
22     if (x < l || r <= x) return -numeric_limits<ld>::
23         max();
24     if (r - l == 1) return arr[i](x);
25     return max({arr[i](x), query(x, i << 1, l, m),
26         query(x, i << 1 | 1, m, r)});
27 }
28 #undef m

```

3.7 Sparse Table

```

1 const int lgmx = 19;
2
3 int n, q;
4 int spt[lgmx][maxn];
5
6 void build() {
7     FOR(k, 1, lgmx, 1) {
8         for (int i = 0; i + (1 << k) - 1 < n; i++) {
9             spt[k][i] = min(spt[k - 1][i], spt[k - 1][i
10                 + (1 << (k - 1))]);
11         }
12     }
13 }
14 int query(int l, int r) {
15     int ln = len(l, r);
16     int lg = __lg(ln);
17     return min(spt[lg][l], spt[lg][r - (1 << lg) + 1]);
18 }

```

3.8 Time Segment Tree

```

1 constexpr int maxn = 1e5 + 5;
2 V<P<int>> arr[(maxn + 1) << 2];
3 V<int> dsu, sz;
4 V<tuple<int, int, int>> his;
5 int cnt, q;
6 int find(int x) {
7     return x == dsu[x] ? x : find(dsu[x]);
8 }
9 inline bool merge(int x, int y) {
10     int a = find(x), b = find(y);
11     if (a == b) return false;
12     if (sz[a] > sz[b]) swap(a, b);
13     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
14         sz[a];
15     return true;
16 }
17 inline void undo() {
18     auto [a, b, s] = his.back();
19     his.pop_back();
20     dsu[a] = a, sz[b] = s;
21 }
22 #define m ((l + r) >> 1)
23 void insert(int ql, int qr, P<int> x, int i = 1, int l
24     = 0, int r = q) {
25     // debug(ql, qr, x); return;
26     if (qr <= l || r <= ql) return;
27     if (ql <= l && r <= qr) {

```

```

26     arr[i].push_back(x);
27     return;
28 }
29 if (qr <= m)
30     insert(q1, qr, x, i << 1, 1, m);
31 else if (m <= q1)
32     insert(q1, qr, x, i << 1 | 1, m, r);
33 else {
34     insert(q1, qr, x, i << 1, 1, m);
35     insert(q1, qr, x, i << 1 | 1, m, r);
36 }
37 }
38 void traversal(V<int>& ans, int i = 1, int l = 0, int r
39             = q) {
40     int opcnt = 0;
41     // debug(i, l, r);
42     for (auto [a, b] : arr[i])
43         if (merge(a, b))
44             opcnt++, cnt--;
45     if (r - l == 1)
46         ans[l] = cnt;
47     else {
48         traversal(ans, i << 1, l, m);
49         traversal(ans, i << 1 | 1, m, r);
50     }
51     while (opcnt--)
52         undo(), cnt++;
53     arr[i].clear();
54 }
55 #undef m
56 inline void solve() {
57     int n, m;
58     cin >> n >> m >> q, q++;
59     dsu.resize(cnt = n), sz.assign(n, 1);
60     iota(dsu.begin(), dsu.end(), 0);
61     // a, b, time, operation
62     unordered_map<ll, V<int>>> s;
63     for (int i = 0; i < m; i++) {
64         int a, b;
65         cin >> a >> b;
66         if (a > b) swap(a, b);
67         s[(((ll)a << 32) | b).emplace_back(0);
68     }
69     for (int i = 1; i < q; i++) {
70         int op, a, b;
71         cin >> op >> a >> b;
72         if (a > b) swap(a, b);
73         switch (op) {
74             case 1:
75                 s[(((ll)a << 32) | b).push_back(i);
76                 break;
77             case 2:
78                 auto tmp = s[(((ll)a << 32) | b).back();
79                 s[(((ll)a << 32) | b).pop_back();
80                 insert(tmp, i, P<int>{a, b});
81         }
82     }
83     for (auto [p, v] : s) {
84         int a = p >> 32, b = p & -1;
85         while (v.size()) {
86             insert(v.back(), q, P<int>{a, b});
87             v.pop_back();
88         }
89     }
90     V<int> ans(q);
91     traversal(ans);
92     for (auto i : ans)
93         cout << i << ' ';
94     cout << endl;
95 }

```

3.9 Dynamic Median

```

1 struct Dynamic_Median {
2     multiset<long long> lo, hi;
3     long long slo = 0, shi = 0;
4     void rebalance() {
5         // keep sz(lo) >= sz(hi) and sz(lo) - sz(hi) <=
6         1
7         while((int)lo.size() > (int)hi.size() + 1) {
8             auto it = prev(lo.end());
9             long long x = *it;

```

```

9             lo.erase(it); slo -= x;
10            hi.insert(x); shi += x;
11        }
12        while((int)lo.size() < (int)hi.size()) {
13            auto it = hi.begin();
14            long long x = *it;
15            hi.erase(it); shi -= x;
16            lo.insert(x); slo += x;
17        }
18    }
19    void add(long long x) {
20        if(lo.empty() || x <= *prev(lo.end())) {
21            lo.insert(x); slo += x;
22        }
23        else {
24            hi.insert(x); shi += x;
25        }
26        rebalance();
27    }
28    void remove_one(long long x) {
29        if(!lo.empty() && x <= *prev(lo.end())) {
30            auto it = lo.find(x);
31            if(it != lo.end()) {
32                lo.erase(it); slo -= x;
33            }
34            else {
35                auto it2 = hi.find(x);
36                hi.erase(it2); shi -= x;
37            }
38        }
39        else {
40            auto it = hi.find(x);
41            if(it != hi.end()) {
42                hi.erase(it); shi -= x;
43            }
44            else {
45                auto it2 = lo.find(x);
46                lo.erase(it2); slo -= x;
47            }
48        }
49        rebalance();
50    }
51 };

```

3.10 SOS DP

```

1 for (int mask = 0; mask < (1 << n); mask++) {
2     for (int submask = mask; submask != 0; submask = (
3         submask - 1) & mask) {
4         int subset = mask ^ submask;
5     }
6 }

```

4 Flow / Matching

4.1 Dinic

```

1 struct Dinic {
2     struct Edge { int to, cap, rev; };
3     int n, s, t;
4     vector<vector<Edge>>> g;
5     vector<int> level, it;
6
7     void init(int _n, int _s, int _t){
8         n=_n; s=_s; t=_t;
9         g.assign(n, {});
10        level.assign(n, 0);
11        it.assign(n, 0);
12    }
13    void add(int a, int b, int c){
14        Edge f{b, c, (int)g[b].size()};
15        Edge r{a, 0, (int)g[a].size()};
16        g[a].push_back(f);
17        g[b].push_back(r);
18    }
19    bool bfs(){
20        fill(level.begin(), level.end(), -1);
21        queue<int> q; level[s]=0; q.push(s);
22        while(!q.empty()){
23            int u=q.front(); q.pop();
24            for(const auto &e: g[u]){
25                if(e.cap>0 && level[e.to]==-1){

```

```

26         level[e.to]=level[u]+1;
27         q.push(e.to);
28     }
29 }
30 }
31 return level[t]!=-1;
32 }
33 int dfs(int u,int f){
34     if(!f || u==t) return f;
35     for(int &i=it[u]; i<(int)g[u].size(); ++i){
36         auto &e=g[u][i];
37         if(e.cap>0 && level[e.to]==level[u]+1){
38             int got=dfs(e.to, min(f, e.cap));
39             if(got){
40                 e.cap-=got;
41                 g[e.to][e.rev].cap+=got;
42                 return got;
43             }
44         }
45     }
46     return 0;
47 }
48 int maxflow(){
49     int flow=0, add;
50     while(bfs()){
51         fill(it.begin(), it.end(), 0);
52         while((add=dfs(s, INF))) flow+=add;
53     }
54     return flow;
55 }
56 };

```

4.2 MCMF

```

1 struct MCMF {
2     int n, s, t, par[N + 5], p_i[N + 5], dis[N + 5],
3         vis[N + 5];
4     struct edge {
5         int to, cap, rev, cost;
6     };
7     vector<edge> path[N];
8     void init(int _n, int _s, int _t) {
9         n = _n, s = _s, t = _t;
10        FOR(i, 0, 2 * n + 5)
11            par[i] = p_i[i] = vis[i] = 0;
12    }
13    void add(int a, int b, int c, int d) {
14        path[a].pb({b, c, sz(path[b]), d});
15        path[b].pb({a, 0, sz(path[a]) - 1, -d});
16    }
17    void spfa() {
18        FOR(i, 0, n * 2 + 5)
19            dis[i] = INF,
20            vis[i] = 0;
21        dis[s] = 0;
22        queue<int> q;
23        q.push(s);
24        while (!q.empty()) {
25            int now = q.front();
26            q.pop();
27            vis[now] = 0;
28            for (int i = 0; i < sz(path[now]); i++) {
29                edge e = path[now][i];
30                if (e.cap > 0 && dis[e.to] > dis[now] +
31                    e.cost) {
32                    dis[e.to] = dis[now] + e.cost;
33                    par[e.to] = now;
34                    p_i[e.to] = i;
35                    if (vis[e.to] == 0) {
36                        vis[e.to] = 1;
37                        q.push(e.to);
38                    }
39                }
40            }
41        }
42    }
43    pii flow() {
44        int flow = 0, cost = 0;
45        while (true) {
46            spfa();
47            if (dis[t] == INF)
48                break;

```

```

47     int mn = INF;
48     for (int i = t; i != s; i = par[i])
49         mn = min(mn, path[par[i]][p_i[i]].cap);
50     flow += mn;
51     cost += dis[t] * mn;
52     for (int i = t; i != s; i = par[i]) {
53         edge &now = path[par[i]][p_i[i]];
54         now.cap -= mn;
55         path[i][now.rev].cap += mn;
56     }
57 }
58 return mp(flow, cost);
59 }
60 };

```

4.3 KM

```

1 struct KM {
2     int n, mx[1005], my[1005], pa[1005];
3     int g[1005][1005], lx[1005], ly[1005], sy[1005];
4     bool vx[1005], vy[1005];
5     void init(int _n) {
6         n = _n;
7         FOR(i, 1, n + 1)
8             fill(g[i], g[i] + 1 + n, 0);
9     }
10    void add(int a, int b, int c) { g[a][b] = c; }
11    void augment(int y) {
12        for (int x, z; y; y = z)
13            x = pa[y], z = mx[x], my[y] = x, mx[x] = y;
14    }
15    void bfs(int st) {
16        FOR(i, 1, n + 1)
17            sy[i] = INF,
18            vx[i] = vy[i] = 0;
19        queue<int> q;
20        q.push(st);
21        for (;;) {
22            while (!q.empty()) {
23                int x = q.front();
24                q.pop();
25                vx[x] = 1;
26                FOR(y, 1, n + 1)
27                    if (!vy[y]) {
28                        int t = lx[x] + ly[y] - g[x][y];
29                        if (t == 0) {
30                            pa[y] = x;
31                            if (!my[y]) {
32                                augment(y);
33                                return;
34                            }
35                            vy[y] = 1, q.push(my[y]);
36                        } else if (sy[y] > t)
37                            pa[y] = x, sy[y] = t;
38                    }
39            }
40            int cut = INF;
41            FOR(y, 1, n + 1)
42                if (!vy[y] && cut > sy[y]) cut = sy[y];
43            FOR(j, 1, n + 1) {
44                if (vx[j]) lx[j] -= cut;
45                if (vy[j]) ly[j] += cut;
46                else sy[j] -= cut;
47            }
48            FOR(y, 1, n + 1) {
49                if (!vy[y] && sy[y] == 0) {
50                    if (!my[y]) {
51                        augment(y);
52                        return;
53                    }
54                }
55                vy[y] = 1;
56                q.push(my[y]);
57            }
58        }
59    }
60 }
61 }
62 int solve() {
63     fill(mx, mx + n + 1, 0);
64     fill(my, my + n + 1, 0);
65     fill(ly, ly + n + 1, 0);

```

```

66     fill(lx, lx + n + 1, 0);
67     FOR(x, 1, n + 1)
68     FOR(y, 1, n + 1)
69     lx[x] = max(lx[x], g[x][y]);
70     FOR(x, 1, n + 1)
71     bfs(x);
72     int ans = 0;
73     FOR(y, 1, n + 1)
74     ans += g[my[y]][y];
75     return ans;
76 }
77 };

```

4.4 Hopcroft-Karp

```

1 struct HopcroftKarp {
2     // id: X = [1, nx], Y = [nx+1, nx+ny]
3     int n, nx, ny, m, MXCNT;
4     vector<vector<int>> > g;
5     vector<int> mx, my, dis, vis;
6     void init(int nnx, int nny, int mm) {
7         nx = nnx, ny = nny, m = mm;
8         n = nx + ny + 1;
9         g.clear();
10        g.resize(n);
11    }
12    void add(int x, int y) {
13        g[x].emplace_back(y);
14        g[y].emplace_back(x);
15    }
16    bool dfs(int x) {
17        vis[x] = true;
18        Each(y, g[x]) {
19            int px = my[y];
20            if (px == -1 ||
21                (dis[px] == dis[x] + 1 &&
22                 !vis[px] && dfs(px))) {
23                mx[x] = y;
24                my[y] = x;
25                return true;
26            }
27        }
28        return false;
29    }
30    void get() {
31        mx.clear();
32        mx.resize(n, -1);
33        my.clear();
34        my.resize(n, -1);
35
36        while (true) {
37            queue<int> q;
38            dis.clear();
39            dis.resize(n, -1);
40            for (int x = 1; x <= nx; x++) {
41                if (mx[x] == -1) {
42                    dis[x] = 0;
43                    q.push(x);
44                }
45            }
46            while (!q.empty()) {
47                int x = q.front();
48                q.pop();
49                Each(y, g[x]) {
50                    if (my[y] != -1 && dis[my[y]] ==
51                        -1) {
52                        dis[my[y]] = dis[x] + 1;
53                        q.push(my[y]);
54                    }
55                }
56            }
57            bool brk = true;
58            vis.clear();
59            vis.resize(n, 0);
60            for (int x = 1; x <= nx; x++)
61                if (mx[x] == -1 && dfs(x))
62                    brk = false;
63
64            if (brk) break;
65        }
66        MXCNT = 0;

```

```

67         for (int x = 1; x <= nx; x++)
68             if (mx[x] != -1) MXCNT++;
69     }
70 } hk;

```

4.5 Blossom

```

1 const int N=5e2+10;
2 struct Graph{
3     int to[N],bro[N],head[N],e;
4     int lnk[N],vis[N],stp,n;
5     void init(int _n){
6         stp=0;e=1;n=_n;
7         FOR(i,0,n+1)head[i]=lnk[i]=vis[i]=0;
8     }
9     void add(int u,int v){
10        to[e]=v,bro[e]=head[u],head[u]=e++;
11        to[e]=u,bro[e]=head[v],head[v]=e++;
12    }
13    bool dfs(int x){
14        vis[x]=stp;
15        for(int i=head[x];i;i=bro[i])
16        {
17            int v=to[i];
18            if(!lnk[v])
19            {
20                lnk[x]=v;lnk[v]=x;
21                return true;
22            }
23            else if(vis[lnk[v]]<stp)
24            {
25                int w=lnk[v];
26                lnk[x]=v,lnk[v]=x,lnk[w]=0;
27                if(dfs(w))return true;
28                lnk[w]=v,lnk[v]=w,lnk[x]=0;
29            }
30        }
31        return false;
32    }
33    int solve(){
34        int ans=0;
35        FOR(i,1,n+1){
36            if(!lnk[i]){
37                stp++;
38                ans+=dfs(i);
39            }
40        }
41        return ans;
42    }
43    void print_matching(){
44        FOR(i,1,n+1)
45            if(i<graph.lnk[i])
46                cout<<i<<" "<<graph.lnk[i]<<endl;
47    }
48 };

```

4.6 Weighted Blossom

```

1 struct WeightGraph { // 1-based
2     static const int inf = INT_MAX;
3     static const int maxn = 514;
4     struct edge {
5         int u, v, w;
6         edge() {}
7         edge(int u, int v, int w) : u(u), v(v), w(w) {}
8     };
9     int n, n_x;
10    edge g[maxn * 2][maxn * 2];
11    int lab[maxn * 2];
12    int match[maxn * 2], slack[maxn * 2], st[maxn * 2],
13        pa[maxn * 2];
14    int flo_from[maxn * 2][maxn + 1], S[maxn * 2], vis[
15        maxn * 2];
16    vector<int> flo[maxn * 2];
17    queue<int> q;
18    int e_delta(const edge &e) { return lab[e.u] + lab[
19        e.v] - g[e.u][e.v].w * 2; }
20    void update_slack(int u, int x) {
21        if (!slack[x] || e_delta(g[u][x]) < e_delta(g[
22            slack[x]][x])) slack[x] = u;
23    }
24    void set_slack(int x) {

```



```

21     slack[x] = 0;
22     for (int u = 1; u <= n; ++u)
23         if (g[u][x].w > 0 && st[u] != x && S[st[u]]
24             == 0)
25             update_slack(u, x);
26 void q_push(int x) {
27     if (x <= n)
28         q.push(x);
29     else
30         for (size_t i = 0; i < flo[x].size(); ++i)
31             q_push(flo[x][i]);
32 }
33 void set_st(int x, int b) {
34     st[x] = b;
35     if (x > n)
36         for (size_t i = 0; i < flo[x].size(); ++i)
37             set_st(flo[x][i], b);
38 }
39 int get_pr(int b, int xr) {
40     int pr = find(flo[b].begin(), flo[b].end(), xr) -
41         flo[b].begin();
42     if (pr % 2 == 1) {
43         reverse(flo[b].begin() + 1, flo[b].end());
44         return (int)flo[b].size() - pr;
45     }
46     return pr;
47 }
48 void set_match(int u, int v) {
49     match[u] = g[u][v].v;
50     if (u <= n) return;
51     edge e = g[u][v];
52     int xr = flo_from[u][e.u], pr = get_pr(u, xr);
53     for (int i = 0; i < pr; ++i) set_match(flo[u][i],
54         flo[u][i ^ 1]);
55     set_match(xr, v);
56     rotate(flo[u].begin(), flo[u].begin() + pr, flo[u].end());
57 }
58 void augment(int u, int v) {
59     for (;;) {
60         int xnv = st[match[u]];
61         set_match(u, v);
62         if (!xnv) return;
63         set_match(xnv, st[pa[xnv]]);
64         u = st[pa[xnv]], v = xnv;
65     }
66 }
67 int get_lca(int u, int v) {
68     static int t = 0;
69     for (++t; u || v; swap(u, v)) {
70         if (u == 0) continue;
71         if (vis[u] == t) return u;
72         vis[u] = t;
73         u = st[match[u]];
74         if (u) u = st[pa[u]];
75     }
76     return 0;
77 }
78 void add_blossom(int u, int lca, int v) {
79     int b = n + 1;
80     while (b <= n_x && st[b]) ++b;
81     if (b > n_x) ++n_x;
82     lab[b] = 0, S[b] = 0;
83     match[b] = match[lca];
84     flo[b].clear();
85     flo[b].push_back(lca);
86     for (int x = u, y; x != lca; x = st[pa[y]])
87         flo[b].push_back(x), flo[b].push_back(y =
88             st[match[x]]), q_push(y);
89     reverse(flo[b].begin() + 1, flo[b].end());
90     for (int x = v, y; x != lca; x = st[pa[y]])
91         flo[b].push_back(x), flo[b].push_back(y =
92             st[match[x]]), q_push(y);
93     set_st(b, b);
94     for (int x = 1; x <= n_x; ++x) g[b][x].w = g[x]
95         [b].w = 0;
96     for (int x = 1; x <= n; ++x) flo_from[b][x] =
97         0;
98     for (size_t i = 0; i < flo[b].size(); ++i) {
99         int xs = flo[b][i];
100         for (int x = 1; x <= n_x; ++x)
101             if (g[b][x].w == 0 || e_delta(g[xs][x])
102                 < e_delta(g[b][x]))
103                 g[b][x] = g[xs][x], g[x][b] = g[x][
104                     xs];
105         for (int x = 1; x <= n; ++x)
106             if (flo_from[xs][x]) flo_from[b][x] =
107                 xs;
108     }
109     set_slack(b);
110 }
111 void expand_blossom(int b) {
112     for (size_t i = 0; i < flo[b].size(); ++i)
113         set_st(flo[b][i], flo[b][i]);
114     int xr = flo_from[b][g[b][pa[b]].u], pr =
115         get_pr(b, xr);
116     for (int i = 0; i < pr; i += 2) {
117         int xs = flo[b][i], xns = flo[b][i + 1];
118         pa[xs] = g[xns][xs].u;
119         S[xs] = 1, S[xns] = 0;
120         slack[xs] = 0, set_slack(xns);
121         q_push(xns);
122     }
123     S[xr] = 1, pa[xr] = pa[b];
124     for (size_t i = pr + 1; i < flo[b].size(); ++i)
125         {
126             int xs = flo[b][i];
127             S[xs] = -1, set_slack(xs);
128         }
129     st[b] = 0;
130 }
131 bool on_found_edge(const edge &e) {
132     int u = st[e.u], v = st[e.v];
133     if (S[v] == -1) {
134         pa[v] = e.u, S[v] = 1;
135         int nu = st[match[v]];
136         slack[v] = slack[nu] = 0;
137         S[nu] = 0, q_push(nu);
138     } else if (S[v] == 0) {
139         int lca = get_lca(u, v);
140         if (!lca)
141             return augment(u, v), augment(v, u),
142                 true;
143         else
144             add_blossom(u, lca, v);
145     }
146     return false;
147 }
148 bool matching() {
149     memset(S + 1, -1, sizeof(int) * n_x);
150     memset(slack + 1, 0, sizeof(int) * n_x);
151     q = queue<int>();
152     for (int x = 1; x <= n_x; ++x)
153         if (st[x] == x && !match[x]) pa[x] = 0, S[x]
154             = 0, q_push(x);
155     if (q.empty()) return false;
156     for (;;) {
157         while (q.size()) {
158             int u = q.front();
159             q.pop();
160             if (S[st[u]] == 1) continue;
161             for (int v = 1; v <= n; ++v)
162                 if (g[u][v].w > 0 && st[u] != st[v]
163                     ) {
164                     if (e_delta(g[u][v]) == 0) {
165                         if (on_found_edge(g[u][v]))
166                             return true;
167                     } else
168                         update_slack(u, st[v]);
169                 }
170         }
171         int d = inf;
172         for (int b = n + 1; b <= n_x; ++b)
173             if (st[b] == b && S[b] == 1) d = min(d,
174                 lab[b] / 2);
175         for (int x = 1; x <= n_x; ++x)
176             if (st[x] == x && slack[x]) {
177                 if (S[x] == -1)
178                     d = min(d, e_delta(g[slack[x]]
179                         [x]));
180                 else if (S[x] == 0)
181                     d = min(d, e_delta(g[slack[x]]
182                         [x]) / 2);
183             }
184     }

```

```

163     }
164     for (int u = 1; u <= n; ++u) {
165         if (S[st[u]] == 0) {
166             if (lab[u] <= d) return 0;
167             lab[u] -= d;
168         } else if (S[st[u]] == 1)
169             lab[u] += d;
170     }
171     for (int b = n + 1; b <= n_x; ++b)
172         if (st[b] == b) {
173             if (S[st[b]] == 0)
174                 lab[b] += d * 2;
175             else if (S[st[b]] == 1)
176                 lab[b] -= d * 2;
177         }
178     q = queue<int>();
179     for (int x = 1; x <= n_x; ++x)
180         if (st[x] == x && slack[x] && st[slack[x]]
181             x] != x && e_delta(g[slack[x]][x])
182             == 0)
183             if (on_found_edge(g[slack[x]][x]))
184                 return true;
185     for (int b = n + 1; b <= n_x; ++b)
186         if (st[b] == b && S[b] == 1 && lab[b]
187             == 0) expand_blossom(b);
188     }
189     return false;
190 }
191 pair<long long, int> solve() {
192     memset(match + 1, 0, sizeof(int) * n);
193     n_x = n;
194     int n_matches = 0;
195     long long tot_weight = 0;
196     for (int u = 0; u <= n; ++u) st[u] = u, flo[u].
197         clear();
198     int w_max = 0;
199     for (int u = 1; u <= n; ++u)
200         for (int v = 1; v <= n; ++v) {
201             flo_from[u][v] = (u == v ? u : 0);
202             w_max = max(w_max, g[u][v].w);
203         }
204     for (int u = 1; u <= n; ++u) lab[u] = w_max;
205     while (matching()) ++n_matches;
206     for (int u = 1; u <= n; ++u)
207         if (match[u] && match[u] < u)
208             tot_weight += g[u][match[u]].w;
209     return make_pair(tot_weight, n_matches);
210 }
211 void add_edge(int ui, int vi, int wi) { g[ui][vi].w
212     = g[vi][ui].w = wi; }
213 void init(int _n) {
214     n = _n;
215     for (int u = 1; u <= n; ++u)
216         for (int v = 1; v <= n; ++v)
217             g[u][v] = edge(u, v, 0);
218 }
219 };

```

4.7 Cover / Independent Set

```

1 V(E) Cover: choose some V(E) to cover all E(V)
2 V(E) Independ: set of V(E) not adj to each other
3
4 M = Max Matching
5 Cv = Min V Cover
6 Ce = Min E Cover
7 Iv = Max V Ind
8 Ie = Max E Ind (equiv to M)
9
10 M = Cv (Konig Theorem)
11 Iv = V \ Cv
12 Ce = V - M
13
14 Construct Cv:
15 1. Run Dinic
16 2. Find s-t min cut
17 3. Cv = {X in T} + {Y in S}

```

4.8 Hungarian Algorithm

```

1 const int N = 2e3;
2 int match[N];

```

```

3 bool vis[N];
4 int n;
5 vector<int> ed[N];
6 int match_cnt;
7 bool dfs(int u) {
8     vis[u] = 1;
9     for (int i : ed[u]) {
10         if (match[i] == 0 || !vis[match[i]] && dfs(match
11             [i])) {
12             match[i] = u;
13             return true;
14         }
15     }
16     return false;
17 }
18 void hungary() {
19     memset(match, 0, sizeof(match));
20     match_cnt = 0;
21     for (int i = 1; i <= n; i++) {
22         memset(vis, 0, sizeof(vis));
23         if (dfs(i)) match_cnt++;
24     }
25 }

```

5 Graph

5.1 Heavy-Light Decomposition

```

1 const int N = 2e5 + 5;
2 int n, dfn[N], son[N], top[N], num[N], dep[N], p[N];
3 vector<int> path[N];
4 struct node {
5     int mx, sum;
6 } seg[N << 2];
7 void update(int x, int l, int r, int qx, int val) {
8     if (l == r) {
9         seg[x].mx = seg[x].sum = val;
10        return;
11    }
12    int mid = (l + r) >> 1;
13    if (qx <= mid) update(x << 1, l, mid, qx, val);
14    else update(x << 1 | 1, mid + 1, r, qx, val);
15    seg[x].mx = max(seg[x << 1].mx, seg[x << 1 | 1].mx);
16    seg[x].sum = seg[x << 1].sum + seg[x << 1 | 1].sum;
17 }
18 int big(int x, int l, int r, int ql, int qr) {
19     if (ql <= l && r <= qr) return seg[x].mx;
20     int mid = (l + r) >> 1;
21     int res = -INF;
22     if (ql <= mid) res = max(res, big(x << 1, l, mid,
23         ql, qr));
24     if (mid < qr) res = max(res, big(x << 1 | 1, mid +
25         1, r, ql, qr));
26     return res;
27 }
28 int ask(int x, int l, int r, int ql, int qr) {
29     if (ql <= l && r <= qr) return seg[x].sum;
30     int mid = (l + r) >> 1;
31     int res = 0;
32     if (ql <= mid) res += ask(x << 1, l, mid, ql, qr);
33     if (mid < qr) res += ask(x << 1 | 1, mid + 1, r, ql
34         , qr);
35     return res;
36 }
37 void dfs1(int now) {
38     son[now] = -1;
39     num[now] = 1;
40     for (auto i : path[now]) {
41         if (!dep[i]) {
42             dep[i] = dep[now] + 1;
43             p[i] = now;
44             dfs1(i);
45             num[now] += num[i];
46             if (son[now] == -1 || num[i] > num[son[now]
47                 ]) son[now] = i;
48         }
49     }
50 }
51 int cnt;
52 void dfs2(int now, int t) {

```



```

49     top[now] = t;
50     cnt++;
51     dfn[now] = cnt;
52     if (son[now] == -1) return;
53     dfs2(son[now], t);
54     for (auto i : path[now])
55         if (i != p[now] && i != son[now]) dfs2(i, i);
56 }
57 int path_big(int x, int y) {
58     int res = -INF;
59     while (top[x] != top[y]) {
60         if (dep[top[x]] < dep[top[y]]) swap(x, y);
61         res = max(res, big(1, 1, n, dfn[top[x]], dfn[x]));
62         x = p[top[x]];
63     }
64     if (dfn[x] > dfn[y]) swap(x, y);
65     res = max(res, big(1, 1, n, dfn[x], dfn[y]));
66     return res;
67 }
68 int path_sum(int x, int y) {
69     int res = 0;
70     while (top[x] != top[y]) {
71         if (dep[top[x]] < dep[top[y]]) swap(x, y);
72         res += ask(1, 1, n, dfn[top[x]], dfn[x]);
73         x = p[top[x]];
74     }
75     if (dfn[x] > dfn[y]) swap(x, y);
76     res += ask(1, 1, n, dfn[x], dfn[y]);
77     return res;
78 }
79 void buildTree() {
80     FOR(i, 0, n - 1) {
81         int a, b;
82         cin >> a >> b;
83         path[a].pb(b);
84         path[b].pb(a);
85     }
86 }
87 void buildHLD(int root) {
88     dep[root] = 1;
89     dfs1(root);
90     dfs2(root, root);
91     FOR(i, 1, n + 1) {
92         int now;
93         cin >> now;
94         update(1, 1, n, dfn[i], now);
95     }
96 }

```

5.2 Centroid Decomposition

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int N = 1e5 + 5;
4 vector<int> a[N];
5 int sz[N], lv[N];
6 bool used[N];
7 int f_sz(int x, int p) {
8     sz[x] = 1;
9     for (int i : a[x])
10         if (i != p && !used[i])
11             sz[x] += f_sz(i, x);
12     return sz[x];
13 }
14 int f_cen(int x, int p, int total) {
15     for (int i : a[x]) {
16         if (i != p && !used[i] && 2 * sz[i] > total)
17             return f_cen(i, x, total);
18     }
19     return x;
20 }
21 void cd(int x, int p) {
22     int total = f_sz(x, p);
23     int cen = f_cen(x, p, total);
24     lv[cen] = lv[p] + 1;
25     used[cen] = 1;
26     // cout << "cd: " << x << " " << p << " " << cen <<
27     // "\n";
28     for (int i : a[cen]) {
29         if (!used[i])
30             cd(i, cen);
31     }
32 }

```

```

30     }
31 }
32 int main() {
33     ios_base::sync_with_stdio(0);
34     cin.tie(0);
35     int n;
36     cin >> n;
37     for (int i = 0, x, y; i < n - 1; i++) {
38         cin >> x >> y;
39         a[x].push_back(y);
40         a[y].push_back(x);
41     }
42     cd(1, 0);
43     for (int i = 1; i <= n; i++)
44         cout << (char)('A' + lv[i] - 1) << " ";
45     cout << "\n";
46 }

```

5.3 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll>>> g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int>& src) {
14     dis.assign(n + 1, LINF);
15     negCycle.assign(n + 1, false);
16     rlx.assign(n + 1, 0);
17     while (!q.empty()) q.pop();
18     inq.assign(n + 1, false);
19     pa.assign(n + 1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s);
24         inq[s] = true;
25     }
26
27     while (!q.empty()) {
28         int u = q.front();
29         q.pop();
30         inq[u] = false;
31         if (rlx[u] >= n) {
32             negCycle[u] = true;
33         } else
34             for (auto& e : g[u]) {
35                 int v = e.first;
36                 ll w = e.second;
37                 if (dis[v] > dis[u] + w) {
38                     dis[v] = dis[u] + w;
39                     rlx[v] = rlx[u] + 1;
40                     pa[v] = u;
41                     if (!inq[v]) {
42                         q.push(v);
43                         inq[v] = true;
44                     }
45                 }
46             }
47     }
48 }
49
50 // Bellman-Ford
51 queue<int> q;
52 vector<int> pa;
53 void BellmanFord(vector<int>& src) {
54     dis.assign(n + 1, LINF);
55     negCycle.assign(n + 1, false);
56     pa.assign(n + 1, -1);
57
58     for (auto& s : src) dis[s] = 0;
59
60     for (int rlx = 1; rlx <= n; rlx++) {
61         for (int u = 1; u <= n; u++) {

```

```

62     if (dis[u] == LINF) continue; // Important
63     for (auto& e : g[u]) {
64         int v = e.first;
65         ll w = e.second;
66         if (dis[v] > dis[u] + w) {
67             dis[v] = dis[u] + w;
68             pa[v] = u;
69             if (rlx == n) negCycle[v] = true;
70         }
71     }
72 }
73 }
74 }
75
76 // Negative Cycle Detection
77 void NegCycleDetect() {
78     /* No Neg Cycle: NO
79     Exist Any Neg Cycle:
80     YES
81     v0 v1 v2 ... vk v0 */
82
83     vector<int> src;
84     for (int i = 1; i <= n; i++)
85         src.emplace_back(i);
86
87     SPFA(src);
88     // BellmanFord(src);
89
90     int ptr = -1;
91     for (int i = 1; i <= n; i++)
92         if (negCycle[i]) {
93             ptr = i;
94             break;
95         }
96
97     if (ptr == -1) {
98         return cout << "NO" << endl, void();
99     }
100
101     cout << "YES\n";
102     vector<int> ans;
103     vector<bool> vis(n + 1, false);
104
105     while (true) {
106         ans.emplace_back(ptr);
107         if (vis[ptr]) break;
108         vis[ptr] = true;
109         ptr = pa[ptr];
110     }
111     reverse(ans.begin(), ans.end());
112
113     vis.assign(n + 1, false);
114     for (auto& x : ans) {
115         cout << x << ' ';
116         if (vis[x]) break;
117         vis[x] = true;
118     }
119     cout << endl;
120 }
121
122 // Distance Calculation
123 void calcDis(int s) {
124     vector<int> src;
125     src.emplace_back(s);
126     SPFA(src);
127     // BellmanFord(src);
128
129     while (!q.empty()) q.pop();
130     for (int i = 1; i <= n; i++)
131         if (negCycle[i]) q.push(i);
132
133     while (!q.empty()) {
134         int u = q.front();
135         q.pop();
136         for (auto& e : g[u]) {
137             int v = e.first;
138             if (!negCycle[v]) {
139                 q.push(v);
140                 negCycle[v] = true;
141             }
142         }
143     }

```

5.4 BCC - AP

```

1  int n, m;
2  int low[maxn], dfn[maxn], instp;
3  vector<int> E, g[maxn];
4  bitset<maxn> isap;
5  bitset<maxn> vis;
6  stack<int> stk;
7  int bccnt;
8  vector<int> bcc[maxn];
9  inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e] ^ u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++;
30             dfs(v);
31             low[u] = min(low[u], low[v]);
32             if (!rt && low[v] >= dfn[u]) {
33                 // bcc found: u is ap
34                 isap[u] = true;
35                 popout(u);
36             }
37         } else {
38             // back edge
39             low[u] = min(low[u], dfn[v]);
40         }
41     }
42     // special case: root
43     if (rt) {
44         if (kid > 1) isap[u] = true;
45         popout(u);
46     }
47 }
48 void init() {
49     cin >> n >> m;
50     fill(low, low + maxn, INF);
51     REP(i, m) {
52         int u, v;
53         cin >> u >> v;
54         g[u].emplace_back(i);
55         g[v].emplace_back(i);
56         E.emplace_back(u ^ v);
57     }
58 }
59 void solve() {
60     FOR(i, 1, n + 1, 1) {
61         if (!dfn[i]) dfs(i, true);
62     }
63     vector<int> ans;
64     int cnt = 0;
65     FOR(i, 1, n + 1, 1) {
66         if (isap[i]) cnt++, ans.emplace_back(i);
67     }
68     cout << cnt << endl;
69     Each(i, ans) cout << i << ' ';
70     cout << endl;
71 }

```

5.5 BCC - Bridge

```

1  int n, m;
2  vector<int> g[maxn], E;
3  int low[maxn], dfn[maxn], instp;

```

```

4  int bccnt, bccid[maxn];
5  stack<int> stk;
6  bitset<maxm> vis, isbrg;
7  void init() {
8      cin >> n >> m;
9      REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u ^ v);
13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low + maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e] ^ u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         } else {
40             // tree edge
41             dfs(v);
42             low[u] = min(low[u], low[v]);
43             if (low[v] == dfn[v]) {
44                 isbrg[e] = true;
45                 popout(u);
46             }
47         }
48     }
49 }
50 void solve() {
51     FOR(i, 1, n + 1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n + 1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e] ^ u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

5.6 SCC - Tarjan

```

1  // 2-SAT
2  vector<int> E, g[maxn]; // 1~n, n+1~2n
3  int low[maxn], in[maxn], instp;
4  int sccnt, sccid[maxn];
5  stack<int> stk;
6  bitset<maxn> ins, vis;
7  int n, m;
8  void init() {
9      cin >> m >> n;
10     E.clear();
11     fill(g, g + maxn, vector<int>());
12     fill(low, low + maxn, INF);
13     memset(in, 0, sizeof(in));
14     instp = 1;
15     sccnt = 0;
16     memset(sccid, 0, sizeof(sccid));

```

```

17     ins.reset();
18     vis.reset();
19 }
20 inline int no(int u) {
21     return (u > n ? u - n : u + n);
22 }
23 int ecnt = 0;
24 inline void clause(int u, int v) {
25     E.eb(no(u) ^ v);
26     g[no(u)].eb(ecnt++);
27     E.eb(no(v) ^ u);
28     g[no(v)].eb(ecnt++);
29 }
30 void dfs(int u) {
31     in[u] = instp++;
32     low[u] = in[u];
33     stk.push(u);
34     ins[u] = true;
35
36     Each(e, g[u]) {
37         if (vis[e]) continue;
38         vis[e] = true;
39
40         int v = E[e] ^ u;
41         if (ins[v])
42             low[u] = min(low[u], in[v]);
43         else if (!in[v]) {
44             dfs(v);
45             low[u] = min(low[u], low[v]);
46         }
47     }
48     if (low[u] == in[u]) {
49         sccnt++;
50         while (!stk.empty()) {
51             int v = stk.top();
52             stk.pop();
53             ins[v] = false;
54             sccid[v] = sccnt;
55             if (u == v) break;
56         }
57     }
58 }
59 int main() {
60     init();
61     REP(i, m) {
62         char su, sv;
63         int u, v;
64         cin >> su >> u >> sv >> v;
65         if (su == '-') u = no(u);
66         if (sv == '-') v = no(v);
67         clause(u, v);
68     }
69     FOR(i, 1, 2 * n + 1, 1) {
70         if (!in[i]) dfs(i);
71     }
72     FOR(u, 1, n + 1, 1) {
73         int du = no(u);
74         if (sccid[u] == sccid[du]) {
75             return cout << "IMPOSSIBLE\n", 0;
76         }
77     }
78     FOR(u, 1, n + 1, 1) {
79         int du = no(u);
80         cout << (sccid[u] < sccid[du] ? '+' : '-') << '
81         ' << ' ';
82     }
83     cout << endl;

```

5.7 SCC - Kosaraju

```

1  const int N = 1e5 + 10;
2  vector<int> ed[N], ed_b[N]; // 反邊
3  vector<int> SCC(N); // 最後SCC的分組
4  bitset<N> vis;
5  int SCC_cnt;
6  int n, m;
7  vector<int> pre; // 後序遍歷
8
9  void dfs(int x) {
10     vis[x] = 1;

```

```

11     for (int i : ed[x]) {
12         if (vis[i]) continue;
13         dfs(i);
14     }
15     pre.push_back(x);
16 }
17
18 void dfs2(int x) {
19     vis[x] = 1;
20     SCC_cnt;
21     for (int i : ed_b[x]) {
22         if (vis[i]) continue;
23         dfs2(i);
24     }
25 }
26
27 void kosaraju() {
28     for (int i = 1; i <= n; i++) {
29         if (!vis[i]) {
30             dfs(i);
31         }
32     }
33     SCC_cnt = 0;
34     vis = 0;
35     for (int i = n - 1; i >= 0; i--) {
36         if (!vis[pre[i]]) {
37             SCC_cnt++;
38             dfs2(pre[i]);
39         }
40     }
41 }

```

5.8 Eulerian Path - Undir

```

1 // from 1 to n
2 #define gg return cout << "IMPOSSIBLE\n", void();
3
4 int n, m;
5 vector<int> g[maxn];
6 bitset<maxn> inodd;
7
8 void init() {
9     cin >> n >> m;
10    inodd.reset();
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;
14        inodd[u] = inodd[u] ^ true;
15        inodd[v] = inodd[v] ^ true;
16        g[u].emplace_back(v);
17        g[v].emplace_back(u);
18    }
19 }
20 stack<int> stk;
21 void dfs(int u) {
22     while (!g[u].empty()) {
23         int v = g[u].back();
24         g[u].pop_back();
25         dfs(v);
26     }
27     stk.push(u);
28 }

```

5.9 Eulerian Path - Dir

```

1 // from node 1 to node n
2 #define gg return cout << "IMPOSSIBLE\n", 0
3
4 int n, m;
5 vector<int> g[maxn];
6 stack<int> stk;
7 int in[maxn], out[maxn];
8
9 void init() {
10    cin >> n >> m;
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;
14        g[u].emplace_back(v);
15        out[u]++, in[v]++;
16    }
17    for (int i = 1; i <= n; i++) {

```

```

18        if (i == 1 && out[i] - in[i] != 1) gg;
19        if (i == n && in[i] - out[i] != 1) gg;
20        if (i != 1 && i != n && in[i] != out[i]) gg;
21    }
22 }
23 void dfs(int u) {
24     while (!g[u].empty()) {
25         int v = g[u].back();
26         g[u].pop_back();
27         dfs(v);
28     }
29     stk.push(u);
30 }
31 void solve() {
32     dfs(1) for (int i = 1; i <= n; i++) if ((int)g[i].
33         size()) gg;
34     while (!stk.empty()) {
35         int u = stk.top();
36         stk.pop();
37         cout << u << ' ';
38     }

```

5.10 Hamilton Path

```

1 // top down DP
2 // Be Aware Of Multiple Edges
3 int n, m;
4 ll dp[maxn][1<<maxn];
5 int adj[maxn][maxn];
6
7 void init() {
8     cin >> n >> m;
9     fill(dp[0], dp[maxn-1]+(1<<maxn), -1);
10 }
11
12 void DP(int i, int msk) {
13     if (dp[i][msk] != -1) return;
14     dp[i][msk] = 0;
15     REP(j, n) if (j != i && (msk & (1<<j)) && adj[j][i]) {
16         int sub = msk ^ (1<<i);
17         if (dp[j][sub] == -1) DP(j, sub);
18         dp[i][msk] += dp[j][sub] * adj[j][i];
19         if (dp[i][msk] >= MOD) dp[i][msk] %= MOD;
20     }
21 }
22
23 int main() {
24     WiWiHorz
25     init();
26
27     REP(i, m) {
28         int u, v;
29         cin >> u >> v;
30         if (u == v) continue;
31         adj[--u][--v]++;
32     }
33
34     dp[0][1] = 1;
35     FOR(i, 1, n, 1) {
36         dp[i][1] = 0;
37         dp[i][1|(1<<i)] = adj[0][i];
38     }
39     FOR(msk, 1, (1<<n), 1) {
40         if (msk == 1) continue;
41         dp[0][msk] = 0;
42     }
43
44     DP(n-1, (1<<n)-1);
45     cout << dp[n-1][(1<<n)-1] << endl;
46
47     return 0;
48 }

```

5.11 Kth Shortest Path

```

1 // time: O(|E| \lg |E| + |V| \lg |V| + K)
2 // memory: O(|E| \lg |E| + |V|)
3 struct KSP { // 1-base

```

```

4 struct nd {
5     int u, v;
6     ll d;
7     nd(int ui = 0, int vi = 0, ll di = INF) {
8         u = ui;
9         v = vi;
10        d = di;
11    }
12};
13struct heap {
14    nd* edge;
15    int dep;
16    heap* chd[4];
17};
18static int cmp(heap* a, heap* b) { return a->edge->
19    d > b->edge->d; }
20struct node {
21    int v;
22    ll d;
23    heap* H;
24    nd* E;
25    node() {}
26    node(ll _d, int _v, nd* _E) {
27        d = _d;
28        v = _v;
29        E = _E;
30    }
31    node(heap* _H, ll _d) {
32        H = _H;
33        d = _d;
34    }
35    friend bool operator<(node a, node b) { return
36        a.d > b.d; }
37};
38int n, k, s, t, dst[N];
39nd* nxt[N];
40vector<nd*> g[N], rg[N];
41heap *nullNd, *head[N];
42void init(int _n, int _k, int _s, int _t) {
43    n = _n;
44    k = _k;
45    s = _s;
46    t = _t;
47    for (int i = 1; i <= n; i++) {
48        g[i].clear();
49        rg[i].clear();
50        nxt[i] = NULL;
51        head[i] = NULL;
52        dst[i] = -1;
53    }
54}
55void addEdge(int ui, int vi, ll di) {
56    nd* e = new nd(ui, vi, di);
57    g[ui].push_back(e);
58    rg[vi].push_back(e);
59}
60queue<int> dfsQ;
61void dijkstra() {
62    while (dfsQ.size()) dfsQ.pop();
63    priority_queue<node> Q;
64    Q.push(node(0, t, NULL));
65    while (!Q.empty()) {
66        node p = Q.top();
67        Q.pop();
68        if (dst[p.v] != -1) continue;
69        dst[p.v] = p.d;
70        nxt[p.v] = p.E;
71        dfsQ.push(p.v);
72        for (auto e : rg[p.v]) Q.push(node(p.d + e
73            ->d, e->u, e));
74    }
75}
76heap* merge(heap* curNd, heap* newNd) {
77    if (curNd == nullNd) return newNd;
78    heap* root = new heap;
79    memcpy(root, curNd, sizeof(heap));
80    if (newNd->edge->d < curNd->edge->d) {
81        root->edge = newNd->edge;
82        root->chd[2] = newNd->chd[2];
83        root->chd[3] = newNd->chd[3];
84        newNd->edge = curNd->edge;
85        newNd->chd[2] = curNd->chd[2];
86        newNd->chd[3] = curNd->chd[3];
87    }
88    if (root->chd[0]->dep < root->chd[1]->dep)
89        root->chd[0] = merge(root->chd[0], newNd);
90    else
91        root->chd[1] = merge(root->chd[1], newNd);
92    root->dep = max(root->chd[0]->dep,
93        root->chd[1]->dep) +
94        1;
95    return root;
96}
97vector<heap*> V;
98void build() {
99    nullNd = new heap;
100    nullNd->dep = 0;
101    nullNd->edge = new nd;
102    fill(nullNd->chd, nullNd->chd + 4, nullNd);
103    while (not dfsQ.empty()) {
104        int u = dfsQ.front();
105        dfsQ.pop();
106        if (!nxt[u])
107            head[u] = nullNd;
108        else
109            head[u] = head[nxt[u]->v];
110        V.clear();
111        for (auto& e : g[u]) {
112            int v = e->v;
113            if (dst[v] == -1) continue;
114            e->d += dst[v] - dst[u];
115            if (nxt[u] != e) {
116                heap* p = new heap;
117                fill(p->chd, p->chd + 4, nullNd);
118                p->dep = 1;
119                p->edge = e;
120                V.push_back(p);
121            }
122        }
123        if (V.empty()) continue;
124        make_heap(V.begin(), V.end(), cmp);
125        #define L(X) ((X << 1) + 1)
126        #define R(X) ((X << 1) + 2)
127        for (size_t i = 0; i < V.size(); i++) {
128            if (L(i) < V.size())
129                V[i]->chd[2] = V[L(i)];
130            else
131                V[i]->chd[2] = nullNd;
132            if (R(i) < V.size())
133                V[i]->chd[3] = V[R(i)];
134            else
135                V[i]->chd[3] = nullNd;
136        }
137        head[u] = merge(head[u], V.front());
138    }
139}
140vector<ll> ans;
141void first_K() {
142    ans.clear();
143    priority_queue<node> Q;
144    if (dst[s] == -1) return;
145    ans.push_back(dst[s]);
146    if (head[s] != nullNd)
147        Q.push(node(head[s], dst[s] + head[s]->edge
148            ->d));
149    for (int _ = 1; _ < k and not Q.empty(); _++) {
150        node p = Q.top();
151        Q.pop();
152        ans.push_back(p.d);
153        if (head[p.H->edge->v] != nullNd) {
154            q.H = head[p.H->edge->v];
155            q.d = p.d + q.H->edge->d;
156            Q.push(q);
157        }
158    }
159}
160}
161}

```

```

162 void solve() { // ans[i] stores the i-th shortest
163     path
164     dijkstra();
165     build();
166     first_K(); // ans.size() might less than k
167 } solver;

```

5.12 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow$ add super vertex $x_0 = 0$, then $x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum \Rightarrow Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_{i+1} needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6 String

6.1 Aho Corasick

```

1 struct ACautomata {
2     struct Node {
3         int cnt;
4         Node *go[26], *fail, *dic;
5         Node() {
6             cnt = 0;
7             fail = 0;
8             dic = 0;
9             memset(go, 0, sizeof(go));
10        }
11    } pool[1048576], *root;
12    int nMem;
13    Node *new_Node() {
14        pool[nMem] = Node();
15        return &pool[nMem++];
16    }
17    void init() {
18        nMem = 0;
19        root = new_Node();
20    }
21    void add(const string &str) { insert(root, str, 0); }
22    void insert(Node *cur, const string &str, int pos) {
23        for (int i = pos; i < str.size(); i++) {
24            if (!cur->go[str[i] - 'a'])
25                cur->go[str[i] - 'a'] = new_Node();
26            cur = cur->go[str[i] - 'a'];
27        }
28        cur->cnt++;
29    }
30    void make_fail() {
31        queue<Node*> que;
32        que.push(root);
33        while (!que.empty()) {
34            Node *fr = que.front();
35            que.pop();
36            for (int i = 0; i < 26; i++) {
37                if (fr->go[i]) {
38                    Node *ptr = fr->fail;
39                    while (ptr && !ptr->go[i]) ptr = ptr->fail;

```

```

fr->go[i]->fail = ptr = (ptr ? ptr
->go[i] : root);
fr->go[i]->dic = (ptr->cnt ? ptr :
ptr->dic);
que.push(fr->go[i]);
}
}
}
} AC;

```

6.2 KMP

```

1 vector<int> f;
2 void buildFailFunction(string &s) {
3     f.resize(s.size(), -1);
4     for (int i = 1; i < s.size(); i++) {
5         int now = f[i - 1];
6         while (now != -1 and s[now + 1] != s[i]) now = f[now];
7         if (s[now + 1] == s[i]) f[i] = now + 1;
8     }
9 }
10
11 void KMPmatching(string &a, string &b) {
12     for (int i = 0, now = -1; i < a.size(); i++) {
13         while (a[i] != b[now + 1] and now != -1) now = f[now];
14         if (a[i] == b[now + 1]) now++;
15         if (now + 1 == b.size()) {
16             cout << "found a match start at position "
17                  << i - now << endl;
18             now = f[now];
19         }
20     }
21 }

```

6.3 Z Value

```

1 string is, it, s;
2 int n;
3 vector<int> z;
4 void init() {
5     cin >> is >> it;
6     s = it + '0' + is;
7     n = (int)s.size();
8     z.resize(n, 0);
9 }
10 void solve() {
11     int ans = 0;
12     z[0] = n;
13     for (int i = 1, l = 0, r = 0; i < n; i++) {
14         if (i <= r) z[i] = min(z[i - l], r - i + 1);
15         while (i + z[i] < n && s[z[i]] == s[i + z[i]])
16             z[i]++;
17         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
18         if (z[i] == (int)it.size()) ans++;
19     }
20     cout << ans << endl;
21 }

```

6.4 Manacher

```

1 int n;
2 string S, s;
3 vector<int> m;
4 void manacher() {
5     s.clear();
6     s.resize(2 * n + 1, '.');
7     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
8     m.clear();
9     m.resize(2 * n + 1, 0);
10    // m[i] := max k such that s[i-k, i+k] is
11    // palindrome
12    int mx = 0, mxk = 0;
13    for (int i = 1; i < 2 * n + 1; i++) {
14        if (mx - (i - mx) >= 0) m[i] = min(m[mx - (i - mx)], mx + mxk - i);
15        while (0 <= i - m[i] - 1 && i + m[i] + 1 < 2 * n + 1 &&

```



```

15         s[i - m[i] - 1] == s[i + m[i] + 1]) m[i]
16             ++;
17     }
18     if (i + m[i] > mx + mxk) mx = i, mxk = m[i];
19 }
20 void init() {
21     cin >> S;
22     n = (int)S.size();
23 }
24 void solve() {
25     manacher();
26     int mx = 0, ptr = 0;
27     for (int i = 0; i < 2 * n + 1; i++)
28         if (mx < m[i]) {
29             mx = m[i];
30             ptr = i;
31         }
32     for (int i = ptr - mx; i <= ptr + mx; i++)
33         if (s[i] != '.') cout << s[i];
34     cout << endl;

```

6.5 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n;
5     string s;
6     vector<int> suf, lcp, rk;
7     vector<int> cnt, pos;
8     vector<pair<pii, int>> buc[2];
9     void init(string _s) {
10         s = _s;
11         n = (int)s.size();
12         // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
13     }
14     void radix_sort() {
15         for (int t : {0, 1}) {
16             fill(cnt.begin(), cnt.end(), 0);
17             for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F.S)]++;
18             for (int i = 0; i < n; i++)
19                 pos[i] = (i ? 0 : pos[i - 1] + cnt[i - 1]);
20             for (auto& i : buc[t])
21                 buc[t ^ 1][pos[(t ? i.F.F : i.F.S)]++] = i;
22         }
23     }
24     bool fill_suf() {
25         bool end = true;
26         for (int i = 0; i < n; i++) suf[i] = buc[0][i].S;
27         rk[suf[0]] = 0;
28         for (int i = 1; i < n; i++) {
29             int dif = (buc[0][i].F != buc[0][i - 1].F);
30             end &= dif;
31             rk[suf[i]] = rk[suf[i - 1]] + dif;
32         }
33         return end;
34     }
35     void sa() {
36         for (int i = 0; i < n; i++)
37             buc[0][i] = make_pair(make_pair(s[i], s[i]), i);
38         sort(buc[0].begin(), buc[0].end());
39         if (fill_suf()) return;
40         for (int k = 0; (1 << k) < n; k++) {
41             for (int i = 0; i < n; i++)
42                 buc[0][i] = make_pair(make_pair(rk[i], rk[(i + (1 << k)) % n]), i);
43             radix_sort();
44             if (fill_suf()) return;
45         }
46     }
47     void LCP() {
48         int k = 0;
49         for (int i = 0; i < n - 1; i++) {
50             if (rk[i] == 0) continue;
51             int pi = rk[i];
52             int j = suf[pi - 1];

```

```

53         while (i + k < n && j + k < n && s[i + k]
54             == s[j + k]) k++;
55         lcp[pi] = k;
56         k = max(k - 1, 0);
57     }
58 };
59 SuffixArray suffixarray;

```

6.6 Minimum Rotation

```

1 // rotate(begin(s), begin(s)+minRotation(s), end(s))
2 int minRotation(string s) {
3     int a = 0, n = s.size();
4     s += s;
5     for (int b = 0; b < n; b++)
6         for (int k = 0; k < n; k++) {
7             if (a + k == b || s[a + k] < s[b + k]) {
8                 b += max(0, k - 1);
9                 break;
10            }
11            if (s[a + k] > s[b + k]) {
12                a = b;
13                break;
14            }
15        }
16     return a;
17 }

```

6.7 Lyndon Factorization

```

1 vector<string> duval(string const& s) {
2     int n = s.size();
3     int i = 0;
4     vector<string> factorization;
5     while (i < n) {
6         int j = i + 1, k = i;
7         while (j < n && s[k] <= s[j]) {
8             if (s[k] < s[j])
9                 k = i;
10            else
11                k++;
12            j++;
13        }
14        while (i <= k) {
15            factorization.push_back(s.substr(i, j - k));
16            i += j - k;
17        }
18    }
19    return factorization; // O(n)
20 }

```

6.8 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) { return c - 'a' + 1; }
3 struct RollingHash {
4     string s;
5     int n;
6     ll mod;
7     vector<ll> Cexp, hs;
8     RollingHash(string& _s, ll _mod) : s(_s), n((int)_s
9         .size()), mod(_mod) {
10         Cexp.assign(n, 0);
11         hs.assign(n, 0);
12         Cexp[0] = 1;
13         for (int i = 1; i < n; i++) {
14             Cexp[i] = Cexp[i - 1] * C;
15             if (Cexp[i] >= mod) Cexp[i] %= mod;
16         }
17         hs[0] = id(s[0]);
18         for (int i = 1; i < n; i++) {
19             hs[i] = hs[i - 1] * C + id(s[i]);
20             if (hs[i] >= mod) hs[i] %= mod;
21         }
22     }
23     inline ll query(int l, int r) {
24         ll res = hs[r] - (l ? hs[l - 1] * Cexp[r - l + 1] : 0);
25         res = (res % mod + mod) % mod;

```

```

25     return res;
26 }
27 };

```

6.9 Trie

```

1 pii a[N][26];
2
3 void build(string &s) {
4     static int idx = 0;
5     int n = s.size();
6     for (int i = 0, v = 0; i < n; i++) {
7         pii &now = a[v][s[i] - 'a'];
8         if (now.first != -1)
9             v = now.first;
10        else
11            v = now.first = ++idx;
12        if (i == n - 1)
13            now.second++;
14    }
15 }

```

7 Geometry

7.1 Basic Operations

```

1 // typedef long long T;
2 typedef long double T;
3 const long double eps = 1e-12;
4
5 short sgn(T x) {
6     if (abs(x) < eps) return 0;
7     return x < 0 ? -1 : 1;
8 }
9
10 struct Pt {
11     T x, y;
12     Pt(T _x = 0, T _y = 0) : x(_x), y(_y) {}
13     Pt operator+(Pt a) { return Pt(x + a.x, y + a.y); }
14     Pt operator-(Pt a) { return Pt(x - a.x, y - a.y); }
15     Pt operator*(T a) { return Pt(x * a, y * a); }
16     Pt operator/(T a) { return Pt(x / a, y / a); }
17     T operator*(Pt a) { return x * a.x + y * a.y; }
18     T operator^(Pt a) { return x * a.y - y * a.x; }
19     bool operator<(Pt a) { return x < a.x || (x == a.x
20         && y < a.y); }
21     // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn
22         (y-a.y) < 0); }
23     bool operator==(Pt a) { return sgn(x - a.x) == 0 &&
24         sgn(y - a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b - a; }
28 T len2(Pt a) { return a * a; }
29 T dis2(Pt a, Pt b) { return len2(b - a); }
30 Pt rotate(Pt u) { return {-u.y, u.x}; }
31 Pt unit(Pt x) { return x / sqrtl(x * x); }
32 short ori(Pt a, Pt b) { return ((a ^ b) > 0) - ((a ^ b)
33     < 0); }
34 bool onseg(Pt p, Pt l1, Pt l2) {
35     Pt a = mv(p, l1), b = mv(p, l2);
36     return ((a ^ b) == 0) && ((a * b) <= 0);
37 }
38
39 inline T cross(const Pt &a, const Pt &b, const Pt &c) {
40     return (b.x - a.x) * (c.y - a.y)
41         - (b.y - a.y) * (c.x - a.x);
42 }
43
44 long double polar_angle(Pt ori, Pt pt) {
45     return atan2(pt.y - ori.y, pt.x - ori.x);
46 }
47
48 // slope to degree atan(Slope) * 180.0 / acos(-1.0);
49 bool argcmp(Pt u, Pt v) {
50     auto half = [](const Pt &p) {
51         return p.y > 0 || (p.y == 0 && p.x >= 0);
52     };
53     if (half(u) != half(v)) return half(u) < half(v);
54     return sgn(u ^ v) > 0;
55 }
56
57 int ori(Pt &o, Pt &a, Pt &b) {
58     return sgn((a - o) ^ (b - o));
59 }

```

```

52 }
53 struct Line {
54     Pt a, b;
55     Pt dir() { return b - a; }
56 };
57 int PtSide(Pt p, Line l) {
58     return sgn(ori(L.a, L.b, p)); // for int
59     return sgn(ori(L.a, L.b, p) / sqrt(len2(L.a - L.b))
60         );
61 }
62 bool PtOnSeg(Pt p, Line l) {
63     return PtSide(p, l) == 0 and sgn((p - L.a) * (p - L
64         .b)) <= 0;
65 }
66 Pt proj(Pt &p, Line &l) {
67     Pt d = l.b - l.a;
68     T d2 = len2(d);
69     if (sgn(d2) == 0) return l.a;
70     T t = ((p - l.a) * d) / d2;
71     return l.a + d * t;
72 }
73 struct Cir {
74     Pt o;
75     T r;
76 };
77 bool disjunct(Cir a, Cir b) {
78     return sgn(sqrtl(len2(a.o - b.o)) - a.r - b.r) >=
79         0;
80 }
81 bool contain(Cir a, Cir b) {
82     return sgn(a.r - b.r - sqrtl(len2(a.o - b.o))) >=
83         0;
84 }

```

7.2 Sort by Angle

```

1 int ud(Pt a) { // up or down half plane
2     if (a.y > 0) return 0;
3     if (a.y < 0) return 1;
4     return (a.x >= 0 ? 0 : 1);
5 }
6 sort(pts.begin(), pts.end(), [&](const Pt &a, const Pt &b) {
7     if (ud(a) != ud(b)) return ud(a) < ud(b);
8     return (a ^ b) > 0;
9 });

```

7.3 Intersection

```

1 bool line_intersect_check(Pt p1, Pt p2, Pt q1, Pt q2) {
2     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) || onseg
3         (q1, p1, p2) || onseg(q2, p1, p2)) return true;
4     Pt p = mv(p1, p2), q = mv(q1, q2);
5     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) <
6         0) && (ori(q, mv(q1, p1)) * ori(q, mv(q1, p2))
7         < 0);
8 }
9 // long double
10 Pt line_intersect(Pt a1, Pt a2, Pt b1, Pt b2) {
11     Pt da = mv(a1, a2), db = mv(b1, b2);
12     T det = da ^ db;
13     if (sgn(det) == 0) { // parallel
14         // return Pt(NAN, NAN);
15     }
16     T t = ((b1 - a1) ^ db) / det;
17     return a1 + da * t;
18 }
19
20 vector<Pt> CircleInter(Cir a, Cir b) {
21     double d2 = len2(a.o - b.o), d = sqrt(d2);
22     if (d < max(a.r, b.r) - min(a.r, b.r) || d > a.r +
23         b.r) return {};
24     Pt u = (a.o + b.o) / 2 + (a.o - b.o) * ((b.r * b.r
25         - a.r * a.r) / (2 * d2));
26     double A = sqrt((a.r + b.r + d) * (a.r - b.r + d) *
27         (a.r + b.r - d) * (-a.r + b.r + d));
28     Pt v = rotate(b.o - a.o) * A / (2 * d2);
29     if (sgn(v.x) == 0 and sgn(v.y) == 0) return {u};
30     return {u - v, u + v}; // counter clockwise of a
31 }
32
33 vector<Pt> CircleLineInter(Cir c, Line l) {
34     Pt H = proj(c.o, l);
35     Pt dir = unit(l.b - l.a);
36 }

```

```

28 T h = sqrt(1 - len2(H - c.o));
29 if (sgn(h - c.r) > 0) return {};
30 T d = sqrt(1 - max((T)0, c.r * c.r - h * h));
31 if (sgn(d) == 0) return {H};
32 return {H - dir * d, H + dir * d};
33 }

```

7.4 Polygon Area

```

1 // 2 * area
2 T dbPoly_area(vector<Pt>& e) {
3     T res = 0;
4     int sz = e.size();
5     for (int i = 0; i < sz; i++) {
6         res += e[i] ^ e[(i + 1) % sz];
7     }
8     return abs(res);
9 }

```

7.5 Convex Hull

```

1 vector<Pt> convexHull(vector<Pt> pts) {
2     vector<Pt> hull;
3     sort(pts.begin(), pts.end());
4     for (int i = 0; i < pts.size(); i++) {
5         int b = hull.size();
6         for (auto ei : pts) {
7             while (hull.size() - b >= 2 && ori(mv(hull[
8                 hull.size() - 2], hull.back()), mv(hull[
9                 hull.size() - 2], ei)) == -1) {
10                 hull.pop_back();
11             }
12             hull.emplace_back(ei);
13         }
14         hull.pop_back();
15         reverse(pts.begin(), pts.end());
16     }
17     return hull;
18 }

```

7.6 Point In Convex

```

1 bool point_in_convex(const vector<Pt> &C, Pt p, bool
2     strict = true) {
3     // only works when no three point are collinear
4     int n = C.size();
5     int a = 1, b = n - 1, r = !strict;
6     if (n == 0) return false;
7     if (n < 3) return r && onseg(p, C[0], C.back());
8     if (ori(mv(C[0], C[a]), mv(C[0], C[b])) > 0) swap(a, b);
9     if (ori(mv(C[0], C[a]), mv(C[0], p)) >= r || ori(mv(
10         C[0], C[b]), mv(C[0], p)) <= -r) return false;
11     while (abs(a - b) > 1) {
12         int c = (a + b) / 2;
13         if (ori(mv(C[0], C[c]), mv(C[0], p)) > 0) b = c;
14         else a = c;
15     }
16     return ori(mv(C[a], C[b]), mv(C[a], p)) < r;
17 }

```

7.7 Point Segment Distance

```

1 double point_segment_dist(Pt q0, Pt q1, Pt p) {
2     if (q0 == q1) {
3         double dx = double(p.x - q0.x);
4         double dy = double(p.y - q0.y);
5         return sqrt(dx * dx + dy * dy);
6     }
7     T d1 = (q1 - q0) * (p - q0);
8     T d2 = (q0 - q1) * (p - q1);
9     if (d1 >= 0 && d2 >= 0) {
10         double area = fabs(double((q1 - q0) ^ (p - q0)));
11         double base = sqrt(double(dis2(q0, q1)));
12         return area / base;
13     }
14     double dx0 = double(p.x - q0.x), dy0 = double(p.y - q0.y);
15     double dx1 = double(p.x - q1.x), dy1 = double(p.y - q1.y);

```

```

16     return min(sqrt(dx0 * dx0 + dy0 * dy0), sqrt(dx1 *
17         dx1 + dy1 * dy1));
18 }

```

7.8 Point in Polygon

```

1 short inPoly(vector<Pt>& pts, Pt p) {
2     // 0=Bound 1=In -1=Out
3     int n = pts.size();
4     for (int i = 0; i < pts.size(); i++) if (onseg(p,
5         pts[i], pts[(i + 1) % n])) return 0;
6     int cnt = 0;
7     for (int i = 0; i < pts.size(); i++) if (
8         line_intersect_check(p, Pt(p.x + 1, p.y + 2e9),
9         pts[i], pts[(i + 1) % n])) cnt ^= 1;
10    return (cnt ? 1 : -1);
11 }

```

7.9 Minimum Euclidean Distance

```

1 long long Min_Euclidean_Dist(vector<Pt> &pts) {
2     sort(pts.begin(), pts.end());
3     set<pair<long long, long long>> s;
4     s.insert({pts[0].y, pts[0].x});
5     long long l = 0, best = LLONG_MAX;
6     for (int i = 1; i < (int)pts.size(); i++) {
7         Pt now = pts[i];
8         long long lim = (long long)ceil(sqrt(1.0 *
9             double(best)));
10        while (now.x - pts[l].x > lim) {
11            s.erase({pts[l].y, pts[l].x}); l++;
12        }
13        auto low = s.lower_bound({now.y - lim,
14            LLONG_MIN});
15        auto high = s.upper_bound({now.y + lim,
16            LLONG_MAX});
17        for (auto it = low; it != high; it++) {
18            long long dy = it->first - now.y;
19            long long dx = it->second - now.x;
20            best = min(best, dx * dx + dy * dy);
21            s.insert({now.y, now.x});
22        }
23    }
24    return best;
25 }

```

7.10 Minkowski Sum

```

1 void reorder(vector<Pt> &P) {
2     rotate(P.begin(), min_element(P.begin(), P.end()),
3         [&](Pt a, Pt b) { return make_pair(a.y, a.x) <
4             make_pair(b.y, b.x); }, P.end());
5 }
6 vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
7     // P, Q: convex polygon
8     reorder(P), reorder(Q);
9     int n = P.size(), m = Q.size();
10    P.push_back(P[0]), P.push_back(P[1]), Q.push_back(Q[0]), Q.push_back(Q[1]);
11    vector<Pt> ans;
12    for (int i = 0, j = 0; i < n || j < m; ) {
13        ans.push_back(P[i] + Q[j]);
14        auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
15        if (val >= 0) i++;
16        if (val <= 0) j++;
17    }
18    return ans;
19 }

```

7.11 Lower Concave Hull

```

1 struct Line {
2     mutable ll m, b, p;
3     bool operator<(const Line& o) const { return m < o.m; }
4     bool operator<(ll x) const { return p < x; }
5 };
6 struct LineContainer : multiset<Line, less<>> {
7     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
8     const ll inf = LLONG_MAX;

```

```

10 ll div(ll a, ll b) { // floored division
11     return a / b - ((a ^ b) < 0 && a % b); }
12 bool isect(iterator x, iterator y) {
13     if (y == end()) { x->p = inf; return false; }
14     if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
15     else x->p = div(y->b - x->b, x->m - y->m);
16     return x->p >= y->p;
17 }
18 void add(ll m, ll b) {
19     auto z = insert({m, b, 0}), y = z++, x = y;
20     while (isect(y, z)) z = erase(z);
21     if (x != begin() && isect(--x, y)) isect(x, y =
22         erase(y));
23     while ((y = x) != begin() && (--x)->p >= y->p)
24         isect(x, erase(y));
25 }
26 ll query(ll x) {
27     assert(!empty());
28     auto l = *lower_bound(x);
29     return l.m * x + l.b;
30 };

```

7.12 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$Area = i + \frac{b}{2} - 1$$

7.13 Rotating SweepLine

```

1 double cross(const Pt &a, const Pt &b) {
2     return a.x*b.y - a.y*b.x;
3 }
4 int rotatingCalipers(const vector<Pt>& hull) {
5     int m = hull.size();
6     if (m < 2) return 0;
7     int j = 1;
8     T maxd = 0;
9     for (int i = 0; i < m; ++i) {
10         int ni = (i + 1) % m;
11         while (abs(cross({hull[ni].x - hull[i].x, hull[
12             ni].y - hull[i].y}, {hull[(j+1)%m].x - hull
13             [i].x, hull[(j+1)%m].y - hull[i].y})) > abs(
14             cross({hull[ni].x - hull[i].x, hull[ni].y
15             - hull[i].y}, {hull[j].x - hull[i].x,
16             hull[j].y - hull[i].y}))) {
17             j = (j + 1) % m;
18         }
19         maxd = max(maxd, dis2(hull[i], hull[j]));
20         maxd = max(maxd, dis2(hull[ni], hull[j]));
21     }
22     return maxd; // TODO
23 }

```

7.14 Half Plane Intersection

```

1 bool cover(Line& L, Line& P, Line& Q) {
2     long double u = (Q.a - P.a) ^ Q.dir();
3     long double v = P.dir() ^ Q.dir();
4     long double x = P.dir().x * u + (P.a - L.a).x * v;
5     long double y = P.dir().y * u + (P.a - L.a).y * v;
6     return sgn(x * L.dir().y - y * L.dir().x) * sgn(v)
7     >= 0;
8 }
9 vector<Line> HPI(vector<Line> P) {
10     sort(P.begin(), P.end(), [&](Line& l, Line& m) {
11         if (argcmp(l.dir(), m.dir()) return true;
12         if (argcmp(m.dir(), l.dir()) return false;
13         return ori(m.a, m.b, l.a) > 0;
14     });
15     int l = 0, r = -1;
16     for (size_t i = 0; i < P.size(); ++i) {
17         if (i && !argcmp(P[i - 1].dir(), P[i].dir()))
18             continue;

```

```

18     while (l < r && cover(P[i], P[r - 1], P[r])) --
19         r;
20     while (l < r && cover(P[i], P[l], P[l + 1])) ++
21         l;
22     P[++r] = P[i];
23 }
24 while (l < r && cover(P[l], P[r - 1], P[r])) --r;
25 while (l < r && cover(P[r], P[l], P[l + 1])) ++l;
26 if (r - l <= 1 || !argcmp(P[l].dir(), P[r].dir()))
27     return {};
28 if (cover(P[l + 1], P[l], P[r])) return {};
29 return vector<Line>(P.begin() + l, P.begin() + r +
30     1);

```

7.15 Minimum Enclosing Circle

```

1 const int INF = 1e9;
2 Pt circumcenter(Pt A, Pt B, Pt C) {
3     // a1(x-A.x) + b1(y-A.y) = c1
4     // a2(x-A.x) + b2(y-A.y) = c2
5     // solve using Cramer's rule
6     T a1 = B.x - A.x, b1 = B.y - A.y, c1 = dis2(A, B) /
7     2.0;
8     T a2 = C.x - A.x, b2 = C.y - A.y, c2 = dis2(A, C) /
9     2.0;
10    T D = Pt(a1, b1) ^ Pt(a2, b2);
11    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
12    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
13    if (D == 0) return Pt(-INF, -INF);
14    return A + Pt(Dx / D, Dy / D);
15 }
16 Pt center;
17 T r2;
18 void minEncloseCircle(vector<Pt> pts) {
19     mt19937 gen(chrono::steady_clock::now().
20         time_since_epoch().count());
21     shuffle(pts.begin(), pts.end(), gen);
22     center = pts[0], r2 = 0;
23     for (int i = 0; i < pts.size(); ++i) {
24         if (dis2(center, pts[i]) <= r2) continue;
25         center = pts[i], r2 = 0;
26         for (int j = 0; j < i; ++j) {
27             if (dis2(center, pts[j]) <= r2) continue;
28             center = (pts[i] + pts[j]) / 2.0;
29             r2 = dis2(center, pts[i]);
30             for (int k = 0; k < j; ++k) {
31                 if (dis2(center, pts[k]) <= r2)
32                     continue;
33                 center = circumcenter(pts[i], pts[j],
34                     pts[k]);
35                 r2 = dis2(center, pts[i]);
36             }
37         }
38     }
39 }

```

7.16 Union of Circles

```

1 // Area[i] : area covered by at least i circle
2 vector<T> CircleUnion(const vector<Cir> &C) {
3     const int n = C.size();
4     vector<T> Area(n + 1);
5     auto check = [&](int i, int j) {
6         if (!contain(C[i], C[j]))
7             return false;
8         return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r
9             - C[j].r) == 0 and i < j);
10    };
11    struct Teve {
12        double ang; int add; Pt p;
13        bool operator<(const Teve &b) { return ang < b.
14            ang; }
15    };
16    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
17    for (int i = 0; i < n; ++i) {
18        int cov = 1;
19        vector<Teve> event;
20        for (int j = 0; j < n; ++j) if (i != j) {

```

```

19     if (check(j, i)) cov++;
20     else if (!check(i, j) and !disjunct(C[i], C[j])) {
21         auto I = CircleInter(C[i], C[j]);
22         assert(I.size() == 2);
23         double a1 = ang(I[0] - C[i].o), a2 =
24             ang(I[1] - C[i].o);
25         event.push_back({a1, 1, I[0]});
26         event.push_back({a2, -1, I[1]});
27         if (a1 > a2) cov++;
28     }
29     if (event.empty()) {
30         Area[cov] += acos(-1) * C[i].r * C[i].r;
31         continue;
32     }
33     sort(event.begin(), event.end());
34     event.push_back(event[0]);
35     for (int j = 0; j + 1 < event.size(); j++) {
36         cov += event[j].add;
37         Area[cov] += (event[j].p ^ event[j + 1].p)
38             / 2.;
39         double theta = event[j + 1].ang - event[j].ang;
40         if (theta < 0) theta += 2 * acos(-1);
41         Area[cov] += (theta - sin(theta)) * C[i].r
42             * C[i].r / 2.;
43     }
44     return Area;

```

7.17 Area Of Circle Polygon

```

1 double AreaOfCirclePoly(Cir C, vector<Pt> &P) {
2     auto arg = [&](Pt p, Pt q) { return atan2(p ^ q, p
3         * q); };
4     double r2 = (double)(C.r * C.r / 2);
5     auto tri = [&](Pt p, Pt q) {
6         Pt d = q - p;
7         T a = (d * p) / (d * d);
8         T b = ((p * p) - C.r * C.r) / (d * d);
9         T det = a * a - b;
10        if (det <= 0) return (double)(arg(p, q) * r2);
11        T s = max((T)0.0L, -a - sqrtl(det));
12        T t = min((T)1.0L, -a + sqrtl(det));
13        if (t < 0 || 1 <= s) return (double)(arg(p, q)
14            * r2);
15        Pt u = p + d * s, v = p + d * t;
16        return (double)(arg(p, u) * r2 + (u ^ v) / 2 +
17            arg(v, q) * r2);
18    };
19    long double sum = 0.0L;
20    for (int i = 0; i < (int)P.size(); i++)
21        sum += tri(P[i] - C.o, P[(i + 1) % P.size()] -
22            C.o);
23    return (double)fabsl(sum);

```

8 Number Theory

8.1 FFT

```

1 typedef complex<double> cp;
2
3 const double pi = acos(-1);
4 const int NN = 131072;
5
6 struct FastFourierTransform {
7     /*
8      * Iterative Fast Fourier Transform
9      * How this works? Look at this
10     0th recursion 0(000) 1(001) 2(010)
11                   3(011) 4(100) 5(101) 6(110)
12                   7(111)
13     1th recursion 0(000) 2(010) 4(100)
14                   6(110) | 1(011) 3(011) 5(101)
15                   7(111)
16     2th recursion 0(000) 4(100) | 2(010)
17                   6(110) | 1(011) 5(101) | 3(011)
18                   7(111)
19
20     */
21     void fft(int n, cplx a[], bool inv = false) {
22         int basic = MAXN / n;
23         int theta = basic;
24         for (int m = n; m >= 2; m >>= 1) {
25             int mh = m >> 1;
26             for (int i = 0; i < mh; i++) {
27                 cplx w = omega[inv ? MAXN - (i * theta %
28                     MAXN) : i * theta % MAXN];
29                 for (int j = i; j < n; j += m) {
30                     int k = j + mh;
31                     cplx x = a[j] - a[k];
32                     a[j] += a[k];
33                     a[k] = w * x;
34                 }
35             }
36             theta = (theta * 2) % MAXN;
37         }
38     }

```

3th recursion 0(000) | 4(100) | 2(010) |
6(110) | 1(011) | 5(101) | 3(011) |
7(111)

All the bits are reversed => We can save
the reverse of the numbers in an array!

```

39     void init(int n_) {
40         n = n_;
41         for (int i = 0; i < n; i++) {
42             // Calculate the nth roots of unity
43             omega[i] = cp(cos(2 * pi * i / n), sin(2 *
44                 pi * i / n));
45             iomega[i] = conj(omega[i]);
46         }
47         int k = __lg(n);
48         for (int i = 0; i < n; i++) {
49             int t = 0;
50             for (int j = 0; j < k; j++) {
51                 if (i & (1 << j)) t |= (1 << (k - j -
52                     1));
53             }
54             rev[i] = t;
55         }
56     }
57
58     void transform(vector<cp> &a, cp *xomega) {
59         for (int i = 0; i < n; i++)
60             if (i < rev[i]) swap(a[i], a[rev[i]]);
61         for (int len = 2; len <= n; len <<= 1) {
62             int mid = len >> 1;
63             int r = n / len;
64             for (int j = 0; j < n; j += len)
65                 for (int i = 0; i < mid; i++) {
66                     cp tmp = xomega[r * i] * a[j + mid
67                         + i];
68                     a[j + mid + i] = a[j + i] - tmp;
69                     a[j + i] = a[j + i] + tmp;
70                 }
71         }
72     }
73
74     void fft(vector<cp> &a) { transform(a, omega); }
75     void ifft(vector<cp> &a) {
76         transform(a, iomega);
77         for (int i = 0; i < n; i++) a[i] /= n;
78     }
79 } FFT;
80
81 const int MAXN = 262144;
82 // (must be 2^k)
83 // 262144, 524288, 1048576, 2097152, 4194304
84 // before any usage, run pre_fft() first
85 typedef long double ld;
86 typedef complex<ld> cplx; // real(), imag()
87 const ld PI = acos(-1);
88 const cplx I(0, 1);
89 cplx omega[MAXN + 1];
90 void pre_fft() {
91     for (int i = 0; i <= MAXN; i++) {
92         omega[i] = exp(i * 2 * PI / MAXN * I);
93     }
94 }
95 // n must be 2^k
96 void fft(int n, cplx a[], bool inv = false) {
97     int basic = MAXN / n;
98     int theta = basic;
99     for (int m = n; m >= 2; m >>= 1) {
100         int mh = m >> 1;
101         for (int i = 0; i < mh; i++) {
102             cplx w = omega[inv ? MAXN - (i * theta %
103                 MAXN) : i * theta % MAXN];
104             for (int j = i; j < n; j += m) {
105                 int k = j + mh;
106                 cplx x = a[j] - a[k];
107                 a[j] += a[k];
108                 a[k] = w * x;
109             }
110         }
111         theta = (theta * 2) % MAXN;
112     }

```

```

88     int i = 0;
89     for (int j = 1; j < n - 1; j++) {
90         for (int k = n >> 1; k > (i ^ k); k >>= 1);
91         if (j < i) swap(a[i], a[j]);
92     }
93     if (inv) {
94         for (i = 0; i < n; i++) a[i] /= n;
95     }
96 }
97 cplx arr[MAXN + 1];
98 inline void mul(int _n, long long a[], int _m, long
99     long b[], long long ans[]) {
100     int n = 1, sum = _n + _m - 1;
101     while (n < sum) n <= 1;
102     for (int i = 0; i < n; i++) {
103         double x = (i < _n ? a[i] : 0), y = (i < _m ? b
104             [i] : 0);
105         arr[i] = complex<double>(x + y, x - y);
106     }
107     fft(n, arr);
108     for (int i = 0; i < n; i++) arr[i] = arr[i] * arr[i
109         ];
110     fft(n, arr, true);
111     for (int i = 0; i < sum; i++) ans[i] = (long long
112         int)(arr[i].real() / 4 + 0.5);
113 }
114 long long a[MAXN];
115 long long b[MAXN];
116 long long ans[MAXN];
117 int a_length;
118 int b_length;

```

8.2 Pollard's rho

```

1 ll add(ll x, ll y, ll p) {
2     return (x + y) % p;
3 }
4 ll qMul(ll x, ll y, ll mod) {
5     ll ret = x * y - (ll)((long double)x / mod * y) *
6     mod;
7     return ret < 0 ? ret + mod : ret;
8 }
9 ll f(ll x, ll mod) { return add(qMul(x, x, mod), 1, mod
10 ); }
11 ll pollard_rho(ll n) {
12     if (!(n & 1)) return 2;
13     while (true) {
14         ll y = 2, x = rand() % (n - 1) + 1, res = 1;
15         for (int sz = 2; res == 1; sz *= 2) {
16             for (int i = 0; i < sz && res <= 1; i++) {
17                 x = f(x, n);
18                 res = __gcd(llabs(x - y), n);
19             }
20             y = x;
21         }
22         if (res != 0 && res != n) return res;
23     }
24 }
25 vector<ll> ret;
26 void fact(ll x) {
27     if (miller_rabin(x)) {
28         ret.push_back(x);
29         return;
30     }
31     ll f = pollard_rho(x);
32     fact(f);
33     fact(x / f);
34 }

```

8.3 Miller Rabin

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633 4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383 6 : pimes <= 13
4 // n < 2^64              7 :
5 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022
6 bool witness(ll a, ll n, ll u, int t) {
7     if (!(a % n)) return 0;
8     ll x = mypow(a, u, n);
9     for (int i = 0; i < t; i++) {
10         ll nx = mul(x, x, n);

```

```

11         if (nx == 1 && x != 1 && x != n - 1) return 1;
12         x = nx;
13     }
14     return x != 1;
15 }
16 bool miller_rabin(ll n, int s = 100) {
17     // iterate s times of witness on n
18     // return 1 if prime, 0 otherwise
19     if (n < 2) return 0;
20     if (!(n & 1)) return n == 2;
21     ll u = n - 1;
22     int t = 0;
23     while (!(u & 1)) u >>= 1, t++;
24     while (s--) {
25         ll a = randll() % (n - 1) + 1;
26         if (witness(a, n, u, t)) return 0;
27     }
28     return 1;
29 }

```

8.4 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

8.5 Extend GCD

```

1 ll GCD;
2 pll extgcd(ll a, ll b) {
3     if (b == 0) {
4         GCD = a;
5         return pll{1, 0};
6     }
7     pll ans = extgcd(b, a % b);
8     return pll{ans.S, ans.F - a / b * ans.S};
9 }
10 pll bezout(ll a, ll b, ll c) {
11     bool negx = (a < 0), negy = (b < 0);
12     pll ans = extgcd(abs(a), abs(b));
13     if (c % GCD != 0) return pll{-LLINF, -LLINF};
14     return pll{ans.F * c / GCD * (negx ? -1 : 1),
15         ans.S * c / GCD * (negy ? -1 : 1)};
16 }
17 ll inv(ll a, ll p) {
18     if (p == 1) return -1;
19     pll ans = bezout(a % p, -p, 1);
20     if (ans == pll{-LLINF, -LLINF}) return -1;
21     return (ans.F % p + p) % p;
22 }

```

8.6 Mu + Phi

```

1 const int maxn = 1e6 + 5;
2 ll f[maxn];
3 vector<int> lpf, prime;
4 void build() {
5     lpf.clear();
6     lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
14         }
15         for (auto& j : prime) {
16             if (i * j >= maxn) break;
17             lpf[i * j] = j;
18             if (i % j == 0)
19                 f[i * j] = ...; /* 0, phi[i]*j */
20             else
21                 f[i * j] = ...; /* -mu[i], phi[i]*phi[j] */
22             if (j >= lpf[i]) break;
23         }
24     }
25 }

```

8.7 Discrete Log

```

1 long long mod_pow(long long a, long long e, long long p
2 ){}

```



```

2   long long r = 1 % p;
3   while(e){
4       if(e & 1) r = (__int128)r * a % p;
5       a = (__int128)a * a % p;
6       e >>= 1;
7   }
8   return r;
9 }
10 long long mod_inv(long long a, long long p){
11     return mod_pow((a%p+p)%p, p-2, p);
12 }
13 // BSGS: solve a^x = y (mod p), gcd(a,p)=1, p prime,
14 // return minimal x>=0, or -1 if no solution
15 long long bsgs(long long a, long long y, long long p){
16     a%=p; y%=p;
17     if(y==1%p) return 0; // x=0
18     long long m = (long long)ceil(sqrt((long double)p));
19     ;
20     // baby steps: a^j
21     unordered_map<long long, long long> table;
22     table.reserve(m*2);
23     long long cur = 1%p;
24     for(long long j=0; j<m; ++j){
25         if(!table.count(cur)) table[cur]=j;
26         cur = (__int128)cur * a % p;
27     }
28     long long am = mod_pow(a, m, p);
29     long long am_inv = mod_inv(am, p);
30     long long gamma = y % p;
31     for(long long i=0; i<=m; ++i){
32         auto it = table.find(gamma);
33         if(it != table.end()){
34             long long x = i*m + it->second;
35             return x;
36         }
37         gamma = (__int128)gamma * am_inv % p;
38     }
39     return -1;
40 }

```

8.8 sqrt mod

```

1 // the Jacobi symbol is a generalization of the
2 // Legendre symbol,
3 // such that the bottom doesn't need to be prime.
4 // (n/p) -> same as legendre
5 // (n/ab) = (n/a)(n/b)
6 // work with long long
7 int Jacobi(int a, int m) {
8     int s = 1;
9     for (; m > 1; ) {
10         a %= m;
11         if (a == 0) return 0;
12         const int r = __builtin_ctz(a);
13         if ((r & 1) && ((m + 2) & 4)) s = -s;
14         a >>= r;
15         if (a & m & 2) s = -s;
16         swap(a, m);
17     }
18     return s;
19 }
20 // solve x^2 = a (mod p)
21 // 0: a == 0
22 // -1: a isn't a quad res of p
23 // else: return X with X^2 % p == a
24 // doesn't work with long long
25 int QuadraticResidue(int a, int p) {
26     if (p == 2) return a & 1;
27     if (int jc = Jacobi(a, p); jc <= 0) return jc;
28     int b, d;
29     for (; ; ) {
30         b = rand() % p;
31         d = (1LL * b * b + p - a) % p;
32         if (Jacobi(d, p) == -1) break;
33     }
34     int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
35     for (int e = (1LL + p) >> 1; e; e >>= 1) {
36         if (e & 1) {
37             tmp = (1LL * g0 * f0 + 1LL * d * (1LL * g1
38                 * f1 % p)) % p;
39             g1 = (1LL * g0 * f0 + 1LL * g1 * f0) % p;
40             g0 = tmp;

```

```

39     }
40     tmp = (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1
41         % p)) % p;
42     f1 = (2LL * f0 * f1) % p;
43     f0 = tmp;
44 }
45 return g0;

```

8.9 Primitive Root

```

1 unsigned long long primitiveRoot(ull p) {
2     auto fac = factor(p - 1);
3     sort(all(fac));
4     fac.erase(unique(all(fac)), fac.end());
5     auto test = [p, fac](ull x) {
6         for(ull d : fac)
7             if (modpow(x, (p - 1) / d, p) == 1)
8                 return false;
9         return true;
10    };
11    uniform_int_distribution<unsigned long long> unif
12        (1, p - 1);
13    unsigned long long root;
14    while(!test(root = unif(rng)));
15    return root;

```

8.10 Other Formulas

- Inversion:
 $aa^{-1} \equiv 1 \pmod{m}$. a^{-1} exists iff $\gcd(a, m) = 1$.
- Linear inversion:
 $a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$
- Fermat's little theorem:
 $a^p \equiv a \pmod{p}$ if p is prime.
- Euler function:
 $\phi(n) = n \prod_{p|n} \frac{p-1}{p}$
- Euler theorem:
 $a^{\phi(n)} \equiv 1 \pmod{n}$ if $\gcd(a, n) = 1$.
- Extended Euclidean algorithm:
 $ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$
- Divisor function:
 $\sigma_x(n) = \sum_{d|n} d^x$. $n = \prod_{i=1}^r p_i^{a_i}$.
 $\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1}$ if $x \neq 0$. $\sigma_0(n) = \prod_{i=1}^r (a_i + 1)$.
- Chinese remainder theorem (Coprime Moduli):
 $x \equiv a_i \pmod{m_i}$.
 $M = \prod m_i$. $M_i = M/m_i$. $t_i = M_i^{-1}$.
 $x = kM + \sum a_i t_i M_i$, $k \in \mathbb{Z}$.
- Chinese remainder theorem:
 $x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$
Solve for (p, q) using ExtGCD.
 $x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$
- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$
- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(d)g(n/d)$
- Important Multiplicative Functions + Properties:
 - $\epsilon(n) = [n = 1]$
 - $1(n) = 1$
 - $id(n) = n$
 - $\mu(n) = 0$ if n has squared prime factor
 - $\mu(n) = (-1)^k$ if $n = p_1 p_2 \cdots p_k$

6. $\epsilon = \mu * 1$
7. $\phi = \mu * id$
8. $[n = 1] = \sum_{d|n} \mu(d)$
9. $[gcd = 1] = \sum_{d|gcd} \mu(d)$

• Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

8.11 Polynomial

```

1  const int maxk = 20;
2  const int maxn = 1<<maxk;
3  const ll LINF = 1e18;
4
5  /* P = r*2^k + 1
6  P          r    k    g
7  998244353    119  23    3
8  1004535809    479  21    3
9
10 P          r    k    g
11 3          1    1    2
12 5          1    2    2
13 17         1    4    3
14 97         3    5    5
15 193        3    6    5
16 257        1    8    3
17 7681       15    9   17
18 12289      3   12   11
19 40961      5   13    3
20 65537      1   16    3
21 786433     3   18   10
22 5767169    11  19    3
23 7340033    7   20    3
24 23068673   11  21    3
25 104857601  25  22    3
26 167772161  5   25    3
27 469762049  7   26    3
28 1004535809 479  21    3
29 2013265921 15  27   31
30 2281701377 17  27    3
31 3221225473 3   30    5
32 75161927681 35  31    3
33 77309411329 9   33    7
34 206158430209 3   36   22
35 2061584302081 15  37    7
36 2748779069441 5   39    3
37 6597069766657 3   41    5
38 39582418599937 9   42    5
39 79164837199873 9   43    5
40 263882790666241 15  44    7
41 1231453023109121 35  45    3
42 1337006139375617 19  46    3
43 3799912185593857 27  47    5
44 4222124650659841 15  48   19
45 7881299347898369 7   50    6
46 31525197391593473 7   52    3
47 180143985094819841 5   55    6
48 1945555039024054273 27  56    5
49 4179340454199820289 29  57    3
50 9097271247288401921 505  54    6 */
51
52 const int g = 3;
53 const ll MOD = 998244353;
54
55 ll pw(ll a, ll n) { /* fast pow */ }
56
57 #define siz(x) (int)x.size()
58
59 template<typename T>
60 vector<T>& operator+=(vector<T>& a, const vector<T>& b) {
61     {
62         if (siz(a) < siz(b)) a.resize(siz(b));
63         for (int i = 0; i < min(siz(a), siz(b)); i++) {
64             a[i] += b[i];
65             a[i] -= a[i] >= MOD ? MOD : 0;
66         }
67         return a;
68     }
69
70 template<typename T>
71 vector<T>& operator-=(vector<T>& a, const vector<T>& b) {
72     {

```

```

71     if (siz(a) < siz(b)) a.resize(siz(b));
72     for (int i = 0; i < min(siz(a), siz(b)); i++) {
73         a[i] -= b[i];
74         a[i] += a[i] < 0 ? MOD : 0;
75     }
76     return a;
77 }
78
79 template<typename T>
80 vector<T> operator-(const vector<T>& a) {
81     vector<T> ret(siz(a));
82     for (int i = 0; i < siz(a); i++) {
83         ret[i] = -a[i] < 0 ? -a[i] + MOD : -a[i];
84     }
85     return ret;
86 }
87
88 vector<ll> X, iX;
89 vector<int> rev;
90
91 void init_ntt() {
92     X.clear(); X.resize(maxn, 1); // x1 = g^((p-1)/n)
93     iX.clear(); iX.resize(maxn, 1);
94
95     ll u = pw(g, (MOD-1)/maxn);
96     ll iu = pw(u, MOD-2);
97
98     for (int i = 1; i < maxn; i++) {
99         X[i] = X[i-1] * u;
100        iX[i] = iX[i-1] * iu;
101        if (X[i] >= MOD) X[i] %= MOD;
102        if (iX[i] >= MOD) iX[i] %= MOD;
103    }
104
105    rev.clear(); rev.resize(maxn, 0);
106    for (int i = 1, hb = -1; i < maxn; i++) {
107        if (!(i & (i-1))) hb++;
108        rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
109    }
110
111 template<typename T>
112 void NTT(vector<T>& a, bool inv=false) {
113
114     int _n = (int)a.size();
115     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
116     int n = 1<<k;
117     a.resize(n, 0);
118
119     short shift = maxk-k;
120     for (int i = 0; i < n; i++)
121         if (i > (rev[i]>>shift))
122             swap(a[i], a[rev[i]>>shift]);
123
124     for (int len = 2, half = 1, div = maxn>>1; len <= n
125         ; len<=1, half<=1, div>>=1) {
126         for (int i = 0; i < n; i += len) {
127             for (int j = 0; j < half; j++) {
128                 T u = a[i+j];
129                 T v = a[i+j+half] * (inv ? iX[j*div] :
130                     X[j*div]) % MOD;
131                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
132                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
133             }
134         }
135     }
136
137     if (inv) {
138         T dn = pw(n, MOD-2);
139         for (auto& x : a) {
140             x *= dn;
141             if (x >= MOD) x %= MOD;
142         }
143     }
144
145 template<typename T>
146 inline void resize(vector<T>& a) {
147     int cnt = (int)a.size();
148     for (; cnt > 0; cnt--) if (a[cnt-1]) break;
149     a.resize(max(cnt, 1));
150
151 template<typename T>
152 vector<T>& operator*=(vector<T>& a, vector<T> b) {
153     int na = (int)a.size();

```

```

150 int nb = (int)b.size();
151 a.resize(na + nb - 1, 0);
152 b.resize(na + nb - 1, 0);
153
154 NTT(a); NTT(b);
155 for (int i = 0; i < (int)a.size(); i++) {
156     a[i] *= b[i];
157     if (a[i] >= MOD) a[i] %= MOD;
158 }
159 NTT(a, true);
160
161 resize(a);
162 return a;
163 }
164
165 template<typename T>
166 void inv(vector<T>& ia, int N) {
167     vector<T> _a(move(ia));
168     ia.resize(1, pw(_a[0], MOD-2));
169     vector<T> a(1, _a[0] + (-_a[0] < 0 ? MOD : 0));
170
171     for (int n = 1; n < N; n<=1) {
172         // n -> 2*n
173         // ia' = ia(2-a*ia);
174
175         for (int i = n; i < min(siz(_a), (n<1)); i++)
176             a.emplace_back(-_a[i] + (-_a[i] < 0 ? MOD : 0));
177
178         vector<T> tmp = ia;
179         ia *= a;
180         ia.resize(n<1);
181         ia[0] = ia[0] + 2 >= MOD ? ia[0] + 2 - MOD : ia[0] + 2;
182         ia *= tmp;
183         ia.resize(n<1);
184     }
185     ia.resize(N);
186 }
187
188 template<typename T>
189 void mod(vector<T>& a, vector<T>& b) {
190     int n = (int)a.size()-1, m = (int)b.size()-1;
191     if (n < m) return;
192
193     vector<T> ra = a, rb = b;
194     reverse(ra.begin(), ra.end()); ra.resize(min(n+1, n-m+1));
195     reverse(rb.begin(), rb.end()); rb.resize(min(m+1, n-m+1));
196
197     inv(rb, n-m+1);
198
199     vector<T> q = move(ra);
200     q *= rb;
201     q.resize(n-m+1);
202     reverse(q.begin(), q.end());
203
204     q *= b;
205     a -= q;
206     resize(a);
207 }
208
209 /* Kitamasa Method (Fast Linear Recurrence):
210 Find a[K] (Given a[j] = c[0]a[j-N] + ... + c[N-1]a[j-1])
211 Let B(x) = x^N - c[N-1]x^(N-1) - ... - c[1]x^1 - c[0]
212 Let R(x) = x^K mod B(x) (get x^K using fast pow and use poly mod to get R(x))
213 Let r[i] = the coefficient of x^i in R(x)
214 => a[K] = a[0]r[0] + a[1]r[1] + ... + a[N-1]r[N-1] */

```

9 Linear Algebra

9.1 Gaussian-Jordan Elimination

```

1 int n;
2 vector<vector<ll>>> v;
3 void gauss(vector<vector<ll>>& v) {
4     int r = 0;
5     for (int i = 0; i < n; i++) {

```

```

6     bool ok = false;
7     for (int j = r; j < n; j++) {
8         if (v[j][i] == 0) continue;
9         swap(v[j], v[r]);
10        ok = true;
11        break;
12    }
13    if (!ok) continue;
14    ll div = inv(v[r][i]);
15    for (int j = 0; j < n + 1; j++) {
16        v[r][j] *= div;
17        if (v[r][j] >= MOD) v[r][j] %= MOD;
18    }
19    for (int j = 0; j < n; j++) {
20        if (j == r) continue;
21        ll t = v[j][i];
22        for (int k = 0; k < n + 1; k++) {
23            v[j][k] -= v[r][k] * t % MOD;
24            if (v[j][k] < 0) v[j][k] += MOD;
25        }
26    }
27    r++;
28 }
29 }

```

9.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then det = 0, otherwise det = product of diagonal elements.
2. Properties of det:
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times det$
 - Row Operation 3 - $k\vec{r}_i$ add to \vec{r}_j : Unchanged

10 Combinatorics

10.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

0	1	1	2	5
4	14	42	132	429
8	1430	4862	16796	58786
12	208012	742900	2674440	9694845

10.2 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

11 Special Numbers

11.1 Fibonacci Series

1	1	1	2	3
5	5	8	13	21
9	34	55	89	144
13	233	377	610	987
17	1597	2584	4181	6765
21	10946	17711	28657	46368
25	75025	121393	196418	317811
29	514229	832040	1346269	2178309
33	3524578	5702887	9227465	14930352

$$f(45) \approx 10^9, f(88) \approx 10^{18}$$

11.2 Prime Numbers

- First 50 prime numbers:

1	2	3	5	7	11
6	13	17	19	23	29
11	31	37	41	43	47
16	53	59	61	67	71
21	73	79	83	89	97
26	101	103	107	109	113
31	127	131	137	139	149
36	151	157	163	167	173
41	179	181	191	193	197
46	199	211	223	227	229

- Very large prime numbers:

1000001333 1000500889 2500001909
 2000000659 900004151 850001359

- $\pi(n) \equiv$ Number of primes $\leq n \approx n/((\ln n) - 1)$

$$\pi(100) = 25, \pi(200) = 46$$

$$\pi(500) = 95, \pi(1000) = 168$$

$$\pi(2000) = 303, \pi(4000) = 550$$

$$\pi(10^4) = 1229, \pi(10^5) = 9592$$

$$\pi(10^6) = 78498, \pi(10^7) = 664579$$

