

Contents

| | |
|---------------------------------------|----------|
| 1 Reminder | 1 |
| 1.1 Bug List | 1 |
| 1.2 OwO | 1 |
| 2 Basic | 1 |
| 2.1 Vimrc | 1 |
| 2.2 Stress | 1 |
| 2.3 Run Sample | 1 |
| 2.4 Runcpp.sh | 1 |
| 2.5 Others | 1 |
| 3 Data Structure | 2 |
| 3.1 BIT | 2 |
| 3.2 Lazy Propagation Segment Tree | 2 |
| 3.3 Treap | 2 |
| 3.4 Persistent Treap | 3 |
| 3.5 Li Chao Tree | 3 |
| 3.6 LineContainer | 4 |
| 3.7 Sparse Table | 4 |
| 3.8 Time Segment Tree | 4 |
| 3.9 Dynamic Median | 4 |
| 3.10 SOS DP | 5 |
| 4 Flow / Matching | 5 |
| 4.1 Dinic | 5 |
| 4.2 MCMF | 5 |
| 4.3 KM | 6 |
| 4.4 Hopcroft-Karp | 6 |
| 4.5 Blossom | 7 |
| 4.6 Cover / Independent Set | 7 |
| 4.7 Hungarian Algorithm | 7 |
| 5 Graph | 7 |
| 5.1 Heavy-Light Decomposition | 7 |
| 5.2 Centroid Decomposition | 8 |
| 5.3 Bellman-Ford + SPFA | 8 |
| 5.4 BCC - AP | 9 |
| 5.5 BCC - Bridge | 9 |
| 5.6 SCC - Tarjan | 10 |
| 5.7 SCC - Kosaraju | 10 |
| 5.8 Eulerian Path - Undir | 11 |
| 5.9 Eulerian Path - Dir | 11 |
| 5.10 Hamilton Path | 11 |
| 5.11 Kth Shortest Path | 11 |
| 5.12 System of Difference Constraints | 13 |

| | |
|---------------------------------|-----------|
| 6 String | 13 |
| 6.1 Aho Corasick | 13 |
| 6.2 KMP | 13 |
| 6.3 Z Value | 13 |
| 6.4 Manacher | 13 |
| 6.5 Suffix Array | 14 |
| 6.6 Suffix Automaton | 14 |
| 6.7 Minimum Rotation | 15 |
| 6.8 Lyndon Factorization | 15 |
| 6.9 Rolling Hash | 15 |
| 6.10 Trie | 15 |
| 7 Geometry | 15 |
| 7.1 Basic Operations | 15 |
| 7.2 Sort by Angle | 16 |
| 7.3 Intersection | 16 |
| 7.4 Polygon Area | 16 |
| 7.5 Convex Hull | 16 |
| 7.6 Point In Convex | 16 |
| 7.7 Point Segment Distance | 17 |
| 7.8 Point in Polygon | 17 |
| 7.9 Minimum Euclidean Distance | 17 |
| 7.10 Minkowski Sum | 17 |
| 7.11 Lower Concave Hull | 17 |
| 7.12 Pick's Theorem | 18 |
| 7.13 Rotating SweepLine | 18 |
| 7.14 Half Plane Intersection | 18 |
| 7.15 Minimum Enclosing Circle | 18 |
| 7.16 Union of Circles | 18 |
| 7.17 Area Of Circle Polygon | 19 |
| 7.18 3D Point | 19 |
| 8 Number Theory | 19 |
| 8.1 FFT | 19 |
| 8.2 Pollard's rho | 20 |
| 8.3 Miller Rabin | 20 |
| 8.4 Fast Power | 20 |
| 8.5 Extend GCD | 20 |
| 8.6 Mu + Phi | 20 |
| 8.7 Discrete Log | 20 |
| 8.8 sqrt mod | 21 |
| 8.9 Primitive Root | 21 |
| 8.10 LinearSieve | 21 |
| 8.11 Other Formulas | 21 |
| 8.12 Polynomial | 22 |
| 9 Linear Algebra | 23 |
| 9.1 Gaussian-Jordan Elimination | 23 |
| 9.2 Determinant | 23 |
| 10 Combinatorics | 23 |
| 10.1 Catalan Number | 23 |
| 10.2 Burnside's Lemma | 24 |

2 Basic

2.1 Vimrc

```
set number relativenumber ai t_Co=256 tabstop=4
set mouse=a shiftwidth=4 encoding=utf8
set bs=2 ruler laststatus=2 cmdheight=2
set clipboard=unnamedplus showcmd autoread
set belloff=all
filetype indent on

inoremap ( (<Esc>i
inoremap " "<Esc>i
inoremap [ <Esc>i
inoremap ' '<Esc>i
inoremap { {<CR><Esc>ko

nnoremap <tab> gt
nnoremap <S-tab> gT
inoremap <C-n> <Esc>:tabnew<CR>
nnoremap <C-n> :tabnew<CR>

inoremap <F9> <Esc>:w<CR>:!~/runcpp.sh %:p:t %:p:h<CR>
nnoremap <F9> :w<CR>:!~/runcpp.sh %:p:t %:p:h<CR>

syntax on
colorscheme desert
set filetype=cpp
set background=dark
hi Normal ctermfg=white ctermbg=black
```

2.2 Stress

```
g++ gen.cpp -o gen.out
g++ ac.cpp -o ac.out
g++ wa.cpp -o wa.out
for ((i=0;;i++))
do
    echo "$i"
    ./gen.out > in.txt
    ./ac.out < in.txt > ac.txt
    ./wa.out < in.txt > wa.txt
    if [ "$?" -ne 0 ]; then
        exit 1
    fi
    diff ac.txt wa.txt || break
done
```

2.3 Run Sample

```
prog=$1
shift
g++ -O2 -std=c++20 -fsanitize=address -Wall -Wextra -
Wshadow ${prog}.cpp -o ${prog}.out
for f in "$@"; do
    out=${prog}_${(basename "$f").out}
    echo "input: $f"
    cat "$f"
    echo "output: $out"
    ./${prog}.out < "$f" | tee "$out"
done
```

2.4 Runcpp.sh

```
#!/bin/bash
clear
echo "Start compiling $1..."
echo
g++ -O2 -std=c++20 -fsanitize=address -Wall -Wextra -
Wshadow $2/$1 -o $2/out
if [ "$?" -ne 0 ]
then
    exit 1
fi
echo
echo "Done compiling"
echo "=====
echo "Input file:"
echo
```

1 Reminder

1.1 Bug List

- 沒開 long long
- 本地編譯請開-Wall -Wextra -Wshadow -fsanitize=address
- 陣列戳出界 / 開不夠大 / 開太大本地 compile 噴怪 error
- 傳之前先確定選對檔案
- 變數打錯
- 0-base / 1-base
- 忘記初始化
- == 打成 =
- dp[i] 從 dp[i-1] 轉移時忘記特判 i > 0
- std::sort 比較運算子寫成 < 或是讓 = 的情況為 true
- 漏 case / 分 case 要好好想
- 線段樹改值懶標初始值不能設為 0
- 少碰動態開點，能離散化就離散化
- 能不用浮點數運算就不用
- DFS 的時候不小心覆寫到全域變數
- 記得刪 cerr

1.2 OwO

- 可以構造複雜點的測資幫助思考
- 真的卡太久請跳題
- Enjoy The Contest!

```

16 cat $2/in.txt
17 echo
18 echo "=====
19 echo
20 declare startTime=`date +%s%N`
21 $2/out < $2/in.txt > $2/out.txt
22 declare endTime=`date +%s%N`
23 delta=`expr $endTime - $startTime`
24 delta=`expr $delta / 1000000`
25 cat $2/out.txt
26 echo
27 echo "time: $delta ms"

```

2.5 Others

```

1 #pragma GCC optimize("Ofast,unroll-loops,no-stack-
  protector,fast-math")
2 #pragma GCC target("see,see2,see3,see4,avx2,bmi,bmi2,
  lzcmt,popcnt,tune=native")
3 #pragma GCC optimize("trapv")
4 mt19937 gen(chrono::steady_clock::now().
  time_since_epoch().count());
5 uniform_int_distribution<int> dis(1, 100);
6 cout << dis(gen) << endl;
7 shuffle(v.begin(), v.end(), gen);
8
9 struct edge {
10     int a, b, w;
11     friend istream& operator>>(istream& in, edge& x) {
12         in >> x.a >> x.b >> x.w; }
13     friend ostream& operator<<(ostream& out, const edge
14         & x) {
15         out << "(" << x.a << ", " << x.b << ", " << x.w
16         << ")";
17         return out;
18     }
19 };
20 struct cmp {
21     bool operator()(const edge& x, const edge& y) const
22     { return x.w < y.w; }
23 };
24 set<edge, cmp> st; // 遞增
25 map<edge, long long, cmp> mp; // 遞增
26 priority_queue<edge, vector<edge>, cmp> pq; // 遞減
27
28 #include <bits/extc++.h>
29 #include <ext/pb_ds/assoc_container.hpp>
30 #include <ext/pb_ds/tree_policy.hpp>
31 using namespace __gnu_pbds;
32
33 // map
34 tree<int, int, less<>, rb_tree_tag,
35     tree_order_statistics_node_update> tr;
36 tr.order_of_key(element);
37 tr.find_by_order(rank);
38
39 // set
40 tree<int, null_type, less<>, rb_tree_tag,
41     tree_order_statistics_node_update> tr;
42 tr.order_of_key(element);
43 tr.find_by_order(rank);
44
45 gp_hash_table<int, int> ht;
46 ht.find(element);
47 ht.insert({key, value});
48 ht.erase(element);
49
50 // priority queue Big First
51 __gnu_pbds::priority_queue<int, less<int>> big_q;
52 __gnu_pbds::priority_queue<int, greater<int>> small_q;
53 // Small First
54 q1.join(q2); // join

```

3 Data Structure

3.1 BIT

```

1 struct BIT {
2     int n;
3     long long bit[N];
4

```

```

5     void init(int x, vector<long long> &a) {
6         n = x;
7         for (int i = 1, j; i <= n; i++) {
8             bit[i] += a[i - 1], j = i + (i & -i);
9             if (j <= n) bit[j] += bit[i];
10        }
11    }
12
13    void update(int x, long long dif) {
14        while (x <= n) bit[x] += dif, x += x & -x;
15    }
16
17    long long query(int l, int r) {
18        if (l != 1) return query(1, r) - query(1, l -
19            1);
20
21        long long ret = 0;
22        while (l <= r) ret += bit[r], r -= r & -r;
23        return ret;
24    }
25 } bm;

```

3.2 Lazy Propagation Segment Tree

```

1 struct lazy_propagation{
2     // 0-based, [l, r], tg[0]->add, tg[1]->set
3     ll seg[N * 4], tg[2][N*4];
4     void assign (bool op, ll val, int idx){
5         if (op == 0){
6             if (tg[1][idx]) tg[1][idx] += val;
7             else tg[0][idx] += val;
8         }
9         else seg[idx] = 0, tg[0][idx] = 0, tg[1][idx]
10            = val;
11    }
12    ll sum (int idx, int len){
13        if (tg[1][idx]) return tg[1][idx] * len;
14        return tg[0][idx] * len + seg[idx];
15    }
16    void pull (int idx, int len){
17        seg[idx] = sum(2*idx, (len+1)/2) + sum(2*idx+1,
18            len/2);
19    }
20    void push (int idx){
21        if (!tg[0][idx] && !tg[1][idx]) return ;
22        if (tg[0][idx]){
23            assign(0, tg[0][idx], 2*idx);
24            assign(0, tg[0][idx], 2*idx+1);
25            tg[0][idx] = 0;
26        }
27        else{
28            assign(1, tg[1][idx], 2*idx);
29            assign(1, tg[1][idx], 2*idx+1);
30            tg[1][idx] = 0;
31        }
32    }
33    void update (bool op, ll val, int gl, int gr, int l
34        , int r, int idx){
35        if (r < l || gr < l || r < gl) return ;
36        if (gl <= l && r <= gr){
37            assign(op, val, idx);
38            return ;
39        }
40
41        int mid = (l + r) / 2;
42        push(idx);
43        update(op, val, gl, gr, l, mid, 2*idx);
44        update(op, val, gl, gr, mid+1, r, 2*idx+1);
45        pull(idx, r-l+1);
46    }
47    ll query (int gl, int gr, int l, int r, int idx){
48        if (r < l || gr < l || r < gl) return 0;
49        if (gl <= l && r <= gr) return sum(idx, r-l+1);
50
51        push(idx), pull(idx, r-l+1);
52        int mid = (l + r) / 2;
53        return query(gl, gr, l, mid, 2*idx) + query(gl,
54            gr, mid+1, r, 2*idx+1);
55    }
56 }bm;

```

3.3 Treap

```

1 mt19937 rng(random_device{}());
2 struct Treap {
3     Treap *l, *r;
4     int val, sum, real, tag, num, pri, rev;
5     Treap(int k) {
6         l = r = NULL;
7         val = sum = k;
8         num = 1;
9         real = -1;
10        tag = 0;
11        rev = 0;
12        pri = rng();
13    }
14};
15 int siz(Treap *now) { return now ? now->num : 0; }
16 int sum(Treap *now) {
17     if (!now) return 0;
18     if (now->real != -1) return (now->real + now->tag)
19         * now->num;
20     return now->sum + now->tag * now->num;
21 }
22 void pull(Treap *&now) {
23     now->num = siz(now->l) + siz(now->r) + 1;
24     now->sum = sum(now->l) + sum(now->r) + now->val *
25         now->num;
26 }
27 void push(Treap *&now) {
28     if (now->rev) {
29         swap(now->l, now->r);
30         now->l->rev ^= 1;
31         now->r->rev ^= 1;
32         now->rev = 0;
33     }
34     if (now->real != -1) {
35         now->real += now->tag;
36         if (now->l) {
37             now->l->tag = 0;
38             now->l->real = now->real;
39             now->l->val = now->real;
40         }
41         if (now->r) {
42             now->r->tag = 0;
43             now->r->real = now->real;
44             now->r->val = now->real;
45         }
46         now->val = now->real;
47         now->sum = now->real * now->num;
48         now->real = -1;
49         now->tag = 0;
50     } else {
51         if (now->l) now->l->tag += now->tag;
52         if (now->r) now->r->tag += now->tag;
53         now->sum += sum(now);
54         now->val += now->tag;
55         now->tag = 0;
56     }
57 }
58 Treap *merge(Treap *a, Treap *b) {
59     if (!a || !b) return a ? a : b;
60     else if (a->pri > b->pri) {
61         push(a);
62         a->r = merge(a->r, b);
63         pull(a);
64         return a;
65     } else {
66         push(b);
67         b->l = merge(a, b->l);
68         pull(b);
69         return b;
70     }
71 }
72 void split_size(Treap *rt, Treap *&a, Treap *&b, int
73     val) {
74     if (!rt) {
75         a = b = NULL;
76         return;
77     }
78     push(rt);
79     if (siz(rt->l) + 1 > val) {
80         b = rt;
81         split_size(rt->l, a, b->l, val);
82         pull(b);
83     } else {
84         a = rt;
85         split_size(rt->r, a->r, b, val - siz(a->l) - 1);
86         pull(a);
87     }
88 }
89 void split_val(Treap *rt, Treap *&a, Treap *&b, int val)
90 {
91     if (!rt) {
92         a = b = NULL;
93         return;
94     }
95     push(rt);
96     if (rt->val <= val) {
97         a = rt;
98         split_val(rt->r, a->r, b, val);
99         pull(a);
100     } else {
101         b = rt;
102         split_val(rt->l, a, b->l, val);
103         pull(b);
104     }
105 }

```

```

78     split_size(rt->l, a, b->l, val);
79     pull(b);
80 } else {
81     a = rt;
82     split_size(rt->r, a->r, b, val - siz(a->l) - 1);
83     pull(a);
84 }
85 }
86 void split_val(Treap *rt, Treap *&a, Treap *&b, int val
87 ) {
88     if (!rt) {
89         a = b = NULL;
90         return;
91     }
92     push(rt);
93     if (rt->val <= val) {
94         a = rt;
95         split_val(rt->r, a->r, b, val);
96         pull(a);
97     } else {
98         b = rt;
99         split_val(rt->l, a, b->l, val);
100         pull(b);
101     }
102 }

```

3.4 Persistent Treap

```

1 struct node {
2     node *l, *r;
3     char c;
4     int v, sz;
5     node(char x = '$') : c(x), v(mt()), sz(1) {
6         l = r = nullptr;
7     }
8     node(node* p) { *this = *p; }
9     void pull() {
10         sz = 1;
11         for (auto i : {l, r})
12             if (i) sz += i->sz;
13     }
14 } arr[maxn], *ptr = arr;
15 inline int size(node* p) { return p ? p->sz : 0; }
16 node* merge(node* a, node* b) {
17     if (!a || !b) return a ? a : b;
18     if (a->v < b->v) {
19         node* ret = new (ptr++) node(a);
20         ret->r = merge(ret->r, b);
21         ret->pull();
22         return ret;
23     } else {
24         node* ret = new (ptr++) node(b);
25         ret->l = merge(a, ret->l);
26         ret->pull();
27         return ret;
28     }
29 }
30 P<node*> split(node* p, int k) {
31     if (!p) return {nullptr, nullptr};
32     if (k >= size(p->l) + 1) {
33         auto [a, b] = split(p->r, k - size(p->l) - 1);
34         node* ret = new (ptr++) node(p);
35         ret->r = a, ret->pull();
36         return {ret, b};
37     } else {
38         auto [a, b] = split(p->l, k);
39         node* ret = new (ptr++) node(p);
40         ret->l = b, ret->pull();
41         return {a, ret};
42     }
43 }

```

3.5 Li Chao Tree

```

1 const int eps=1e-9;
2 struct line
3 {
4     double m,k;
5 } p[N];
6 int seg[N<<2],cnt;
7 double cal(int id,int x){return 1.0*p[id].m*x+p[id].k;}
8 void add(int x0,int y0,int x1,int y1)
9 {

```

```

10 cnt++;
11 if(x0==x1)p[cnt].m=0,p[cnt].k=max(y0,y1);
12 else p[cnt].m=1.0*(y1-y0)/(x1-x0),p[cnt].k=y0-p[
    cnt].m*x0;
13 }
14 void update(int x,int l,int r,int ql,int qr,int u)
15 {
16     int v=seg[x],mid=(l+r)>>1;
17     double resu=cal(u,mid),resv=cal(v,mid);
18     if(qr<l||r<ql)return;
19     if(ql<=l&&r<=qr)
20     {
21         if(l==r)
22         {
23             if(resu>resv)seg[x]=u;
24             return;
25         }
26         if(p[u].m-p[v].m>eps)
27         {
28             if(resu-resv>eps)
29             {
30                 seg[x]=u;
31                 update(x<<1,l,mid,ql,qr,v);
32             }
33             else update(x<<1,l,mid+1,r,ql,qr,u);
34         }
35         else if(p[v].m-p[u].m>eps)
36         {
37             if(resu-resv>eps)
38             {
39                 seg[x]=u;
40                 update(x<<1,l,mid+1,r,ql,qr,v);
41             }
42             else update(x<<1,l,mid,ql,qr,u);
43         }
44         else if(p[u].k-p[v].k>eps)seg[x]=u;
45         return;
46     }
47     update(x<<1,l,mid,ql,qr,u);
48     update(x<<1,l,mid+1,r,ql,qr,u);
49 }
50 double ask(int x,int l,int r,int qx)
51 {
52     if(r<qx||qx<l)return{0,0};
53     int mid=(l+r)>>1;
54     double res=cal(seg[x],qx);
55     if(l==r)return res;
56     return max({res,seg[x],ask(x<<1,l,mid,qx),ask(x
        <<1,l,mid+1,r,qx)});
57 }

```

3.6 LineContainer

```

1 struct Line {
2     mutable ll k, m, p;
3     bool operator<(const Line& o) const { return k < o.
        k; }
4     bool operator<(ll x) const { return p < x; }
5 };
6
7
8 struct LineContainer : multiset<Line, less<>> {
9     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
10    static const ll inf = LLONG_MAX;
11    ll div(ll a, ll b) { // floored division
12        return a / b - ((a ^ b) < 0 && a % b); }
13    bool isect(iterator x, iterator y) {
14        if (y == end()) return x->p = inf, 0;
15        if (x->k == y->k) x->p = x->m > y->m ? inf : -
            inf;
16        else x->p = div(y->m - x->m, x->k - y->k);
17        return x->p >= y->p;
18    }
19    void add(ll k, ll m) {
20        auto z = insert({k, m, 0}), y = z++, x = y;
21        while (isect(y, z)) z = erase(z);
22        if (x != begin() && isect(--x, y)) isect(x, y =
            erase(y));
23        while ((y = x) != begin() && (--x)->p >= y->p)
24            isect(x, erase(y));
25    }
26    ll query(ll x) {

```

```

27     assert(!empty());
28     auto l = *lower_bound(x);
29     return l.k * x + l.m;
30 }
31 };

```

3.7 Sparse Table

```

1 int a[N];
2 int st[N][30];
3 void pre(int n)
4 {
5     FOR(i,1,n+1)st[i][0]=a[i];
6     for(int j=1;(1<<j)<=n+1;j++)
7         for(int i=0;i+(1<<j)<=n+1;i++)
8             st[i][j]=min(st[i][j-1],st[i+(1<<(j-1))
                ][j-1]);
9 }
10 int ask(int l,int r)
11 {
12     int k=__lg(r-l+1);
13     return min(st[l][k],st[r-(1<<k)+1][k]);
14 }

```

3.8 Time Segment Tree

```

1 constexpr int maxn = 1e5 + 5;
2 V<P<int>> arr[(maxn + 1) << 2];
3 V<int> dsu, sz;
4 V<tuple<int, int, int>> his;
5 int cnt, q;
6 int find(int x) {
7     return x == dsu[x] ? x : find(dsu[x]);
8 };
9 inline bool merge(int x, int y) {
10     int a = find(x), b = find(y);
11     if (a == b) return false;
12     if (sz[a] > sz[b]) swap(a, b);
13     his.emplace_back(a, b, sz[b]), dsu[a] = b, sz[b] +=
        sz[a];
14     return true;
15 };
16 inline void undo() {
17     auto [a, b, s] = his.back();
18     his.pop_back();
19     dsu[a] = a, sz[b] = s;
20 }
21 #define m ((l + r) >> 1)
22 void insert(int ql, int qr, P<int> x, int i = 1, int l
    = 0, int r = q) {
23     // debug(ql, qr, x); return;
24     if (qr <= l || r <= ql) return;
25     if (ql <= l && r <= qr) {
26         arr[i].push_back(x);
27         return;
28     }
29     if (qr <= m)
30         insert(ql, qr, x, i << 1, l, m);
31     else if (m <= ql)
32         insert(ql, qr, x, i << 1 | 1, m, r);
33     else {
34         insert(ql, qr, x, i << 1, l, m);
35         insert(ql, qr, x, i << 1 | 1, m, r);
36     }
37 }
38 void traversal(V<int>& ans, int i = 1, int l = 0, int r
    = q) {
39     int opcnt = 0;
40     // debug(i, l, r);
41     for (auto [a, b] : arr[i])
42         if (merge(a, b))
43             opcnt++, cnt--;
44     if (r - l == 1)
45         ans[l] = cnt;
46     else {
47         traversal(ans, i << 1, l, m);
48         traversal(ans, i << 1 | 1, m, r);
49     }
50     while (opcnt--)
51         undo(), cnt++;
52     arr[i].clear();
53 }

```

```

54 #undef m
55 inline void solve() {
56     int n, m;
57     cin >> n >> m >> q, q++;
58     dsu.resize(cnt = n), sz.assign(n, 1);
59     iota(dsu.begin(), dsu.end(), 0);
60     // a, b, time, operation
61     unordered_map<ll, V<int>> s;
62     for (int i = 0; i < m; i++) {
63         int a, b;
64         cin >> a >> b;
65         if (a > b) swap(a, b);
66         s[((ll)a << 32) | b].emplace_back(0);
67     }
68     for (int i = 1; i < q; i++) {
69         int op, a, b;
70         cin >> op >> a >> b;
71         if (a > b) swap(a, b);
72         switch (op) {
73             case 1:
74                 s[((ll)a << 32) | b].push_back(i);
75                 break;
76             case 2:
77                 auto tmp = s[((ll)a << 32) | b].back();
78                 s[((ll)a << 32) | b].pop_back();
79                 insert(tmp, i, P<int>{a, b});
80             }
81     }
82     for (auto [p, v] : s) {
83         int a = p >> 32, b = p & -1;
84         while (v.size()) {
85             insert(v.back(), q, P<int>{a, b});
86             v.pop_back();
87         }
88     }
89     V<int> ans(q);
90     traversal(ans);
91     for (auto i : ans)
92         cout << i << ' ';
93     cout << endl;
94 }

```

3.9 Dynamic Median

```

1 struct Dynamic_Median {
2     multiset<long long> lo, hi;
3     long long slo = 0, shi = 0;
4     void rebalance() {
5         // keep sz(lo) >= sz(hi) and sz(lo) - sz(hi) <= 1
6         while((int)lo.size() > (int)hi.size() + 1) {
7             auto it = prev(lo.end());
8             long long x = *it;
9             lo.erase(it); slo -= x;
10            hi.insert(x); shi += x;
11        }
12        while((int)lo.size() < (int)hi.size()) {
13            auto it = hi.begin();
14            long long x = *it;
15            hi.erase(it); shi -= x;
16            lo.insert(x); slo += x;
17        }
18    }
19    void add(long long x) {
20        if(lo.empty() || x <= *prev(lo.end())) {
21            lo.insert(x); slo += x;
22        }
23        else {
24            hi.insert(x); shi += x;
25        }
26        rebalance();
27    }
28    void remove_one(long long x) {
29        if(!lo.empty() && x <= *prev(lo.end())) {
30            auto it = lo.find(x);
31            if(it != lo.end()) {
32                lo.erase(it); slo -= x;
33            }
34            else {
35                auto it2 = hi.find(x);
36                hi.erase(it2); shi -= x;
37            }

```

```

38        }
39        else {
40            auto it = hi.find(x);
41            if(it != hi.end()) {
42                hi.erase(it); shi -= x;
43            }
44            else {
45                auto it2 = lo.find(x);
46                lo.erase(it2); slo -= x;
47            }
48        }
49        rebalance();
50    }
51 };

```

3.10 SOS DP

```

1 for (int mask = 0; mask < (1 << n); mask++) {
2     for (int submask = mask; submask != 0; submask = (
3         submask - 1) & mask) {
4         int subset = mask ^ submask;

```

4 Flow / Matching

4.1 Dinic

```

1 using namespace std;
2 const int N = 2000 + 5;
3 int n, m, s, t, level[N], iter[N];
4 struct edge {int to, cap, rev;};
5 vector<edge> path[N];
6 void add(int a, int b, int c) {
7     path[a].pb({b, c, sz(path[b])});
8     path[b].pb({a, 0, sz(path[a]) - 1});
9 }
10 void bfs() {
11     memset(level, -1, sizeof(level));
12     level[s] = 0;
13     queue<int> q;
14     q.push(s);
15     while (q.size()) {
16         int now = q.front(); q.pop();
17         for (edge e : path[now]) if (e.cap > 0 && level
18             [e.to] == -1) {
19             level[e.to] = level[now] + 1;
20             q.push(e.to);
21         }
22     }
23 }
24 int dfs(int now, int flow) {
25     if (now == t) return flow;
26     for (int &i = iter[now]; i < sz(path[now]); i++) {
27         edge &e = path[now][i];
28         if (e.cap > 0 && level[e.to] == level[now] + 1) {
29             int res = dfs(e.to, min(flow, e.cap));
30             if (res > 0) {
31                 e.cap -= res;
32                 path[e.to][e.rev].cap += res;
33                 return res;
34             }
35         }
36     }
37     return 0;
38 }
39 int dinic() {
40     int res = 0;
41     while (true) {
42         bfs();
43         if (level[t] == -1) break;
44         memset(iter, 0, sizeof(iter));
45         int now = 0;
46         while ((now = dfs(s, INF)) > 0) res += now;
47     }
48     return res;

```

4.2 MCMF

```

1 struct MCMF {

```

```

2   int n, s, t, par[N + 5], p_i[N + 5], dis[N + 5],
3       vis[N + 5];
4   struct edge {
5       int to, cap, rev, cost;
6   };
7   vector<edge> path[N];
8   void init(int _n, int _s, int _t) {
9       n = _n, s = _s, t = _t;
10      FOR(i, 0, 2 * n + 5)
11          par[i] = p_i[i] = vis[i] = 0;
12  }
13  void add(int a, int b, int c, int d) {
14      path[a].pb({b, c, sz(path[b]), d});
15      path[b].pb({a, 0, sz(path[a]) - 1, -d});
16  }
17  void spfa() {
18      FOR(i, 0, n * 2 + 5)
19          dis[i] = INF,
20          vis[i] = 0;
21      dis[s] = 0;
22      queue<int> q;
23      q.push(s);
24      while (!q.empty()) {
25          int now = q.front();
26          q.pop();
27          vis[now] = 0;
28          for (int i = 0; i < sz(path[now]); i++) {
29              edge e = path[now][i];
30              if (e.cap > 0 && dis[e.to] > dis[now] +
31                  e.cost) {
32                  dis[e.to] = dis[now] + e.cost;
33                  par[e.to] = now;
34                  p_i[e.to] = i;
35                  if (vis[e.to] == 0) {
36                      vis[e.to] = 1;
37                      q.push(e.to);
38                  }
39              }
40          }
41      }
42  }
43  pii flow() {
44      int flow = 0, cost = 0;
45      while (true) {
46          spfa();
47          if (dis[t] == INF)
48              break;
49          int mn = INF;
50          for (int i = t; i != s; i = par[i])
51              mn = min(mn, path[par[i]][p_i[i]].cap);
52          flow += mn;
53          cost += dis[t] * mn;
54          for (int i = t; i != s; i = par[i]) {
55              edge &now = path[par[i]][p_i[i]];
56              now.cap -= mn;
57              path[i][now.rev].cap += mn;
58          }
59          return mp(flow, cost);
60      }
61  };

```

4.3 KM

```

1  struct KM {
2      int n, mx[1005], my[1005], pa[1005];
3      int g[1005][1005], lx[1005], ly[1005], sy[1005];
4      bool vx[1005], vy[1005];
5      void init(int _n) {
6          n = _n;
7          FOR(i, 1, n + 1)
8              fill(g[i], g[i] + 1 + n, 0);
9      }
10     void add(int a, int b, int c) { g[a][b] = c; }
11     void augment(int y) {
12         for (int x, z; y; y = z)
13             x = pa[y], z = mx[x], my[y] = x, mx[x] = y;
14     }
15     void bfs(int st) {
16         FOR(i, 1, n + 1)
17             sy[i] = INF,
18             vx[i] = vy[i] = 0;

```

```

19     queue<int> q;
20     q.push(st);
21     for (;;) {
22         while (!q.empty()) {
23             int x = q.front();
24             q.pop();
25             vx[x] = 1;
26             FOR(y, 1, n + 1)
27                 if (!vy[y]) {
28                     int t = lx[x] + ly[y] - g[x][y];
29                     if (t == 0) {
30                         pa[y] = x;
31                         if (!my[y]) {
32                             augment(y);
33                             return;
34                         }
35                         vy[y] = 1, q.push(my[y]);
36                     } else if (sy[y] > t)
37                         pa[y] = x, sy[y] = t;
38                 }
39             }
40         int cut = INF;
41         FOR(y, 1, n + 1)
42             if (!vy[y] && cut > sy[y]) cut = sy[y];
43         FOR(j, 1, n + 1) {
44             if (vx[j]) lx[j] -= cut;
45             if (vy[j])
46                 ly[j] += cut;
47             else
48                 sy[j] -= cut;
49         }
50         FOR(y, 1, n + 1) {
51             if (!vy[y] && sy[y] == 0) {
52                 if (!my[y]) {
53                     augment(y);
54                     return;
55                 }
56                 vy[y] = 1;
57                 q.push(my[y]);
58             }
59         }
60     }
61 }
62 int solve() {
63     fill(mx, mx + n + 1, 0);
64     fill(my, my + n + 1, 0);
65     fill(ly, ly + n + 1, 0);
66     fill(lx, lx + n + 1, 0);
67     FOR(x, 1, n + 1)
68         FOR(y, 1, n + 1)
69             lx[x] = max(lx[x], g[x][y]);
70     FOR(x, 1, n + 1)
71         bfs(x);
72     int ans = 0;
73     FOR(y, 1, n + 1)
74         ans += g[my[y]][y];
75     return ans;
76 }
77 };

```

4.4 Hopcroft-Karp

```

1  struct HopcroftKarp {
2      // id: X = [1, nx], Y = [nx+1, nx+ny]
3      int n, nx, ny, m, MXCNT;
4      vector<vector<int>> g;
5      vector<int> mx, my, dis, vis;
6      void init(int nnx, int nny, int mm) {
7          nx = nnx, ny = nny, m = mm;
8          n = nx + ny + 1;
9          g.clear();
10         g.resize(n);
11     }
12     void add(int x, int y) {
13         g[x].emplace_back(y);
14         g[y].emplace_back(x);
15     }
16     bool dfs(int x) {
17         vis[x] = true;
18         Each(y, g[x]) {
19             int px = my[y];
20             if (px == -1 ||

```



```

21         (dis[px] == dis[x] + 1 &&
22         !vis[px] && dfs(px))) {
23             mx[x] = y;
24             my[y] = x;
25             return true;
26         }
27     }
28     return false;
29 }
30 void get() {
31     mx.clear();
32     mx.resize(n, -1);
33     my.clear();
34     my.resize(n, -1);
35
36     while (true) {
37         queue<int> q;
38         dis.clear();
39         dis.resize(n, -1);
40         for (int x = 1; x <= nx; x++) {
41             if (mx[x] == -1) {
42                 dis[x] = 0;
43                 q.push(x);
44             }
45         }
46         while (!q.empty()) {
47             int x = q.front();
48             q.pop();
49             Each(y, g[x]) {
50                 if (my[y] != -1 && dis[my[y]] ==
51                     -1) {
52                     dis[my[y]] = dis[x] + 1;
53                     q.push(my[y]);
54                 }
55             }
56         }
57         bool brk = true;
58         vis.clear();
59         vis.resize(n, 0);
60         for (int x = 1; x <= nx; x++)
61             if (mx[x] == -1 && dfs(x))
62                 brk = false;
63
64         if (brk) break;
65     }
66     MXCNT = 0;
67     for (int x = 1; x <= nx; x++)
68         if (mx[x] != -1) MXCNT++;
69 }
70 } hk;

```

4.5 Blossom

```

1  const int N=5e2+10;
2  struct Graph{
3      int to[N],bro[N],head[N],e;
4      int lnk[N],vis[N],stp,n;
5      void init(int _n){
6          stp=0;e=1;n=_n;
7          FOR(i,0,n+1)head[i]=lnk[i]=vis[i]=0;
8      }
9      void add(int u,int v){
10         to[e]=v,bro[e]=head[u],head[u]=e++;
11         to[e]=u,bro[e]=head[v],head[v]=e++;
12     }
13     bool dfs(int x){
14         vis[x]=stp;
15         for(int i=head[x];i;i=bro[i])
16         {
17             int v=to[i];
18             if(!lnk[v])
19             {
20                 lnk[x]=v;lnk[v]=x;
21                 return true;
22             }
23             else if(vis[lnk[v]]<stp)
24             {
25                 int w=lnk[v];
26                 lnk[x]=v,lnk[v]=x,lnk[w]=0;
27                 if(dfs(w))return true;
28                 lnk[w]=v,lnk[v]=w,lnk[x]=0;

```

```

29     }
30     }
31     return false;
32 }
33 int solve(){
34     int ans=0;
35     FOR(i,1,n+1){
36         if(!lnk[i]){
37             stp++;
38             ans+=dfs(i);
39         }
40     }
41     return ans;
42 }
43 void print_matching(){
44     FOR(i,1,n+1)
45         if(i<graph.lnk[i])
46             cout<<i<<" "<<graph.lnk[i]<<endl;
47 }
48 };

```

4.6 Cover / Independent Set

1 V(E) Cover: choose some V(E) to cover all E(V)
2 V(E) Independ: set of V(E) **not** adj to each other

3
4 M = Max Matching
5 Cv = Min V Cover
6 Ce = Min E Cover
7 Iv = Max V Ind
8 Ie = Max E Ind (equiv to M)

9
10 M = Cv (Konig Theorem)
11 Iv = V \ Cv
12 Ce = V - M

13
14 Construct Cv:
15 1. Run Dinic
16 2. Find s-t min cut
17 3. Cv = {X in T} + {Y in S}

4.7 Hungarian Algorithm

```

1  const int N = 2e3;
2  int match[N];
3  bool vis[N];
4  int n;
5  vector<int> ed[N];
6  int match_cnt;
7  bool dfs(int u) {
8      vis[u] = 1;
9      for(int i : ed[u]) {
10         if(match[i] == 0 || !vis[match[i]] && dfs(match
11             [i])) {
12             match[i] = u;
13             return true;
14         }
15     }
16     return false;
17 }
18 void hungary() {
19     memset(match, 0, sizeof(match));
20     match_cnt = 0;
21     for(int i = 1; i <= n; i++) {
22         memset(vis, 0, sizeof(vis));
23         if(dfs(i)) match_cnt++;
24     }

```

5 Graph

5.1 Heavy-Light Decomposition

```

1  const int N = 2e5 + 5;
2  int n, dfn[N], son[N], top[N], num[N], dep[N], p[N];
3  vector<int> path[N];
4  struct node {
5      int mx, sum;
6  } seg[N << 2];
7  void update(int x, int l, int r, int qx, int val) {
8      if (l == r) {

```

```

9     seg[x].mx = seg[x].sum = val;
10    return;
11 }
12 int mid = (l + r) >> 1;
13 if (qx <= mid) update(x << 1, l, mid, qx, val);
14 else update(x << 1 | 1, mid + 1, r, qx, val);
15 seg[x].mx = max(seg[x << 1].mx, seg[x << 1 | 1].mx);
16 seg[x].sum = seg[x << 1].sum + seg[x << 1 | 1].sum;
17 }
18 int big(int x, int l, int r, int ql, int qr) {
19     if (ql <= l && r <= qr) return seg[x].mx;
20     int mid = (l + r) >> 1;
21     int res = -INF;
22     if (ql <= mid) res = max(res, big(x << 1, l, mid, ql, qr));
23     if (mid < qr) res = max(res, big(x << 1 | 1, mid + 1, r, ql, qr));
24     return res;
25 }
26 int ask(int x, int l, int r, int ql, int qr) {
27     if (ql <= l && r <= qr) return seg[x].sum;
28     int mid = (l + r) >> 1;
29     int res = 0;
30     if (ql <= mid) res += ask(x << 1, l, mid, ql, qr);
31     if (mid < qr) res += ask(x << 1 | 1, mid + 1, r, ql, qr);
32     return res;
33 }
34 void dfs1(int now) {
35     son[now] = -1;
36     num[now] = 1;
37     for (auto i : path[now]) {
38         if (!dep[i]) {
39             dep[i] = dep[now] + 1;
40             p[i] = now;
41             dfs1(i);
42             num[now] += num[i];
43             if (son[now] == -1 || num[i] > num[son[now]]) son[now] = i;
44         }
45     }
46 }
47 int cnt;
48 void dfs2(int now, int t) {
49     top[now] = t;
50     cnt++;
51     dfn[now] = cnt;
52     if (son[now] == -1) return;
53     dfs2(son[now], t);
54     for (auto i : path[now])
55         if (i != p[now] && i != son[now]) dfs2(i, i);
56 }
57 int path_big(int x, int y) {
58     int res = -INF;
59     while (top[x] != top[y]) {
60         if (dep[top[x]] < dep[top[y]]) swap(x, y);
61         res = max(res, big(1, 1, n, dfn[top[x]], dfn[x]));
62         x = p[top[x]];
63     }
64     if (dfn[x] > dfn[y]) swap(x, y);
65     res = max(res, big(1, 1, n, dfn[x], dfn[y]));
66     return res;
67 }
68 int path_sum(int x, int y) {
69     int res = 0;
70     while (top[x] != top[y]) {
71         if (dep[top[x]] < dep[top[y]]) swap(x, y);
72         res += ask(1, 1, n, dfn[top[x]], dfn[x]);
73         x = p[top[x]];
74     }
75     if (dfn[x] > dfn[y]) swap(x, y);
76     res += ask(1, 1, n, dfn[x], dfn[y]);
77     return res;
78 }
79 void buildTree() {
80     FOR(i, 0, n - 1) {
81         int a, b;
82         cin >> a >> b;
83         path[a].pb(b);
84         path[b].pb(a);

```

```

85     }
86 }
87 void buildHLD(int root) {
88     dep[root] = 1;
89     dfs1(root);
90     dfs2(root, root);
91     FOR(i, 1, n + 1) {
92         int now;
93         cin >> now;
94         update(1, 1, n, dfn[i], now);
95     }
96 }

```

5.2 Centroid Decomposition

```

1 #include <bits/stdc++.h>
2 using namespace std;
3 const int N = 1e5 + 5;
4 vector<int> a[N];
5 int sz[N], lv[N];
6 bool used[N];
7 int f_sz(int x, int p) {
8     sz[x] = 1;
9     for (int i : a[x])
10         if (i != p && !used[i])
11             sz[x] += f_sz(i, x);
12     return sz[x];
13 }
14 int f_cen(int x, int p, int total) {
15     for (int i : a[x]) {
16         if (i != p && !used[i] && 2 * sz[i] > total)
17             return f_cen(i, x, total);
18     }
19     return x;
20 }
21 void cd(int x, int p) {
22     int total = f_sz(x, p);
23     int cen = f_cen(x, p, total);
24     lv[cen] = lv[p] + 1;
25     used[cen] = 1;
26     // cout << "cd: " << x << " " << p << " " << cen <<
27     // "\n";
28     for (int i : a[cen]) {
29         if (!used[i])
30             cd(i, cen);
31     }
32 }
33 int main() {
34     ios_base::sync_with_stdio(0);
35     cin.tie(0);
36     int n;
37     cin >> n;
38     for (int i = 0, x, y; i < n - 1; i++) {
39         cin >> x >> y;
40         a[x].push_back(y);
41         a[y].push_back(x);
42     }
43     cd(1, 0);
44     for (int i = 1; i <= n; i++)
45         cout << (char)('A' + lv[i] - 1) << " ";
46     cout << "\n";

```

5.3 Bellman-Ford + SPFA

```

1 int n, m;
2
3 // Graph
4 vector<vector<pair<int, ll> > > g;
5 vector<ll> dis;
6 vector<bool> negCycle;
7
8 // SPFA
9 vector<int> rlx;
10 queue<int> q;
11 vector<bool> inq;
12 vector<int> pa;
13 void SPFA(vector<int> &src) {
14     dis.assign(n + 1, LINF);
15     negCycle.assign(n + 1, false);
16     rlx.assign(n + 1, 0);
17     while (!q.empty()) q.pop();

```



```

18     inq.assign(n + 1, false);
19     pa.assign(n + 1, -1);
20
21     for (auto& s : src) {
22         dis[s] = 0;
23         q.push(s);
24         inq[s] = true;
25     }
26
27     while (!q.empty()) {
28         int u = q.front();
29         q.pop();
30         inq[u] = false;
31         if (rlx[u] >= n) {
32             negCycle[u] = true;
33         } else
34             for (auto& e : g[u]) {
35                 int v = e.first;
36                 ll w = e.second;
37                 if (dis[v] > dis[u] + w) {
38                     dis[v] = dis[u] + w;
39                     rlx[v] = rlx[u] + 1;
40                     pa[v] = u;
41                     if (!inq[v]) {
42                         q.push(v);
43                         inq[v] = true;
44                     }
45                 }
46             }
47     }
48 }
49
50 // Bellman-Ford
51 queue<int> q;
52 vector<int> pa;
53 void BellmanFord(vector<int>& src) {
54     dis.assign(n + 1, LINF);
55     negCycle.assign(n + 1, false);
56     pa.assign(n + 1, -1);
57
58     for (auto& s : src) dis[s] = 0;
59
60     for (int rlx = 1; rlx <= n; rlx++) {
61         for (int u = 1; u <= n; u++) {
62             if (dis[u] == LINF) continue; // Important
63             for (auto& e : g[u]) {
64                 int v = e.first;
65                 ll w = e.second;
66                 if (dis[v] > dis[u] + w) {
67                     dis[v] = dis[u] + w;
68                     pa[v] = u;
69                     if (rlx == n) negCycle[v] = true;
70                 }
71             }
72         }
73     }
74 }
75
76 // Negative Cycle Detection
77 void NegCycleDetect() {
78     /* No Neg Cycle: NO
79     Exist Any Neg Cycle:
80     YES
81     v0 v1 v2 ... vk v0 */
82
83     vector<int> src;
84     for (int i = 1; i <= n; i++)
85         src.emplace_back(i);
86
87     SPFA(src);
88     // BellmanFord(src);
89
90     int ptr = -1;
91     for (int i = 1; i <= n; i++)
92         if (negCycle[i]) {
93             ptr = i;
94             break;
95         }
96
97     if (ptr == -1) {
98         return cout << "NO" << endl, void();

```

```

99     }
100
101     cout << "YES\n";
102     vector<int> ans;
103     vector<bool> vis(n + 1, false);
104
105     while (true) {
106         ans.emplace_back(ptr);
107         if (vis[ptr]) break;
108         vis[ptr] = true;
109         ptr = pa[ptr];
110     }
111     reverse(ans.begin(), ans.end());
112
113     vis.assign(n + 1, false);
114     for (auto& x : ans) {
115         cout << x << ' ';
116         if (vis[x]) break;
117         vis[x] = true;
118     }
119     cout << endl;
120 }
121
122 // Distance Calculation
123 void calcDis(int s) {
124     vector<int> src;
125     src.emplace_back(s);
126     SPFA(src);
127     // BellmanFord(src);
128
129     while (!q.empty()) q.pop();
130     for (int i = 1; i <= n; i++)
131         if (negCycle[i]) q.push(i);
132
133     while (!q.empty()) {
134         int u = q.front();
135         q.pop();
136         for (auto& e : g[u]) {
137             int v = e.first;
138             if (!negCycle[v]) {
139                 q.push(v);
140                 negCycle[v] = true;
141             }
142         }
143     }
144 }

```

5.4 BCC - AP

```

1  int n, m;
2  int low[maxn], dfn[maxn], instp;
3  vector<int> E, g[maxn];
4  bitset<maxn> isap;
5  bitset<maxn> vis;
6  stack<int> stk;
7  int bccnt;
8  vector<int> bcc[maxn];
9  inline void popout(int u) {
10     bccnt++;
11     bcc[bccnt].emplace_back(u);
12     while (!stk.empty()) {
13         int v = stk.top();
14         if (u == v) break;
15         stk.pop();
16         bcc[bccnt].emplace_back(v);
17     }
18 }
19 void dfs(int u, bool rt = 0) {
20     stk.push(u);
21     low[u] = dfn[u] = ++instp;
22     int kid = 0;
23     Each(e, g[u]) {
24         if (vis[e]) continue;
25         vis[e] = true;
26         int v = E[e] ^ u;
27         if (!dfn[v]) {
28             // tree edge
29             kid++;
30             dfs(v);
31             low[u] = min(low[u], low[v]);
32             if (!rt && low[v] >= dfn[u]) {
33                 // bcc found: u is ap

```

```

34         isap[u] = true;
35         popout(u);
36     }
37     } else {
38         // back edge
39         low[u] = min(low[u], dfn[v]);
40     }
41 }
42 // special case: root
43 if (rt) {
44     if (kid > 1) isap[u] = true;
45     popout(u);
46 }
47 }
48 void init() {
49     cin >> n >> m;
50     fill(low, low + maxn, INF);
51     REP(i, m) {
52         int u, v;
53         cin >> u >> v;
54         g[u].emplace_back(i);
55         g[v].emplace_back(i);
56         E.emplace_back(u ^ v);
57     }
58 }
59 void solve() {
60     FOR(i, 1, n + 1, 1) {
61         if (!dfn[i]) dfs(i, true);
62     }
63     vector<int> ans;
64     int cnt = 0;
65     FOR(i, 1, n + 1, 1) {
66         if (isap[i]) cnt++, ans.emplace_back(i);
67     }
68     cout << cnt << endl;
69     Each(i, ans) cout << i << ' ';
70     cout << endl;
71 }

```

5.5 BCC - Bridge

```

1 int n, m;
2 vector<int> g[maxn], E;
3 int low[maxn], dfn[maxn], instp;
4 int bccnt, bccid[maxn];
5 stack<int> stk;
6 bitset<maxn> vis, isbrg;
7 void init() {
8     cin >> n >> m;
9     REP(i, m) {
10         int u, v;
11         cin >> u >> v;
12         E.emplace_back(u ^ v);
13         g[u].emplace_back(i);
14         g[v].emplace_back(i);
15     }
16     fill(low, low + maxn, INF);
17 }
18 void popout(int u) {
19     bccnt++;
20     while (!stk.empty()) {
21         int v = stk.top();
22         if (v == u) break;
23         stk.pop();
24         bccid[v] = bccnt;
25     }
26 }
27 void dfs(int u) {
28     stk.push(u);
29     low[u] = dfn[u] = ++instp;
30
31     Each(e, g[u]) {
32         if (vis[e]) continue;
33         vis[e] = true;
34
35         int v = E[e] ^ u;
36         if (dfn[v]) {
37             // back edge
38             low[u] = min(low[u], dfn[v]);
39         } else {
40             // tree edge
41             dfs(v);

```

```

42         low[u] = min(low[u], low[v]);
43         if (low[v] == dfn[v]) {
44             isbrg[e] = true;
45             popout(u);
46         }
47     }
48 }
49 }
50 void solve() {
51     FOR(i, 1, n + 1, 1) {
52         if (!dfn[i]) dfs(i);
53     }
54     vector<pii> ans;
55     vis.reset();
56     FOR(u, 1, n + 1, 1) {
57         Each(e, g[u]) {
58             if (!isbrg[e] || vis[e]) continue;
59             vis[e] = true;
60             int v = E[e] ^ u;
61             ans.emplace_back(mp(u, v));
62         }
63     }
64     cout << (int)ans.size() << endl;
65     Each(e, ans) cout << e.F << ' ' << e.S << endl;
66 }

```

5.6 SCC - Tarjan

```

1 // 2-SAT
2 vector<int> E, g[maxn]; // 1~n, n+1~2n
3 int low[maxn], in[maxn], instp;
4 int sccnt, sccid[maxn];
5 stack<int> stk;
6 bitset<maxn> ins, vis;
7 int n, m;
8 void init() {
9     cin >> m >> n;
10    E.clear();
11    fill(g, g + maxn, vector<int>());
12    fill(low, low + maxn, INF);
13    memset(in, 0, sizeof(in));
14    instp = 1;
15    sccnt = 0;
16    memset(sccid, 0, sizeof(sccid));
17    ins.reset();
18    vis.reset();
19 }
20 inline int no(int u) {
21     return (u > n ? u - n : u + n);
22 }
23 int ecnt = 0;
24 inline void clause(int u, int v) {
25     E.eb(no(u) ^ v);
26     g[no(u)].eb(ecnt++);
27     E.eb(no(v) ^ u);
28     g[no(v)].eb(ecnt++);
29 }
30 void dfs(int u) {
31     in[u] = instp++;
32     low[u] = in[u];
33     stk.push(u);
34     ins[u] = true;
35
36     Each(e, g[u]) {
37         if (vis[e]) continue;
38         vis[e] = true;
39
40         int v = E[e] ^ u;
41         if (ins[v])
42             low[u] = min(low[u], in[v]);
43         else if (!in[v]) {
44             dfs(v);
45             low[u] = min(low[u], low[v]);
46         }
47     }
48     if (low[u] == in[u]) {
49         sccnt++;
50         while (!stk.empty()) {
51             int v = stk.top();
52             stk.pop();
53             ins[v] = false;
54             sccid[v] = sccnt;

```

```

55         if (u == v) break;
56     }
57 }
58 }
59 int main() {
60     init();
61     REP(i, m) {
62         char su, sv;
63         int u, v;
64         cin >> su >> u >> sv >> v;
65         if (su == '-') u = no(u);
66         if (sv == '-') v = no(v);
67         clause(u, v);
68     }
69     FOR(i, 1, 2 * n + 1, 1) {
70         if (!in[i]) dfs(i);
71     }
72     FOR(u, 1, n + 1, 1) {
73         int du = no(u);
74         if (sccid[u] == sccid[du]) {
75             return cout << "IMPOSSIBLE\n", 0;
76         }
77     }
78     FOR(u, 1, n + 1, 1) {
79         int du = no(u);
80         cout << (sccid[u] < sccid[du] ? '+' : '-') << '
81     }
82     cout << endl;
83 }

```

5.7 SCC - Kosaraju

```

1  const int N = 1e5 + 10;
2  vector<int> ed[N], ed_b[N]; // 反邊
3  vector<int> SCC(N); // 最後SCC的分組
4  bitset<N> vis;
5  int SCC_cnt;
6  int n, m;
7  vector<int> pre; // 後序遍歷
8
9  void dfs(int x) {
10     vis[x] = 1;
11     for (int i : ed[x]) {
12         if (vis[i]) continue;
13         dfs(i);
14     }
15     pre.push_back(x);
16 }
17
18 void dfs2(int x) {
19     vis[x] = 1;
20     SCC[x] = SCC_cnt;
21     for (int i : ed_b[x]) {
22         if (vis[i]) continue;
23         dfs2(i);
24     }
25 }
26
27 void kosaraju() {
28     for (int i = 1; i <= n; i++) {
29         if (!vis[i]) {
30             dfs(i);
31         }
32     }
33     SCC_cnt = 0;
34     vis = 0;
35     for (int i = n - 1; i >= 0; i--) {
36         if (!vis[pre[i]]) {
37             SCC_cnt++;
38             dfs2(pre[i]);
39         }
40     }
41 }

```

5.8 Eulerian Path - Undir

```

1 // from 1 to n
2 #define gg return cout << "IMPOSSIBLE\n", void();
3
4 int n, m;

```

```

5 vector<int> g[maxn];
6 bitset<maxn> inodd;
7
8 void init() {
9     cin >> n >> m;
10    inodd.reset();
11    for (int i = 0; i < m; i++) {
12        int u, v;
13        cin >> u >> v;
14        inodd[u] = inodd[u] ^ true;
15        inodd[v] = inodd[v] ^ true;
16        g[u].emplace_back(v);
17        g[v].emplace_back(u);
18    }
19 }
20 stack<int> stk;
21 void dfs(int u) {
22     while (!g[u].empty()) {
23         int v = g[u].back();
24         g[u].pop_back();
25         dfs(v);
26     }
27     stk.push(u);
28 }

```

5.9 Eulerian Path - Dir

```

1 // from node 1 to node n
2 #define gg return cout << "IMPOSSIBLE\n", 0
3
4 int n, m;
5 vector<int> g[maxn];
6 stack<int> stk;
7 int in[maxn], out[maxn];
8
9 void init() {
10     cin >> n >> m;
11     for (int i = 0; i < m; i++) {
12         int u, v;
13         cin >> u >> v;
14         g[u].emplace_back(v);
15         out[u]++, in[v]++;
16     }
17     for (int i = 1; i <= n; i++) {
18         if (i == 1 && out[i] - in[i] != 1) gg;
19         if (i == n && in[i] - out[i] != 1) gg;
20         if (i != 1 && i != n && in[i] != out[i]) gg;
21     }
22 }
23 void dfs(int u) {
24     while (!g[u].empty()) {
25         int v = g[u].back();
26         g[u].pop_back();
27         dfs(v);
28     }
29     stk.push(u);
30 }
31 void solve() {
32     dfs(1) for (int i = 1; i <= n; i++) if ((int)g[i].
33         size()) gg;
34     while (!stk.empty()) {
35         int u = stk.top();
36         stk.pop();
37         cout << u << ' ';
38     }
39 }

```

5.10 Hamilton Path

```

1 // top down DP
2 // Be Aware Of Multiple Edges
3 int n, m;
4 ll dp[maxn][1<maxn];
5 int adj[maxn][maxn];
6
7 void init() {
8     cin >> n >> m;
9     fill(dp[0], dp[maxn-1]+(1<maxn), -1);
10 }
11
12 void DP(int i, int msk) {
13     if (dp[i][msk] != -1) return;

```

```

14     dp[i][msk] = 0;
15     REP(j, n) if (j != i && (msk & (1<<j)) && adj[j][i]) {
16         int sub = msk ^ (1<<i);
17         if (dp[j][sub] == -1) DP(j, sub);
18         dp[i][msk] += dp[j][sub] * adj[j][i];
19         if (dp[i][msk] >= MOD) dp[i][msk] %= MOD;
20     }
21 }
22
23 int main() {
24     WiwiHorz
25     init();
26
27     REP(i, m) {
28         int u, v;
29         cin >> u >> v;
30         if (u == v) continue;
31         adj[--u][--v]++;
32     }
33
34     dp[0][1] = 1;
35     FOR(i, 1, n, 1) {
36         dp[i][1] = 0;
37         dp[i][1|(1<<i)] = adj[0][i];
38     }
39     FOR(msk, 1, (1<<n), 1) {
40         if (msk == 1) continue;
41         dp[0][msk] = 0;
42     }
43
44     DP(n-1, (1<<n)-1);
45     cout << dp[n-1][(1<<n)-1] << endl;
46
47     return 0;
48 }

```

5.11 Kth Shortest Path

```

1 // time: O(|E| lg |E|+|V| lg |V|+K)
2 // memory: O(|E| lg |E|+|V|)
3 struct KSP { // 1-base
4     struct nd {
5         int u, v;
6         ll d;
7         nd(int ui = 0, int vi = 0, ll di = INF) {
8             u = ui;
9             v = vi;
10            d = di;
11        }
12    };
13    struct heap {
14        nd* edge;
15        int dep;
16        heap* chd[4];
17    };
18    static int cmp(heap* a, heap* b) { return a->edge->d > b->edge->d; }
19    struct node {
20        int v;
21        ll d;
22        heap* H;
23        nd* E;
24        node() {}
25        node(ll _d, int _v, nd* _E) {
26            d = _d;
27            v = _v;
28            E = _E;
29        }
30        node(heap* _H, ll _d) {
31            H = _H;
32            d = _d;
33        }
34        friend bool operator<(node a, node b) { return a.d > b.d; }
35    };
36    int n, k, s, t, dst[N];
37    nd* nxt[N];
38    vector<nd*> g[N], rg[N];
39    heap *nullNd, *head[N];

```

```

void init(int _n, int _k, int _s, int _t) {
    n = _n;
    k = _k;
    s = _s;
    t = _t;
    for (int i = 1; i <= n; i++) {
        g[i].clear();
        rg[i].clear();
        nxt[i] = NULL;
        head[i] = NULL;
        dst[i] = -1;
    }
}

void addEdge(int ui, int vi, ll di) {
    nd* e = new nd(ui, vi, di);
    g[ui].push_back(e);
    rg[vi].push_back(e);
}

queue<int> dfsQ;
void dijkstra() {
    while (dfsQ.size()) dfsQ.pop();
    priority_queue<node> Q;
    Q.push(node(0, t, NULL));
    while (!Q.empty()) {
        node p = Q.top();
        Q.pop();
        if (dst[p.v] != -1) continue;
        dst[p.v] = p.d;
        nxt[p.v] = p.E;
        dfsQ.push(p.v);
        for (auto e : rg[p.v]) Q.push(node(p.d + e->d, e->u, e));
    }
}

heap* merge(heap* curNd, heap* newNd) {
    if (curNd == nullNd) return newNd;
    heap* root = new heap;
    memcpy(root, curNd, sizeof(heap));
    if (newNd->edge->d < curNd->edge->d) {
        root->edge = newNd->edge;
        root->chd[2] = newNd->chd[2];
        root->chd[3] = newNd->chd[3];
        newNd->edge = curNd->edge;
        newNd->chd[2] = curNd->chd[2];
        newNd->chd[3] = curNd->chd[3];
    }
    if (root->chd[0]->dep < root->chd[1]->dep)
        root->chd[0] = merge(root->chd[0], newNd);
    else
        root->chd[1] = merge(root->chd[1], newNd);
    root->dep = max(root->chd[0]->dep, root->chd[1]->dep) + 1;
    return root;
}

vector<heap*> V;
void build() {
    nullNd = new heap;
    nullNd->dep = 0;
    nullNd->edge = new nd;
    fill(nullNd->chd, nullNd->chd + 4, nullNd);
    while (not dfsQ.empty()) {
        int u = dfsQ.front();
        dfsQ.pop();
        if (!nxt[u])
            head[u] = nullNd;
        else
            head[u] = head[nxt[u]->v];
        V.clear();
        for (auto& e : g[u]) {
            int v = e->v;
            if (dst[v] == -1) continue;
            e->d += dst[v] - dst[u];
            if (nxt[u] != e) {
                heap* p = new heap;
                fill(p->chd, p->chd + 4, nullNd);
                p->dep = 1;
                p->edge = e;
                V.push_back(p);
            }
        }
        if (V.empty()) continue;

```

```

121     make_heap(V.begin(), V.end(), cmp);
122 #define L(X) ((X << 1) + 1)
123 #define R(X) ((X << 1) + 2)
124     for (size_t i = 0; i < V.size(); i++) {
125         if (L(i) < V.size())
126             V[i]->chd[2] = V[L(i)];
127         else
128             V[i]->chd[2] = nullNd;
129         if (R(i) < V.size())
130             V[i]->chd[3] = V[R(i)];
131         else
132             V[i]->chd[3] = nullNd;
133     }
134     head[u] = merge(head[u], V.front());
135 }
136 }
137 vector<ll> ans;
138 void first_K() {
139     ans.clear();
140     priority_queue<node> Q;
141     if (dst[s] == -1) return;
142     ans.push_back(dst[s]);
143     if (head[s] != nullNd)
144         Q.push(node(head[s], dst[s] + head[s]->edge
145             ->d));
146     for (int _ = 1; _ < k and not Q.empty(); _++) {
147         node p = Q.top(), q;
148         Q.pop();
149         ans.push_back(p.d);
150         if (head[p.H->edge->v] != nullNd) {
151             q.H = head[p.H->edge->v];
152             q.d = p.d + q.H->edge->d;
153             Q.push(q);
154         }
155         for (int i = 0; i < 4; i++)
156             if (p.H->chd[i] != nullNd) {
157                 q.H = p.H->chd[i];
158                 q.d = p.d + p.H->edge->d + p.H->chd
159                     [i]->edge->d;
160                 Q.push(q);
161             }
162     }
163     void solve() { // ans[i] stores the i-th shortest
164         path
165         dijkstra();
166         build();
167         first_K(); // ans.size() might less than k
168     }
169 } solver;

```

5.12 System of Difference Constraints

```

1 vector<vector<pair<int, ll>>> G;
2 void add(int u, int v, ll w) {
3     G[u].emplace_back(make_pair(v, w));
4 }

```

- $x_u - x_v \leq c \Rightarrow \text{add}(v, u, c)$
- $x_u - x_v \geq c \Rightarrow \text{add}(u, v, -c)$
- $x_u - x_v = c \Rightarrow \text{add}(v, u, c), \text{add}(u, v, -c)$
- $x_u \geq c \Rightarrow \text{add super vertex } x_0 = 0, \text{ then } x_u - x_0 \geq c \Rightarrow \text{add}(u, 0, -c)$
- Don't forget non-negative constraints for every variable if specified implicitly.
- Interval sum \Rightarrow Use prefix sum to transform into differential constraints. Don't forget $S_{i+1} - S_i \geq 0$ if x_i needs to be non-negative.
- $\frac{x_u}{x_v} \leq c \Rightarrow \log x_u - \log x_v \leq \log c$

6 String

6.1 Aho Corasick

```

1 struct ACautomata {
2     struct Node {
3         int cnt; // 停在此節點的數量
4         Node *go[26], *fail, *dic;
5         // 子節點 fail指標 最近的模式結尾
6         Node() {
7             cnt = 0;
8             fail = 0;
9             dic = 0;
10            memset(go, 0, sizeof(go));
11        }
12    } pool[1048576], *root;
13    int nMem;
14    Node *new_Node() {
15        pool[nMem] = Node();
16        return &pool[nMem++];
17    }
18    void init() {
19        nMem = 0;
20        root = new_Node();
21    }
22    void add(const string &str) { insert(root, str, 0);
23    }
24    void insert(Node *cur, const string &str, int pos) {
25        for (int i = pos; i < str.size(); i++) {
26            if (!cur->go[str[i] - 'a'])
27                cur->go[str[i] - 'a'] = new_Node();
28            cur = cur->go[str[i] - 'a'];
29        }
30        cur->cnt++;
31    }
32    void make_fail() { // 全部 add 完做
33        queue<Node> * que;
34        que.push(root);
35        while (!que.empty()) {
36            Node *fr = que.front();
37            que.pop();
38            for (int i = 0; i < 26; i++) {
39                if (fr->go[i]) {
40                    Node *ptr = fr->fail;
41                    while (ptr && !ptr->go[i]) ptr = ptr->fail;
42                    fr->go[i]->fail = ptr = (ptr ? ptr->go[i] : root);
43                    fr->go[i]->dic = (ptr->cnt ? ptr : ptr->dic);
44                    que.push(fr->go[i]);
45                }
46            }
47        }
48    }
49    // 出現過不同string的總數
50    int query_unique(const string &text) {
51        Node* p = root;
52        int ans = 0;
53        for (char ch : text) {
54            int i = ch - 'a';
55            while (p && !p->go[i]) p = p->fail;
56            p = p ? p->go[i] : root;
57            if (p->cnt) {ans += p->cnt; p->cnt = 0;}
58            for (Node* t = p->dic; t; t = t->dic) if (t->cnt) {
59                ans += t->cnt; t->cnt = 0;
60            }
61        }
62        return ans;
63    } AC;

```

6.2 KMP

```

1 vector<int> f;
2 // 沒匹配到可以退回哪裡
3 void buildFailFunction(string &s) {
4     f.resize(s.size(), -1);
5     for (int i = 1; i < s.size(); i++) {

```

```

6   int now = f[i - 1];
7   while (now != -1 and s[now + 1] != s[i]) now =
    f[now];
8   if (s[now + 1] == s[i]) f[i] = now + 1;
9   }
10 }
11
12 void KMPmatching(string &a, string &b) {
13     for (int i = 0, now = -1; i < a.size(); i++) {
14         while (a[i] != b[now + 1] and now != -1) now =
            f[now];
15         if (a[i] == b[now + 1]) now++;
16         if (now + 1 == b.size()) {
17             cout << "found a match start at position "
                << i - now << endl;
18             now = f[now];
19         }
20     }
21 }

```

6.3 Z Value

```

1 string is, it, s;
2 // is: 被搜尋 it: 要找的
3 int n;
4 vector<int> z;
5 // 計算每個位置 i 開始的字串, 和 s 的共前綴長度
6 void init() {
7     cin >> is >> it;
8     s = it + '0' + is;
9     n = (int)s.size();
10    z.resize(n, 0);
11 }
12 void solve() {
13     int ans = 0;
14     z[0] = n;
15     for (int i = 1, l = 0, r = 0; i < n; i++) {
16         if (i <= r) z[i] = min(z[i - l], r - i + 1);
17         while (i + z[i] < n && s[z[i]] == s[i + z[i]])
18             z[i]++;
19         if (i + z[i] - 1 > r) l = i, r = i + z[i] - 1;
20         if (z[i] == (int)it.size()) ans++;
21     }
22     cout << ans << endl;
23 }

```

6.4 Manacher

```

1 // 找最長回文
2 int n;
3 string S, s;
4 vector<int> m;
5 void manacher() {
6     s.clear();
7     s.resize(2 * n + 1, '.');
8     for (int i = 0, j = 1; i < n; i++, j += 2) s[j] = S[i];
9     m.clear();
10    m.resize(2 * n + 1, 0);
11    // m[i] := max k such that s[i-k, i+k] is
        palindrome
12    int mx = 0, mxk = 0;
13    for (int i = 1; i < 2 * n + 1; i++) {
14        if (mx - (i - mx) >= 0) m[i] = min(m[mx - (i -
            mx)], mx + mxk - i);
15        while (0 <= i - m[i] - 1 && i + m[i] + 1 < 2 *
            n + 1 &&
16            s[i - m[i] - 1] == s[i + m[i] + 1]) m[i]
            ++;
17        if (i + m[i] > mx + mxk) mx = i, mxk = m[i];
18    }
19 }
20 void init() {
21     cin >> S;
22     n = (int)S.size();
23 }
24 void solve() {
25     manacher();
26     int mx = 0, ptr = 0;
27     for (int i = 0; i < 2 * n + 1; i++)
28         if (mx < m[i]) {

```

```

29         mx = m[i];
30         ptr = i;
31     }
32     for (int i = ptr - mx; i <= ptr + mx; i++)
33         if (s[i] != '.') cout << s[i];
34     cout << endl;
35 }

```

6.5 Suffix Array

```

1 #define F first
2 #define S second
3 struct SuffixArray { // don't forget s += "$";
4     int n;
5     string s;
6     vector<int> suf, lcp, rk;
7     // 後綴陣列: suf[i] = 第 i 小的後綴起點
8     // LCP 陣列: lcp[i] = suf[i] 與 suf[i-1] 的最長共同
        前綴長度
9     // rank 陣列: rk[i] = 起點在 i 的後綴的名次
10    vector<int> cnt, pos;
11    vector<pair<pair<int, int>, int>> buc[2];
12    void init(string _s) {
13        s = _s;
14        n = (int)s.size();
15        // resize(n): suf, rk, cnt, pos, lcp, buc[0~1]
16        suf.assign(n, 0);
17        rk.assign(n, 0);
18        lcp.assign(n, 0);
19        cnt.assign(n, 0);
20        pos.assign(n, 0);
21        buc[0].assign(n, {{0,0},0});
22        buc[1].assign(n, {{0,0},0});
23    }
24    void radix_sort() {
25        for (int t = {0, 1}) {
26            fill(cnt.begin(), cnt.end(), 0);
27            for (auto& i : buc[t]) cnt[(t ? i.F.F : i.F
                .S)++]++;
28            for (int i = 0; i < n; i++)
29                pos[i] = (i ? 0 : pos[i - 1] + cnt[i -
                    1]);
30            for (auto& i : buc[t])
31                buc[t ^ 1][pos[(t ? i.F.F : i.F.S)++]
                    ] = i;
32        }
33    }
34    bool fill_suf() {
35        bool end = true;
36        for (int i = 0; i < n; i++) suf[i] = buc[0][i].
            S;
37        rk[suf[0]] = 0;
38        for (int i = 1; i < n; i++) {
39            int dif = (buc[0][i].F != buc[0][i - 1].F);
40            end &= dif;
41            rk[suf[i]] = rk[suf[i - 1]] + dif;
42        }
43        return end;
44    }
45    void sa() {
46        for (int i = 0; i < n; i++)
47            buc[0][i] = make_pair(make_pair(s[i], s[i]),
                i);
48        sort(buc[0].begin(), buc[0].end());
49        if (!fill_suf()) return;
50        for (int k = 0; (1 << k) < n; k++) {
51            for (int i = 0; i < n; i++)
52                buc[0][i] = make_pair(make_pair(rk[i],
                    rk[(i + (1 << k)) % n]), i);
53            radix_sort();
54            if (!fill_suf()) return;
55        }
56    }
57    void LCP() {
58        int k = 0;
59        for (int i = 0; i < n - 1; i++) {
60            if (rk[i] == 0) continue;
61            int pi = rk[i];
62            int j = suf[pi - 1];
63            while (i + k < n && j + k < n && s[i + k]
                == s[j + k]) k++;

```



```

64         lcp[pi] = k;
65         k = max(k - 1, 0);
66     }
67 }
68 };
69 SuffixArray suffixarray;

```

6.6 Suffix Automaton

```

1 struct SAM {
2     struct State {
3         int next[26];
4         int link, len;
5         // suffix link, 指向最長真後綴所對應的狀態
6         // 該狀態代表的字串集合中的最長字串長度
7         State() : link(-1), len(0) { memset(next, -1,
8             sizeof next); }
9     };
10    vector<State> st;
11    int last;
12    vector<long long> occ; // 每個狀態的出現次數 (
13        // endpos 個數)
14    vector<int> first_bkpos; // 出現在哪裡
15    SAM(int maxlen = 0) {
16        st.reserve(2 * maxlen + 5); st.push_back(State
17            ()); last = 0;
18        occ.reserve(2 * maxlen + 5); occ.push_back(0);
19        first_bkpos.push_back(-1);
20    }
21    void extend(int c) {
22        int cur = (int)st.size();
23        st.push_back(State());
24        occ.push_back(0);
25        first_bkpos.push_back(0);
26        st[cur].len = st[last].len + 1;
27        first_bkpos[cur] = st[cur].len - 1;
28        int p = last;
29        while (p != -1 && st[p].next[c] == -1) {
30            st[p].next[c] = cur;
31            p = st[p].link;
32        }
33        if (p == -1) {
34            st[cur].link = 0;
35        } else {
36            int q = st[p].next[c];
37            if (st[p].len + 1 == st[q].len) {
38                st[cur].link = q;
39            } else {
40                int clone = (int)st.size();
41                st.push_back(st[q]);
42                first_bkpos.push_back(first_bkpos[q]);
43                occ.push_back(0);
44                st[clone].len = st[p].len + 1;
45                while (p != -1 && st[p].next[c] == q) {
46                    st[p].next[c] = clone;
47                    p = st[p].link;
48                }
49                st[q].link = st[cur].link = clone;
50            }
51        }
52        last = cur;
53        occ[cur] += 1;
54    }
55    void finalize_occ() {
56        int m = (int)st.size();
57        vector<int> order(m);
58        iota(order.begin(), order.end(), 0);
59        sort(order.begin(), order.end(), [&](int a, int
60            b){ return st[a].len > st[b].len; });
61        for (int v : order) {
62            int p = st[v].link;
63            if (p != -1) occ[p] += occ[v];
64        }
65    }
66 };

```

6.7 Minimum Rotation

```

1 // rotate(begin(s), begin(s)+minRotation(s), end(s))
2 // 找出字串的最小字典序旋轉
3 int minRotation(string s) {

```

```

4     int a = 0, n = s.size();
5     s += s;
6     for (int b = 0; b < n; b++)
7         for (int k = 0; k < n; k++) {
8             if (a + k == b || s[a + k] < s[b + k]) {
9                 b += max(0, k - 1);
10                break;
11            }
12            if (s[a + k] > s[b + k]) {
13                a = b;
14                break;
15            }
16        }
17     return a;
18 }

```

6.8 Lyndon Factorization

```

1 // Duval: 將字串唯一分解為字典序非遞增的 Lyndon 子字串
2 vector<string> duval(string const& s) {
3     int n = s.size();
4     int i = 0;
5     vector<string> factorization;
6     while (i < n) {
7         int j = i + 1, k = i;
8         while (j < n && s[k] <= s[j]) {
9             if (s[k] < s[j])
10                k = i;
11            else
12                k++;
13            j++;
14        }
15        while (i <= k) {
16            factorization.push_back(s.substr(i, j - k));
17            i += j - k;
18        }
19    }
20    return factorization; // O(n)
21 }

```

6.9 Rolling Hash

```

1 const ll C = 27;
2 inline int id(char c) { return c - 'a' + 1; }
3 struct RollingHash {
4     string s;
5     int n;
6     ll mod;
7     vector<ll> Cexp, hs;
8     RollingHash(string& _s, ll _mod) : s(_s), n((int)_s
9         .size()), mod(_mod) {
10         Cexp.assign(n, 0);
11         hs.assign(n, 0);
12         Cexp[0] = 1;
13         for (int i = 1; i < n; i++) {
14             Cexp[i] = Cexp[i - 1] * C;
15             if (Cexp[i] >= mod) Cexp[i] %= mod;
16         }
17         hs[0] = id(s[0]);
18         for (int i = 1; i < n; i++) {
19             hs[i] = hs[i - 1] * C + id(s[i]);
20             if (hs[i] >= mod) hs[i] %= mod;
21         }
22     }
23     inline ll query(int l, int r) {
24         ll res = hs[r] - (l ? hs[l - 1] * Cexp[r - l +
25             1] : 0);
26         res = (res % mod + mod) % mod;
27         return res;
28     }
29 };

```

6.10 Trie

```

1 pii a[N][26];
2
3 void build(string &s) {
4     static int idx = 0;
5     int n = s.size();
6     for (int i = 0, v = 0; i < n; i++) {

```

```

7     pii &now = a[v][s[i] - 'a'];
8     if (now.first != -1)
9         v = now.first;
10    else
11        v = now.first = ++idx;
12    if (i == n - 1)
13        now.second++;
14    }
15 }

```

7 Geometry

7.1 Basic Operations

```

1 // typedef long long T;
2 typedef long double T;
3 const long double eps = 1e-12;
4
5 short sgn(T x) {
6     if (abs(x) < eps) return 0;
7     return x < 0 ? -1 : 1;
8 }
9
10 struct Pt {
11     T x, y;
12     Pt(T _x = 0, T _y = 0) : x(_x), y(_y) {}
13     Pt operator+(Pt a) { return Pt(x + a.x, y + a.y); }
14     Pt operator-(Pt a) { return Pt(x - a.x, y - a.y); }
15     Pt operator*(T a) { return Pt(x * a, y * a); }
16     Pt operator/(T a) { return Pt(x / a, y / a); }
17     T operator*(Pt a) { return x * a.x + y * a.y; }
18     T operator^(Pt a) { return x * a.y - y * a.x; }
19     bool operator<(Pt a) { return x < a.x || (x == a.x
20         && y < a.y); }
21     // return sgn(x-a.x) < 0 || (sgn(x-a.x) == 0 && sgn
22         (y-a.y) < 0); }
23     bool operator==(Pt a) { return sgn(x - a.x) == 0 &&
24         sgn(y - a.y) == 0; }
25 };
26
27 Pt mv(Pt a, Pt b) { return b - a; }
28 T len2(Pt a) { return a * a; }
29 T dis2(Pt a, Pt b) { return len2(b - a); }
30 Pt rotate(Pt u) { return {-u.y, u.x}; }
31 Pt unit(Pt x) { return x / sqrtl(x * x); }
32 short ori(Pt a, Pt b) { return ((a ^ b) > 0) - ((a ^ b)
33     < 0); }
34 bool onseg(Pt p, Pt l1, Pt l2) {
35     Pt a = mv(p, l1), b = mv(p, l2);
36     return ((a ^ b) == 0) && ((a * b) <= 0);
37 }
38
39 inline T cross(const Pt &a, const Pt &b, const Pt &c) {
40     return (b.x - a.x) * (c.y - a.y)
41         - (b.y - a.y) * (c.x - a.x);
42 }
43
44 long double polar_angle(Pt ori, Pt pt) {
45     return atan2(pt.y - ori.y, pt.x - ori.x);
46 }
47 // slope to degree atan(Slope) * 180.0 / acos(-1.0);
48 bool argcmp(Pt u, Pt v) {
49     auto half = [](const Pt &p) {
50         return p.y > 0 || (p.y == 0 && p.x >= 0);
51     };
52     if (half(u) != half(v)) return half(u) < half(v);
53     return sgn(u ^ v) > 0;
54 }
55
56 int ori(Pt &o, Pt &a, Pt &b) {
57     return sgn((a - o) ^ (b - o));
58 }
59
60 struct Line {
61     Pt a, b;
62     Pt dir() { return b - a; }
63 };
64
65 int PtSide(Pt p, Line L) {
66     return sgn(ori(L.a, L.b, p)); // for int
67     return sgn(ori(L.a, L.b, p) / sqrt(len2(L.a - L.b))
68         );
69 }
70
71 bool PtOnSeg(Pt p, Line L) {

```

```

62     return PtSide(p, L) == 0 and sgn((p - L.a) * (p - L
63         .b)) <= 0;
64 }
65 Pt proj(Pt &p, Line &l) {
66     Pt d = l.b - l.a;
67     T d2 = len2(d);
68     if (sgn(d2) == 0) return l.a;
69     T t = ((p - l.a) * d) / d2;
70     return l.a + d * t;
71 }
72 struct Cir {
73     Pt o;
74     T r;
75 };
76 bool disjunct(Cir a, Cir b) {
77     return sgn(sqrtl(len2(a.o - b.o)) - a.r - b.r) >=
78         0;
79 }
80 bool contain(Cir a, Cir b) {
81     return sgn(a.r - b.r - sqrtl(len2(a.o - b.o))) >=
82         0;
83 }

```

7.2 Sort by Angle

```

1 int ud(Pt a) { // up or down half plane
2     if (a.y > 0) return 0;
3     if (a.y < 0) return 1;
4     return (a.x >= 0 ? 0 : 1);
5 }
6 sort(pts.begin(), pts.end(), [&](const Pt &a, const Pt &
7     b) {
8     if (ud(a) != ud(b)) return ud(a) < ud(b);
9     return (a ^ b) > 0;
10 });

```

7.3 Intersection

```

1 bool line_intersect_check(Pt p1, Pt p2, Pt q1, Pt q2) {
2     if (onseg(p1, q1, q2) || onseg(p2, q1, q2) || onseg
3         (q1, p1, p2) || onseg(q2, p1, p2)) return true;
4     Pt p = mv(p1, p2), q = mv(q1, q2);
5     return (ori(p, mv(p1, q1)) * ori(p, mv(p1, q2)) <
6         0) && (ori(q, mv(q1, p1)) * ori(q, mv(q1, p2))
7         < 0);
8 }
9 // long double
10 Pt line_intersect(Pt a1, Pt a2, Pt b1, Pt b2) {
11     Pt da = mv(a1, a2), db = mv(b1, b2);
12     T det = da ^ db;
13     if (sgn(det) == 0) { // parallel
14         // return Pt(NAN, NAN);
15     }
16     T t = ((b1 - a1) ^ db) / det;
17     return a1 + da * t;
18 }
19
20 vector<Pt> CircleInter(Cir a, Cir b) {
21     double d2 = len2(a.o - b.o), d = sqrt(d2);
22     if (d < max(a.r, b.r) - min(a.r, b.r) || d > a.r +
23         b.r) return {};
24     Pt u = (a.o + b.o) / 2 + (a.o - b.o) * ((b.r * b.r
25         - a.r * a.r) / (2 * d2));
26     double A = sqrt((a.r + b.r + d) * (a.r - b.r + d) *
27         (a.r + b.r - d) * (-a.r + b.r + d));
28     Pt v = rotate(b.o - a.o) * A / (2 * d2);
29     if (sgn(v.x) == 0 and sgn(v.y) == 0) return {u};
30     return {u - v, u + v}; // counter clockwise of a
31 }
32
33 vector<Pt> CircleLineInter(Cir c, Line l) {
34     Pt H = proj(c.o, l);
35     Pt dir = unit(l.b - l.a);
36     T h = sqrtl(len2(H - c.o));
37     if (sgn(h - c.r) > 0) return {};
38     T d = sqrtl(max((T)0, c.r * c.r - h * h));
39     if (sgn(d) == 0) return {H};
40     return {H - dir * d, H + dir * d};
41 }

```

7.4 Polygon Area

```

1 // 2 * area

```

```

2 T dbPoly_area(vector<Pt>& e) {
3     T res = 0;
4     int sz = e.size();
5     for (int i = 0; i < sz; i++) {
6         res += e[i] ^ e[(i + 1) % sz];
7     }
8     return abs(res);
9 }

```

7.5 Convex Hull

```

1 vector<Pt> convexHull(vector<Pt> pts) {
2     vector<Pt> hull;
3     sort(pts.begin(), pts.end());
4     for (int i = 0; i < 2; i++) {
5         int b = hull.size();
6         for (auto ei : pts) {
7             while (hull.size() - b >= 2 && ori(mv(hull[
8                 hull.size() - 2], hull.back()), mv(hull[
9                 hull.size() - 2], ei)) == -1) {
10                 hull.pop_back();
11             }
12             hull.emplace_back(ei);
13         }
14         hull.pop_back();
15         reverse(pts.begin(), pts.end());
16     }
17     return hull;
18 }

```

7.6 Point In Convex

```

1 bool point_in_convex(const vector<Pt> &C, Pt p, bool
2     strict = true) {
3     // only works when no three point are collinear
4     int n = C.size();
5     int a = 1, b = n - 1, r = !strict;
6     if (n == 0) return false;
7     if (n < 3) return r && onseg(p, C[0], C.back());
8     if (ori(mv(C[0], C[a]), mv(C[0], C[b])) > 0) swap(a
9         , b);
10    if (ori(mv(C[0], C[a]), mv(C[0], p)) >= r || ori(mv
11        (C[0], C[b]), mv(C[0], p)) <= -r) return false;
12    while (abs(a - b) > 1) {
13        int c = (a + b) / 2;
14        if (ori(mv(C[0], C[c]), mv(C[0], p)) > 0) b = c
15        ;
16        else a = c;
17    }
18    return ori(mv(C[a], C[b]), mv(C[a], p)) < r;
19 }

```

7.7 Point Segment Distance

```

1 double point_segment_dist(Pt q0, Pt q1, Pt p) {
2     if (q0 == q1) {
3         double dx = double(p.x - q0.x);
4         double dy = double(p.y - q0.y);
5         return sqrt(dx * dx + dy * dy);
6     }
7     T d1 = (q1 - q0) * (p - q0);
8     T d2 = (q0 - q1) * (p - q1);
9     if (d1 >= 0 && d2 >= 0) {
10         double area = fabs(double((q1 - q0) ^ (p - q0))
11             );
12         double base = sqrt(double(dis2(q0, q1)));
13         return area / base;
14     }
15     double dx0 = double(p.x - q0.x), dy0 = double(p.y -
16         q0.y);
17     double dx1 = double(p.x - q1.x), dy1 = double(p.y -
18         q1.y);
19     return min(sqrt(dx0 * dx0 + dy0 * dy0), sqrt(dx1 *
20         dx1 + dy1 * dy1));
21 }

```

7.8 Point in Polygon

```

1 short inPoly(vector<Pt>& pts, Pt p) {
2     // 0=Bound 1=In -1=Out
3     int n = pts.size();

```

```

4     for (int i = 0; i < pts.size(); i++) if (onseg(p,
5         pts[i], pts[(i + 1) % n])) return 0;
6     int cnt = 0;
7     for (int i = 0; i < pts.size(); i++) if (
8         line_intersect_check(p, Pt(p.x + 1, p.y + 2e9),
9         pts[i], pts[(i + 1) % n])) cnt ^= 1;
10    return (cnt ? 1 : -1);
11 }

```

7.9 Minimum Euclidean Distance

```

1 long long Min_Euclidean_Dist(vector<Pt> &pts) {
2     sort(pts.begin(), pts.end());
3     set<pair<long long, long long>> s;
4     s.insert({pts[0].y, pts[0].x});
5     long long l = 0, best = LLONG_MAX;
6     for (int i = 1; i < (int)pts.size(); i++) {
7         Pt now = pts[i];
8         long long lim = (long long)ceil(sqrt1((long
9             double)best));
10        while (now.x - pts[l].x > lim) {
11            s.erase({pts[l].y, pts[l].x}); l++;
12        }
13        auto low = s.lower_bound({now.y - lim,
14            LLONG_MIN});
15        auto high = s.upper_bound({now.y + lim,
16            LLONG_MAX});
17        for (auto it = low; it != high; it++) {
18            long long dy = it->first - now.y;
19            long long dx = it->second - now.x;
20            best = min(best, dx * dx + dy * dy);
21        }
22        s.insert({now.y, now.x});
23    }
24    return best;
25 }

```

7.10 Minkowski Sum

```

1 void reorder(vector<Pt> &P) {
2     rotate(P.begin(), min_element(P.begin(), P.end()),
3         [&](Pt a, Pt b) { return make_pair(a.y, a.x) <
4             make_pair(b.y, b.x); }, P.end());
5 }
6 vector<Pt> Minkowski(vector<Pt> P, vector<Pt> Q) {
7     // P, Q: convex polygon
8     reorder(P), reorder(Q);
9     int n = P.size(), m = Q.size();
10    P.push_back(P[0]), P.push_back(P[1]), Q.push_back(Q
11        [0]), Q.push_back(Q[1]);
12    vector<Pt> ans;
13    for (int i = 0, j = 0; i < n || j < m; ) {
14        ans.push_back(P[i] + Q[j]);
15        auto val = (P[i + 1] - P[i]) ^ (Q[j + 1] - Q[j]);
16        if (val >= 0) i++;
17        if (val <= 0) j++;
18    }
19    return ans;
20 }

```

7.11 Lower Concave Hull

```

1 struct Line {
2     mutable ll m, b, p;
3     bool operator<(const Line& o) const { return m < o.m;
4     }
5     bool operator<(ll x) const { return p < x; }
6 };
7 struct LineContainer : multiset<Line, less<>> {
8     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
9     const ll inf = LLONG_MAX;
10    ll div(ll a, ll b) { // floored division
11        return a / b - ((a ^ b) < 0 && a % b);
12    }
13    bool isect(iterator x, iterator y) {
14        if (y == end()) { x->p = inf; return false; }
15        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
16        else x->p = div(y->b - x->b, x->m - y->m);
17        return x->p >= y->p;
18    }
19    void add(ll m, ll b) {

```

```

19 auto z = insert({m, b, 0}), y = z++, x = y;
20 while (isect(y, z)) z = erase(z);
21 if (x != begin() && isect(--x, y)) isect(x, y =
    erase(y));
22 while ((y = x) != begin() && (--x)->p >= y->p)
23     isect(x, erase(y));
24 }
25 ll query(ll x) {
26     assert(!empty());
27     auto l = *lower_bound(x);
28     return l.m * x + l.b;
29 }
30 };

```

7.12 Pick's Theorem

Consider a polygon which vertices are all lattice points.

Let i = number of points inside the polygon.

Let b = number of points on the boundary of the polygon.

Then we have the following formula:

$$Area = i + \frac{b}{2} - 1$$

7.13 Rotating SweepLine

```

1 double cross(const Pt &a, const Pt &b) {
2     return a.x*b.y - a.y*b.x;
3 }
4 int rotatingCalipers(const vector<Pt>& hull) {
5     int m = hull.size();
6     if (m < 2) return 0;
7     int j = 1;
8     T maxd = 0;
9     for (int i = 0; i < m; ++i) {
10        int ni = (i + 1) % m;
11        while (abs(cross({hull[ni].x - hull[i].x, hull[
12            ni].y - hull[i].y}, {hull[(j+1)%m].x - hull
13            [i].x, hull[(j+1)%m].y - hull[i].y})) > abs(
14            cross({hull[ni].x - hull[i].x, hull[ni].y
15            - hull[i].y}, {hull[j].x - hull[i].x,
16            hull[j].y - hull[i].y}))) {
17            j = (j + 1) % m;
18        }
19        maxd = max(maxd, dis2(hull[i], hull[j]));
20        maxd = max(maxd, dis2(hull[ni], hull[j]));
21    }
22    return maxd; // TODO
23 }

```

7.14 Half Plane Intersection

```

1 bool cover(Line& L, Line& P, Line& Q) {
2     long double u = (Q.a - P.a) ^ Q.dir();
3     long double v = P.dir() ^ Q.dir();
4     long double x = P.dir().x * u + (P.a - L.a).x * v;
5     long double y = P.dir().y * u + (P.a - L.a).y * v;
6     return sgn(x * L.dir().y - y * L.dir().x) * sgn(v)
7     >= 0;
8 }
9 vector<Line> HPI(vector<Line> P) {
10    sort(P.begin(), P.end(), [&](Line& l, Line& m) {
11        if (argcmp(l.dir(), m.dir()) return true;
12        if (argcmp(m.dir(), l.dir()) return false;
13        return ori(m.a, m.b, l.a) > 0;
14    });
15    int l = 0, r = -1;
16    for (size_t i = 0; i < P.size(); ++i) {
17        if (i && !argcmp(P[i - 1].dir(), P[i].dir()))
18            continue;
19        while (l < r && cover(P[i], P[r - 1], P[r])) --r;
20        while (l < r && cover(P[i], P[l], P[l + 1])) ++l;
21        P[++r] = P[i];
22    }
23    while (l < r && cover(P[l], P[r - 1], P[r])) --r;
24    while (l < r && cover(P[r], P[l], P[l + 1])) ++l;
25 }

```

```

25 if (r - 1 <= 1 || !argcmp(P[l].dir(), P[r].dir()))
    return {};
26 if (cover(P[l + 1], P[l], P[r])) return {};
27
28 return vector<Line>(P.begin() + l, P.begin() + r +
    1);
29 }

```

7.15 Minimum Enclosing Circle

```

1 const int INF = 1e9;
2 Pt circumcenter(Pt A, Pt B, Pt C) {
3     // a1(x-A.x) + b1(y-A.y) = c1
4     // a2(x-A.x) + b2(y-A.y) = c2
5     // solve using Cramer's rule
6     T a1 = B.x - A.x, b1 = B.y - A.y, c1 = dis2(A, B) /
7     2.0;
8     T a2 = C.x - A.x, b2 = C.y - A.y, c2 = dis2(A, C) /
9     2.0;
10    T D = Pt(a1, b1) ^ Pt(a2, b2);
11    T Dx = Pt(c1, b1) ^ Pt(c2, b2);
12    T Dy = Pt(a1, c1) ^ Pt(a2, c2);
13    if (D == 0) return Pt(-INF, -INF);
14    return A + Pt(Dx / D, Dy / D);
15 }
16 Pt center;
17 T r2;
18 void minEncloseCircle(vector<Pt> pts) {
19    mt19937 gen(chrono::steady_clock::now().
20        time_since_epoch().count());
21    shuffle(pts.begin(), pts.end(), gen);
22    center = pts[0], r2 = 0;
23    for (int i = 0; i < pts.size(); ++i) {
24        if (dis2(center, pts[i]) <= r2) continue;
25        center = pts[i], r2 = 0;
26        for (int j = 0; j < i; ++j) {
27            if (dis2(center, pts[j]) <= r2) continue;
28            center = (pts[i] + pts[j]) / 2.0;
29            r2 = dis2(center, pts[i]);
30            for (int k = 0; k < j; ++k) {
31                if (dis2(center, pts[k]) <= r2)
32                    continue;
33                center = circumcenter(pts[i], pts[j],
34                    pts[k]);
35                r2 = dis2(center, pts[i]);
36            }
37        }
38    }
39 }

```

7.16 Union of Circles

```

1 // Area[i] : area covered by at least i circle
2 vector<T> CircleUnion(const vector<Cir> &C) {
3     const int n = C.size();
4     vector<T> Area(n + 1);
5     auto check = [&](int i, int j) {
6         if (!contain(C[i], C[j]))
7             return false;
8         return sgn(C[i].r - C[j].r) > 0 or (sgn(C[i].r
9             - C[j].r) == 0 and i < j);
10    };
11    struct Teve {
12        double ang; int add; Pt p;
13        bool operator<(const Teve &b) { return ang < b.
14            ang; }
15    };
16    auto ang = [&](Pt p) { return atan2(p.y, p.x); };
17    for (int i = 0; i < n; ++i) {
18        int cov = 1;
19        vector<Teve> event;
20        for (int j = 0; j < n; ++j) if (i != j) {
21            if (check(j, i)) cov++;
22            else if (!check(i, j) and !disjunct(C[i], C
23                [j])) {
24                auto I = CircleInter(C[i], C[j]);
25                assert(I.size() == 2);
26                double a1 = ang(I[0] - C[i].o), a2 =
27                    ang(I[1] - C[i].o);
28                event.push_back({a1, 1, I[0]});
29                event.push_back({a2, -1, I[1]});
30            }
31        }
32    }
33 }

```

```

26         if (a1 > a2) cov++;
27     }
28 }
29 if (event.empty()) {
30     Area[cov] += acos(-1) * C[i].r * C[i].r;
31     continue;
32 }
33 sort(event.begin(), event.end());
34 event.push_back(event[0]);
35 for (int j = 0; j + 1 < event.size(); j++) {
36     cov += event[j].add;
37     Area[cov] += (event[j].p ^ event[j + 1].p)
38         / 2.;
39     double theta = event[j + 1].ang - event[j].ang;
40     if (theta < 0) theta += 2 * acos(-1);
41     Area[cov] += (theta - sin(theta)) * C[i].r
42         * C[i].r / 2.;
43 }
44 }
45 return Area;
46 }

```

7.17 Area Of Circle Polygon

```

1 double AreaOfCirclePoly(Cir C, vector<Pt> &P) {
2     auto arg = [&](Pt p, Pt q) { return atan2(p ^ q, p
3         * q); };
4     double r2 = (double)(C.r * C.r / 2);
5     auto tri = [&](Pt p, Pt q) {
6         Pt d = q - p;
7         T a = (d * p) / (d * d);
8         T b = ((p * p) - C.r * C.r) / (d * d);
9         T det = a * a - b;
10        if (det <= 0) return (double)(arg(p, q) * r2);
11        T s = max((T)0.0L, -a - sqrtl(det));
12        T t = min((T)1.0L, -a + sqrtl(det));
13        if (t < 0 || 1 <= s) return (double)(arg(p, q)
14            * r2);
15        Pt u = p + d * s, v = p + d * t;
16        return (double)(arg(p, u) * r2 + (u ^ v) / 2 +
17            arg(v, q) * r2);
18    };
19    long double sum = 0.0L;
20    for (int i = 0; i < (int)P.size(); i++)
21        sum += tri(P[i] - C.o, P[(i + 1) % P.size()] -
22            C.o);
23    return (double)fabsl(sum);
24 }

```

7.18 3D Point

```

1 struct Pt {
2     double x, y, z;
3     Pt(double _x = 0, double _y = 0, double _z = 0): x(_x
4         ), y(_y), z(_z){}
5     Pt operator + (const Pt &o) const
6     { return Pt(x + o.x, y + o.y, z + o.z); }
7     Pt operator - (const Pt &o) const
8     { return Pt(x - o.x, y - o.y, z - o.z); }
9     Pt operator * (const double &k) const
10    { return Pt(x * k, y * k, z * k); }
11    Pt operator / (const double &k) const
12    { return Pt(x / k, y / k, z / k); }
13    double operator * (const Pt &o) const
14    { return x * o.x + y * o.y + z * o.z; }
15    Pt operator ^ (const Pt &o) const
16    { return {Pt(y * o.z - z * o.y, z * o.x - x * o.z, x
17        * o.y - y * o.x)}; }
18 };
19 double abs2(Pt o) { return o * o; }
20 double abs(Pt o) { return sqrt(abs2(o)); }
21 Pt cross3(Pt a, Pt b, Pt c)
22 { return (b - a) ^ (c - a); }
23 double area(Pt a, Pt b, Pt c)
24 { return abs(cross3(a, b, c)); }
25 double volume(Pt a, Pt b, Pt c, Pt d)
26 { return cross3(a, b, c) * (d - a); }
27 bool coplaner(Pt a, Pt b, Pt c, Pt d)
28 { return sign(volume(a, b, c, d)) == 0; }
29 Pt proj(Pt o, Pt a, Pt b, Pt c) // o proj to plane abc
30 { Pt n = cross3(a, b, c);

```

```

31     return o - n * ((o - a) * (n / abs2(n)));}
32 Pt line_plane_intersect(Pt u, Pt v, Pt a, Pt b, Pt c) {
33     // intersection of line uv and plane abc
34     Pt n = cross3(a, b, c);
35     double s = n * (u - v);
36     if (sign(s) == 0) return {-1, -1, -1}; // not found
37     return v + (u - v) * ((n * (a - v)) / s); }
38 Pt rotateAroundAxis(Pt v, Pt axis, double theta) {
39     axis = axis / abs(axis); // axis must be unit
40     // vector
41     double cosT = cos(theta);
42     double sinT = sin(theta);
43     Pt term1 = v * cosT;
44     Pt term2 = (axis ^ v) * sinT;
45     Pt term3 = axis * ((axis * v) * (1 - cosT));
46     return term1 + term2 + term3;
47 }

```

8 Number Theory

8.1 FFT

```

1 typedef complex<double> cp;
2
3 const double pi = acos(-1);
4 const int NN = 131072;
5
6 struct FastFourierTransform {
7     /*
8      * Iterative Fast Fourier Transform
9      * How this works? Look at this
10     0th recursion 0(000) 1(001) 2(010)
11     3(011) 4(100) 5(101) 6(110)
12     7(111)
13     1th recursion 0(000) 2(010) 4(100)
14     6(110) | 1(011) 3(011) 5(101)
15     7(111)
16     2th recursion 0(000) 4(100) | 2(010)
17     6(110) | 1(011) 5(101) | 3(011)
18     7(111)
19     3th recursion 0(000) | 4(100) | 2(010) |
20     6(110) | 1(011) | 5(101) | 3(011) |
21     7(111)
22     All the bits are reversed => We can save
23     the reverse of the numbers in an array!
24     */
25     int n, rev[NN];
26     cp omega[NN], iomega[NN];
27     void init(int n_) {
28         n = n_;
29         for (int i = 0; i < n; i++) {
30             // Calculate the nth roots of unity
31             omega[i] = cp(cos(2 * pi * i / n), sin(2 *
32                 pi * i / n));
33             iomega[i] = conj(omega[i]);
34         }
35         int k = __lg(n);
36         for (int i = 0; i < n; i++) {
37             int t = 0;
38             for (int j = 0; j < k; j++) {
39                 if (i & (1 << j)) t |= (1 << (k - j -
40                     1));
41             }
42             rev[i] = t;
43         }
44     }
45
46     void transform(vector<cp> &a, cp *xomega) {
47         for (int i = 0; i < n; i++)
48             if (i < rev[i]) swap(a[i], a[rev[i]]);
49         for (int len = 2; len <= n; len <= 1) {
50             int mid = len >> 1;
51             int r = n / len;
52             for (int j = 0; j < n; j += len)
53                 for (int i = 0; i < mid; i++) {
54                     cp tmp = xomega[r * i] * a[j + mid
55                         + i];
56                     a[j + mid + i] = a[j + i] - tmp;
57                     a[j + i] = a[j + i] + tmp;
58                 }
59         }
60     }
61 }

```



```

48     }
49
50     void fft(vector<cp> &a) { transform(a, omega); }
51     void ifft(vector<cp> &a) {
52         transform(a, iomega);
53         for (int i = 0; i < n; i++) a[i] /= n;
54     }
55 } FFT;
56
57 const int MAXN = 262144;
58 // (must be 2^k)
59 // 262144, 524288, 1048576, 2097152, 4194304
60 // before any usage, run pre_fft() first
61 typedef long double ld;
62 typedef complex<ld> cplx; // real(), imag()
63 const ld PI = acos(-1);
64 const cplx I(0, 1);
65 cplx omega[MAXN + 1];
66 void pre_fft() {
67     for (int i = 0; i <= MAXN; i++) {
68         omega[i] = exp(i * 2 * PI / MAXN * I);
69     }
70 }
71 // n must be 2^k
72 void fft(int n, cplx a[], bool inv = false) {
73     int basic = MAXN / n;
74     int theta = basic;
75     for (int m = n; m >= 2; m >>= 1) {
76         int mh = m >> 1;
77         for (int i = 0; i < mh; i++) {
78             cplx w = omega[inv ? MAXN - (i * theta %
79                 MAXN) : i * theta % MAXN];
80             for (int j = i; j < n; j += m) {
81                 int k = j + mh;
82                 cplx x = a[j] - a[k];
83                 a[j] += a[k];
84                 a[k] = w * x;
85             }
86             theta = (theta * 2) % MAXN;
87         }
88         int i = 0;
89         for (int j = 1; j < n - 1; j++) {
90             for (int k = n >> 1; k > (i ^= k); k >>= 1);
91             if (j < i) swap(a[i], a[j]);
92         }
93         if (inv) {
94             for (i = 0; i < n; i++) a[i] /= n;
95         }
96     }
97     cplx arr[MAXN + 1];
98     inline void mul(int _n, long long a[], int _m, long
99         long b[], long long ans[]) {
100         int n = 1, sum = _n + _m - 1;
101         while (n < sum) n <<= 1;
102         for (int i = 0; i < n; i++) {
103             double x = (i < _n ? a[i] : 0), y = (i < _m ? b
104                 [i] : 0);
105             arr[i] = complex<double>(x + y, x - y);
106         }
107         fft(n, arr);
108         for (int i = 0; i < n; i++) arr[i] = arr[i] * arr[i
109             ];
110         fft(n, arr, true);
111         for (int i = 0; i < sum; i++) ans[i] = (long long
112             int)(arr[i].real() / 4 + 0.5);
113     }
114 }
115
116 long long a[MAXN];
117 long long b[MAXN];
118 long long ans[MAXN];
119 int a_length;
120 int b_length;

```

8.2 Pollard's rho

```

1 ll add(ll x, ll y, ll p) {
2     return (x + y) % p;
3 }
4 ll qMul(ll x, ll y, ll mod) {
5     ll ret = x * y - (ll)((long double)x / mod * y) *
    mod;

```

```

6     return ret < 0 ? ret + mod : ret;
7 }
8 ll f(ll x, ll mod) { return add(qMul(x, x, mod), 1, mod
    ); }
9 ll pollard_rho(ll n) {
10     if (!(n & 1)) return 2;
11     while (true) {
12         ll y = 2, x = rand() % (n - 1) + 1, res = 1;
13         for (int sz = 2; res == 1; sz *= 2) {
14             for (int i = 0; i < sz && res <= 1; i++) {
15                 x = f(x, n);
16                 res = __gcd(llabs(x - y), n);
17             }
18             y = x;
19         }
20         if (res != 0 && res != n) return res;
21     }
22 }
23 vector<ll> ret;
24 void fact(ll x) {
25     if (miller_rabin(x)) {
26         ret.push_back(x);
27         return;
28     }
29     ll f = pollard_rho(x);
30     fact(f);
31     fact(x / f);
32 }

```

8.3 Miller Rabin

```

1 // n < 4,759,123,141      3 : 2, 7, 61
2 // n < 1,122,004,669,633  4 : 2, 13, 23, 1662803
3 // n < 3,474,749,660,383  6 : pimes <= 13
4 // n < 2^64              7 :
5 // 2, 325, 9375, 28178, 450775, 9780504, 1795265022
6 bool witness(ll a, ll n, ll u, int t) {
7     if (!(a % n)) return 0;
8     ll x = mypow(a, u, n);
9     for (int i = 0; i < t; i++) {
10         ll nx = mul(x, x, n);
11         if (nx == 1 && x != 1 && x != n - 1) return 1;
12         x = nx;
13     }
14     return x != 1;
15 }
16 bool miller_rabin(ll n, int s = 100) {
17     // iterate s times of witness on n
18     // return 1 if prime, 0 otherwise
19     if (n < 2) return 0;
20     if (!(n & 1)) return n == 2;
21     ll u = n - 1;
22     int t = 0;
23     while (!(u & 1)) u >>= 1, t++;
24     while (s--) {
25         ll a = randll() % (n - 1) + 1;
26         if (witness(a, n, u, t)) return 0;
27     }
28     return 1;
29 }

```

8.4 Fast Power

Note: $a^n \equiv a^{(n \bmod (p-1))} \pmod{p}$

8.5 Extend GCD

```

1 ll GCD;
2 pll extgcd(ll a, ll b) {
3     if (b == 0) {
4         GCD = a;
5         return pll{1, 0};
6     }
7     pll ans = extgcd(b, a % b);
8     return pll{ans.S, ans.F - a / b * ans.S};
9 }
10 pll bezout(ll a, ll b, ll c) {
11     bool negx = (a < 0), negy = (b < 0);
12     pll ans = extgcd(abs(a), abs(b));
13     if (c % GCD != 0) return pll{-LLINF, -LLINF};
14     return pll{ans.F * c / GCD * (negx ? -1 : 1),
15         ans.S * c / GCD * (negy ? -1 : 1)};

```



```

16 }
17 ll inv(ll a, ll p) {
18     if (p == 1) return -1;
19     pll ans = bezout(a % p, -p, 1);
20     if (ans == pll{-LLINF, -LLINF}) return -1;
21     return (ans.F % p + p) % p;
22 }

```

8.6 Mu + Phi

```

1 const int maxn = 1e6 + 5;
2 ll f[maxn];
3 vector<int> lpf, prime;
4 void build() {
5     lpf.clear();
6     lpf.resize(maxn, 1);
7     prime.clear();
8     f[1] = ...; /* mu[1] = 1, phi[1] = 1 */
9     for (int i = 2; i < maxn; i++) {
10         if (lpf[i] == 1) {
11             lpf[i] = i;
12             prime.emplace_back(i);
13             f[i] = ...; /* mu[i] = 1, phi[i] = i-1 */
14         }
15         for (auto& j : prime) {
16             if (i * j >= maxn) break;
17             lpf[i * j] = j;
18             if (i % j == 0)
19                 f[i * j] = ...; /* 0, phi[i]*j */
20             else
21                 f[i * j] = ...; /* -mu[i], phi[i]*phi[j] */
22             if (j >= lpf[i]) break;
23         }
24     }
25 }

```

8.7 Discrete Log

```

1 long long mod_pow(long long a, long long e, long long p) {
2     long long r = 1 % p;
3     while(e) {
4         if (e & 1) r = (__int128)r * a % p;
5         a = (__int128)a * a % p;
6         e >>= 1;
7     }
8     return r;
9 }
10 long long mod_inv(long long a, long long p) {
11     return mod_pow((a%p+p)%p, p-2, p);
12 }
13 // BSGS: solve a^x = y (mod p), gcd(a,p)=1, p prime,
14 // return minimal x>=0, or -1 if no solution
15 long long bsgs(long long a, long long y, long long p) {
16     a%=p; y%=p;
17     if (y==1%p) return 0; // x=0
18     long long m = (long long)ceil(sqrt((long double)p));
19     // baby steps: a^j
20     unordered_map<long long, long long> table;
21     table.reserve(m*2);
22     long long cur = 1%p;
23     for (long long j=0; j<m; ++j) {
24         if (!table.count(cur)) table[cur]=j;
25         cur = (__int128)cur * a % p;
26     }
27     long long am = mod_pow(a, m, p);
28     long long am_inv = mod_inv(am, p);
29     long long gamma = y % p;
30     for (long long i=0; i<m; ++i) {
31         auto it = table.find(gamma);
32         if (it != table.end()) {
33             long long x = i*m + it->second;
34             return x;
35         }
36         gamma = (__int128)gamma * am_inv % p;
37     }
38     return -1;
39 }

```

8.8 sqrt mod

```

1 // the Jacobi symbol is a generalization of the
2 // Legendre symbol,
3 // such that the bottom doesn't need to be prime.
4 // (n/p) -> same as legendre
5 // (n/ab) = (n/a)(n/b)
6 // work with long long
7 int Jacobi(int a, int m) {
8     int s = 1;
9     for (; m > 1; ) {
10         a %= m;
11         if (a == 0) return 0;
12         const int r = __builtin_ctz(a);
13         if ((r & 1) && ((m + 2) & 4)) s = -s;
14         a >>= r;
15         if (a & m & 2) s = -s;
16         swap(a, m);
17     }
18     return s;
19 }
20 // solve x^2 = a (mod p)
21 // 0: a == 0
22 // -1: a isn't a quad res of p
23 // else: return X with X^2 % p == a
24 // doesn't work with long long
25 int QuadraticResidue(int a, int p) {
26     if (p == 2) return a & 1;
27     if (int jc = Jacobi(a, p); jc <= 0) return jc;
28     int b, d;
29     for (; ; ) {
30         b = rand() % p;
31         d = (1LL * b * b + p - a) % p;
32         if (Jacobi(d, p) == -1) break;
33     }
34     int f0 = b, f1 = 1, g0 = 1, g1 = 0, tmp;
35     for (int e = (1LL + p) >> 1; e; e >>= 1) {
36         if (e & 1) {
37             tmp = (1LL * g0 * f0 + 1LL * d * (1LL * g1
38                 * f1 % p)) % p;
39             g1 = (1LL * g0 * f1 + 1LL * g1 * f0) % p;
40             f0 = tmp;
41             g0 = tmp;
42         }
43         tmp = (1LL * f0 * f0 + 1LL * d * (1LL * f1 * f1
44             % p)) % p;
45         f1 = (2LL * f0 * f1) % p;
46         f0 = tmp;
47     }
48     return g0;
49 }

```

8.9 Primitive Root

```

1 unsigned long long primitiveRoot(ull p) {
2     auto fac = factor(p - 1);
3     sort(all(fac));
4     fac.erase(unique(all(fac)), fac.end());
5     auto test = [p, fac](ull x) {
6         for (ull d : fac)
7             if (modpow(x, (p - 1) / d, p) == 1)
8                 return false;
9         return true;
10    };
11    uniform_int_distribution<unsigned long long> unif
12        (1, p - 1);
13    unsigned long long root;
14    while (!test(root = unif(rng)));
15    return root;
16 }

```

8.10 LinearSieve

```

1 const int C = 1e7 + 2;
2 int mo[C], lp[C], phi[C], isp[C];
3 vector<int> prime;
4 void sieve() {
5     mo[1] = phi[1] = 1;
6     for (int i = 1; i < C; i++) lp[i] = 1;
7     for (int i = 2; i < C; i++) {
8         if (lp[i] == 1) {
9             lp[i] = i;
10            prime.push_back(i);

```

```

11     isp[i] = 1;
12     mo[i] = -1;
13     phi[i] = i - 1;
14 }
15 for(int p : prime) {
16     if(i * p >= C) break;
17     lp[i * p] = p;
18     if(i % p == 0) {
19         phi[p * i] = phi[i] * p;
20         break;
21     }
22     phi[i * p] = phi[i] * (p - 1);
23     mo[i * p] = mo[i] * mo[p];
24 }
25 }
26 }

```

8.11 Other Formulas

- Inversion:

$$aa^{-1} \equiv 1 \pmod{m}, a^{-1} \text{ exists iff } \gcd(a, m) = 1.$$

- Linear inversion:

$$a^{-1} \equiv (m - \lfloor \frac{m}{a} \rfloor) \times (m \bmod a)^{-1} \pmod{m}$$

- Fermat's little theorem:

$$a^p \equiv a \pmod{p} \text{ if } p \text{ is prime.}$$

- Euler function:

$$\phi(n) = n \prod_{p|n} \frac{p-1}{p}$$

- Euler theorem:

$$a^{\phi(n)} \equiv 1 \pmod{n} \text{ if } \gcd(a, n) = 1.$$

- Extended Euclidean algorithm:

$$ax + by = \gcd(a, b) = \gcd(b, a \bmod b) = \gcd(b, a - \lfloor \frac{a}{b} \rfloor b) = bx_1 + (a - \lfloor \frac{a}{b} \rfloor b)y_1 = ay_1 + b(x_1 - \lfloor \frac{a}{b} \rfloor y_1)$$

- Divisor function:

$$\sigma_x(n) = \sum_{d|n} d^x, n = \prod_{i=1}^r p_i^{a_i}.$$

$$\sigma_x(n) = \prod_{i=1}^r \frac{p_i^{(a_i+1)x} - 1}{p_i^x - 1} \text{ if } x \neq 0. \sigma_0(n) = \prod_{i=1}^r (a_i + 1).$$

- Chinese remainder theorem (Coprime Moduli):

$$x \equiv a_i \pmod{m_i}.$$

$$M = \prod m_i, M_i = M/m_i, t_i = M_i^{-1}.$$

$$x = kM + \sum a_i t_i M_i, k \in \mathbb{Z}.$$

- Chinese remainder theorem:

$$x \equiv a_1 \pmod{m_1}, x \equiv a_2 \pmod{m_2} \Rightarrow x = m_1 p + a_1 = m_2 q + a_2 \Rightarrow m_1 p - m_2 q = a_2 - a_1$$

Solve for (p, q) using ExtGCD.

$$x \equiv m_1 p + a_1 \equiv m_2 q + a_2 \pmod{\text{lcm}(m_1, m_2)}$$

- Avoiding Overflow: $ca \bmod cb = c(a \bmod b)$

- Dirichlet Convolution: $(f * g)(n) = \sum_{d|n} f(n)g(n/d)$

- Important Multiplicative Functions + Properties:

$$1. \epsilon(n) = [n = 1]$$

$$2. 1(n) = 1$$

$$3. id(n) = n$$

$$4. \mu(n) = 0 \text{ if } n \text{ has squared prime factor}$$

$$5. \mu(n) = (-1)^k \text{ if } n = p_1 p_2 \cdots p_k$$

$$6. \epsilon = \mu * 1$$

$$7. \phi = \mu * id$$

$$8. [n = 1] = \sum_{d|n} \mu(d)$$

$$9. [gcd = 1] = \sum_{d|gcd} \mu(d)$$

- Möbius inversion: $f = g * 1 \Leftrightarrow g = f * \mu$

8.12 Polynomial

```

1  const int maxk = 20;
2  const int maxn = 1<<maxk;
3  const ll LINF = 1e18;
4
5  /* P = r*2^k + 1
6  P          r    k    g
7  998244353      119 23   3
8  1004535809     479 21   3
9
10 P          r    k    g
11 3           1    1    2
12 5           1    2    2
13 17          1    4    3
14 97          3    5    5
15 193         3    6    5
16 257         1    8    3
17 7681        15    9   17
18 12289       3   12   11
19 40961       5   13    3
20 65537       1   16    3
21 786433      3   18   10
22 5767169     11   19    3
23 7340033     7   20    3
24 23068673    11  21    3
25 104857601   25  22    3
26 167772161   5   25    3
27 469762049   7   26    3
28 1004535809  479 21    3
29 2013265921  15  27   31
30 2281701377  17  27    3
31 3221225473  3   30    5
32 75161927681 35  31    3
33 77309411329 9   33    7
34 206158430209 3   36   22
35 2061584302081 15 37    7
36 2748779069441 5   39    3
37 6597069766657 3   41    5
38 39582418599937 9   42    5
39 79164837199873 9   43    5
40 263882790666241 15 44    7
41 1231453023109121 35 45    3
42 1337006139375617 19 46    3
43 3799912185593857 27 47    5
44 4222124650659841 15 48   19
45 7881299347898369 7   50    6
46 31525197391593473 7   52    3
47 180143985094819841 5   55    6
48 1945555039024054273 27 56    5
49 4179340454199820289 29 57    3
50 9097271247288401921 505 54    6 */
51
52 const int g = 3;
53 const ll MOD = 998244353;
54
55 ll pw(ll a, ll n) { /* fast pow */ }
56
57 #define siz(x) (int)x.size()
58
59 template<typename T>
60 vector<T>& operator+=(vector<T>& a, const vector<T>& b)
61 {
62     if (siz(a) < siz(b)) a.resize(siz(b));
63     for (int i = 0; i < min(siz(a), siz(b)); i++) {
64         a[i] += b[i];
65         a[i] -= a[i] >= MOD ? MOD : 0;
66     }
67     return a;
68 }
69
70 template<typename T>
71 vector<T>& operator-=(vector<T>& a, const vector<T>& b)
72 {
73     if (siz(a) < siz(b)) a.resize(siz(b));
74     for (int i = 0; i < min(siz(a), siz(b)); i++) {
75         a[i] -= b[i];
76         a[i] += a[i] < 0 ? MOD : 0;
77     }
78     return a;
79 }

```

```

79 template<typename T>
80 vector<T> operator-(const vector<T>& a) {
81     vector<T> ret(siz(a));
82     for (int i = 0; i < siz(a); i++) {
83         ret[i] = -a[i] < 0 ? -a[i] + MOD : -a[i];
84     }
85     return ret;
86 }
87
88 vector<ll> X, iX;
89 vector<int> rev;
90
91 void init_ntt() {
92     X.clear(); X.resize(maxn, 1); // x1 = g^((p-1)/n)
93     iX.clear(); iX.resize(maxn, 1);
94
95     ll u = pw(g, (MOD-1)/maxn);
96     ll iu = pw(u, MOD-2);
97
98     for (int i = 1; i < maxn; i++) {
99         X[i] = X[i-1] * u;
100        iX[i] = iX[i-1] * iu;
101        if (X[i] >= MOD) X[i] %= MOD;
102        if (iX[i] >= MOD) iX[i] %= MOD;
103    }
104
105    rev.clear(); rev.resize(maxn, 0);
106    for (int i = 1, hb = -1; i < maxn; i++) {
107        if (!(i & (i-1))) hb++;
108        rev[i] = rev[i ^ (1<<hb)] | (1<<(maxk-hb-1));
109    }
110
111 template<typename T>
112 void NTT(vector<T>& a, bool inv=false) {
113
114     int _n = (int)a.size();
115     int k = __lg(_n) + ((1<<__lg(_n)) != _n);
116     int n = 1<<k;
117     a.resize(n, 0);
118
119     short shift = maxk-k;
120     for (int i = 0; i < n; i++)
121         if (i > (rev[i]>>shift))
122             swap(a[i], a[rev[i]>>shift]);
123
124     for (int len = 2, half = 1, div = maxn>>1; len <= n; len<=1, half<=1, div>>=1) {
125         for (int i = 0; i < n; i += len) {
126             for (int j = 0; j < half; j++) {
127                 T u = a[i+j];
128                 T v = a[i+j+half] * (inv ? iX[j*div] : X[j*div]) % MOD;
129                 a[i+j] = (u+v >= MOD ? u+v-MOD : u+v);
130                 a[i+j+half] = (u-v < 0 ? u-v+MOD : u-v);
131             }
132         }
133
134         if (inv) {
135             T dn = pw(n, MOD-2);
136             for (auto& x : a) {
137                 x *= dn;
138                 if (x >= MOD) x %= MOD;
139             }
140         }
141     }
142
143     inline void resize(vector<T>& a) {
144         int cnt = (int)a.size();
145         for (; cnt > 0; cnt--) if (a[cnt-1]) break;
146         a.resize(max(cnt, 1));
147     }
148
149 template<typename T>
150 vector<T>& operator*=(vector<T>& a, vector<T> b) {
151     int na = (int)a.size();
152     int nb = (int)b.size();
153     a.resize(na + nb - 1, 0);
154     b.resize(na + nb - 1, 0);
155
156     NTT(a); NTT(b);
157     for (int i = 0; i < (int)a.size(); i++) {
158         a[i] *= b[i];
159         if (a[i] >= MOD) a[i] %= MOD;
160     }

```

```

158 }
159 NTT(a, true);
160
161 resize(a);
162 return a;
163 }
164
165 template<typename T>
166 void inv(vector<T>& ia, int N) {
167     vector<T> _a(move(ia));
168     ia.resize(1, pw(_a[0], MOD-2));
169     vector<T> a(1, -_a[0] + (-_a[0] < 0 ? MOD : 0));
170
171     for (int n = 1; n < N; n<=1) {
172         // n -> 2*n
173         // ia' = ia(2-a*ia);
174
175         for (int i = n; i < min(siz(_a), (n<<1)); i++)
176             a.emplace_back(-_a[i] + (-_a[i] < 0 ? MOD : 0));
177
178         vector<T> tmp = ia;
179         ia *= a;
180         ia.resize(n<<1);
181         ia[0] = ia[0] + 2 >= MOD ? ia[0] + 2 - MOD : ia[0] + 2;
182         ia *= tmp;
183         ia.resize(n<<1);
184     }
185     ia.resize(N);
186 }
187
188 template<typename T>
189 void mod(vector<T>& a, vector<T>& b) {
190     int n = (int)a.size()-1, m = (int)b.size()-1;
191     if (n < m) return;
192
193     vector<T> ra = a, rb = b;
194     reverse(ra.begin(), ra.end()); ra.resize(min(n+1, n-m+1));
195     reverse(rb.begin(), rb.end()); rb.resize(min(m+1, n-m+1));
196
197     inv(rb, n-m+1);
198
199     vector<T> q = move(ra);
200     q *= rb;
201     q.resize(n-m+1);
202     reverse(q.begin(), q.end());
203
204     q *= b;
205     a -= q;
206     resize(a);
207 }
208
209 /* Kitamasa Method (Fast Linear Recurrence):
210 Find a[K] (Given a[j] = c[0]a[j-N] + ... + c[N-1]a[j-1])
211 Let B(x) = x^N - c[N-1]x^(N-1) - ... - c[1]x^1 - c[0]
212 Let R(x) = x^K mod B(x) (get x^K using fast pow and use poly mod to get R(x))
213 Let r[i] = the coefficient of x^i in R(x)
214 => a[K] = a[0]r[0] + a[1]r[1] + ... + a[N-1]r[N-1] */

```

9 Linear Algebra

9.1 Gaussian-Jordan Elimination

```

1 int n;
2 vector<vector<ll>> v;
3 void gauss(vector<vector<ll>>& v) {
4     int r = 0;
5     for (int i = 0; i < n; i++) {
6         bool ok = false;
7         for (int j = r; j < n; j++) {
8             if (v[j][i] != 0) continue;
9             swap(v[j], v[r]);
10            ok = true;
11            break;
12        }
13        if (!ok) continue;

```

```

14     ll div = inv(v[r][i]);
15     for (int j = 0; j < n + 1; j++) {
16         v[r][j] *= div;
17         if (v[r][j] >= MOD) v[r][j] %= MOD;
18     }
19     for (int j = 0; j < n; j++) {
20         if (j == r) continue;
21         ll t = v[j][i];
22         for (int k = 0; k < n + 1; k++) {
23             v[j][k] -= v[r][k] * t % MOD;
24             if (v[j][k] < 0) v[j][k] += MOD;
25         }
26     }
27     r++;
28 }
29 }

```

9.2 Determinant

1. Use GJ Elimination, if there's any row consists of only 0, then $\det = 0$, otherwise $\det = \text{product of diagonal elements}$.
2. Properties of \det :
 - Transpose: Unchanged
 - Row Operation 1 - Swap 2 rows: $-\det$
 - Row Operation 2 - $k\vec{r}_i$: $k \times \det$
 - Row Operation 3 - $k\vec{r}_i$ add to \vec{r}_j : Unchanged

10 Combinatorics

10.1 Catalan Number

$$C_0 = 1, C_n = \sum_{i=0}^{n-1} C_i C_{n-1-i}, C_n = C_n^{2n} - C_{n-1}^{2n}$$

| | | | | |
|----|--------|--------|---------|---------|
| 0 | 1 | 1 | 2 | 5 |
| 4 | 14 | 42 | 132 | 429 |
| 8 | 1430 | 4862 | 16796 | 58786 |
| 12 | 208012 | 742900 | 2674440 | 9694845 |

10.2 Burnside's Lemma

Let X be the original set.

Let G be the group of operations acting on X .

Let X^g be the set of x not affected by g .

Let X/G be the set of orbits.

Then the following equation holds:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$

