

youtube-spam-v1

April 24, 2019

V1: + All models uses the TfidfVectorizer to do the the preprocessing

```
In [1]: import numpy as np
import pandas as pd
import matplotlib as mpl
import matplotlib.pyplot as plt
import seaborn as sns
import string
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.model_selection import train_test_split
from nltk.corpus import stopwords
from sklearn.preprocessing import LabelEncoder
%matplotlib inline

In [2]: # Dataset from https://archive.ics.uci.edu/ml/datasets/YouTube+Spam+Collection#
df1 = pd.read_csv("../data/UCI-YouTube-Spam-Collection/Youtube01-Psy.csv")

In [3]: df1.head()
```

Out [3]:

	COMMENT_ID	AUTHOR	\
0	LZQPQhLyRh80UYxNuaDWhIGQYNQ96IuCg-AYWqNPjpU	Julius NM	
1	LZQPQhLyRh_C2cTtd9MvFRJedxydaVW-2sNg5Diuo4A	adam riyati	
2	LZQPQhLyRh9MSZYnf8djyk0gEF9BHDPYrrK-qCczIY8	Evgeny Murashkin	
3	z13jhp0bxqncu512g22wvzkasxmvvzjaz04	ElNino Melendez	
4	z13fwbwp1oujthgqj04chlngpvzmtt3r3dw	GsMega	

	DATE	CONTENT	\
0	2013-11-07T06:20:48	Huh, anyway check out this you[tube] channel: ...	
1	2013-11-07T12:37:15	Hey guys check out my new channel and our firs...	
2	2013-11-08T17:34:21	just for test I have to say murdev.com	
3	2013-11-09T08:28:43	me shaking my sexy ass on my channel enjoy ^_^	
4	2013-11-10T16:05:38	watch?v=vtaRGgvGtWQ Check this out .	

	CLASS
0	1
1	1
2	1
3	1
4	1

```
In [4]: # Load all our dataset to merge them
df2 = pd.read_csv("../data/UCI-YouTube-Spam-Collection/Youtube02-KatyPerry.csv")
df3 = pd.read_csv("../data/UCI-YouTube-Spam-Collection/Youtube03-LMFAO.csv")
df4 = pd.read_csv("../data/UCI-YouTube-Spam-Collection/Youtube04-Eminem.csv")
df5 = pd.read_csv("../data/UCI-YouTube-Spam-Collection/Youtube05-Shakira.csv")
```

```
In [5]: frames = [df1,df2,df3,df4,df5]
```

```
In [6]: # Merging or Concatenating our DF
df_merged = pd.concat(frames)
```

```
In [7]: df_merged.head()
```

```
Out[7]:
```

	COMMENT_ID	AUTHOR \
0	LZQPQhLyRh80UYxNuaDWhIGQYNQ96IuCg-AYWqNPjpU	Julius NM
1	LZQPQhLyRh_C2cTtd9MvFRJedxydaVW-2sNg5Diuo4A	adam riyati
2	LZQPQhLyRh9MSZYnf8djykOgEF9BHDPYrrK-qCczIY8	Evgeny Murashkin
3	z13jhp0bxqncu512g22wvzkasxmvvzjaz04	ElNino Melendez
4	z13fbwbp1oujthgqj04chlngpvzmtt3r3dw	GsMega

	DATE	CONTENT \
0	2013-11-07T06:20:48	Huh, anyway check out this you[tube] channel: ...
1	2013-11-07T12:37:15	Hey guys check out my new channel and our firs...
2	2013-11-08T17:34:21	just for test I have to say murdev.com
3	2013-11-09T08:28:43	me shaking my sexy ass on my channel enjoy ^_^
4	2013-11-10T16:05:38	watch?v=vtaRGgvGtWQ Check this out .

	CLASS
0	1
1	1
2	1
3	1
4	1

```
In [8]: # Total Size
df_merged.shape
```

```
Out[8]: (1956, 5)
```

Now let's create new feature "message length" and plot it to see if it's of any interest

```
In [9]: # Save and Write Merged Data to csv
df_merged.to_csv("../data/youtube-spam-merged.csv")
```

```
In [10]: df = df_merged
```

Data Cleaning

```
In [11]: # Check for missing nan
df.isnull().isnull().sum()
```

```
Out[11]: COMMENT_ID    0
         AUTHOR        0
         DATE          0
         CONTENT       0
         CLASS         0
         dtype: int64
```

Now drop “COMMENT_ID”, ‘AUTHOR’, ‘DATE’, columns and rename CLASS and CONTENT to “label” and “content”

```
In [12]: ytb = df[["CONTENT", "CLASS"]]
         ytb = df.rename(columns = {'CONTENT': 'content', 'CLASS': 'label'})
```

Let’s look into our data

```
In [13]: ytb.groupby('label').describe()
```

```
Out[13]:
```

	AUTHOR			COMMENT_ID			
	count	unique		top freq	count	unique	
label							
0	951	922	5000palo	7	951	950	
1	1005	871	M.E.S	8	1005	1003	

			DATE				
			top freq	count	unique		
label							
0	_2viQ_Qnc68fX3dYsfYuM-m4ELMJvxOQBmBOFHqG0k0	2	951	950			
1	LneaDw26bFuH6iFsSrlJLJIX3qD4R8-emuZ-aGUj0o	2	760	760			

			content				
			top freq	count	unique		
label							
0	2013-10-05T00:57:25.078000	2	951	919			
1	2013-10-12T09:13:19.285000	1	1005	841			

			top freq				
label							
0			Like	4			
1	Check out this video on YouTube:			97			

Now let’s create new feature “message length” and plot it to see if it’s of any interest

```
In [14]: ytb['length'] = ytb['content'].apply(len)
         ytb['label'] = ytb['label'].apply(lambda x: 'spam' if x==1 else 'ham')
         ytb.head()
```

```
Out[14]:
```

	COMMENT_ID		AUTHOR	
0	LZQPQhLyRh80UYxNuaDWhIGQYNQ96IuCg-AYWqNPjpU		Julius NM	

```

1 LZQPQhLyRh_C2cTtd9MvFRJedxydaVW-2sNg5Diuo4A      adam riyati
2 LZQPQhLyRh9MSZYnf8djyk0gEF9BHPYrrK-qCczIY8      Evgeny Murashkin
3      z13jhp0bxqncu512g22wvzkasxmvvzjaz04      ElNino Melendez
4      z13fwbwp1oujthgqj04chlngpvzmtt3r3dw      GsMega

      DATE      content \
0 2013-11-07T06:20:48 Huh, anyway check out this you[tube] channel: ...
1 2013-11-07T12:37:15 Hey guys check out my new channel and our firs...
2 2013-11-08T17:34:21      just for test I have to say murdev.com
3 2013-11-09T08:28:43 me shaking my sexy ass on my channel enjoy ^_^
4 2013-11-10T16:05:38      watch?v=vtaRGgvGtWQ Check this out .


label length
0 spam      56
1 spam     166
2 spam      38
3 spam      48
4 spam      39

```

```

In [15]: mpl.rcParams['patch.force_edgecolor'] = True
plt.style.use('seaborn-bright')
ytb.hist(column='length', by='label', bins=50,figsize=(11,5))
plt.savefig("../img/ytb-length-distribution.eps")
plt.show()

```



0.0.1 Text processing and vectorizing our meddages

Let's create new data frame. We'll need a copy later on

```

In [16]: text_feat = ytb['content'].copy()

```

Now define our text preprocessing function. It will remove any punctuation and stopwords aswell.

```
In [17]: # def text_process(text):

        #     text = text.translate(str.maketrans('', '', string.punctuation))
        #     text = [word for word in text.split() if word.lower() not in stopwords.words('e

        #     return " ".join(text)

In [18]: # text_feat = text_feat.apply(text_process)

In [19]: vectorizer = TfidfVectorizer("english")

In [20]: features = vectorizer.fit_transform(text_feat)

In [21]: labels = LabelEncoder().fit_transform(ytb['label'])
        labels = labels.reshape(-1,1)

In [22]: text_feat.shape

Out[22]: (1956,)
```

```
In [23]: features.shape

Out[23]: (1956, 4454)
```

0.0.2 Classifiers and predictions

First of all let's split our features to test and train set

Now let's import bunch of classifiers, initialize them and make a dictionary to iterate through

```
In [24]: from sklearn.linear_model import LogisticRegression
        from sklearn.svm import SVC
        from sklearn.naive_bayes import MultinomialNB
        from sklearn.tree import DecisionTreeClassifier
        from sklearn.neighbors import KNeighborsClassifier
        from sklearn.ensemble import RandomForestClassifier
        from sklearn.ensemble import AdaBoostClassifier
        from sklearn.ensemble import BaggingClassifier
        from sklearn.ensemble import ExtraTreesClassifier
        from sklearn.metrics import precision_score
        from sklearn.metrics import recall_score
        from sklearn.metrics import accuracy_score
        from sklearn.metrics import f1_score

/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/sklearn/ensemble/weight_boosting.py:2
from numpy.core.umath_tests import inner1d
```

```

In [25]: svc = SVC(kernel='sigmoid', gamma=1.0)
         knc = KNeighborsClassifier()
         mnb = MultinomialNB()
         dtc = DecisionTreeClassifier(random_state=111)
         lrc = LogisticRegression(solver='liblinear', penalty='l1')
         rfc = RandomForestClassifier(n_estimators=500, random_state=111)
         abc = AdaBoostClassifier(random_state=111)
         bc = BaggingClassifier(random_state=111)
         etc = ExtraTreesClassifier(random_state=111)

In [26]: features_train, features_test, labels_train, labels_test = train_test_split(features,

In [27]: clfs = {'SVC' : svc, 'KN' : knc, 'NB': mnb, 'DT': dtc, 'LR': lrc, 'RF': rfc, 'AdaBoost'

```

Let's make functions to fit our classifiers and make predictions

```

In [28]: def train_classifier(clf, feature_train, labels_train):
         clf.fit(feature_train, labels_train)

In [29]: def predict_labels(clf, features):
         return (clf.predict(features))

```

Now iterate through classifiers and save the results

```

In [30]: import time

In [31]: pred_scores = []
         for k,v in clfs.items():
             since = time.time()

             train_classifier(v, features_train, labels_train)
             time_elapsed = time.time() - since

             pred = predict_labels(v, features_test)
             pred_scores.append((k, [precision_score(labels_test, pred), recall_score(labels_test, pred)]))

/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/sklearn/utils/validation.py:578: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/ipykernel/__main__.py:2: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
from ipykernel import kernelapp as app
/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/ipykernel/__main__.py:2: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
from ipykernel import kernelapp as app
/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/sklearn/utils/validation.py:578: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/sklearn/utils/validation.py:578: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
/Users/alex/anaconda/envs/gc/lib/python3.6/site-packages/ipykernel/__main__.py:2: DataConversionWarning: A column-vector y was passed when a 1d array was expected. Please change the shape of y to (n_samples, ), for example using y = column_or_1d(y, warn=True)
from ipykernel import kernelapp as app

```


```
In [32]: # pred_scores
```

```
In [33]: df = pd.DataFrame.from_items(pred_scores,orient='index', columns=['Precision', 'Recall', 'Accuracy', 'F1', 'Training Time (s)'])
df
```

```
Out[33]:
```

	Precision	Recall	Accuracy	F1	Training Time (s)
SVC	0.958621	0.920530	0.938671	0.939189	0m 0.1041s
KN	0.988095	0.274834	0.625213	0.430052	0m 0.0017s
NB	0.907937	0.947020	0.923339	0.927066	0m 0.0018s
DT	0.958763	0.923841	0.940375	0.940978	0m 0.0450s
LR	0.953405	0.880795	0.916525	0.915663	0m 0.0081s
RF	0.979021	0.927152	0.952300	0.952381	0m 3.5051s
AdaBoost	0.941980	0.913907	0.926746	0.927731	0m 0.4922s
BgC	0.972222	0.927152	0.948893	0.949153	0m 0.2403s
ETC	0.944828	0.907285	0.925043	0.925676	0m 0.1329s

```
In [34]: df.plot(kind='bar', y="Accuracy", ylim=(0.3,1.0), figsize=(11,6), align='center', col=0)
plt.xticks(np.arange(9), df.index)
plt.ylabel('Accuracy Score')
plt.title('Distribution by Classifier')
plt.legend(bbox_to_anchor=(1.05, 1), loc=2, borderaxespad=0.)
plt.savefig("../img/ytb-acc-basemodel-v1.eps")
plt.show()
```



0.0.3 RNN

Define the RNN structure.

```
In [35]: from keras.models import Model
        from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
        from keras.optimizers import RMSprop
        from keras.preprocessing.text import Tokenizer
        from keras.preprocessing import sequence
        from keras.utils import to_categorical
        from keras.callbacks import EarlyStopping
        from keras.callbacks import Callback
```

Using TensorFlow backend.

```
In [36]: max_words = features_train.shape[0]
        max_len = features_train.shape[1]
```

```
In [37]: def RNN():
        inputs = Input(name='inputs', shape=[max_len])
        layer = Embedding(max_words, 50, input_length=max_len)(inputs)
        layer = LSTM(100)(layer)
        layer = Dense(256, name='FC1')(layer)
        layer = Activation('relu')(layer)
        layer = Dropout(0.1)(layer)
        layer = Dense(1, name='out_layer')(layer)
        layer = Activation('sigmoid')(layer)
        model = Model(inputs=inputs, outputs=layer)
        return model
```

```
In [38]: model = RNN()
        model.summary()
        model.compile(loss='binary_crossentropy', optimizer=RMSprop(), metrics=['accuracy'])
```

Layer (type)	Output Shape	Param #
inputs (InputLayer)	(None, 4454)	0
embedding_1 (Embedding)	(None, 4454, 50)	68450
lstm_1 (LSTM)	(None, 100)	60400
FC1 (Dense)	(None, 256)	25856
activation_1 (Activation)	(None, 256)	0
dropout_1 (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_2 (Activation)	(None, 1)	0


```
=====
Total params: 154,963
Trainable params: 154,963
Non-trainable params: 0
-----
```

```
In [39]: since = time.time()

        model.fit(features_train, labels_train, epochs=10, batch_size=128, validation_split=0.1,
                  callbacks=[EarlyStopping(monitor='val_loss', min_delta=0.0001)])

        time_elapsed = time.time() - since

Train on 1095 samples, validate on 274 samples
Epoch 1/10
1095/1095 [=====] - 98s 90ms/step - loss: 0.6941 - acc: 0.4721 - val_loss: 0.6941 - val_acc: 0.4721
Epoch 2/10
1095/1095 [=====] - 78s 71ms/step - loss: 0.6934 - acc: 0.5032 - val_loss: 0.6934 - val_acc: 0.5032
```

```
In [40]: print('Training complete in {:.0f}m {:.4f}s'.format(
            time_elapsed // 60, time_elapsed % 60))
```

Training complete in 2m 56.7070s

```
In [41]: pred = (np.asarray(model.predict(features_test, batch_size=128))).round()
```

```
In [42]: pred_scores.append(("LSTM", [precision_score(labels_test, pred), recall_score(labels_test, pred)]))
```

0.0.4 gcForest

```
In [43]: import sys
        sys.path.append("..")
        from gcforest.gcforest import GCForest
        from gcforest.utils.config_utils import load_json
```

```
In [44]: def get_toy_config():
        config = {}
        ca_config = {}
        ca_config["random_state"] = 111
        ca_config["max_layers"] = 20
        ca_config["early_stopping_rounds"] = 3
        ca_config["n_classes"] = 2
        ca_config["estimators"] = []
        ca_config["estimators"].append({"n_folds": 5, "type": "DecisionTreeClassifier"})
        ca_config["estimators"].append({"n_folds": 5, "type": "MultinomialNB"})
        ca_config["estimators"].append({"n_folds": 5, "type": "LogisticRegression"})
        config["cascade"] = ca_config
        return config
```

```

In [45]: config = get_toy_config()
         gc = GCForest(config)

         # features_train ndarraylabels_train (n_samples, )(n_samples, 1)
         features_gc_train = features_train.toarray()
         labels_gc_train = labels_train.reshape(-1)

         since = time.time()
         gc.fit_transform(features_gc_train, labels_gc_train)

         time_elapsed = time.time() - since

[ 2019-04-24 11:55:18,299] [cascade_classifier.fit_transform] X_groups_train.shape=[(1369, 4454)
[ 2019-04-24 11:55:18,349] [cascade_classifier.fit_transform] group_dims=[4454]
[ 2019-04-24 11:55:18,350] [cascade_classifier.fit_transform] group_starts=[0]
[ 2019-04-24 11:55:18,351] [cascade_classifier.fit_transform] group_ends=[4454]
[ 2019-04-24 11:55:18,353] [cascade_classifier.fit_transform] X_train.shape=(1369, 4454),X_test
[ 2019-04-24 11:55:18,394] [cascade_classifier.fit_transform] [layer=0] look_indexs=[0], X_cur_t
[ 2019-04-24 11:55:18,783] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:19,107] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:19,340] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:19,696] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:20,094] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:20,095] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_0 - 5_
[ 2019-04-24 11:55:20,134] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,160] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,203] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,249] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,277] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,279] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_1 - 5_
[ 2019-04-24 11:55:20,349] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,376] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,415] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,450] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,480] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,481] [kfold_wrapper.log_eval_metrics] Accuracy(layer_0 - estimator_2 - 5_
[ 2019-04-24 11:55:20,482] [cascade_classifier.calc_accuracy] Accuracy(layer_0 - train.classifi
[ 2019-04-24 11:55:20,504] [cascade_classifier.fit_transform] [layer=1] look_indexs=[0], X_cur_t
[ 2019-04-24 11:55:20,683] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:20,980] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:21,167] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:21,347] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:21,482] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:21,483] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_0 - 5_
[ 2019-04-24 11:55:21,519] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_1 - 5_
[ 2019-04-24 11:55:21,594] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_1 - 5_
[ 2019-04-24 11:55:21,641] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_1 - 5_
[ 2019-04-24 11:55:21,668] [kfold_wrapper.log_eval_metrics] Accuracy(layer_1 - estimator_1 - 5_

```

[illegible]

```

[ 2019-04-24 11:55:25,305][cascade_classifier.calc_accuracy] Accuracy(layer_3 - train.classifi
[ 2019-04-24 11:55:25,334][cascade_classifier.fit_transform] [layer=4] look_indexes=[0], X_cur_t
[ 2019-04-24 11:55:25,500][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:25,631][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:25,758][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:26,094][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:26,403][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:26,405][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_0 - 5_
[ 2019-04-24 11:55:26,429][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,497][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,542][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,607][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,672][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,673][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_1 - 5_
[ 2019-04-24 11:55:26,737][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,800][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,878][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,928][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,974][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,979][kfold_wrapper.log_eval_metrics] Accuracy(layer_4 - estimator_2 - 5_
[ 2019-04-24 11:55:26,981][cascade_classifier.calc_accuracy] Accuracy(layer_4 - train.classifi
[ 2019-04-24 11:55:26,982][cascade_classifier.fit_transform] [Result][Optimal Level Detected]

```

```

In [46]: print('Training complete in {:.0f}m {:.4f}s'.format(
           time_elapsed // 60, time_elapsed % 60))

```

Training complete in 0m 8.7054s

```

In [47]: pred = predict_labels(gc,features_test.toarray())
         pred_scores.append(("DCF", [precision_score(labels_test,pred), recall_score(labels_test,

```

```

[ 2019-04-24 11:55:27,054][cascade_classifier.transform] X_groups_test.shape=[(587, 4454)]
[ 2019-04-24 11:55:27,089][cascade_classifier.transform] group_dims=[4454]
[ 2019-04-24 11:55:27,090][cascade_classifier.transform] X_test.shape=(587, 4454)
[ 2019-04-24 11:55:27,122][cascade_classifier.transform] [layer=0] look_indexes=[0], X_cur_test
[ 2019-04-24 11:55:27,215][cascade_classifier.transform] [layer=1] look_indexes=[0], X_cur_test

```

```

In [48]: df = pd.DataFrame.from_items(pred_scores,orient='index', columns=['Precision', 'Recall',
           df

```

```


Out[48]:

```

	Precision	Recall	Accuracy	F1	Training Time (s)
SVC	0.958621	0.920530	0.938671	0.939189	0m 0.1041s
KN	0.988095	0.274834	0.625213	0.430052	0m 0.0017s
NB	0.907937	0.947020	0.923339	0.927066	0m 0.0018s
DT	0.958763	0.923841	0.940375	0.940978	0m 0.0450s
LR	0.953405	0.880795	0.916525	0.915663	0m 0.0081s

RF	0.979021	0.927152	0.952300	0.952381	0m 3.5051s
AdaBoost	0.941980	0.913907	0.926746	0.927731	0m 0.4922s
BgC	0.972222	0.927152	0.948893	0.949153	0m 0.2403s
ETC	0.944828	0.907285	0.925043	0.925676	0m 0.1329s
LSTM	0.514480	1.000000	0.514480	0.679415	2m 56.7070s
DCF	0.956522	0.947020	0.950596	0.951747	0m 8.7054s

```
In [49]: df.plot(kind='bar', y="Accuracy", ylim=(0.5,1.0), figsize=(11,6), align='center', col
plt.xticks(np.arange(11), df.index)
plt.ylabel('Accuracy Score')
plt.title('Distribution by Classifier')
plt.legend(bbox_to_anchor=(1.05, 1), loc=2, borderaxespad=0.)
plt.savefig("../img/ytb-acc-v1.eps")
plt.show()
```



```
In [50]: import pickle
# dump
with open("../pkl/ytb-gc-v1.pkl", "wb") as f:
    pickle.dump(gc, f, pickle.HIGHEST_PROTOCOL)

# # load
# with open("../pkl/2018_gc.pkl", "rb") as f:
#     gc = pickle.load(f)
```

```
In [ ]:
```