



36	Key 32x18x90	1	45		GB/T 1096-2003 A
35	Machine cover	1	Cast iron		GB/T 117
34	Optic foramen cover	1	Q235A		
33	Spur gear	1	45		
32	Optic foramen cover	1	Q235A		
31	Vent	2	Q235A		
30	Oil plug pad	2	Asbestos rubber sheet		
29	Oil plug	2	Q235A		
28	Sleeve	1	Q235A		
27	Bolt M12 x 45	6	Grade 8.8		GB/T 5785
26	Spring washer M12	16	65Mn		GB/T 93-1987
25	Taper pin A 10 x 40	1	35		
24	Screw M8	5	Grade 8.8		GB/T 831-1988
23	Key 22x14x140	1	45		GB/T 1096-2003 B
22	Bolt M12 x 110	10	Grade 8.8		GB/T 5785
21	Deep groove ball bearing	2			GB/T 276-1994 61922
20	Bearing cap	1	HT150		
19	Adjusting washer	1	08F		
18	Output shaft	1	45		
17	Bolt M6 x 30	2	Grade 8.8		GB 32.1
16	Shaft end retaining ring	1	45		
15	Spur gear	1	40Cr		
14	Key 14x6x90	1	45		GB/T 1096-2003 A
13	Intermediate shaft	1	45		
12	Stuffy cover	1	HT150		
11	Adjusting washer	2	08F		
10	Driven shaft adjusting ring	1	HT150		
9	Nut M10	16	Grade 8		GB/T 6175-2000
8	Dipstick	1	Q235A		
7	Lock washer	1	65Mn		
6	Nut M33 x1.5	1	Grade 8		GB/T 610-1988
5	Cylindrical roller bearing 2313 E	2			GB/T 283 NUP
4	Oil retaining ring	1	Q235A		
3	Input shaft	1	45		
2	Key 8x7x36	1	45		GB/T 1096-2003 A
1	Base	1	Cast iron		
Item	Description	QTY	MATL	Note	
				Exploded view	
				Two stage cylindrical spur gear reducer with lateral offset	
Material:	Change	Blocks	Revision No	Signature	YY/MY/DD
Designed	Reviewed	Standard			
Checked					
Production	Approved				
				Status	Material (Kg)
					Scale
					1:3