TraceSmith — GPU Profiling & Replay Architecture

Applications, pybind11 binding, C++17 core, GPU backends, and output formats

Dashed frame = architecture zone · Solid frame = subsystem · Box = module and responsibility

CORE LIBRARY · C++17 · continued

Replay Module

- **ReplayEngine** — core orchestrator
- **StreamScheduler** — operation order
- **OperationExecutor** — launch replay
- **DeterminismChecker** — result compare
- **FrameCapture** — RenderDoc-style

Common Module

- **Types** — TraceEvent · EventType KernelParams
- **RingBuffer** — lock-free SPSC
- **StackCapture** — libunwind
- **XRayImporter** — LLVM XRay
- **Timestamps** — ns precision
- **TraceMetadata** — DeviceInfo

Format Module

- **SBTWriter** — binary writer
- **SBTReader** — binary reader
- **.sbt** — header + events counters

Configuration

- **ProfilerConfig** — buffer · overflow
- **ReplayConfig** — mode · speed
- **StackCaptureConfig** — stack policy
- **NCCLTrackerConfig** — collective policy

GDB Module

- **RSPHandler** — GDB protocol
- **ProcessController** — ptrace / Mach
- **GPUDebugEngine** — breakpoints · replay
- **tracesmith-gdbserver** — v0.10.0

GPU BACKENDS · system interfaces

- **NVIDIA CUDA** — CUPTI SDK
- **Apple Metal** — Metal API
- **MetaX MACA** — MCPTI SDK
- **NCCL** — distributed
- **Nsight Systems** — nsys
- **mcTracer** — MetaX
- **xctrace** — Apple
- **libunwind** — host stacks
- **Perfetto SDK** — trace export