Optimasi Pemrosesan Template LaTeX Menggunakan Pendekatan Berbasis AI

Academic Support Agent

19 Pebruari 2025

Ringkasan

PENDAHULUAN
TINJAUAN PUSTAKA
[utf8]inputenc
[ngerman,english]babel fontawesome biblatex hyperref graphicx
amsmath gensymb csquotes
tikz
xcolor alertHTMLCD5C5C myblueHTML616AC5
tcolorbox most
tcbox width=auto,left=1mm,top=1mm,bottom=1mm, right=1mm,boxsep=1mm,middle=1pt
Fast typing with LaTeX Marie Musterfrau 19 Pebruari 2025

Daftar Isi

1 Introduction **1**
1.1 test 2

2 In case you need TikZ **4**

3 Tables, graphics, etc. **5**

4 Feel free to add stuff according to your own needs **5**

1 Introduction

This is a test sentence.
This is another one.

1.1 test

Powered by the LaTeX Ninja.

makes text italic, a similar but different effect is achieved with *which highlights*. Make some **bold** statements and don't forget the "quotes".

will cause a manual pagebreak. Now copy this sentence into your test document.

```
@Article{CiteKey,
author = {Max Mustermann and Marie Musterfrau},
title = {Important Findings on Fast Typing in \LaTeX{}},
journal = {The LaTeX Ninja Blog},
year = {2019},
volume = {1},
number = {3},
pages = {22--23},
url = {https://latex-ninja.com}
}
```

`\emph{}` is used for highlighting.

`some code` always looks cooler in a typewriter font. AUTHORS really love it when their names are set in small caps.

I just wanted to add that somestimes people have stuff so incredibly important *to say that they want multiple layers of highlighting possible.* Thank God, *unlike textit*, `\emph{}` is totally up for the job.

- used to note down some stuff using bullet points → very practical
- additional item

1. note down stuff in ordered form
2. use the `enumerate` environment

[](Kreismittelpunkt) at (0,0) ; [](K1) at (0,6) ; [](K2) at (4,5) ;
[] (Kreismittelpunkt) – ++(0:5cm) node[](C) – ++(0:5cm) node[](K2); [] (Kreismittelpunkt) – ++(30:4cm) node[](A) –
++(30:2cm) node[](B) – ++(30:4cm) node[](K1); [] (K2) – (K1); [fill=myblue] (K2) circle (2.5pt) node[below=0.5em]K_2;
[fill=myblue] (K1) circle (2.5pt) node[above=0.5em]K^1;
[fill=myblue] (A) circle (2.5pt) node[above=0.5em]A; [fill=myblue] (B) circle (2.5pt) node[above=0.5em]B; [fill=myblue]
(C) circle (2.5pt) node[below=0.5em]C; [] (A) – (C); [] (C) – (B); [] (B) – (K2);
(K2) at (K2); (K1) at (K1); (A) at (A); (B) at (B); (C) at (C);
[fill=myblue] (Kreismittelpunkt) circle (2.5pt) node[below=0.5em]K;


[-,draw=black!70] (K2) to[bend right=12] (K1);

Gambar 1: a sketch

2 In case you need TikZ

3 Tables, graphics, etc.

[capture=minipage,fonttitle=, enhanced jigsaw,boxsep=1mm,colback=myblue!50!white,on line,tcbox width=auto, toptitle=0mm,colframe=myblue,opacityback=0.7,nobeforeafter,title=Satz von der Winkelsumme in der euklidischen Geometrie] Liegt das Polygon in einer euklidischen Ebene, ist die Winkelsumme durch die Formel $(\mathrm{n} \cdot 180) - 360 = (n-2) \cdot 180$
gegeben, wobei n f^{o}r die Zahl der Ecken des Polygons steht.



Like shown in 1, LaTeX is really cool.[cf.][33–55]mycitation

4 Feel free to add stuff according to your own needs

Pustaka

[1] Lawrence R. **Principe**, *The Secrets of Alchemy* (Chicago 2013).

[2] Sometimes, people have extra things to say.