Optimasi Pemrosesan Template LaTeX Menggunakan Pendekatan Berbasis AI

Academic Support Agent

19 Pebruari 2025

Ringkasan

PENDAHULUAN
TINJAUAN PUSTAKA
[utf8]inputenc amsmath nd3
24.241 Pset Template Your MIT ID 19 Pebruari 2025
Here is an example derivation:
[][][][][0.7] 1$P \rightarrow Q$A 2PA 1,2Q1, 2 MP
It is produced with the following code:

```
\begin{ND}[][][][][0.7\linewidth]
    \ndl{1}{$P \rightarrow Q$}{A}
    \ndl{2}{$P$}{A}
    \ndl{1,2}{$Q$}{1, 2 MP}
\end{ND}
```

The lines of the derivation are enclosed by the `ND` environment: `\begin{ND}`...`\end{ND}`. (The `[][][][][0.7\linewidth]` part just sets the sizing of the derivation; it's optional.)
To typeset a line, use `\ndl{`lines of the assumptions`}{`sentence`}{`rule of inference`}`.
Mathmatical symbols need to be enclosed by `$`s, e.g., `$P \rightarrow Q$` for $P \rightarrow Q$.
Here are some of the symbols we'll use:

- $\neg$: `\neg`
- $\land$: `\land`
- $\lor$: `\lor`
- $\rightarrow$: `\rightarrow`
- $\forall$: `\forall`
- $\exists$: `\exists`