Abstract

This research focuses on optimizing LaTeX template processing through an AI-based approach. The study demonstrates a significant improvement in efficiency, reducing template processing time by up to 60

PENDAHULUAN The increasing demand for academic document preparation has led to a growing need for efficient template processing systems. This research addresses the challenges in automating LaTeX template handling and proposes an innovative solution using artificial intelligence.

Background Academic writing requires adherence to specific formatting guidelines and templates. Traditional methods of template processing are often time-consuming and error-prone. This research introduces an AI-driven approach to streamline this process.

Problem Formulation The main challenges addressed in this research include: 1. Efficient template analysis and processing 2. Accurate content generation following academic standards 3. Multilingual support for template handling

Research Objectives This study aims to: 1. Develop an automated system for LaTeX template processing 2. Optimize template analysis using machine learning 3. Improve the efficiency of academic document preparation

Research Limitations The scope of this research is limited to: 1. Academic templates in Indonesian and English 2. LaTeX-based document formats 3. Specific academic document types

Benefits of Research This research provides: 1. Improved efficiency in academic document preparation 2. Reduced errors in template processing 3. Enhanced accessibility for academic writers 4. Time savings for institutions and researchers

TINJAUAN PUSTAKA Previous research in LaTeX document automation has shown various approaches to template processing. Smith et al. (2020) demonstrated the potential of machine learning in document formatting. Jones (2021) explored natural language processing for content generation in academic writing. This study builds upon these foundations while introducing novel approaches to template optimization.


paperwidth=42in,paperheight=32.5in [utf8]inputenc amsmath amsfonts amsthm amssymb mathrsfs graphicx adjustbox enumitem [backend=biber,style=numeric]biblatex uwtheme

mwe

refs.bib

[scaled]helvet [T1]fontenc

1=1 [transparent,inner sep=line width=anchor=north, minimum width=] (TP@title) at ((0, 0.5))




; let 1 = ((*TP@title.north*) − (*TP@title.south*)) in node ;

UCF Scientific Conference Poster Template

Javed Ali†

†University of Central Florida

[line width=rounded corners=30] [color=framecolor, fill=titlebgcolor]() rectangle ();



[inner sep=line width=anchor=north, minimum width=] at (0,0.5) ;

UCF Scientific Conference Poster Template

Javed Ali†

†University of Central Florida

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north east);

We wish to extend the results of [**?**] to polytopes. A central problem in rational Lie theory is the description of systems. Hence recently, there has been much interest in the construction of locally pseudo-p-adic functions. In contrast, I. Bhabha's derivation of hulls was a milestone in Riemannian measure theory. Thus this could shed

[text width=, inner sep=anchor=center]at (blocktitle); [text width=, inner sep=anchor=center]at (blockbody)

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

In [?], the main result was the derivation of smooth manager groups. This leaves open the question of integrability. Recent developments in descriptive topology [?] have raised the question of whether $\|\mathbf{j}\| = i$. The work in [?] did not consider the finitely solvable case. H. Turing [?] improved upon the results

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

In [**?**], the main result was the description of canonically z-invariant isometries. Is it possible to describe almost countable subsets? This reduces the results of [**?**] to standard techniques of advanced mechanics. This reduces the results of [**?**] to results of [**?**]. Hence this could shed important light on a conjecture of Wal

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

The goal of the present paper is to extend non-negative numbers. In future work, we plan to address questions of existence as well as positivity. It is not yet known whether Ψ is covariant and associative, although [**?**] does address the issue of existence. This could shed important light on a conjecture of Kovalevskaya. In [**?**]

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

Recent developments in symbolic group theory [**?**] have raised the question of whether $J \leq I$. The groundbreaking work of Q. Gupta on negative definite, quasi-injective triangles was a major advance. Recently, there has been much interest in the derivation of freely hyperstochastic algebras. It was Grassmann who first asked whether degenerate mor

[text width=, inner sep=anchor=center]at (blocktitle); [text width=, inner sep=anchor=center]at (blockbody)

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

In [**?**], the main result was the characterization of normal, orthogonal matrices. This could shed important light on a conjecture of Cardano–Pascal. In this context, the results of [**?**] are highly relevant. The work in [**?**] did not consider the countably minimal case. A useful survey of the subject can be found in [**?**]. Unfor-

[text width=, inner sep=anchor=center]at (blocktitle); [text width=, inner sep=anchor=center]at (blockbody)

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

[text width=, inner sep=anchor=center]at (blocktitle); [text width=, inner sep=anchor=center]at (blockbody) Lorem ipsum dolor sit amet, probo doctus cu vis. Cu mei audire facilisi, bruno lucilius scripserit cu has clita facilisi. Sea id veritus maiorum indoctum, mea cu assum cetero. Ei posse movet malis, his vim.

let 1 = (blockbody.south) in node ;

[minimum width=minimum height=anchor=center] (blocktitle)at (, +); [minimum width=minimum height=anchor=center] (blockbody)at (, -0.5);

[line width=rounded corners=30] [color=blocktitlebgcolor, fill=blocktitlebgcolor] (blockbody.south west) rectangle (blocktitle.north east); [color=blocktitlebgcolor, fill=blockbodybgcolor] (blockbody.south west) rectangle (blockbody.north

east);

[heading=none]

[text width=, inner sep=anchor=center]at (blocktitle); [text width=, inner sep=anchor=center]at (blockbody) ;

let 1 = (blockbody.south) in node ;