Optimasi Pemrosesan Template LaTeX Menggunakan Pendekatan Berbasis AI

Academic Support Agent

19 Pebruari 2025

Ringkasan

PENDAHULUAN
TINJAUAN PUSTAKA
[10pt, a4paper]article [a4paper,outer=1.5cm,inner=1.5cm,top=1.75cm,bottom=1.5cm]geometry

graphicx [colorlinks,linkcolor=black,citecolor=blue!80!black,urlcolor=blue!80!black]hyperref [parfill]parskip lmodern watermark lipsum xcolor listings float titlesec amsmath algorithm2e

0pt-3pt

0pt-

0pt
escapeinside=/*@@*/, language=C++, basicstyle=, numbers=left,numbersep=2pt,xleftmargin=2pt,frame=tb, columns=fullflexible,showstringspaces=false,tabsize=4, keepspaces=true,showtabs=false,showspaces=false, backgroundcolor=white, morekeywords=inline,public, class,private,protected,struct,captionpos=t,lineskip=-0.4em, aboveskip=10pt, extendedchars=true, breaklines=true, prebreak = ↩, keywordstyle=[rgb]0,0,1, commentstyle=[rgb]0.133,0.545,0.133, stringstyle=[rgb]0.627,0.126,0.941

Coursework Report Cool Student
4008000@napier.ac.uk
Edinburgh Napier University - Advanced Web Technologies (SET09103)

Ringkasan

[2]

Keywords –

1 Introduction

Referencing You should cite References like this: [**?**]. The references are saved in an external .bib file, and will automatically be added to the bibliography at the end once cited.

Gambar 1: **ImageTitle** - Some Descriptive Text

2 Formatting

Some common formatting you may need uses these commands for **Bold Text**, *Italics*, and underlined.

2.1 LineBreaks

Here is a line

Here is a line followed by a double line break. This line is only one line break down from the above, Notice that latex can ignore this

We can force a break
with the break operator.

2.2 Maths

Embedding Maths is Latex's bread and butter

$$J = \frac{\delta e}{\delta \theta_0}\frac{\delta e}{\delta \theta_1}\frac{\delta e}{\delta \theta_2} = e_{current} - e_{target}$$

2.3 Code Listing

You can load segments of code from a file, or embed them directly.

[caption = Hello World! in c++] include <iostream>

int main() std::cout « "Hello World!" « std::endl; std::cin.get(); return 0;

2.4 PseudoCode

[h] $i = 0$ 100 print_number = true i is divisible by 3 print "Fizz" print_number = false i is divisible by 5 print "Buzz" print_number = false print_number print i print a newline FizzBuzz

3 Conclusion