Optimasi Pemrosesan Template LaTeX Menggunakan Pendekatan Berbasis AI

Academic Support Agent

19 Pebruari 2025

Ringkasan

PENDAHULUAN
TINJAUAN PUSTAKA
[framed,numbered,autolinebreaks,useliterate]mcode
url `mcode.sty` Demo Florian Knorn, `florian@knorn.org`

Usage — 3 ways

1) This inline demo for i=1:3, disp('cool'); end; uses the `\mcode{}` command.[1]

2) The following is a block using the `lstlisting` environment. for i = 1:3 if i >= 5 disp('cool'); end
[,ind] = max(vec); x$_{l}ast = x(1, end); v(end);$ *reallyreallylongreallyreallylongreallyreallylongreallyreallylongreallyrea*
Note: Here, the package was loaded with the `framed`, `numbered`, `autolinebreaks` and `useliterate` options. **Please see the top of mcode.sty for a detailed explanation of these options.**

3) Finally, you can also directly include an external m-file from somewhere on your hard drive (the very code you use in MATLAB, if you want) using the `\lstinputlisting{/SOME/PATH/FILENAME.M}` command. If you only want to include certain lines from that file (for instance to skip a header), you can use `\lstinputlisting[firstline=6, lastline=15]{/SOME/PATH/FILENAME.M}`.

Florian (`florian@knorn.org`)

[1] Works also in footnotes: for i=1:3, disp('cool'); end;

red **NOTE — BEFORE YOU START**

All that this package does is to configure the `listings` package for you. If anything is not working the way you want it, refer to the `listings` documentation first and / or take a look at the `mcode.sty` file itself, which is well documented internally.

The `listings` documentation can be accessed either by typing `texdoc listings` into a command prompt on your system, or online:
`http://mirrors.ctan.org/macros/latex/contrib/listings/listings.pdf`