Template Document

Academic Support Agent

February 19, 2025

Brazilian Review of Finance: A Template
BRF: A Template
Submitted on February 8, 2024. Revised on May 25, 2024. Accepted on June 9, 2024. Published online in January 2024. Editor in charge: Mr. Editor.
1Imaginary University 2Real Institute of Research **Author One**author.one@email 1 0000-0000-0000 **Author Two**author.two@email 2 0000-0000-0000 **Author Three**author.three@email 1 2 0000-0000-0000

1 Revista Brasileira de Finan as (Online) Rio de Janeiro, Vol. XX, No. Y, August 2024, pp. x–xx ISSN 1679-0731, ISSN online 1984-5146 ©2024 Sociedade Brasileira de Finan as, under a Creative Commons Attribution 4.0 license https://doi.org/10.xxxx/xxxxxxxx Revista Brasileira de Finan as (Online) XX(Y), 2024

Abstract

Your abstract goes here! [1-1]
Risk measures; Standard deviation.
E3, C41, C43.

1 Introduction

Below you can find a scheme of citation commands and corresponding outputs. You can also cite multiple references with a single \cite command; for instance, \citep{markowitz52, rockafellar 02, rockafellar 06} produces the output markowitz52,rockafellar02,rockafellar06. [][1-21]

\citet{markowitz52}	markowitz52
\citep[p.9]{markowitz52}	[p.9]markowitz52
\citename{markowitz52}	markowitz52
\citeyear*{markowitz52}	*markowitz52
\citeyear{markowitz52}	markowitz52

In the References section, you can make the title of a reference *clickable* by including the doi field in the references .bib file, as shown in the example below. In practice, the doi field accepts any type of web address; this can be useful when you have a reference which has no DOI but does have a permalink. Additionally, if you want to explicitly display the URL for a given reference, then just add the url field in the bib file. These possibilities are illustrated in the References section.

```
@article{rockafellar02,
title={Conditional value-at-risk for general loss distributions},
author={Rockafellar, R Tyrrell and Uryasev, Stanislav},
journal={Journal of banking \& finance},
volume={26},
number={7},
pages={1443--1471},
year={2002},
doi = {https://doi.org/10.1016/S0378-4266(02)00271-6},
}
```

1.1 Useful tools for reference managing

There are several useful tools to help organize your references. Here are some of them:

(i) https://www.mendeley.com
(ii) https://www.jabref.org
(iii) https://www.zotero.org/
(iv) https://truben.no/latex/bibtex/

2 Methodology


In this section you should discuss the methodology.[1]

2.1 Figures


Figure 1 was generated in R through the following code:

```
x = seq(from=0, to=2*pi, length=100)
cm = 1/2.54 # this is just for defining units of measurement
pdf(file='plot.pdf', width=9*cm, height=7*cm, bg=rgb(0,0,0,.1))
par(mai = c(2*cm,1*cm,.5*cm,1*cm))
plot(x, sin(x), type='l')
dev.off()
```

Figure 1: A figure



Ideally, the dimensions of the figure should be controlled *outside* of LaTeX, as the preceding R code illustrates. If you cannot generate or obtain the figure with appropriate sizing, then adding the optional argument [width=9cm] to the \ includegraphics command will do the job. Below we illustrate usage of the \ includegraphics [width=2cm]{media/plot.pdf} command.



2.2 The model

We write inline equations as $x = x$ or displayed equations as

$$\mathrm{d}X_t = \mu \mathrm{d}t + \sigma \mathrm{d}B_t \tag{1}$$

and reference equations using \eqref{eq1} to display as equation (1). Maybe we should have added this in section 1. You can also reference theorems, for example \ autoref {thm:1} will produce Equation 2.2.

We say that x **is equal to** x whenever $x = x$.

$x \geq y$ if and only if $y \leq x$. This is left as an exercise.

$x = x$ if and only if $x = x$.

If $x = x$ and $y = y$, then $x > y$ implies $x > y$.

A proof with default title.

[1] Footnote links should come after punctuation.

[A proof with custom title] This is trivial.
$x > y$ of and only if $y < x$.
This is a remark.
[2-2]

3 Results

You can add tables easily: see Table 1. There are three custom column types that accept width specification: L, C and R, which work similarly to the standard p column type; for instance, use C{4cm} for a (horizontally) centered column 4cm wide. Notice, however, that LaTeX has some inconsistencies regarding lengths, as Example 3 illustrates. Thus, some manual fine-tuning may be necessary to obtain tables with the desired width.

0.9

Table 1: A simple table

variable	value	p-value
X	1	0.0
Y	-1	0.8
You can write long texts insidetable cells, with custom linebreaks	A	B

Table descriptions go here. [1-1]

This example illustrates length inconsistencies in LaTeX.



a	b	c
x	y	z

The source code yielding the rule and table above is as follows:

```
\noindent\rule{.6\textwidth}{1cm}
\noindent\begin{tabular}{L{.2\textwidth}C{.2\textwidth}R{.2\textwidth}}
\toprule
x & y & z\tabularnewline\bottomrule
\end{tabular}
```

3.1 Some additional features

Table 2 illustrates how to align numbers by the decimal place marker. It also shows how to implement the \multirow command.

0.9

Table 2: Another simple table

variable		value		p-value.
X		1	001	0.0.
Y		-10	00	0.8.
Z	Z_1	1	1	0.
	Z_2	2	2	0.

Here are two useful tools to help formatting LaTeX tables:

(i) `https://www.tablesgenerator.com`

(ii) `https://truben.no/table/`

Acknowledgments Author One would like to thank Institution One for financial support.

Conflict of interest The authors declare no conflict of interest.

Artificial Intelligence This research utilized AI tools to assist in data analysis, manuscript drafting, and figure generation. All AI-generated content was critically reviewed and validated by the authors to ensure accuracy and alignment with the scientific integrity of the study. The use of AI adhered to ethical guidelines, ensuring transparency and compliance with academic standards. Any biases or limitations inherent to the AI tools were carefully considered in the interpretation of results. The authors affirm that the AI tools did not compromise the originality or integrity of the work.

4 Additional tables and figures

This appendix has some additional tables and figures, for example Table 4 illustrates how to generate a sideways table, and also shows how to implement the \multicolumn command. Figure 2 illustrates usage of subfigures. Panels 2a and 2b were generated in R through the following code:

```
set.seed(123)
cm = 1/2.54
x = rnorm(50)
pdf(file='plot2a.pdf', width=4*cm, height=4*cm, bg=rgb(0,0,0,.1))
```

```
par(mai = c(.5*cm,.5*cm,.5*cm,.5*cm))
plot(x, x+rnorm(50,sd=.4), pch=16, col=rgb(0,0,0,.7), bty='n', axes=FALSE, ann=FALSE)
dev.off()

pdf(file='plot2b.pdf', width=4*cm, height=4*cm, bg=rgb(0,0,0,.1))
par(mai = c(.5*cm,.5*cm,.5*cm,.5*cm))
plot(x, rnorm(50,sd=1), pch=16, col=rgb(0,0,0,.7), bty='n', axes=FALSE, ann=FALSE)
dev.off()
```

Figure 2: Adding subfigures

(a) Bivariate Normal with $\rho = 1$



(b) Bivariate Normal with $\rho = 0$



	variable	estimation outputs		
		value	t-stat.	p-value
.9	X	1	3.59	0.0
	Y	-1	-0.1	0.8
	You can write long texts insidetable cells, with custom linebreaks	A	B	C