Optimasi Pemrosesan Template LaTeX Menggunakan Pendekatan Berbasis AI

Academic Support Agent

19 Pebruari 2025

Ringkasan

PENDAHULUAN
TINJAUAN PUSTAKA
hyperref natbib fontspec times xeCJK
FandolSong AR PL UMing HK AR PL UKai HK
Writing Cantonese with XeLaTeX on Overleaf LO, Chi-kiu (Jackie)
Multilingual Text Processing
Digital Technologies Research Center
National Research Council Canada (NRC-CNRC)
1200 Montreal Road, Ottawa, ON K1A 0R6, Canada
chikiu.lo@nrc-cnrc.gc.ca June 2020

This article demonstrates how to write Cantonese characters in documents using XeLaTeX on Overleaf.

1 Introduction

The Hong Kong Supplementary Character Set (latest version HKSCS-2016 HKSCS2016) is a set of specific Cantonese characters that is not included in common traditional Chinese character set for various reasons LuCheungXiongYuXu2014. Without appropriate settings in the LaTeX document, these Cantonese characters may not be rendered properly. In this article, we show a working example on writing these characters with XeLaTex on Overleaf.

2 XeLaTeX and xeCJK

To setup an Overleaf project for Chinese document using xeCJK with XeLaTeX, we follow the example in `https://www.overleaf.com/learn/latex/Chinese`. Essentially, it includes the following two steps:

1. Click on "Menu" at the top left corner and choose "XeLaTeX" as compiler in settings.
2. Add "`\usepackage{xeCJK}`" at the beginning of the document source.

3 Fonts

The default xeCJK font on Overleaf is *FandolSong*, which covers both Simplified Chinese and Traditional Chinese glyphs but not the characters in HKSCS-2016. For example, using *FandolSong* as the CJK font, the second, fourth and the fifth character of cannot be rendered.

Lim2020 listed all the OTF/TTF fonts installed on Overleaf that can be used with fontspec in XeLaTeX. A general principle for selecting font when writing Cantonese is to use fonts specified with "HK" locality, such as *AR PL UMing HK* and *AR PL UKai HK*. As we can see below, using the two mentioned fonts, all the characters in previous example can be rendered properly.

AR PL UMing HK:

AR PL UKai HK:

To use the selected font, add "`\setCJKmainfont{<fontname>}`" at the beginning of the document source.