Template Document

Academic Support Agent

February 19, 2025

The Name of the Title is Hope

Ben Trovato Both authors contributed equally to this research. trovato@corporation.com 1234-5678-9012 G.K.M. Tobin [1] webmaster@marysville-ohio.com Institute for Clarity in Documentation P.O. Box 1212 Dublin Ohio 43017-6221

Lars Thørväld The Thørväld Group 1 Thørväld Circle Hekla Iceland larst@affiliation.org

Valerie Béranger Inria Paris-Rocquencourt Rocquencourt France

Aparna Patel Rajiv Gandhi University Rono-Hills Doimukh Arunachal Pradesh India

Huifen Chan Tsinghua University 30 Shuangqing Rd Haidian Qu Beijing Shi China

Charles Palmer Palmer Research Laboratories 8600 Datapoint Drive San Antonio Texas 78229 cpalmer@prl.com

John Smith The Thørväld Group jsmith@affiliation.org

Julius P. Kumquat The Kumquat Consortium jpkumquat@consortium.net

Abstract

A clear and well-documented LaTeX document is presented as an article formatted for publication by ACM in a conference proceedings or journal publication. Based on the "acmart" document class, this article presents and explains many of the common variations, as well as many of the formatting elements an author may use in the preparation of the documentation of their work.

<ccs2012> <concept> <concept$_i d$ > 10010520.10010553.10010562 < /concept$_i d$ >< concept$_d esc$ > $Computersystemsorganization\ Embeddedsystems$ < /concept$_d esc$ >< concept$_s ignificance$ > 500 < /concept$_s ignificance$ >< /concept >< concept >< concept$_i d$ > 10010520.10010575.10010755 < /concept$_i d$ >< concept$_d esc$ > $Computersystemsorganization\ Redundancy$ < /concept$_d esc$ >< concept$_s ignificance$ > 300 < /concept$_s ignificance$ >< /concept >< concept >< concept$_i d$ > 10010520.10010553.10010554 < /concept$_i d$ >< concept$_d esc$ > $Computersystemsorganization\ Robotics$ < /concept$_d esc$ >< concept$_s ignificance$ > 100 < /concept$_s ignificance$ >< /concept >< concept >< concept$_i d$ > 10003033.10003083.10003095 < /concept$_i d$ >< concept$_d esc$ > $Networks\ Networkreliability$ < /concept$_d esc$ >< concept$_s ignificance$ > 100 < /concept$_s ignificance$ >< /concept >< /$ccs2012$ >

[500]Computer systems organization Embedded systems [300]Computer systems organization Redundancy Computer systems organization Robotics [100]Networks Network reliability

datasets, neural networks, gaze detection, text tagging

1 Introduction

ACM's consolidated article template, introduced in 2017, provides a consistent LaTeX style for use across ACM publications, and incorporates accessibility and metadata-extraction functionality necessary for future Digital Library endeavors. Numerous ACM and SIG-specific LaTeX templates have been examined, and their unique features incorporated into this single new template.

If you are new to publishing with ACM, this document is a valuable guide to the process of preparing your work for publication. If you have published with ACM before, this document provides insight and instruction into more recent changes to the article template.

The "`acmart`" document class can be used to prepare articles for any ACM publication — conference or journal, and for any stage of publication, from review to final "camera-ready" copy, to the author's own version, with *very* few changes to the source.

2 Template Overview

As noted in the introduction, the "`acmart`" document class can be used to prepare many different kinds of documentation — a double-blind initial submission of a full-length technical paper, a two-page SIGGRAPH Emerging Technologies abstract, a "camera-ready" journal article, a SIGCHI Extended Abstract, and more — all by selecting the appropriate *template style* and *template parameters*.

This document will explain the major features of the document class. For further information, the *LaTeX User's Guide* is available from `https://www.acm.org/publications/proceedings-template`.

2.1 Template Styles

The primary parameter given to the "`acmart`" document class is the *template style* which corresponds to the kind of publication or SIG publishing the work. This parameter is enclosed in square brackets and is a part of the `documentclass` command:

```
\documentclass[STYLE]{acmart}
```

Journals use one of three template styles. All but three ACM journals use the `acmsmall` template style:

- `acmsmall`: The default journal template style.
- `acmlarge`: Used by JOCCH and TAP.
- `acmtog`: Used by TOG.

The majority of conference proceedings documentation will use the `acmconf` template style.

- `acmconf`: The default proceedings template style.
- `sigchi`: Used for SIGCHI conference articles.
- `sigchi-a`: Used for SIGCHI "Extended Abstract" articles.
- `sigplan`: Used for SIGPLAN conference articles.

2.2 Template Parameters

In addition to specifying the *template style* to be used in formatting your work, there are a number of *template parameters* which modify some part of the applied template style. A complete list of these parameters can be found in the *LaTeX User's Guide.*

Frequently-used parameters, or combinations of parameters, include:

- `anonymous,review`: Suitable for a "double-blind" conference submission. Anonymizes the work and includes line numbers. Use with the `\acmSubmissionID` command to print the submission's unique ID on each page of the work.
- `authorversion`: Produces a version of the work suitable for posting by the author.
- `screen`: Produces colored hyperlinks.

This document uses the following string as the first command in the source file:

```
\documentclass[sigchi-a]{acmart}
```

3 Modifications

Modifying the template — including but not limited to: adjusting margins, typeface sizes, line spacing, paragraph and list definitions, and the use of the `\vspace` command to manually adjust the vertical spacing between elements of your work — is not allowed.

Your document will be returned to you for revision if modifications are discovered.

4 Typefaces

The "acmart" document class requires the use of the "Libertine" typeface family. Your TEX installation should include this set of packages. Please do not substitute other typefaces. The "lmodern" and "ltimes" packages should not be used, as they will override the built-in typeface families.

5 Title Information

The title of your work should use capital letters appropriately - https://capitalizemytitle.com/ has useful rules for capitalization. Use the title command to define the title of your work. If your work has a subtitle, define it with the subtitle command. Do not insert line breaks in your title.

If your title is lengthy, you must define a short version to be used in the page headers, to prevent overlapping text. The title command has a "short title" parameter:

```
\title[short title]{full title}
```

6 Authors and Affiliations

Each author must be defined separately for accurate metadata identification. Multiple authors may share one affiliation. Authors' names should not be abbreviated; use full first names wherever possible. Include authors' e-mail addresses whenever possible.

Grouping authors' names or e-mail addresses, or providing an "e-mail alias," as shown below, is not acceptable:

```
\author{Brooke Aster, David Mehldau}
\email{dave,judy,steve@university.edu}
\email{firstname.lastname@phillips.org}
```

The authornote and authornotemark commands allow a note to apply to multiple authors — for example, if the first two authors of an article contributed equally to the work.

If your author list is lengthy, you must define a shortened version of the list of authors to be used in the page headers, to prevent overlapping text. The following command should be placed just after the last \author{} definition:

```
\renewcommand{\shortauthors}{McCartney, et al.}
```

Omitting this command will force the use of a concatenated list of all of the authors' names, which may result in overlapping text in the page headers.

The article template's documentation, available at https://www.acm.org/publications/proceedings-templat has a complete explanation of these commands and tips for their effective use.

Note that authors' addresses are mandatory for journal articles.

7 Rights Information

Authors of any work published by ACM will need to complete a rights form. Depending on the kind of work, and the rights management choice made by the author, this may be copyright transfer, permission, license, or an OA (open access) agreement.

Regardless of the rights management choice, the author will receive a copy of the completed rights form once it has been submitted. This form contains LATEX commands that must be copied into the source document. When the document source is compiled, these commands and their parameters add formatted text to several areas of the final document:

- the "ACM Reference Format" text on the first page.
- the "rights management" text on the first page.
- the conference information in the page header(s).

Rights information is unique to the work; if you are preparing several works for an event, make sure to use the correct set of commands with each of the works.

The ACM Reference Format text is required for all articles over one page in length, and is optional for one-page articles (abstracts).

Table 1: Some Typical Commands

Command	A Number	Comments
`\author`	100	Author
`\table`	300	For tables
`\table*`	400	For wider tables

8 CCS Concepts and User-Defined Keywords

Two elements of the "acmart" document class provide powerful taxonomic tools for you to help readers find your work in an online search.

The ACM Computing Classification System — `https://www.acm.org/publications/class-2012` — is a set of classifiers and concepts that describe the computing discipline. Authors can select entries from this classification system, via `https://dl.acm.org/ccs/ccs.cfm`, and generate the commands to be included in the LaTeX source.

User-defined keywords are a comma-separated list of words and phrases of the authors' choosing, providing a more flexible way of describing the research being presented.

CCS concepts and user-defined keywords are required for for all articles over two pages in length, and are optional for one- and two-page articles (or abstracts).

9 Sectioning Commands

Your work should use standard LaTeX sectioning commands: `section`, `subsection`, `subsubsection`, and `paragraph`. They should be numbered; do not remove the numbering from the commands.

Simulating a sectioning command by setting the first word or words of a paragraph in boldface or italicized text is **not allowed.**

10 Tables

The "`acmart`" document class includes the "`booktabs`" package — `https://ctan.org/pkg/booktabs` — for preparing high-quality tables.

Table captions are placed *above* the table.

Because tables cannot be split across pages, the best placement for them is typically the top of the page nearest their initial cite. To ensure this proper "floating" placement of tables, use the environment **table** to enclose the table's contents and the table caption. The contents of the table itself must go in the **tabular** environment, to be aligned properly in rows and columns, with the desired horizontal and vertical rules. Again, detailed instructions on **tabular** material are found in the *LaTeX User's Guide*.

Immediately following this sentence is the point at which Table 10 is included in the input file; compare the placement of the table here with the table in the printed output of this document.

Non-English or Math	Frequency	Comments
Ø	1 in 1,000	For Swedish names
π	1 in 5	Common in math
\$	4 in 5	Used in business
Ψ_1^2	1 in 40,000	Unexplained usage

To set a wider table, which takes up the whole width of the page's live area, use the environment **table*** to enclose the table's contents and the table caption. As with a single-column table, this wide table will "float" to a location deemed more desirable. Immediately following this sentence is the point at which Table 1 is included in the input file; again, it is instructive to compare the placement of the table here with the table in the printed output of this document.

11 Math Equations

You may want to display math equations in three distinct styles: inline, numbered or non-numbered display. Each of the three are discussed in the next sections.

11.1 Inline (In-text) Equations

A formula that appears in the running text is called an inline or in-text formula. It is produced by the **math** environment, which can be invoked with the usual `\begin ... \end` construction or with the short form `$ ... $`. You can use any of the symbols and structures, from α to ω, available in LaTeX [**?**]; this section will simply show a few examples of in-text equations in context. Notice how this equation: $\lim_{n\to\infty} x = 0$, set here in in-line math style, looks slightly different when set in display style. (See next section).

11.2 Display Equations

A numbered display equation—one set off by vertical space from the text and centered horizontally—is produced by the **equation** environment. An unnumbered display equation is produced by the **displaymath** environment.

Again, in either environment, you can use any of the symbols and structures available in LaTeX; this section will just give a couple of examples of display equations in context. First, consider the equation, shown as an inline equation above:

$$\lim_{n\to\infty} x = 0 \tag{1}$$

Notice how it is formatted somewhat differently in the **displaymath** environment. Now, we'll enter an unnumbered equation:

$$\sum_{i=0}^{\infty} x + 1$$

and follow it with another numbered equation:

$$\sum_{i=0}^{\infty} x_i = \int_0^{\pi+2} f \tag{2}$$

just to demonstrate LaTeX's able handling of numbering.

12 Figures

The "`figure`" environment should be used for figures. One or more images can be placed within a figure. If your figure contains third-party material, you must clearly identify it as such, as shown in the example below. The 1907 Franklin Model D roadster.

Your figures should contain a caption which describes the figure to the reader. Figure captions go below the figure. Your figures should **also** include a description suitable for screen readers, to assist the visually-challenged to better understand your work.

Figure captions are placed *below* the figure.

12.1 The "Teaser Figure"

A "teaser figure" is an image, or set of images in one figure, that are placed after all author and affiliation information, and before the body of the article, spanning the page. If you wish to have such a figure in your article, place the command immediately before the `\maketitle` command:

```
\begin{teaserfigure}
  \includegraphics[width=\textwidth]{sampleteaser}
  \caption{figure caption}
  \Description{figure description}
\end{teaserfigure}
```

13 Citations and Bibliographies

The use of for the preparation and formatting of one's references is strongly recommended. Authors' names should be complete — use full first names ("Donald E. Knuth") not initials ("D. E. Knuth") — and the salient identifying features of a reference should be included: title, year, volume, number, pages, article DOI, etc.

The bibliography is included in your source document with these two commands, placed just before the