

# Feedback linearization of nonlinear differential-algebraic control systems

Yahao Chen 

Bernoulli Institute for Mathematics, Computer Science, and Artificial Intelligence, University of Groningen, Groningen, The Netherlands

## Correspondence

Yahao Chen, Bernoulli Institute for Mathematics, Computer Science, and Artificial Intelligence, University of Groningen, Groningen, The Netherlands.  
Email: yahao.chen@rug.nl

## Funding information

The Dutch Research Council, Grant/Award Number: Vidi-grant 639.032.733.

## Abstract

In this article, we study feedback linearization problems for nonlinear differential-algebraic control systems (DACs). We consider two kinds of feedback equivalences, namely, external feedback equivalence, which is defined (locally) on the whole generalized state space, and internal feedback equivalence, which is defined on the locally maximal controlled invariant submanifold (i.e., on the set where solutions exist). We define a notion called explicitation with driving variables, which is a class of ordinary differential equation control systems (ODECSs) attaching to a given DACS. Then we give necessary and sufficient conditions for both internal and external feedback linearization problems of the DACS. We show that the feedback linearizability of the DACS is closely related to the involutivity of the linearizability distributions of the explicitation systems. Finally, we illustrate the results of the by an academic example and a constrained mechanical system.

## KEYWORDS

controlled invariant submanifolds, constrained mechanical system, differential-algebraic control systems, explicitation, external and internal feedback equivalence, feedback linearization

## 1 | INTRODUCTION

Consider a nonlinear differential-algebraic control system (DACs) of the form

$$\Xi^u : E(x)\dot{x} = F(x) + G(x)u, \quad (1)$$

where  $x \in X$  is called the generalized state and  $(x, \dot{x}) \in TX$ , where  $TX$  is the tangent bundle of an open subset  $X$  in  $\mathbb{R}^n$  (or, more general, of an  $n$ -dimensional smooth manifold  $X$ ), and  $u \in \mathbb{R}^m$  is the vector of inputs, and where  $E : TX \rightarrow \mathbb{R}^l$ ,  $F : X \rightarrow \mathbb{R}^l$  and  $G : X \rightarrow \mathbb{R}^{l \times m}$  are smooth maps. The word “smooth” will always mean  $C^\infty$ -smooth throughout the article. We denote a DACS of the form (1) by  $\Xi_{l,n,m}^u = (E, F, G)$  or, simply,  $\Xi^u$ . A linear DACS is of the form

$$\Delta^u : E\dot{x} = Hx + Lu, \quad (2)$$

where  $E, H \in \mathbb{R}^{l \times n}$  and  $L \in \mathbb{R}^{l \times m}$ . Denote a linear DACS by  $\Delta_{l,n,m}^u = (E, H, L)$  or, simply,  $\Delta^u$ . Linear DACSs have been studied for decades, there is a rich literature devoted to them (see, e.g., the surveys<sup>1,2</sup> and textbook<sup>3</sup>).

This is an open access article under the terms of the Creative Commons Attribution-NonCommercial License, which permits use, distribution and reproduction in any medium, provided the original work is properly cited and is not used for commercial purposes.

© 2021 The Author. *International Journal of Robust and Nonlinear Control* published by John Wiley & Sons Ltd.