


Outline

- Three steps for finding similar items
 1. Shingling: documents \rightarrow sets
 2. Min-hashing: sets \rightarrow signatures
 3. Locality-sensitive-hashing: signatures \rightarrow similarity
- Locality-Sensitive-Hashing (LSH)
- Characteristics of LSH
- Two Applications
 - Finding similar finger-prints
 - Finding similar news articles



Locality Sensitive Hashing

Step 3: *Locality-Sensitive Hashing:*


Focus on pairs of signatures likely to be from similar documents

Motivation for Locality Sensitive Hashing

- *Used **k-shingles** to create sets that summarize documents*
- *Used **Minhashing** to generate signatures that represent sets of shingles, reflect their similarity*
- **Suppose we need to find near-duplicate documents among a million 10^6 documents**
- Naïvely, we would have to compute **pairwise Jaccard similarities** for **every pair of signatures**
 - 10^6 choose 2
 - Recall: for large n , $\binom{n}{2}$ is approximately $n^2/2$
 - $\approx 5 \cdot 10^{11}$ comparisons
 - At 10^5 secs/day and 10^6 comparisons/sec, it would take **6 days**

Locality Sensitive Hashing

- *Or Near-neighbor search*
- Minhashing is one example of a **family of functions** (the minhash functions) **that can be combined** (by the banding technique) **to distinguish strongly between pairs at a low distance from pairs at a high distance**
- Steepness of the S-curve reflects how effectively we can **avoid false positives and false negatives** among the candidate pairs
- Section 3.6: more general theory of Locality Sensitive Functions



Locality Sensitive Hashing Overview

- **Hash items several times**
 - In a way that **similar items are more likely to be hashed to the same bucket than dissimilar items**
- **Candidate Pair:** Any pair that hashes to the same bucket for **any** of the hashings
- **Check only the candidate pairs for similarity**
- **False positives:** dissimilar pairs that hash to the same bucket
- **False negatives:** truly similar pairs do not hash to the same bucket for at least one of the hash functions

LSH: First Cut

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |

- **Goal:** Find documents with Jaccard similarity at least s for some similarity threshold s (e.g. $s=0.8$)
- **LSH – General idea:** Use a function $f(x,y)$ that tells whether x and y are a *candidate pair*: a pair of elements whose similarity must be evaluated
- **For Min-Hash matrix:**
 - Hash columns of *signature matrix* M to many buckets
 - Each pair of documents that hashes into the same bucket is a *candidate pair*

Candidates from Min-Hash

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |

- Pick a similarity threshold s ($0 < s < 1$)
- Columns \mathbf{x} and \mathbf{y} of \mathbf{M} are a **candidate pair** if their signatures agree on at least fraction s of their rows:
 $M(i, \mathbf{x}) = M(i, \mathbf{y})$ for at least frac. s values of i
 - We expect documents \mathbf{x} and \mathbf{y} to have the same (Jaccard) similarity as their signatures


LSH for Min-Hash

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |

- **Big idea:** Hash columns of signature matrix M several times
- Arrange that (only) **similar columns** are likely to **hash to the same bucket**, with high probability
- Candidate pairs are those that hash to the same bucket


Partition M into b Bands

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |



Partition Signatures M into Bands

- Divide matrix M into b bands of r rows
 - Signatures are still too big, so we check band by band
 - So, check “similar signatures” becomes check “similar bands”
- For each band, hash its portion of each column to a hash table with k buckets
 - Make k as large as possible
 - Use a separate bucket array for each band so columns with the same vector in different bands don’t hash to same bucket
- **Candidate column pairs** are those that hash to the same bucket for ≥ 1 band
- Tune b and r to catch most similar pairs, but few non-similar pairs



Example of Bands

Assume the following case:


- Suppose 100,000 columns of M
 - Correspond to signatures for 100,000 documents
- Signatures of 100 integers (rows)
 - Correspond to 100 hash functions used in minhashing
- 4 bytes per integer
- Therefore, signatures take 40Mb ($4 \times 100 \times 100,000$)
- Choose $b = 20$ bands of $r = 5$ rows of integers/band
- **Goal:** Find pairs of documents that are at least $s = 0.8$ or 80% similar

Recall: Minhashing Example

| | | |
|---|---|---|
| 1 | 4 | 3 |
| 3 | 2 | 4 |
| 7 | 1 | 7 |
| 6 | 3 | 6 |
| 2 | 6 | 1 |
| 5 | 7 | 2 |
| 4 | 5 | 5 |

Input matrix

| | | | |
|---|---|---|---|
| 1 | 0 | 1 | 0 |
| 1 | 0 | 0 | 1 |
| 0 | 1 | 0 | 1 |
| 0 | 1 | 0 | 1 |
| 0 | 1 | 0 | 1 |
| 1 | 0 | 1 | 0 |
| 1 | 0 | 1 | 0 |



Signature matrix M

| | | | |
|---|---|---|---|
| 2 | 1 | 2 | 1 |
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |

Analysis of Banding Technique

- Use b bands of r rows each
- **Pair of documents have Jaccard similarity t**
 - Probability that minhash signatures for the documents agree in any one particular row of the signature matrix is t
- Columns C_1 and C_2 in signature matrix have similarity t
- Pick any band (r rows)
 - Prob. that **all rows in band are equal** = t^r
 - Prob. **that not all r rows are equal** (some row in band is unequal) = $1 - t^r$
- Prob. that **no band has rows that are all equal** = $(1 - t^r)^b$
- Prob. that **at least 1 band has rows that are all equal** (which is the **probability of being a candidate pair**) = $1 - (1 - t^r)^b$

C_1, C_2 are 80% Similar

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |

- Find pairs of $\geq s=0.8$ similarity, set $b=20$, $r=5$
- **Assume:** $\text{sim}(C_1, C_2) = 0.8$
 - Since $\text{sim}(C_1, C_2) \geq s$, we want C_1, C_2 to be a **candidate pair**
 - We want them to hash to at **least 1 common bucket** (at least one band is identical)
- **Probability C_1, C_2 identical in one particular band:**
 $t^r = (0.8)^5 = 0.328$
- Probability C_1, C_2 are **not** similar in all of the 20 bands:
 $(1 - t^r)^b = (1 - 0.328)^{20} = 0.00035$
 - i.e., about .035% of the 80%-similar column pairs are **false negatives** (truly similar pairs that we miss)
 - We would find 99.965% pairs of truly similar documents

| | | | |
|---|---|---|---|
| 2 | 1 | 4 | 1 |
| 1 | 2 | 1 | 2 |
| 2 | 1 | 2 | 1 |

C_1, C_2 are 30% Similar

- Find pairs of $\geq s=0.3$ similarity, set $b=20, r=5$
- **Assume:** $\text{sim}(C_1, C_2) = 0.3$
 - Since $\text{sim}(C_1, C_2) < s$ we want C_1, C_2 to hash to **NO common buckets** (all bands should be different)
 - Should **NOT** be a candidate pair!
- **Probability C_1, C_2 identical in one particular band:** $t^r = (0.3)^5 = 0.00243$
- Will identify C_1, C_2 as candidate pair if they are **identical in at least one band**
- Probability C_1, C_2 identical in at least 1 of 20 bands: $1 - (1 - t^r)^b = 1 - (1 - 0.00243)^{20} = 0.0474$
 - Approximately 4.74% pairs of docs with similarity 0.3% end up becoming **candidate pairs**
 - They are **false positives** (dissimilar documents that must be examined as candidate pairs but will have similarity below threshold s)

LSH Involves a Tradeoff

- **Pick:**

- The number of Min-Hashes (rows of M)
- The number of bands b , and
- The number of rows r per band


to balance false positives/negatives

- **Example:** If we had only 15 bands of 5 rows, the number of false positives would go down, but the number of false negatives would go up

Example of Tradeoffs

- Previous example: 20 rows of 5 bands each
 - Probability of false negatives when C1, C2 are 80% similar: 0.00035
 - Probability of false positives when C1, C2 are 30% similar: 0.0474
- What if we use 15 rows of 5 bands each (smaller signature matrix)?
 - **Probability of false negatives higher** when C1, C2 are 80% similar:
 - $(1 - t')^b = (1 - 0.328)^{15} = 0.002573$
 - **Probability of false positives lower** when C1, C2 are 30% similar:
 - $1 - (1 - t')^b = 1 - (1 - 0.00243)^{15} = 0.0358$


Analysis of LSH – What We Want



What 1 Band (b=1) of 1 Row (r=1) Gives You


- Compare two values in similarity matrix

$$1 - (1 - t^r)^b = 1 - (1 - t^1)^1 = t$$



What b Bands of r Rows Gives You: $1 - (1 - t^r)^b$

- Form of an S-curve, regardless of values of b and r
- Threshold s is where rise of curve is steepest: approximately $(1/b)^{1/r}$



$r=5, b=20$, for $t=0.9$: $1-(1-t^r)^b=0.99999$; for $t=0.1$: 0.0000199

Example: $b = 20; r = 5$

- Similarity t of two columns
- Prob. that at least 1 band is identical (so a candidate pair):


| t | $1-(1-t^r)^b$ |
|-----|---------------|
| .2 | .006 |
| .3 | .047 |
| .4 | .186 |
| .5 | .470 |
| .6 | .802 |
| .7 | .975 |
| .8 | .9996 |

- Not an ideal step function
- Probability rises by more than 0.6 going from similarity $t = 0.4$ to $t = 0.6$
- Slope in middle > 3.0
 $0.6/(0.6-0.4)=3.0$

Picking r and b : The S-curve


- Picking r and b to get the best S-curve

- 50 hash-functions ($r=5$, $b=10$)



Picking b and r

- Threshold s defines how similar documents have to be for them to be regarded as a similar pair (e.g., $s = 0.8$)
- Length n for minhash signatures
- Pick number of bands b and number of rows r such that $br = n$ and threshold s is approximately $(1/b)^{1/r}$
- To avoid false negatives (green area):
 - Select b and r to produce a threshold lower than s
- To avoid false positives (blue area):
 - Select b and r to produce a higher threshold than s



Example:
 $n=100$

| b | r | $(1/b)^{1/r}$ |
|-----|-----|---------------|
| 50 | 2 | 0.1414 |
| 20 | 5 | 0.5493 |
| 10 | 10 | 0.7943 |
| 5 | 20 | 0.9227 |

Example

- $(1/b)^{1/r}$ represents the threshold of the S curve for function $1 - (1 - t^r)^b$, the probability of being a candidate pair
- If $s=0.6$ (similarity of documents to be a candidate pair) what values should you choose for b and r to reduce the number of **false negatives**?
- **To avoid false negatives:** Select b and r to produce a threshold lower than s
- **To avoid false positives:** Select b and r to produce a higher threshold than s
- Could choose $(b=20, r=5)$ or $(b=50, r=2)$: both give threshold lower than s
- Better answer probably $b=20, r=5$
- Because $b=50, r=20$ will have a higher rate of false positives: **TRADEOFFS**

Example:
 $n=100$

| b | r | $(1/b)^{1/r}$ |
|----------|----------|---------------------------------|
| 50 | 2 | 0.1414 |
| 20 | 5 | 0.5493 |
| 10 | 10 | 0.7943 |
| 5 | 20 | 0.9227 |

LSH Summary

- Tune M , b , r to identify almost all candidate pairs with similar signatures, but eliminate most pairs that do not have similar signatures
- Then check in main memory that candidate pairs really do have similar signatures
- **Optional:** In another 2nd pass through data, check that the remaining candidate pairs really represent similar documents

Summary: 3 Steps

- **Shingling:** Convert documents to sets
 - We used hashing to assign each shingle an ID
- **Min-Hashing:** Convert large sets to short signatures, while preserving similarity
 - We used **similarity preserving hashing** to generate signatures with property $\Pr[h_{\pi}(C_1) = h_{\pi}(C_2)] = \text{sim}(C_1, C_2)$
 - We used hashing to get around generating random permutations
- **Locality-Sensitive Hashing:** Focus on pairs of signatures likely to be from similar documents
 - We used hashing to find **candidate pairs** of similarity $\geq s$

Combining the techniques (1)

1. Pick a value of k and **construct from each document the set of k -shingles**
 - Optionally **hash the k -shingles** to shorter bucket numbers
2. **Sort the document-shingle pairs** to order them by shingle
 - Which sets contain which elements (shingles)
3. Pick a length n for minhash signatures corresponding to n minhash functions and **compute the minhash signatures** for all the documents

Combining the techniques (2)

4. **Choose threshold s** that defines how similar documents have to be for them to be regarded as a “similar pair”
 - **Pick number of bands b and number of rows r** such that $br = n$
 - **Adjust b and r to limit false positives or negatives**
5. **Construct candidate pairs with LSH technique**
6. **Examine candidate pair signatures** and determine whether fraction of components where they agree is at least s
7. **Optionally**, if signatures are sufficiently similar, **compare documents** to check they are truly similar

CHARACTERISTICS OF LSH

Locality Sensitive Hashing

- *Or Near-neighbor search*
- Minhashing is one example of a **family of functions** (the minhash functions) **that can be combined** (by the banding technique) **to distinguish strongly between pairs at a low distance from pairs at a high distance**
- Steepness of the S-curve reflects how effectively we can **avoid false positives and false negatives** among the candidate pairs
- Section 3.6: more general theory of Locality Sensitive Functions




Figure 3.7: The S-curve

Families of Functions for LSH

- **Families of functions** (including minhash functions) that can serve to **produce candidate pairs efficiently**
 - Space of sets and Jaccard distance OR other space and/or distance measure
- **Three conditions for family of functions:**
 1. **More likely to make close pairs be candidate pairs than distant pairs**
 2. **Statistically independent**
 3. **Efficient** in two ways
 1. **Be able to identify candidate pairs in time much less than time to look at all pairs**
 2. **Combinable to build functions better at avoiding false positives and negatives** (e.g., banding technique takes single minhash functions, combines them to produce S-curve shape we want)

Locality-Sensitive Functions




Figure 3.9: Behavior of a (d_1, d_2, p_1, p_2) -sensitive function

LS Families of Hash Functions

- Suppose we have a **space S of points** with a **distance measure d**
- A **family H of hash functions** is said to be **(d_1, d_2, p_1, p_2) -sensitive** if for any x and y in S :
 1. If $d(x, y) \leq d_1$, then prob. over all h in H , that $h(x) = h(y)$ is at least p_1
 2. If $d(x, y) \geq d_2$, then prob. over all h in H , that $h(x) = h(y)$ is at most p_2
- Note: we say nothing about what happens when the distance between items is between d_1 and d_2
 - But can make d_1 and d_2 as close as we wish
 - Can drive p_1 and p_2 apart while keeping d_1 and d_2 fixed

Locality Sensitive Hashing for Other Distance Measures

- We focused on **minhashing**, a locality sensitive hashing family that uses **Jaccard distance**
 - Based on sets representing documents and their Jaccard similarity
- Book covers LSH families for **other distance measures**:
 - **Euclidean distance**: based on the locations of points in a *Euclidean space* with some number of real-valued dimensions
 - **Cosine distance**: angle between vectors from the origin to the points in question
 - **Edit distance**: number of inserts and deletes to change one string into another
 - **Hamming Distance**: number of positions in which bit vectors differ


LSH and Shingling Application Examples

- Matching fingerprints
- Identifying similar news articles

LSH for Fingerprints

- Typical representation is not an image, but **set of locations in which minutiae are located**
 - **Place where something unusual happens**: two ridges merging or a ridge ending
- **Place a grid over a fingerprint**
 - Normalize for size and orientation so that identical prints will overlap
- **Represent fingerprint by set of grid points where minutiae are located**
 - Possibly, treat minutiae near a grid boundary as if also present in adjacent grid points

Discretizing Minutiae



Place a **minutia** in several adjacent grid squares if it lies close to the border of the squares

Applying LSH to Fingerprints

- **Make a bit vector for each fingerprint's set of grid points with minutiae**
 - Similar to set representing a document: 1 if the shingle is in the document, 0 otherwise
- We could minhash the bit vectors to obtain signatures
 - But since there probably aren't too many grid points, we can work from the bit-vectors directly

Matching Fingerprints with LSH:

Many-to-many problem

- **Many-to-many version of fingerprint matching:** take an entire database of fingerprints and identify if there are any pairs that represent the same individual
 - Analogous to finding similar documents among millions of documents
- **Define a locality-sensitive family of hash functions:**
 - Each function f in the family F is defined by 3 grid squares
 - Function f says “yes” for two fingerprints if both have minutiae in all three grid squares, otherwise, f says “no”
 - “Yes” means the two fingerprints are candidate pairs
- **Sort of “bucketization”**
 - Each set of three points creates one bucket
 - Function f sends fingerprints to its bucket that have minutae in all three grid points of f
- **Compare all fingerprints in each of the buckets**

Matching Fingerprints with LSH: Many-to-One Problem

- **Many-to-one version** : A fingerprint has been found at a crime scene, and we want to **compare it with all fingerprints in a large database to see if there is a match**
- Could use many functions f from family F
- **Precompute their buckets of fingerprints to which they answer “yes” on the large database**
- **For a new fingerprint:**
 - **Determine which buckets it belongs to**
 - **Compare it with all fingerprints found in any of those buckets**

Example 3.22

- 1024 functions chosen randomly from F
 - Each function f says “yes” for two fingerprints if both have minutiae in all three grid squares, otherwise, f says “no”
- Suppose **typical fingerprints have minutiae in 20% of the grid points**
- Suppose **fingerprints from the same finger agree in at least 80% of their points**
- **Probability two random fingerprints each have 1 in all three points = $(0.2)^6 = .000064$**
 - 2 fingerprints, 3 points each, all independent events

Example: Continued

First image has 1 in a point

Second image of same finger also has 1

● Probability **two fingerprints from the same finger each have 1's in three given points** =

$$((0.2)(0.8))^3 = .004096$$

(Analogy: t)

● Prob. for **at least one of 1024 sets of three points** = $1 - (1 - .004096)^{1024} = .985$

(Analogy: $1 - (1 - t)^b$)

● But for **random fingerprints**:

$$1 - (1 - .000064)^{1024} = .063$$

6.3% false positives

1.5% false negatives

Choosing the number of functions from F

- **Want to use many functions from F , but not too many**
- **Want a good probability of matching fingerprints from the same finger while not having too many false positives**
- Previous example: only 1.5% chance we fail to identify a print on the gun (false negative), but have to look at 6.3% of entire database (due to false positives)
- **Increasing number of functions from F increases number of false positives**
 - Only a small benefit in reducing false negatives below 1.5%
- **Can use constructions/combinations of functions**
 - Several examples in the chapter

Finding Same/Similar News Articles

- **Want to organize large repository of on-line news articles**
 - Group together web pages derived from same basic text
- **Scenario:** the same article, say from the Associated Press, appears on the Web site of many newspapers, but looks quite different
- **Each newspaper surrounds the text of the article with:**
 - Its own logo and text
 - Ads
 - Perhaps links to other articles
- **A newspaper may also “crop” the article (delete parts)**

Variation on Shingling

- **Looks like earlier problem:** find documents whose shingles have high Jaccard similarity
- **But: Shingling treats all parts of document equally**
- For this application, **we want to ignore certain parts of the documents** (e.g., ads, links to other articles, etc.)
- **There is a difference between text that appears in prose and text in ads or headlines/links**
 - Prose contains greater frequency of *stop_words*
 - E.g., common words like “and” or “the”
 - Common to use list of several hundred most frequent words

New Shingling Technique

- **News articles have a lot of stop words, while ads do not**
 - “Buy Sudzo” vs. “I recommend that you buy Sudzo for your laundry.”
- **Define a *shingle* to be a stop word plus the next two following words**
 - Shingles are: “I recommend that”, “that you buy”, “you buy Sudzo”, “for your laundry”, “your laundry <nextword>”
- **Then compare the similarity of the sets of shingles that represent each document**
 - Don’t use minhashing or LSH in this example

Why it Works

- By requiring each shingle to have a stop word: **bias the mapping from documents to shingles** so it picked more shingles from the article than from the ads
- **Pages with the same article, but different ads, have higher Jaccard similarity** than those with the same ads, but different articles