

QUIZ-4 SOLUTIONS

BUCKETS	HASH FUNC 1 (i+j mod 3) ①	HASH FUNC 2 (j mod 3) ②	[1.5] Counts		[1.5] Bitmap	
			①	②	①	②
0	(1,2) (1,5) (2,4) (4,5)	(1,3) (1,3) (2,3) (2,3)	4	4	1	1
1	(1,3) (3,4) (1,3) (3,4)	(2,4) (3,4) (3,4)	4	3	1	1
2	(2,3) (3,5) (2,3) (3,5)	(1,2) (3,5) (3,5) (4,5) (1,5)	4	5	1	1

Multihash

1st PASS

[0.75]

Item counts:

$1 \Rightarrow 2, 2 \Rightarrow 2, 3 \Rightarrow 4, 4 \Rightarrow 2, 5 \Rightarrow 2$

Buckets	Hash ①	Hash ②
0	4	4
1	4	3
2	4	5

2ND PASS [0.75]

Freq items: 1, 2, 3, 4, 5

BITMAP ① :

B0	B1	B2
1	1	1

BITMAP ② :

B0	B1	B2
1	1	1

Candidate item pairs:

{1,2} {1,3} {1,5} {2,3} {2,4}
{3,4} {3,5} {4,5}

Counts of pairs

{1,2} $\Rightarrow 1$ {1,3} $\Rightarrow 2$ {1,5} $\Rightarrow 1$
{2,3} $\Rightarrow 2$ {2,4} $\Rightarrow 1$ {3,4} $\Rightarrow 2$
{3,5} $\Rightarrow 2$ {4,5} $\Rightarrow 1$

\therefore Frequent Pairs :- {1,3}, {2,3}, {3,4}, {3,5}

MULTI STAGE

1st PASS [0.5 POINTS]

item counts:

$1 \Rightarrow 2, 2 \Rightarrow 2, 3 \Rightarrow 4, 4 \Rightarrow 2, 5 \Rightarrow 2$

HASH ①

BUCKET	COUNT
0	4
1	4
2	4

2ND PASS [0.5 POINTS]

frequent items : 1, 2, 3, 4, 5

BITMAP ① :

B0	B1	B2
1	1	1

HASH ②

BUCKET	COUNT
0	4
1	3
2	5

3RD PASS [0.5 POINTS]

frequent items : 1, 2, 3, 4, 5

BITMAP ②

B0	B1	B2
1	1	1

Count of pairs :

$\{1, 2\} \Rightarrow 1, \{1, 3\} \Rightarrow 2, \{1, 5\} \Rightarrow 1, \{2, 3\} \Rightarrow 2, \{2, 4\} \Rightarrow 1,$

$\{3, 4\} \Rightarrow 2, \{3, 5\} \Rightarrow 2, \{4, 5\} = 1$

Frequent Pairs : $\{1, 3\}, \{2, 3\}, \{3, 4\}, \{3, 5\}$

2) General idea - [0.5]
for some applications, it is sufficient to discover most frequent itemsets and is not essential ~~easy~~ to discover every single one.

Pros: less I/O cost, time, Cons: false positive, false
[0.25] Panes. [0.25] Negative are induced in the results.

3) PHASE 1 MAP I/P :-

[0.25] a chunk/subset of all baskets
(sample of i/p file)

PHASE 1 REDUCE I/P :-

[0.25] set of pairs $(f, 1)$

PHASE 2 MAP I/P :-

[0.25] Result from phase 1 and total output file

PHASE 2 REDUCE I/P

[0.25] $C(V)$

PHASE 1 MAP O/P :-

set of pairs $(f, 1)$ where f is a frequent itemset from sample.

PHASE 1 REDUCE O/P :-

candidate itemsets

PHASE 2 MAP O/P :-

Set of pairs (C, V) , C is candidate itemsets, V is the support for that itemset.

PHASE 2 REDUCE O/P :-

if $V \geq S$, emit (C, V)

4) false positive :- Infrequent in entire data, frequent in sample.

[0.25] false Negative :- Frequent in entire data, Infrequent in sample.

Increasing Support : will increase FN as it will be harder to be frequent in the sample, decrease FP.

[0.5] Decreasing Support : will induce more FP in the data as it is easier to be frequent in the data/sample decrease FNs.

5)
[0.25]

Singleton : $\{a\}$ is in -ve border,
iff $\{a\}$ is not frequent in the sample

[0.25]

Pair : $\{a, b\}$ is in -ve border,
iff $\{a, b\}$ is not frequent in the sample
 $\{a\}, \{b\}$ are frequent

0.5
marks

① Construct sample data set

② Find candidate frequent items from sample

③ Construct Negative border.

④ process the whole file,

if no itemset from -ve border turns out to be
frequent in whole dataset, correct V
if some ..., Repeat the algo with random sample.